

## Maxtor OneTouch™ II Small Business Edition

### HIGHLIGHTS

- Microsoft Windows Server 2000 and 2003 families
- Comprehensive backup includes operating system, settings, updates, applications, databases, documents and even open files
- Unattended, automated backup schedules
- Remote backup status and initiation

### FEATURES

- Easy installation, setup, and restore wizards
- Initiate backups remotely
- Self-manages backups and deletes older backup versions if needed
- Open file backup
- Creates historical backup versions
- Full system restore to a point in time
- Maxtor DriveLock™ for added security of contents if drive is lost or stolen
- Simple user interface for drive management, security and backup settings, and file restoration
- Power on/off switch and power management utilities included
- EMC®/Dantz® Retrospect® Server HD backup software included

### SERVER BACKUP

**200GB Native / 300GB Compressed\***

### Simple backup for a small business server

Designed for the small business, the Maxtor OneTouch II, Small Business Edition installs easily and includes a simple wizard interface for setting up unattended, automated backup schedules, drive management, security and backup settings, and file restoration.

Specifically developed for the small business server, comprehensive backups include operating system, settings, updates, applications, databases, address books, emails, documents and even open files! You can even receive status updates via email or a simple desktop icon, and know that your backup is working—wherever you are.

The Maxtor OneTouch II, Small Business Edition saves historical versions of the same files and lets you restore your system to its previous status at a given point in time. The 200GB drive can backup up to 300GB of compressed files and features Maxtor DriveLock™ to password-protect the contents of the drive in case of loss or unauthorized use.








Rotate multiple Maxtor OneTouch drives and store them offsite as part of an even broader data protection strategy.

It's your livelihood—protect your critical data! Now it's simple.



\* Compression assumes 3:2 compression ratio. Actual compression may vary dependent on type of data.

## Included in the box

	Server backup drive
	USB cable
	External AC power adapter
	Installation software and user guide CD
	Vertical stand
	Quick start guide
	Maxtor limited warranty

## System Requirements

### Server:

- Pentium III, 500 MHz equivalent processor or higher (does not support Intel IA64 family)
- Windows Server (Server 2000, Advanced Server 2000, and Server 2003 Standard Edition)
- Windows Small Business Server (2000 and 2003)
- 32 bit OS versions only
- 256MB RAM or more as required by operating system
- CD-ROM drive
- Internet connection (for software updates)
- Remote e-mail notification: SMTP mail server access

### Client (remote status support only):

- Pentium III, 500 MHz equivalent processor or higher
- Windows XP Professional and Windows 2000 Professional
- 128MB RAM or more as required by operating system
- Network connection to server (must be connected to the same subnet)
- CD-ROM drive
- Internet connection (for software updates)
- Remote e-mail notification: SMTP mail server access

## Interface Requirements

### USB:

- Available USB 1.1 or 2.0 port



## Specifications

Interface	USB 2.0 / 1.1
Capacity (model numbers)	200GB native/300GB compressed* (Y01E200)
RPM	7200 RPM
Cache Buffer	8MB
Platform	Windows Server

## Integrated Interface

USB 2.0 and 1.1 compliant

- External 4-pin connector with hot-plug capability
- Supports data transfer rates up to 480 Mb/sec

## Performance

Average seek time:

- $\leq 9.0$ ms

Sustained transfer rate (maximum):

- USB2—34 MB/sec

Bus transfer rate (maximum):

- USB2—480 Mb/sec

## Environmental Specifications

Operating temperature: 5° C to 35° C (41° F to 95° F)

## Physical Specifications

Dimensions: 1 5/8 x 5 1/2 x 8 11/16 inches (41 x 140 x 220 mm)

Weight: 3.1 lbs (1.38 Kgrams)

## Power Requirements

AC Input Voltage: 100–240 VAC

Input Frequency: 47–63 Hz AC



For support or information, call us at 1-800-2Maxtor or visit us at [www.maxtor.com](http://www.maxtor.com)

\* Compression assumes 3:2 compression ratio. Actual compression may vary dependent on type of data.

For purposes of measuring storage capacity, a gigabyte (GB) equals 1,000,000,000 bytes. Total accessible capacity varies depending on operating environment. Maxtor OneTouch is an element of your overall data protection plan. © 2005 Maxtor Corporation. Maxtor, What drives you and the Maxtor stylized logo are registered trademarks, and Maxtor OneTouch and Maxtor DriveLock are trademarks, of Maxtor Corporation. Dantz, the Dantz logo, and Retrospect are registered trademarks of Dantz Development Corporation. (Dantz Development Corporation: U.S. patents 5,150,473 and 5,366,730. Other patents pending.) Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the U.S. and other countries. The USB-IF logos are trademarks of Universal Serial Bus Implementers Forum, Inc. Microsoft, Windows and the Windows logo are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Other trademarks are the property of their respective holders. Actual product may vary from photo shown. Specifications are subject to change without notice. Maxtor Corporation, 500 McCarthy Boulevard, Milpitas, CA 95035. [www.maxtor.com](http://www.maxtor.com). DS-OneTouch2SBE-4/05-CL

**Maxtor**<sup>®</sup>  
What drives you.<sup>®</sup>