

# PACKAGED TERMINAL AIR CONDITIONERS

## *Performance Specifications*

Model Number		SPTAC-09H	SPTAC-12H	SPTAC-15H
Refrigerant	Type	R22	R22	R22
Refrigerant Quantity	oz	24.69	30.69	35.27
Power Supply	V/Ph/Hz	208-230/1/60	208-230/1/60	208-230/1/60
Cooling Capacity	Btu/Hr	9600	12,000	15,000
Cooling Power Input	W	880	1140	1700
Cooling Power Amp	AMP	3.83	4.96	7.39
Heating Capacity	Btu/Hr	9000	11,000	14,000
Heating Power Input	W	810	1060	1700
Heating Power Amp	AMP	3.52	4.61	7.39
Electric Heating Power Input	W	3020	3020	3020
Electric Heating Current Input	AMP	13.3	13.3	13.1
Rated Power Input	W	990	1320	4820
Rated Current Input	AMP	4.3	5.74	20.96
Dehumidification	Pints/day	21.6	32.4	51.6
EER	Btu/W	10.8	10.4	9
COP	Btu/W	11	10.4	8.5
Compressor	Brand	MATSUSHITA	MATSUSHITA	MATSUSHITA
Air Flow	CFM	330	400	400
Unit Full Load Current	AMP	17.4	18.6	21
Breaker Min	AMP	20	30	30
Noise Level	dBa	45-50 (Indoor) / 69 (Outdoor)	45-50 (Indoor) / 69 (Outdoor)	45-50 (Indoor) / 69 (Outdoor)
Coil	Type	Inner groove tube	Inner groove tube	Inner groove tube
Net Dimension	W x H x D (inch)	42X22X16	42X22X16	42X22X16
Packing Dimension	W x H x D (inch)	45 1/4 X 18 1/2 X 24 1/5	45 1/4 X 18 1/2 X 24 1/5	45 1/4 X 18 1/2 X 24 1/5
Net Weight	lb	109.5	112.5	114.5
Shipping Weight	lb	125	127.5	130.2



*Innovative products for a more energy efficient world.*

### Soleus International, Inc.

20035 E. Walnut Dr. N.  
 City of Industry, CA 91789 USA  
 office 909.718.0478  
 fax 909.718.0468  
 www.soleusair.com