


4"/6" TFT- LCD COLOR TV

CTV-5040 / 60



INSTRUCTION MANUAL

RECOMMENDED GUIDELINES FOR THE USE OF A VIDEO MONITOR/TV IN A MOTOR VEHICLE

- A VIDEO MONITOR/TV is designed for rear passenger viewing only. This product may only be installed in the rear seat compartment of the vehicle, out of the driver's view.
- Installation in any other area of the vehicle, including anywhere within the driver's view, is illegal in most states, provinces and countries and may lead to driver distraction resulting in an accident, injury and/or death. If you are unsure of regulations regarding this, please consult your local laws to determine how this applies to you.
- Users should be aware of possible noise distraction caused by the use of the product and should carefully monitor the volume so as not to interfere with the driver's attention to surrounding traffic conditions.

FUNCTION------




FIG. 1 FRONT

- 1. POWER INDICATOR
- 1. REMOTE CONTROL SENSOR
- 1. SCREEN



- 1. POWER ON / STAND BY key
- 1. AUTO PROGRAM key
- 1. TV / AV1 / AV2 key
- 1. PICTURE SELECT key
- VOLUME DOWN key (PICTURE SELECT DOWN)
- 1. VOLUME UP key (PICTURE SELECT UP)
- 1. CHANNEL DOWN key
- 1. CHANNEL UP key
- 1. ROD ANTENNA








FIG. 3 RIGHT

- 14. ANTENNA jack
- 15. AV1 INPUT jack
- 15. AV2 INPUT jack
- 15. EARPHONE jack









24

FIG. 4 LEFT

- 18. SPEAKER
- 19. BACKLIGHT HIGH/LOW switch (Model 5040 only)
- 20. DIVERSITY OUTPUT jack
- 21. DC INPUT jack
- 22. POWER ON / OFF switch

FIG. 5 BACK

23. STAND

24. FIXING NUT

FIG.6 REMOTE CONTROL UNIT

- 31. POWER ON / STAND BY key
- 32. AUDIO MUTE key
- 33. TV / AV1 / AV2 key
- 34. AUTO PROGRAM key
- 35. PICTURE SELECT key
- 37. VOLUME DOWN key (PICTURE SELECT DOWN)
- 38. VOLUME UP key (PICTURE SELECT UP)
- 39. CHANNEL DOWN key
- 40. CHANNEL UP key

INSTALLATION------

POWER

- 1. One of the following power sources can be used.
 - 1) AC power adapter.
 - 2) Car battery (with car cord connected).
 - 3) 8 x UM-3 batteries (optional battery box used). For longer operation time, the alkaline batteries are recommended and move the BACKLIGHT HIGH / LOW switch (19) to "LO" for power saving. (Model 5040 only)
- 2. Move the POWER ON / OFF switch (22) to "ON" to make the TV unit at stand-by status. At this time the POWER INDICATOR (1) lights up. Then the remote control unit can work.
- 3. Press the POWER ON / STAND BY key (4,31) to turn on the TV unit and lighten the screen. The POWER INDICATOR (1) is brighter. Pressing the key (4,31) again will recover the TV unit to stand by.

BACK LIGHT SWITCH (MODEL 5040 ONLY)


- Move the BACKLIGHT HIGH / LOW switch (19) to "HI" for normal use.
- 2. For battery power saving, move the switch (19) to "LO". The luminance of the screen will lower down.

FM TRANSMITTER (for Japan only)

- 1. Move the TRANSMITTER OFF / FM1 / FM2 switch (13) to "FM1" (or "FM2").
- 2. Turn on the FM radio and set the same channel frequency to receive FM1 (or FM2) signal. The efficiency distance is about 5m.
- 3. When the function is unused, move the switch (13) to "OFF".

TV OPERATION-----

- 1. Pull out the ROD ANT (2) or connect an external antenna to ANT jack (14) for better reception.
- 2. Used in the vehicle, the diversity unit (with boost function) is recommended to use to improve the reception performance.



3. Press the TV / AV1 / AV2 key (6,33) to the TV mode.




- 4. Press the AUTO PROGRAM key (5,34) to scan the whole channels and memorize them.
- 5. Press the CHANNEL UP (11,40) or DOWN (10,39) key to select the desired TV station. If the channel number displayed on the screen has not been memorized. Repeat step 1 to 5 until the number turns green.
- 6. If the ROD ANT (12) is used, adjust the antenna direction to get the best quality of reception.
- 7. Adjust the viewing angle. The recommended viewing angle of the TV unit is $+30^{\circ} \sim -10^{\circ}$ vertical and $+45^{\circ} \sim -45^{\circ}$ horizontal.

8. Picture Adjustment

1) Press the PICTURE SELECT key (35) several times, the screen will appear the picture control bar in the following order sequentially.



2) Before the disappearance of the PICTURE SELECT UP (VOLUME UP) (9,38) or DOWN (VOLUME DOWN) key (8,37), to adjust the picture quality. For example,




3) Press the PICTURE RESET key (36) on the remote control unit to recover the original picture setting.

9. Audio Operation

- 1) Press the VOLUME UP (9,38) or DOWN (8,37) key to adjust the volume output level. If the channel number displayed on the screen is red (it means the channel has not been memorized), the volume control is in vain.
- 2) For earphone use, insert the earphone plug into the EAR jack (17).
- 3) No volume output when the MUTE key (32) on the remote control unit is pressed. Press again to recover.

MONITOR OPERATION-----

1. Input the AV signal from the sources (VCR, Video camera, GPS, etc.) to the AV1 (15) and /or AV2 (16) jacks. The yellow terminal of the AV cord connects with the video signal; the white terminal with audio.



- 2. Press the TV / AV1 / AV2 key (6,33) to select the desired AV source. The screen is dark with no video inputs.
- 3. Picture adjustment: as the TV operation described above.
- 4. Audio operation: as the TV operation described above.

IMPORTANT NOTES-----

- 1. Do not expose to temperature extremes or direct sunlight. (See specifications)
- 2. Avoid dust and wet.
- 3. Avoid dropping and strong impact.
- 4. Turn power off and unplug the adapter when not in use or thundering.
- 5. Never watch while driving a vehicle.
- 6. Never attempt your own maintenance.

TROUBLESHOOTING-----

Before assuming malfunction of TV, check as follows:

SYMPTOMS	POSSIBLE CAUSES	WHAT TO DO		
No power	AC adapter or car cord not properly connected	Connect correctly		
	Fuse of car cord blown	Replace fuse		
	Dead batteries	Replace batteries		
	 Incorrect polarity of 	Make sure the battery		
	batteries (battery box	poles are properly		
	used)	aligned.		
Remote control unit cannot work	Batteries unloaded, dead or incorrect polarity	replace batteries		
	Remote control distance too far.	Distance must be less than 2M.		
	Direction of remote control	Point the remote control		
	improper	unit to the sensor directly		
No picture and	TV/AV1/AV2 selected	Press the TV/AV1/Av2		
sound	incorrectly	key to correct mode		
	Incorrectly connected AV	Check the connection		
Diumu niatuma	sources and the TV	and correct it		
Blurry picture and noise	External antenna not	Check the connection. Extend red entenne.		
and noise	connected properly or rod antenna folded	Extend rod antenna.		
	Not properly tuned.	 Press auto program key again. 		
	Interference from	Move further away from		
	automobiles, electric	appliances causing		
	appliances, etc.	interference. Change		
	- Decention had due to	antenna position.		
	 Reception bad due to weak signals, buildings, 	In locations with poor reception, it may not be		
	mountains, etc.	possible to get a clear		
	mountains, etc.	picture or any picture at		
		all.		
Sound heard but	Brightness control not set	Adjust brightness		
picture all white	correctly			
or dark				
Sound heard but color light	Color control not set correctly.	Adjust color.		
Picture visible	Mute function working.	Mute off.		
but no sound	Volume control turned too	Turn volume up.		
	low			
	Earphone inserted	Disconnect earphone.		

SPECIFICATIONS-----

CTV-5040 / 60

TYPE	Color LCD TV	
DISPLAY SCREEN	SIZE	4 inches (82.1 x 61.7mm)(W x H)
		6 inches (112.9 x 84.7mm) (W x H)
	ELEMENT	TFT-LCD
	FORMAT	4": 480 (W) x 234 (H)
		Total 112,320 dots
		6": 720 (W) x 234 (H)
		Total 168,480 dots
BACK LIGHT	Cold cathode fluorescent lamp	
POWER SUPPLY	AC adapter (AC 120V 60 Hz DC 12V)	
	Car battery (DC 12V)	
POWER CONSUMPTION	DC 12V	4": 7W
		6": 11W
RECEPTION CHANNELS	VHF-L	CH 2 ~ 6
	VHF-H	CH 7 ~ 13
	UHF	CH 14 ~ 69
INPUT TERMINALS	External power jack (DC IN 12 ~ 14V) External antenna jack (3.5Ø mm)	
	AV1 input jack (3.5∅ mm)	
	AV2 input jack (3.5	5∅ mm)
OUTPUT TERMINALS Diversity jack (3.5Ø mm)		∅ mm)
	Earphone jack (3.5	5Ø mm)
OPERATION	5° ~ 40° C	
TEMPERATURE		
STORAGE	-20° ~ +60° C	
TEMPERATURE		
DIMENSIONS	4": 150 x 116 x 45r	mm (W x H x D)
	6": 180 x 145 x 48r	nm (W x H x D)
WEIGHT	4": 460g	
	6": 650g	

ACCESSORY LIST-----

Description	Part Number
AVT-988 9" Color Television with Remote (12V)	AVT988
AVT-597 5" Color Television with Remote (12V)	AVT597
AVT-1498 13" Color Television with Remote (12V)	AVT1498
AVP-7000 Video Cassette Player (12V)	AVP7000
AVP-7285 Video Cassette Player (12V)	AVP7285
Wireless Headphone Kit: Includes 2 sets Wireless	WRFKIT1
Headphones and Transmitter	
BPA-501-12 4 Amp Adapter for use with AVT-988 9" and	0891412
AVT-1498 13" Televisions	
AC2A- 2 Amp Adapter for use with AVT-597 5" TV and	0891436
AVP-7000 Video Cassette Player	
Unified Remote Control	0892325
VAC-21- 12 Volt Corded Vacuum	VAC21
AVF-1 12 Volt Rechargeable Flashlight	AVF1
HP-175 Headphones with Pivoting Ear Cup	HP175
HP-275 Headphones with Volume Control on Cord	HP275
HP-375 Studio Quality Headphones	HP375

Unlike household electronics, all of our products have been specifically designed and tested for the mobile environment and are only available through ASA. To order any of these products, please contact Audiovox Specialized Applications at www.asaelectronics.com or 800-688-3135.