



Reliable source for
IP Surveillance Systems



FINE

CCTV PROFESSIONAL

FINEST SECURITY SYSTEMS CO., LTD.

No. 103 12th Floor, Sec. 3, Nan King East Road, Taipei, Taiwan R.O.C.

Tel: 886-2-2506-6788, 886-2-2506-6799

Fax: 886-2-2506-8887, 886-2-2506-7887

www.finecctv.com



E-mail: sales@finecctv.com

Distributed by

Products



STORCK Speed Dome Series

<p>High Speed Dome with IR LEDs SP-PTIR737(37X) / SP-PTIR026 (26X) / SP-PTIR018 (18X)</p>	<p>WDR High Speed Dome SP-1036WQ (36X) / SP-1029WQ (26X) / SP-1019WQ (18X)</p>	<p>High Speed Dome SP-1023D (Day & Night)</p>
	 <p>Outdoor SP-1019WQ / SP-1029WQ SP-1036WQ</p> <p>In-Ceiling SP-1019WI / SP-1029WI SP-1036WI</p> <p>Surface Mount SP-1019WS / SP-1029WS SP-1036WS</p>	 <p>Outdoor SP-1023DQ</p> <p>In-Ceiling SP-1023DI</p> <p>Surface Mount SP-1023DS</p>
<p>Features</p> <ul style="list-style-type: none"> • Unique Design, all in one Integrated Hi-Speed Dome • Integrated with High Quality IR Leds, maximum distance 200M • Powerful Mechanism Structure with shocking resistance • 3-Level Lighting Protection • IR Distance: 100M • IR Distance with Laser: 200M • IP65 Outdoor 	<p>Features</p> <ul style="list-style-type: none"> • More than 540TV Lines of Horizontal Resolution, with Wide Dynamic Range • Full equipped with high sensitivity 1/4" Sony Exview CCD • 8 privacy masking zones • Day & Night +ICR for true day & night surveillance • 4 alarm inputs, 2 outputs • 2 pattern tours each one with up to 80 seconds of record • 8 tours, 24 presets / tour, speed and time selectable • 128 presets with editable time • Baud Rate: 2400 / 4800 / 9600 bps • Multiple protocols support • IP66 Rated • Multiple Language 	<p>Features</p> <ul style="list-style-type: none"> • More than 480TV Lines of Horizontal Resolution • 8 privacy masking zones • Full equipped with high sensitivity 1/4" Sony CCD • Day & Night +ICR for true day & night surveillance • 4 alarm inputs, 2 outputs • 2 pattern tours each one with up to 40 seconds of record • 8 tours, 24 presets/tour, speed and time selectable • 128 presets with editable time • Baud Rate: 2400/4800/9600 bps • Multiple protocols support • IP66 Rated • Multiple Language

STORK Speed Dome Accessory

<p>Wall Mount Bracket ST-BF</p>	<p>Pendant Mount Bracket ST-D05</p>	<p>Mount Adapter ST-AD01</p>	<p>Power Case ST-HV</p>
			
<p>Corner Bracket ST-T01</p>	<p>PTZ Keyboard (2D Axis) CK-103</p>	<p>PTZ keyboard (3D Axis) CK-104</p>	<p>H.264 IP Board NETCD-H</p>
			

Mini Speed Dome Series

Mini Speed Dome Accessory




Mini 10X Pan/Tilt Dome SP-PTZ1054	Mini 10X Outdoor Pan/Tilt Dome SP-PTZ1054W	PTZ Keyboard KB-1048S	PTZ Keyboard KB-1054S
			
Features <ul style="list-style-type: none"> • Pan & Tilt Speed Up to 360° per second • Digital Flip, extra tilt angle 5° • Support total 100X Power Zoom • Support Day & Night function • IR Cut Filter Removable • AGC, ALC, AES, BLC, AWB detection zones • 360 Degree Rotation, 127 Preset Positions • 8 Groups for present program • 8 set of swing action • Support 4 pattern • 4 privacy zones 	Features <ul style="list-style-type: none"> • 1/4" Interline Transfer CCD • Auto Day/Night; color/B&W function, Dual IR filter switch (IR Cut function) • 100x (10x Optical zoom, 10x Digital Zoom) • Horizontal RES: 500TVL (Color), 570TVL (B/W) • Min Illumination: Color 0.7Lux/F1.8(50 IRE), B/W 0.02Lux/F1.8(50 IRE) • 127 Preset • 4 Privacy Zone • Preset Speed: Max 360°/sec • Rotation Range: Pan 360 degree rotating • Tilt 180 degree rotating (Auto-Flip) • Manual Speed: 0.05° ~360°/Sec (proportional to zoom) • 8 Cruise Group (20 action entities per Group) • With outside cover, built-in fan and heater • IP66 Rated outdoor 	Features <ul style="list-style-type: none"> • Easily ID, protocols setup on OSD • RS-485 communication • 2D joystick rotation 	Features <ul style="list-style-type: none"> • Easily ID, protocols setup on OSD • RS-485 communication • 3D joystick rotation
		Wall Mount Bracket VD-B1048	Ceiling Straight Bracket VD-B1048C
			

Camera Series



License Plate Recognition CT-DN938H, CT-L938HIO, CT-L960WD, CT-L960WD-ICR	WDR Camera WITH OSD, 680TVL CT-WD1680, CT-WD1680-ICR	DVR CAMERA WITH SD BACK UP CK-DH1190	BOX TYPE CAMERA WITH D-WDR + OSD CK-2600D
			
Features <ul style="list-style-type: none"> • 1/3" Digital Wide Dynamic Car License Plate Camera (Effio) • Color: 610TVL, B/W:630TVL • Color: 0.05Lux@F1.0, B/W:0.03Lux@F1.0, Sense-up: 0.0001Lux@F1.0 • Capable of Capturing Car License Plate Numbers at High Speed • Day:up to200km/hr (125mile/hr) • Night:up to150km/hr (90mile/hr), CT-L938HIO with External IR LEDs • Three Shutter Modes (Auto, Manual, Scheduled Shutter) • Multi-Language OSD Control / RS485 Remote Control • Powerful 128X Digital Wide Dynamic Range (52dB) • 2D/3D Noise Reduction & Sense Up (512x) Functions • Face Detection of up to 4 faces • E-zoom Function (1~256x) • Advanced Motion Detection Function • Polygonal Mosaic Privacy Mask • Freeze / Timer Clock 	Features <ul style="list-style-type: none"> • 1/3" Hyper Wide Dynamic Infrared Camera (Effio WDR) • Color: 680TVL, B/W:700TVL • Color: 0.03 Lux @F1.0 , B/W: 0.01 Lux@F1.0, Sense, up:0.0001Lux@F1.0 • Multi-Language OSD Control / RS485 Control • RS485 Interface OSD Control by Pelco -D, Pelco -P • Powerful 510X WDR (54dB) • Ideal for Backlight Environments • 2D/3D Noise Reduction & Sense Up (512x) Function • Shutter Mode (Schedule/ Day & Night) • Face Detection of up to 4 faces • E-Zoom Function (1~256x) • Advanced Motion Detection Function • Polygonal Mosaic Privacy Mask • Freeze / Timer Clock 	Features <ul style="list-style-type: none"> • Super enhance video quality with 1/3" SONY CCD • New design camera concept • Ready to Use Digital Video Recorder • SD Back up • Save money for small retailers, kiosk, shops, home security • Audio support • Full function camera • MPEG 4 compression • With remote controller • With privacy mask • Day and Night with ICR for true surveillance Other Accessory <div data-bbox="837 1915 1141 2116">  <p>Remote Controller Real View</p> </div>	Features <ul style="list-style-type: none"> • 1/3" SONY CCD • 600 TV Lines • DNR (Digital Noise Reduction) • WDR (Wide Dynamic Range) • Motion detection (4 zones) • Auto White balance • Built in mechanical IR Cut Filter for True Day Night Function • OSD Control for camera setting • Optional use with controller board for easy set up from remote distance

Products

Vandal Dome Series

Hyper WD IR Vandal Dome CDV-3D610WD-ICR, CDV-3D700WD-ICR	3" Vandal Varifocal Dome VD-2V220 / VD-2V260 / VD-2V280	3" Vandal Varifocal IR Dome VD-2VIR220 / VD-2VIR260 / VD-2VIR280	3" Vandal IR Dome with fixed lens VD-IR220 / VD-IR260 / VD-IR280	Anti-Grip Mini Dome ABS with Fixed lens DC-420 / DC-480 / DC-540
				
Features <ul style="list-style-type: none"> 1/3" Hyper Wide Dynamic Infrared Dome camera (Effio WDR) Color: 610 TVL, B/W: 630TVL, 0 Lux (IR LEDs on at 2Lux) for CDV-3D610WD-ICR Color: 680 TVL, B/W: 700TVL, 0 Lux (IR LEDs on at 2Lux) for CDV-3D700WD-ICR Multi Language OSD Control Powerful 256X WDR (53dB) for CDV-3D610WD-ICR Powerful 510X WDR (53dB) for CDV-3D700WD-ICR Ideal for backlight Environments 2D/3D Noise Reduction & Sense Up(512X) Functions Face Detection of up to 4 faces E-zoom Function (1~256X) Advanced Motion Detection Water Resistance: IP 66, breaking Strength : 656.1 Kgs Built in Varifocal lens & Unique 3-Axis Gimble Mechanism Other Accessory  	Features <ul style="list-style-type: none"> Ultra Compact and Light Weight Integrated of Varifocal DC Iris 3.5 ~ 9.5 mm Lens 3 Dimensional Design IP66 with Waterproof Housing Stable Picture Quality Vandal Proof Design Dual Power AC24V / DC12V Aluminum Housing Other Accessory 	Features <ul style="list-style-type: none"> IP66 Rated Housing 3 Dimensional Design Compact & Vandal Resistant Construction DSP controls for BLC, white balance and gain control Day & Night switchable with ICR mechanism Digital Noise Reduction Integrated of Varifocal DC Iris 3.5 ~ 9.5 mm Lens Fitted with 18 pieces LED with micro IR sensor for a better illumination at night Heater Built in Aluminum Housing Other Accessory 	Features <ul style="list-style-type: none"> Ultra Compact and Light Weight 3 Dimensional Design Vandal proof design Integrated Board Lens 4.3mm (standard), 3.6mm, 6mm, 8mm (option) Stable picture quality Digital Noise Reduction IP66 with Waterproof Housing With IR Leds IR Cut Filter (Option) Other Accessory 	Features <ul style="list-style-type: none"> Ultra Compact and Light Weight Anti-Grip with Tri-Axis Gimble design Integrated Fixed Lens 3.6mm (standard), 4.3mm, 6mm Aspherical Lens With 1/3" CCDs: Sharp and Panasonic Stable Picture Quality ABS Housing Audio (option) Wide Angle 2.5mm Lens (option)

Dome Series

Anti-Grip Dome Camera DC-420 ^A -W25 / DC-480 ^A -W25 / DC-525A-W25	Anti-Grip Mini Dome ABS with Varifocal Lens DC-420V4 / DC-480V4 / DC-540V4	IR Dome Camera CF-P115SH	IR Dome Camera CF-DM836 / CF-DM828
			
Features <ul style="list-style-type: none"> Ultra Compact and Light Weight Integrated 2.5mm Wide Angle Lens Anti-Grip with Tri-Axis Gimble design With 1/3" CCDs: Sony or Sharp Stable Picture Quality ABS Housing 	Features <ul style="list-style-type: none"> Ultra Compact and Light Weight Integrated of Varifocal DC Iris 3.5 ~ 9.5 mm Lens Anti-Grip with Tri-Axis Gimble design With 1/3" CCDs: SONY and Sharp Stable Picture Quality ABS Housing 	Features <ul style="list-style-type: none"> Equipped with 1/3" High Sensitivity SONY CCD Integrated Fixed 4mm Lens (standard) Lens Using oval beam LEDs delivering clean vivid picture at night time 20 Pieces IR LEDs Automatic Gain Control Low Power Consumption 	Features <ul style="list-style-type: none"> 1/3" Sony Super HAD CCD 550 TVL Horizontal Resolution 6 Pcs Ø5 IR Leds IR Distance 6-8M Under 5 Lux Auto Switched IR LEDs by CDS Electronic Day / Night Aluminum Housing
Color IR Dome Camera CF-P620IR / CF-P660IR	3 Axis IR Dome DA-282C / DA-286SP / DA-288C		Dome Camera DC-CM550
			
Features <ul style="list-style-type: none"> Equipped with 1/3" High Sensitivity SONY CCD Horizontal resolution of 420TVL / 540TVL Using oval beam LEDs delivering clean vivid picture at night time 24 Pieces IR LEDs Electronic shutter speed up to 1/100,000 sec Automatic Gain Control Low Power Consumption ABS housing 	Features <ul style="list-style-type: none"> Well Equipped Advanced 1/3" CCD Good Sensitivity at Low Light Horizontal resolution of 420TVL / 480TVL / 540TVL Aspherical lens 3.6mm, 4.3mm, 6mm, 8mm for Better Illumination at dark 3-Axis Gimble Design For Flexible Adjustment Angle 18 IR LEDs with 15-20M IR Range Built in Mechanical IR Cut Filter For True Color at Daylight Aluminum Housing 		Features <ul style="list-style-type: none"> Built in standard 3.6mm (standard) ABS housing With crisp image 550 TV Lines With superb quality






IR LED Auto Detector Light Camera

IR LED Auto Detector Light Camera FL-101IR / FL-101IRH	Halogen Tube Auto Detector Light Camera FL-150 / FL-500 / FL-150H/ FL-500H	White Light LED Auto Detector Camera FL-201WL/ FL-201WLH
		
<p>Features</p> <ul style="list-style-type: none"> • 1/3" Sony Super HAD Color CCD Sensor • Auto Electronic Shutter • Horizontal resolution 420 TV Lines or 540 TV Lines • Excellent Picture Performance with Hi-resolution (540TVL) • Apply to School, Supermarket, Restaurant, Government Building, Bank, Hotel, Parking Lots, Lanes • 120PCs 50IR LED • IP55 Weather-proof • Working Voltage: AC110V, AC220V • Video Output Dual Port (Optional): BNC & Balun (Balun: extend To 600 meters) 	<p>Features</p> <ul style="list-style-type: none"> • 1/3" Sony Super HAD Color CCD Sensor • Auto Electronic Shutter • Horizontal resolution 420 TV Lines or 540 TV Lines • Excellent Picture Performance with Hi-resolution (540TVL) • Apply to School, Supermarket, Restaurant, Government Building, Bank, Hotel, Parking Lots, Lanes • IP55 Weather-proof • Compatible for AC110V or AC220V • Halogen Tube: 150W / 500W • Video Output Dual Port (Optional): BNC & Balun 	<p>Features</p> <ul style="list-style-type: none"> • 1/3" Sony Super HAD Color CCD Sensor • Auto Electronic Shutter • Horizontal resolution 420 TV Lines or 540 TV Lines • Apply to School, Supermarket, Restaurant, Government Building, Bank, Hotel, Parking Lots, Lanes • 150PCs 5φ White-light LED • IP55 Weather-proof • Working Voltage: DC12V • Video Output Dual Port (Optional): BNC & Balun

IR Bullet Series

Long Range Outdoor Camera YV-XP8860/YV-XP8862/YV-XP8864/ YV-XP9100 /YV-XP9650	IR NIGHT VISION IR BULLET WITH OSD AV-B600V28, AV-B600V65	IR Color Bullet Camera ICX-IR108SH / ICX-IR120SH	Sensifier Bullet Camera ICN-480-8SL / ICN-560-8SL	IR Color Camera ICX-3450V4 ICX-3550V4
				
<p>Features</p> <ul style="list-style-type: none"> • Horizontal resolutions 600 TVL lines camera • Maximum IR effective distance can up to 120 Meters, with Hi-Power LEDs • True Day Night Surveillance with ICR filter mechanism • Built In aspherical varifocal DC Iris lens: 4~9mm, 2.8~11mm, 6~50mm, 9~22mm, 18~50mm • Easy to be installed • Tri-Axis Bracket for Wall, Ceiling and Roof • Concealed Cabling Management • Low Power Consumption • Powered with AC24V/DC12V • IP66 Rated for Outdoor Use • Built in heater • Standard Color: Silver 	<p>Features</p> <ul style="list-style-type: none"> • CCD options : 1/3" SONY CCD 600TVL • Lens options : 2.8-11mm, 6-50mm, V.F. Lens in the same housing • IR control by light sensor • Outdoor projecting distance: 30 meters (2.8-11mm LENS) / 70 meters (6-50mm Lens) with High Power IR LEDs • Build in ICR Filter • DNR, D-WDR • OSD function control by the RS-485 pocket controller • Build in audio with equalizer function • External control rings for easy focus, distance adjustment • Vandal bracket for wall / ceiling mount • IP66 Water Proof rated • Power supply: Dual power design • Automatic heater & indicator for extreme cold environment 	<p>Features</p> <ul style="list-style-type: none"> • IR distance: 30 meters • Horizontal resolution 420 TV Lines, 550 TV Lines • Built in fixed lens 4 mm, 6 mm Lens • Attractive white housing/stainless steel joint for long durability • 40 pcs IR LED 	<p>Features</p> <ul style="list-style-type: none"> • Vivid Color Picture remains under low light • No IR required at night. • Horizontal resolution 480TVL & 560 TVL • No overheat problem. Save energy • Horizontal Resolution 480TVL, 560 TV Lines. • IP66 weatherproof housing for outdoor use • Available with 4.3m, 6mm, 8mm lens 	<p>Features</p> <ul style="list-style-type: none"> • Horizontal resolution 450 TV Lines, 550 TV Lines • Auto Gain Control • IR distance: 60 Meters • LED: 77 unit 840nm infrared LED • Power on: CDS auto control

H.264 Stand Alone DVR System

SR-H2004-N / SR-H2008-N / SR-H2016-N	SR-LD304(4 CH) / SR-LD308(8 CH)	SR-LD304WS / SR-LD308WS	SR-HD9916	TFDR-1904TH / TFDR-1908TH 19" Touch COMBO DVR
 <p>Mobile View Support</p>	 <p>Mobile View Support</p>	 <p>Mobile View Support</p>	 <p>Mobile View Support</p>	
<p>Features</p> <ul style="list-style-type: none"> • 4 / 8 / 16 channels Full D1 720x480 Display • HDMI Output, DVD (option) • Full D1 recording and playback • H.264 Hardware Compression • Digital zoom x 8 • On Board VGA • With free bundled CMS • 3GPP, PDA, Smart phone Blackberry, HTC, iPhone support • 2 USB port • RS485 support • Audio Input & output 	<p>Features</p> <ul style="list-style-type: none"> • 4 / 8 channels Full D1 720x480 Display • Full D1 recording and playback • H.264 Hardware Compression • Digital zoom x 8 • On Board VGA • With free bundled CMS • 3GPP, PDA, Smart phone Blackberry, HTC, iPhone support • 2 USB port • RS485 support • 1 Audio Input & output • VGA & BNC output 	<p>Features</p> <ul style="list-style-type: none"> • 4/8 channels Full D1 720x480 Display • Full D1 recording and playback • H.264 Hardware Compression • Digital zoom x 8 • On Board VGA • With free bundled CMS • 3GPP, PDA, Smart phone Blackberry, HTC, iPhone support • 2 USB port • RS485 support • 1 Audio Input & output 	<p>Features</p> <ul style="list-style-type: none"> • One HD (1280x720P) analogue camera and Eight D1 (720x480) analogue cameras supported • High Definition Picture Quality • HD Multiplexer • Auto Switching for 4:3, 16:9 Screen Aspect Ratio • True D1 Real-Time Triple Streaming for Live display, Playback and Recording • Intelligent Video Surveillance (IVS) features Supported with CMS • Tampering (Screen Changes for Lost Signal, Redirection, Lost Focus) • Region of Interest (Tripwire, People Counting, Missing and Unattended object) • CMS Supported (Support Matrix Display and E-Map) • MAC System Support • Extra Excellent Features • Touch-Panel LCD Monitor Supported • Video looping and Auto input Supported • 3G Mobile System Supported 	<p>Features</p> <ul style="list-style-type: none"> • Touch Screen display integrated with LCD • NTSC/PAL auto detect • Supports up to 1280 x 1024 SXGA high resolution • High contrast ratio up to 1000:1 • 4CH or 8CH DVR with H.264 Video compression • Provide Graphical User Interface (GUI) and mouse/touch screen for easier and user friendly configuration and operation. • Supports smart search function for faster and easier playback retrieval • Picture-in-picture display & channel screen popup on monitor/sensor • Role-based multiple network users access to exclusive channel view & Operation

Products


CMS SOFTWARE FOR SR SERIES DVR



DVR View (Max. 16 Channels)



Remote Event play




E-Map



Remote Playback



Event



User Management & Multiple Language



Group View (Max. 64 Channels)

DVR GUI



System Set Up



Network Set Up



MENU



PTZ & RS-485 Set Up



Sensor Set Up



Utility Set Up



EVENT Set Up



Record Set Up



Motion Set Up



Schedule Setup





Access Control System

<p>FR-310</p>  <p>Proximity Standard Wiegand Reader</p>	<p>FR-310 K</p>  <p>Proximity Standard Wiegand Reader with keypad</p>	<p>FC-4852C</p>  <p>RS-485 to RS-232 Converter</p>	<p>FC-4120C</p>  <p>TCP/IP Converter</p>
<p>Features A proximity sub-reader complying with the 26 bits Wieg and format of the international standards. A bicolor (green/red) LED and a beeper offer feedback to users</p>	<p>Features A proximity sub-reader complying with the 26 bits Wieg and format of the international standards. A bicolor (green/red) LED and a beeper offer feedback to users</p>	<p>Features</p> <ul style="list-style-type: none"> This communication converter is special for online access control devices and computer time recorder to form a network configuration. The communication baud rate such as 19200, 9600, 4800, 2400, 1200, 600, 300, 150 BPS can be selected through the DIP Switch. Please reset the device (power off and on again) after new rate selected. The maximums connecting access control reader up to 64 units for one of FC-4852C, which divided to two RS485 data bus. 	<p>Features</p> <ul style="list-style-type: none"> Make your serial devices Internet ready Versatile socket operation modes, including TCP & REAL COM Easy-to-use Windows Utility for mass installation Cigarette pack size 50bps~ 230.4K bps Ethernet 2 wire RS-485 with patented Automatic Data Direction
<p>FR-0312</p>  <p>Relay I/O board, 2DI/3DO (2DI-Door sensor, push button) (3DO-Strike,alarm,-option one)</p>			


Cards

<p>FSD-1000</p>  <p>Thin Card, 125KHZ, EM Format</p>	<p>FSD-1000-K</p>  <p>EM Format With Key Chain</p>	<p>FSD-2000-K</p>  <p>Mifare Format With Key Chain</p>	<p>FSD-1000RD</p>  <p>Thick Card, 125KHZ, EM Format (Read Only) (Continuative Number)</p>
<p>FSD-2000</p>  <p>Mifare Iso Card</p>	<p>FT-160</p>  <p>Series Electronic Strike</p>	<p>FEB-250</p>  <p>Electronic Bolt Lock</p>	<p>FSD-3000</p>  <p>HID Isoprox II ISO Card</p>
<p>FML-300</p> <p>Magnetic Lock Wiring Instruction Voltage : 12/24VDC Size : 130x8x32mm Weight 0.9 kgs</p> 		<p>FML-600</p> <p>Magnetic Lock Wiring Instruction Voltage : 12/24VDC Size : 232x48x25mm Weight 1.5 kgs</p> 	
<p>FSD-3300</p>  <p>HID Clamshell Card (26BIT)</p>			

Access Control System

FA-1038	FA-2030	FA-2038	FA-9099
			
All-in-One Stand-Alone Access Control System (Control Relay Built-in)	Stand Alone Access Control System	Stand Alone Access Control System	Stand Alone Network Access Control System
Features <ul style="list-style-type: none"> Proximity Stand-Alone control System with built-in Relay NC/NO Proximity Stand-Alone control System with built-in Relay NC/NO Proximity type reader, read range up to 10 cm Memory capacity store upto 1,000 user cards Anti-duress function available Access mode selectable reading proximity card data + personal password or main password Key in card data Force alarm function Arm or disarm connected security system Alarm activated when wrong password being input more than five times FA-1038E (EM), FA-1038-H (HID), FA-1038-M (MIFARE) 	Features <ul style="list-style-type: none"> Proximity type reader, read range upto 7cm Memory capacity store up to 5000 user records Large LCD display Access mode selectable Anti - duress function available Arm or disarm connected security system Patrol function available Security function available User card can be registered / deleted in batch mode Last ten history records available Audible key tone for easy operate Strike , alarm and duress relay drive time selectable (1 - 255 seconds) Door left open time selectable (1-255 seconds) Two - piece enclosure design the reader is patted for weather and hazard proofing A separate relay module design, high security provided FA-2030E (EM), FA-2030-H (HID), FA-2030-M (MIFARE) 	Features <ul style="list-style-type: none"> Proximity type reader, read range upto 7cm Reader is potted for water and dust proofing, makes it a popular choice for both indoor and outdoor installation Two - piece enclosure design the reader is patted for weather and hazard proofing Memory capacity store upto 1,000 user cards Master code function Main code function Security password function Force alarm function Key beeper sound selectable Drive time of electric lock and alarm relays programmable (1~99 seconds) Drive relay board separated from controller, module design, higher safety index Anti-duress function available Arm or disarm connected security system FA-2038E (EM), FA-2038-H (HID), FA-2038-M (MIFARE) 	Features <ul style="list-style-type: none"> Proximity type reader, read range upto 10cm 9000 card holders/ 9500 transactions Network configuration up to 99 devices or 320 devices Antipass back Access mode available Door left open alarm function Force entry alarm Temporary suspend all function Password time zone restraint Ten access time zone restrain Twelve months holiday restraint Communication interface: RS232 - RS485 and TCP/IP available Can be used as stand alone device without personal computer connected Eight groups personal password time zone programmable pre-define time Device model and version number can be displayed Up to 2 months battery back-up capacity for data storage during power failure With power saver function , the back light of LED turn off once no there is operation within 3 minutes Communication baud rate can be programmed via keypad Four error message available (all records are stored in controlled software) <ol style="list-style-type: none"> Invalid card Restricted Time Time zone Unmatched Code Unmatched FA-9099-E (EM), FA-9099-H (HID), FA-9099-M (MIFARE)

FEC-6016/6032 Lift Control System



Features

- Elevator Controller (16/32 floors)
- Relay Contact NO/NC type selectable
- Relay dry contact by pass mode auto and manual operation selectable
- Suitable for FA-9099 (EE, HE, ME)






Diagram showing a central FC-4120C controller connected to multiple sets of FA-9099 readers and FE-6016/FEC-6032 units, which are then connected to elevators. A note indicates 'Max. 40 sets'.


Total Solution-CCTV, IP, Access Control+Capture Cards



CP-3004M / CP-3004H



CP-3008M / CP-3008H



CP-3016M / CP-3016H




Diagram illustrating a comprehensive security solution. It includes a central recording server connected to various components:

- Cameras:** FINE Analogue Cameras, TCP-HPC960WI IP cameras.
- Monitoring:** Four Monitor setup for Live, Playback, Second Live, and VCD.
- Access Control:** FC-4120 controller, FA9099 readers, FP1506 access control units.
- Storage:** External I/O Device (Max. 16 in or 16 out), SCSI-390U4B (Max.2pcs), Level 0, 1, 0+1, 5 Disk Rcds (Max.2pcs).
- Integration:** Alarm In/Out, Access Control, and integration with CMS, Remote I.E. Browser, Remote AP Software, PDA, and Smart Phone.

Features

- CP-3004M, CP-3008M, CP-3016M
- Support 32CH CIF real-time recording
- H.264 H/W Compression
- Support up to 32 channels
- Support megapixel IP camera
- Triple monitor display
- Support Joystick
- E-map
- Unique GUI recording schedule
- Digital PTZ and multi-view
- Smart detection of 6 events with 10 instant responses
- Counting application
- Intelligent playback system with 5 video analytics searches
- POS and I/O device integration
- Remote live viewer, remote playback, remote backup, remote I/O control and remote desktop configuration
- Supported by Central Management System
- Supports 30 brands of IP cameras and more than 520 models
- Hybrid function (option)

Features

- CP-3004H, CP-3008H, CP-3016H
- Support 32CH D1 real-time recording
- H.264 H/W Compression
- Support up to 32 channels
- Support megapixel IP camera
- Triple monitor display
- Support Joystick
- E-map
- Unique GUI recording schedule
- Digital PTZ and multi-view
- Smart detection of 6 events with 10 instant responses
- Counting application
- Intelligent playback system with 5 video analytics searches
- POS and I/O device integration
- Remote live viewer, remote playback, remote backup, remote I/O control and remote desktop configuration
- Supported by Central Management System
- Supports 30 brands of IP cameras and more than 520 models
- Hybrid function (option)

IP Cameras

IR IP High Speed Dome SP-PTIR737	Eagle Series (Indoor, Outdoor Type) IP Speed Dome WDR, D/N, 540 TVL H.264 EP-Q2036HW-IP, EP-Q2026HW-IP, EP-Q2018HW-IP	H.264 Megapixel IP Camera TCP-MH802WI, TCP-MH802DN/WI TCP-MH802, TCP-MH802DN	H.264 Megapixel IP Vandal Dome CDV-3VM501
			
Features <ul style="list-style-type: none"> H.264/JPEG / MPEG4 Compression Wide Dynamic Range Unique Design, all in one Integrated Hi-Speed Dome Integrated with High Quality IR Leds, 100M normal distance, maximum distance 200M with Laser Powerful Mechanism Structure with shocking resistance 3 Level Lighting Protection IP 65 rated housing 	Features <ul style="list-style-type: none"> H.264/JPEG/MPEG4 Compression Wide Dynamic Range Support 3GPP/PDA Service Day Night + ICR, more than 540 TV Lines of Horizontal Resolution Quick and easy to install in just a few seconds Auto running: allows the dome to return any preset, sequence, pattern, panning automatically after a period of time without getting signal 8 programmable zones 220 presets with editable time 24 privacy zones for EP-Q2036HW-IP, 8 privacy masking EP-Q2026HW-IP for EP-Q2018HW-IP Positioning accuracy up to 0.1 degree 4 auto scans with 355 degree scan range 	Features <ul style="list-style-type: none"> 720P@30 FPS 2.0 Megapixel H.264/ MJPEG/MPEG4 compression Video motion detection Support 2 Way Audio Support 3Gpp / PDA service Easy set up with UPnP support Expansion SD back up for data storage SDK for software integration provided Free Bundled Basic 36 Channel Recording Software Provided Support Maxi-Watch Professional IP software (option) Wireless (option) TCP-MH802WI TCP-MH802DN/WI 	Features <ul style="list-style-type: none"> 2.0 Megapixel 1/3" Micron Progressive Scan CMOS Megapixel Integrated 2.7*9 mm DC Iris lens True day & night with Mechanism IR Cut Filter IP 66 rated weatherproof housing Up to 1600x1200 resolution at 15 fps Video motion detection Dual streaming H.264 / MJPEG/ MPEG4 compression format Support 3GPP / PDA Service With SD Back up Free bundled 36 channel recording software SDK For Software Integration
H.264 Megapixel IR IP Camera TCP-VM501	Megapixel Network Camera GP-100CB, WGP-100-CB GE-100CB, WGE-100-CB	H.264 IP Camera TCP-HPC960, TCP- HPC960WI, TCP- HPCDN960, TCP- HPCDN960WI	H.264 IP Wide Dynamic Camera TCP-IPWD700DN/WI
			
Features <ul style="list-style-type: none"> 2.0 Megapixel 1600 x 1200 1/3" Progressive Scan CMOS Integrated 3.6*16 mm lens True day & night with Mechanism IR Cut Filter IP 66 rated weatherproof housing Up to 1600x1200 resolution at 15 fps Video motion detection DC12V or Power over Ethernet (IEEE802.3af) Triple streaming H.264 / JPEG / MPEG4 compression format Support 2 Way Audio Support cell phone / PDA / 3GPP Free bundled 36 channel recording software SDK For Software Integration Support Maxi-Watch Professional IP Software (option) 	Features <ul style="list-style-type: none"> Functional and smart design Multiple H.264 streams Built in microphone & speaker H.264 , MPEG4, and MJPEG triple code compression Resolution 1280 x 800 Easy & flexible installation PIR sensor and illumination LED Support Maxi-watch Professional IP Software (option) Free bundled 64 channel recording software 	Features <ul style="list-style-type: none"> High definition 540TV Lines with 1/3" Hi-Sensitivity technology Supreme day & night function with automatic ICR filter TCP-HPDN960U TCP-HPDN960WIU Auto IRIS control, auto white balance, back light compensation available Triple streaming H.264 / MPEG4 / JPEG compression Remote Surveillance through Internet or Intranet Event triggered picture can be sent via FTP or E-mail PPPoE or DDNS support Video motion detection Support 3GPP / PDA service Easy set up with UPnP support Two way audio integration Support Maxi-Watch Professional IP software (option). Free Bundle Basic 36 Channel Recording Software Provided SDK for software integration provided 	Features <ul style="list-style-type: none"> D-WDR system Next Generation 3D DNR Sens-Up function Support video out Power over Ethernet available H.264/ JPEG / MPEG4 compression SD card backup 2-way audio Support Cell Phone/PDA/3GPP Triple Streaming Wireless available SDK for Software Integration Free Bundled Basic 36 channel AP Client Software Provided Wireless (option) TCP-IPWD700 DN/WI
H.264 IP Vandal Dome Indoor/Outdoor CAMERA CDV-3VWD960	H.264 WDR IP Camera TCP-IRWH540P/N	H.264 IP Pan/Tilt Network Camera MD-D1612	H.264 One Channel Decoder / Encoder WB-H811, WB-H811W
			
Features <ul style="list-style-type: none"> D-WDR Support 3D DNR Sense up function Produce high quality video images with 560 TVL Unique design with weatherproof IP66 rated housing Compact vandal resistant construction Triple streaming H.264 / JPEG/ MPEG4 compression Suitable for indoor & outdoor use with roof dome cover Support 3GPP / PDA service Easy set up with UPnP support DSP controls for BLC, white balance and gain control Burglarproof screw Support Maxi-Watch Professional IP software (option). Free Bundle Basic 36 Channel Recording Software Provided SDK for software integration provided 	Features <ul style="list-style-type: none"> D-WDR Support 3D DNR IP66 Sens-Up Function External Vari-focal lens adjustment True Day/Night Function Mechanism IR Cut Filter available IR Distance: 20 Meter H.264/MJPEG/MPEG4 compression Support cell phone/PDA/3GPP Triple streaming SDK for software integration Free Bundle 36 Channel Recording Software 8 Step shutter Adjustment Free bundled basic 36 Channel recording software provided Support Maxi-Watch Professional IP software (option). 	Features <ul style="list-style-type: none"> Remote Pan 270° Tilt 120° H.264/ MJPEG/MPEG4 compression Day/Night Function- IR Cut Filter(ICR) Power over Ethernet available Support SD card 2-Way Audio Triple Streaming Support Cell Phone/PDA/3GPP SDK for Software Integration Free bundled 36 channel recording software Support Maxi-Watch Professional IP software (option) 	Features <ul style="list-style-type: none"> H.264 Compression 1 Channel Input With SD Back Up for Data Storage Support 3Gpp Service 3 Streaming H.264/JPEG/MPEG4 (3Gpp) Compression Built in Power Over Ethernet Wired/Wireless available Free bundled 36 channel recording software SDK For Software Integration

4/8/16 Channel NAS Mini Linux NVR

NAS-E1040, NAS-E1080 / NAS-E1016



Features


- Linux Embedded – Free from PC crash and virus attack
- Server-Client Architecture
- Web-based management (Recommend on IE7 or above)
- Easy installation
- Manage 2 / 4 / 8 / 16 IP cameras
- Online GUI recording schedule
- RAID 0,1,5,5+spare and 10, prevention of data loss
- Support 25 brands of IP cameras and 735 models
- Support ImmerVision lens
- Support Megapixel camera and H.264 compression format
- Support D1, real-time and audio recording
- Up to 128 channels live display on multiple monitors
- Multiple camera streams to display in LiveView
- Support E-map with device indicator
- Playback system with 5 intelligent search
- Support Point of Sale (POS)
- 2/4 SATA HDD bays Embedded
- External storage – Up to 16TB total recording space
- Recording without PC turning on
- Remote I/O solution and camera I/O integration
- Supported by FINE CMS
- Supported by iPhone Security Eye apps

Model	NAS-E1040	NAS-E1080	NAS-E1016
Recording Cameras	1~4	1~8	1~16
Playback channels	4	8	16
Number of Drives	2xSATA II	4xSATA II	4xSATA II
Max Storage of Compatible HDD	2TB	2TB	2TB
RAID Level	RAID 0,1	RAID 0, 1, 5, 10	RAID 0, 1, 5, 10
I/O Interface	1xUSB 2.0 (for UPS)	2xUSB 2.0 (for UPS); 1xeSATA (for external storage2: DAS)	2xUSB 2.0 (for UPS); 1xeSATA (for external storage3: DAS)
LAN Transmission Speed	10/100/1000 Mbps (RJ45)		
Voltage	100-240V	100-230V	100-230V
Power Consumption	39W	72W	72W
Device Dimension	92.0 x 145.2 x 213.2 mm	188.2 x 152.5 x 229.6 mm	188.2 x 152.5 x 229.6 mm
Device Weight (without drive)	1.0 kg (2.2lbs)	2.5 kg (5.5lbs)	2.5 kg (5.5lbs)
Temperature	Operating: 5°C to 35°C (±5°C)		
Humidity	Operating: 10%-85%		
Supported IP Camera Brand(s): 25 brands	FINE, Axis, Panasonic, SONY, Vivotek, Acti, Arecont Vision, SANYO, Basler, Brickcom, CISCO, CNB, DLINK, ENEO, Hikvision, IQinVision, Levelone, Linksys, Lumenera, Mobotix, Samsung, SANTEC, StarDot, Toshiba, Videosec, ZAVIO		
Compression Format	MPEG4, M-JPEG, H.264, MxPEG (depends on IP camera)		
Recording Performance	Around 60fps at 1.3M Total bitrate: 20Mbps	Around 160fps at 1.3M Total bitrate: 65 / 55Mbps	Around 160fps at 1.3M Total bitrate: 65 / 55Mbps
Recording Type	Continuous record, Record by schedule, Event trigger record, Digital input trigger record		
Remote Live View Control	Liveview, PTZ control, Patrol/Focus, Preset set/go, Auto Scan, Snapshot		
Audio & Video Recording	Audio and video recording in synchronization		
POS	Liveview, record and search for every transaction		
Auto Backup	Automatically backup the recorded video of the date before to FTP server		
Intelligent Search	General motion, Missing object, Foreign object, Lose focus, Camera occlusion		
Remote Live View Connection	Live view maximum 16 connections at the same time		
Supported Language	English, Japanese, Traditional Chinese, Spanish, Deutsch, French, Italian, Russian, Czech, Korean, Polish, Dutch, Swedish, Portuguese (Brazil)		
System Minimum Requirement			
OS	Windows XP / 2003 / Vista / Win7		
CPU	Intel Core 2 Duo, 2.6GHz		
RAM	1GB		
LAN Transmission Speed	10/100/1000 Mbps (RJ45)		
UI	1. Web browser: Internet Explorer 7 or 8 2. Client Application Program 3. Security Eye Apps		

Specifications are subjected to change without prior notice.

Products

Maxiwatch Professional IP Software



Live



Playback



I.E




Remote Software

Features

- Support megapixel IP camera
- Support H.264 compression format
- Triple monitor display
- Support Joystick
- E-map
- Unique GUI recording schedule
- Digital PTZ and multi-view
- Smart detection of 6 events with 10 instant responses
- Counting application
- Intelligent playback system with 5 video analytics searches
- POS and I/O device integration
- Remote live viewer, remote playback, remote backup, remote I/O control and remote desktop configuration
- Supported by Central Management System
- Supports 36 brands of IP cameras and more than 560 models
- Supports 25 languages

Maxiwatch Professional Video Smart Intelligence



General Motion

Help users to monitor motions and can pinpoints subjects in defined area that detected intruders and trigger alarm



Camera Occlusion

Automatically detects if unidentified personal block cameras lens in an area to deter any vandalism, and alarms activated when any of the cameras is blocked



Missing Object

When an objects has been removed, missing from a detected zone, it will detects and identified to prevent Crime



Foreign Object

It can detects objects such as unidentified suitcase, Baggage appeared in area to help security people to take actions on potentially threat and damages



Lose Focus

When camera has been tore down, blurred pictures occurred for long period, it will show focus lose in the camera channel to alarm the user



Signal Lost

Automatically detects poor signals or signals lost from camera operation under surveillance to create seamless monitoring environment for best management



Counting Application


It can mark up two areas and count objects from in and out direction to monitor flow of movement in detected zone.



Multiple IP Brands Support

Central Management System (CMS)

Software Block Diagram



Features

- Authentic client-server architecture
- Centralized management
- Supports all recording servers (NDVR, NVR, DVR and NAS NVR)
- Supports unlimited cameras, I/O devices and POS
- Supports unlimited display matrices for remote live view with PTZ and joystick control
- Supports unlimited layers of E-map
- Supports H.264, MPEG4, MJPEG, and MxPeg video compressions
- Supports IP cameras, megapixel cameras and video servers
- Device groups
- Advanced GUI alarm management
- Alarm status, data mining and reporting function
- Instant playback
- Remote backup
- Embedded remote desktop access to any servers (NDVR, NVR, DVR and NAS NVR)



Manage all NVR / NDVR and supported IP camera/video server



Up to 64 concurrent live camera viewing for each video matrix



Intuitive EMap GUI to indicate all the alarms



Remote desktop and configuration to manage remote server



Display mode with E-Map support Navigation design for zoom in/out




Alarm Live Video Pop up notification



Remote Playback Window




Remote Back up Recorded Video



Low Disk Space, Disconnect Servers, Unusual System Health Alarm



Remote PTZ control



Advanced Alarm Search