

AT-S63 Version 3.0.0

Management Software for the

AT-9400 Basic Layer 3 Gigabit Ethernet Switches

Software Release Notes

Please read this document before you begin to use the management software.

Supported Platforms

AT-S63 Version 3.0.0 Management Software is supported on the following AT-9400 Gigabit Ethernet Switches:

Basic Layer 3 Models	AT-9424Ts (AC)
	AT-9424Ts/XP (AC)
	AT-9448T/SP (AC)
	AT-9448Ts/XP (AC)

This version is not supported on the following AT-9400 Switches:

Layer 2+ Models	AT-9408LC/SP (AC)
	AT-9424T/GB (AC)
	AT-9424T/SP (AC)
	AT-9424T/GB-80 (DC)
	AT-9424T/SP-80 (DC)

For information on the availability of future releases of the management software for the Layer 2+ switches, contact your Allied Telesis sales representative.

This release supports the following redundant power supply on the AC models:

- AT-RPS3204

For a list of supported GBIC, SFP, and XFP modules, contact your Allied Telesis sales representative.

Caution:

The software described in the documentation contains certain cryptographic functionality and its export is restricted by U.S. law. As of this writing, it has been submitted for review as a "retail encryption item" in accordance with the Export Administration Regulations, 15 C.F.R. Part 730-772, promulgated by the U.S. Department of Commerce, and conditionally may be exported in accordance with the pertinent terms of License Exception ENC (described in 15 C.F.R. Part 740.17). In no case may it be exported to Cuba, Iran, Iraq, Libya, North Korea, Sudan, or Syria. If you wish to transfer this software outside the United States or Canada, please contact your local Allied Telesis sales representative for current information on this product's export status.

Product Documentation

Refer to the Allied Telesis web site at www.alliedtelesis.com for the latest installation and user guides:

Switch Models and Management Software Versions

The following table provides the version number of the management software where each switch model was initially supported. You can refer to the table to determine whether a version of the management software supports a particular model in the event you load an older version onto a unit. For example, support for the AT-9424Ts switch, the newest model in the series, was introduced in version 2.1.1. Any attempt to load an earlier version of the software onto that model will be unsuccessful.

Model	AT-S63 Management Software Version
AT-9424T/GB	1.0.0
AT-9424T/SP	1.0.0
AT-9408LC/SP	1.1.0
AT-9448Ts/XP	1.3.0
AT-9448T/SP	2.0.0
AT-9424Ts/XP	2.0.0
AT-9424Ts	2.1.1

What's New in Version 3.0.0

- Stacking
- Virtual Router Redundancy Protocol (VRRP)
- Ethernet Protection Switching Ring (EPSR) snooping
- Internet Protocol version 4 packet routing enhancements:
 - Auto-summarization of routes
 - Split horizon with poison reverse
 - DHCP/BOOTP relay
- 802.1x port-based network access control. Added the following authentication methods:
 - EAP-TLS (Extensible Authentication Protocol - Transport Layer Security)
 - EAP-TTLS (Extensible Authentication Protocol - Tunneled Transport Layer Security)
 - PEAP (Protected Extensible Authentication Protocol)

Stacking

All the models in the AT-9400 Gigabit Ethernet Switch Series can be installed as stand-alone devices. But three of the models also support stacking. Built with the AT-StackXG Stacking Module and its two 12-Gbps ports, a stack merges and synchronizes the network operations of two or more AT-9400 Switches to form a single, logical unit in which network functions, such as spanning tree protocols, virtual LANs, and static port trunks, can span all the Gigabit Ethernet ports of the devices.

Supported Models

Stacking is supported on the following AT-9400 Switches:

- AT-9424Ts
- AT-9424Ts/XP
- AT-9448Ts/XP

Supported Features with Stacking

Supported features include:

- Basic port configuration (e.g., speed, duplex mode, Auto-Negotiation, etc.)
- Port statistics
- Static port trunks
- Port mirroring
- Event logs
- Syslog client
- Spanning Tree Protocol
- Rapid Spanning Tree Protocol
- Port-based and tagged virtual LANs
- One Internet Protocol (IP) version 4 routing interface*
- Telnet server

(* Used to assign an IP address to the stack.)

Note:

Because of the limited number of supported features, stacking might not be suitable for all network environments. To utilize all the features of the AT-9400 Switches, install the units as stand-alone devices.

Known Issues Related to Stacking

- Switches of a stack. This version of the management software does not support stacks of both 48-port switches (i.e., AT-9448Ts/XP) and 24-port switches (AT-9424Ts and AT-9424Ts/XP).
- SHOW SWITCH FDB command. Do not use the SHOW SWITCH FDB command. The command, used for viewing the MAC addresses in the MAC address table, can take several minutes to complete and might not display all the addresses in the table. (5231, 5398)

- ❑ Default values. If you return the parameter settings to the default values using the RESTART SWITCH command on a stack that has static ID numbers, be sure to issue the SAVE CONFIGURATION command after the stack has reset. Otherwise, in some situations the previous parameter settings might be reapplied to the stack.
- ❑ Remote management functions. Remote management transactions, such as Telnet management sessions and TCP/IP pings, must be conducted through ports on the master switch of a stack. They cannot be conducted through ports on a member switch. (5403)

Known Issues

- ❑ MAC address-based authentication in 802.1x port-based network access control. The MAC address-based method of authentication in 802.1x port-based network access control is nonfunctional. Authentication must be established using the 802.1x username and password method. (5425)
- ❑ Routing Information Protocol (RIP) on the AT-9448Ts/XP Switch. The performance of RIP on the AT-9448Ts/XP Switch might not be predictable. The switch does not always update its routing table in response to routes received from other units and may lose routes. (5422)
- ❑ Multiple supplicants and 802.1x port-based network access control. The multiple operating mode of an authenticator port in 802.1x port-based network access control is nonfunctional. The switch authenticates only the first supplicant and denies entry to all subsequent supplicants. For authenticator ports with multiple supplicants, use the single operating mode and activate the piggy-back feature. (5431)
- ❑ Limited security mode in MAC address-based port security. The limited security mode in MAC address-based port security is nonfunctional. Do not use this security mode. (5327)
- ❑ Class of Service (CoS) priority override. The priority override feature, used to apply a temporary CoS priority value to the tagged and untagged ingress traffic on a port, is nonfunctional. Assigning a priority value to a port has no effect. (5492)
- ❑ Compact flash memory card slot. This version of the AT-S63 Management Software does not support the compact flash memory card slot in the AT-9424Ts, AT-9424Ts/XP, and AT-9448Ts/XP switches. (5509)
- ❑ MAC address-based virtual LANs. This version does not support MAC address-based virtual LANs. (5384, 5387)
- ❑ Unknown unicast rate limiting. Unknown unicast rate limiting has been changed at the driver level to accommodate stacking and can no longer be disabled. At the default setting, the rate limit for unknown unicast packets for each port is 25 packets per second. This should not be changed when a switch is part of a stack. If you are operating the switch as a stand-alone device and want to increase rate limiting for unknown unicast packets on all the ports, issue this command:


```
set switch port=all unkucastratelimiting=yes unkucastrate=value
```

 The *value* parameter has a range of 0 to 262,143 packets per second.
 Since this change was made at the driver level, the SHOW SWITCH PORT command will not display the correct status of unknown unicast rate limiting on the ports of a switch at the default setting. It will show the feature as disabled, when in fact it is enabled.
- ❑ Enhanced stacking. To be a slave switch of an enhanced stack the AT-9400 Switch must have a routing interface on the common VLAN that interconnects the switches of the stack, and the interface must be designated as the local interface. This applies even when the Default_VLAN is used as the common VLAN of the switches.

Resolved Issues

- ❑ LACP trunks. There was a delay of upwards of thirty seconds before the switch would resume forwarding traffic over reestablished links on active ports in an LACP trunk. This issue has been resolved. (4514)
- ❑ 802.1x "control direction" feature. The "control direction" feature of 802.1x port-based network access control was nonfunctional for IGMP multicast packets when IGMP snooping was enabled on the switch. This issue has been resolved. (4206)
- ❑ Static port trunks and dynamic LACP port trunks. The switch allowed you to create more than the maximum number of six static and dynamic port trunks. This issue has been resolved. An error message is displayed if you exceed the maximum number of port trunks. (4630)
- ❑ Guest VLAN. The Guest VLAN feature of 802.1x port-based network access control was nonfunctional. This issue has been resolved. (4641)
- ❑ Switch's MAC address and IP multicast packets. The switch would stop forwarding network traffic if it received an IP multicast packet that had the switch's MAC address as the destination address and a TCP header in the payload. This issue has been resolved. (4722)

Operational Notes

- ❑ Maximum bandwidth parameter in QoS policies. A QoS policy that has multiple traffic classes with different values for the maximum bandwidth parameter uses the lowest specified maximum bandwidth value for traffic flows that match more than one traffic class. (4137)
- ❑ VLAN ingress filtering. Untagged packets on the AT-9424Ts and AT-9424Ts/XP Switches may periodically cross VLAN boundaries and be retransmitted as tagged packets when the VLAN ingress filtering feature for tagged packets is disabled. (4455)
- ❑ LACP aggregators. The ports of an LACP trunk must be untagged members of the same VLAN. The management software does not always display an error message if you violate this rule while modifying port-based and tagged VLANs on the switch. For example, the management software will not display an error message if you move a port that is part of an LACP trunk to a different VLAN or if you change the port's status from untagged to tagged. (4585)
- ❑ Web server. The default setting for the web server on the switch has been changed from enabled to disabled. To use a web browser to manage the switch, you must first enable the server with the ENABLE HTTP SERVER command.
- ❑ Classifier criteria on AT-9424Ts and AT-9424Ts/XP switches. Access control lists and Quality of Service policies on these switches cannot filter on the following combinations of classifier criteria:
 - VLAN ID with source or destination IP address.
 - Protocol with source or destination IP address
 This rule applies whether the criteria are in the same classifier or in different classifiers applied to the same access control list or Quality of Service policy.
- ❑ Spanning tree and LACP trunks. A spanning tree protocol on a switch with two or more LACP trunks uses the trunk ID number to select a trunk to place in the blocking state if the trunks form a network loop. The trunk ID number is automatically assigned by the management software when an aggregator is created, starting with 0 (zero) and incremented by 1 with each new aggregator. The lower the trunk ID number, the higher the priority. For instance, if a

switch has two LACP trunks, a spanning tree protocol will block the ports of the trunk with the higher ID number (lower priority) should it determine that the trunks form a loop. (4261)

- ❑ Denial of Service defense mechanisms. The operation of a Denial or Service defense mechanism on the switch might be unpredictable when a defense is assigned to more than one port or when more than one defense is assigned to the same port. This issue can be avoided by not assigning a defense mechanism to more than one port or more than one defense mechanism to a port. This issue is limited to the AT-9424Ts and AT-9424Ts/XP switches. (4196)
- ❑ QoS policies and unicast and multicast addresses. The filtering properties of a QoS policy are designed for known unicast addresses. The behavior of a policy may be unpredictable if it filters on unknown unicast addresses or known or unknown multicast addresses. (3196)
- ❑ Enhanced stacking and slave switches. The AT-S63 Version 2.0.0 Management Software User Guides incorrectly state that slave switches in an enhanced stack do not need a routing interface on the common VLAN that interconnects them with the master switch. Actually, a routing interface is required in the common VLAN of a slave switch, but it does not have to be designated as the local interface, except on the master switch. The only exception to this rule is if you use the Default_VLAN (VID 1) as the common VLAN, in which case the common VLAN on a slave switch does not need a routing interface. (4517)
- ❑ Lowest numbered port in an LACP aggregator. You cannot delete the lowest numbered port from an LACP aggregator, referred to as the base port, or add a port to an aggregator that is below the base port. The OperKey parameter for the ports in an aggregator is based on the lowest numbered port and cannot be changed after the aggregator is created. For example, if you create an aggregator of ports 10 to 15 on a switch, you cannot later delete port 10 from the aggregator or add a port less than port 10. You must recreate the aggregator if you need to change the base port. (4369)
- ❑ Saving a configuration. The management software on the switch may experience a problem if you save configuration changes in rapid succession. To avoid this issue, you should wait for the Fault LED on the front panel of the switch to go off after you save a configuration change and before you save another configuration change. If you are in a different location from the switch and cannot view the Fault LED, you should wait 30 to 45 seconds between your save commands. (2683)
- ❑ Multiple VLAN modes and IPv4 packet routing. The 802.1Q-compliant and non-802.1Q-compliant multiple VLAN modes do not support IPv4 packet routing. You cannot configure routing interfaces when the switch is running in either of these VLAN modes, and all existing routing interfaces, with the exception of the local interface, are deleted when one of these VLAN modes is activated. To assign an IP address to a switch running one of these VLAN modes, you must create one routing interface and designate it as the local interface while the switch is running in the user-configured VLAN mode, and afterwards change the switch's VLAN mode to 802.1Q-compliant or non-802.1Q-compliant. The local interface is automatically moved to the VLAN on port 1 of the switch. (3806)
- ❑ Switch to switch upload of a configuration file. The *AT-S63 Management Software User Guides* state that the routing interface commands in the configuration file on a master switch are retained when the file is uploaded to a slave switch. This is incorrect when the file being uploaded is the master switch's active configuration file. To prevent an IP address conflict on the units, all routing interface commands are removed from the active configuration file during the transfer. However, uploading any other configuration file from a master switch to a slave switch retains the routing interface definitions in the file. (4272)

- ❑ Telnet management session. Changing the VLAN mode of a switch (e.g., from the user-configured VLAN mode to a multiple VLAN mode) from a remote Telnet management session may end your management session. To continue managing the switch, you must reestablish the management session (3806)
- ❑ SNMPv3 management. The enhanced stacking feature is not supported from SNMPv3. (4065)
- ❑ AtiStkSwVlanConfigEntry MIB table. The response time of the management firmware on the switch will be slow if you have more than one instance of the AtiStkSwVlanConfigEntry MIB table open at a time. (2231)
- ❑ Compact flash card. Removing a compact flash card from the switch while the management software is writing a file to it may cause the switch to stop responding to management commands and forwarding network packets. To avoid this issue, never remove a compact flash card from the switch while the Fault LED on the front panel is on. Wait for the Fault LED to turn off before removing the card.(4253)
- ❑ LACP priority value and the event log. A change to a switch's LACP priority value is registered in the event log with a message that reflects the current status of LACP, rather than the change to the priority value. The log message is either "lACP:enabled" or "lACP:disabled." (3345)
- ❑ MAC address-based VLANs and static trunks. The documentation states that the ports of a MAC address-based VLAN form a community and that the assignment of a MAC address to one port in a VLAN is equivalent to assigning it to all ports. This is true except in the case where the ports of a MAC address-based VLAN encompass a static port trunk, in which case the same MAC addresses must be assigned to all the ports in the trunk. (3249)
- ❑ File upload or download. The switch's response to management instructions may be slow while it uploads or downloads a file to the file system.
- ❑ Flow control and back pressure. Flow control and back pressure are operational *among* devices connected to ports 1 through 12 or ports 13 through 24 on the AT-9424T/GB and AT-9424T/SP switches, but not *between* devices connected to ports 1 through 12 and 13 through 24. (1321, 1322)
- ❑ Reserved multicast traffic and port mirroring. The destination port of a port mirror may transmit duplicates of some reserved multicast traffic, such as STP BPDUs and other control packets. The duplication results from the destination mirror port transmitting both the reserved multicast traffic it receives from flooded multicast traffic and the same multicast traffic from the mirrored ports. (3055)
- ❑ Fiber optic port configuration display. The Auto-Negotiation, speed, and duplex mode settings in the menus interface for ports 23 and 24 on the AT-9424T/GB and AT-9424T/SP switches always reflect the settings of the corresponding twisted pair ports 23R and 24R. They do not reflect the current settings of an active GBIC or SFP fiber optic port. (3047)
- ❑ GVRP compatibility. There may be some compatibility issues with GVRP and other switches. To work around this issue, change the Join and Leave time from the defaults to: Join Timer = 60 and Leave Timer = 120.
- ❑ Port configuration. The speed, duplex mode, and MDI/MDIX settings of a 10/100/1000Base-T twisted pair port are changed as a unit when multiple ports are configured simultaneously. The settings of the lowest numbered port being configured are automatically copied to the other ports. For example, if you configure ports 1 to 4 simultaneously and change the MDI/MDIX setting, the speed and duplex mode settings of port 1, along with the new MDI/MDIX setting, are copied to ports 2 to 4. (1262)

- ❑ Static and LACP port trunks and load distribution methods. The following load distribution methods for static and LACP port trunks are nonfunctional: source IP address, destination IP address, and source/destination IP addresses. The switch uses source MAC address, destination MAC address, or source/destination MAC addresses, respectively, if a nonfunctional load distribution method is selected.
- ❑ Jumbo frames. Frame loss may occur when jumbo frames (1522 bytes or larger) are transferred to more than two ports. (1412, 2783, 2792)
- ❑ Xmodem downloads. The switch does not respond to echo requests or send or respond to STP BPDU packets during an Xmodem download of system software. Also, echo request responses are slowed when there is a TFTP transfer in progress and the echo requests are received within the same port group as the TFTP server. (1663, 1582)
- ❑ SFP and GBIC ports. The switch considers the fiber optic port on an optional SFP or GBIC module in the AT-9424T/GB and AT-9424T/SP switches as active even if the port is receiving a signal but has not established a valid link with the remote node. If an optional fiber optic port loses or is unable to establish a link but is receiving a signal, it remains as the active port and the switch does not activate the corresponding twisted pair port 23R or 24R. (2850)
- ❑ Web browser interface. The web browser interface works best with Microsoft Internet Explorer version 6.0 and above. Results using other versions or other web browser applications may vary.
- ❑ Configuration files. Do not use Microsoft NotePad to edit or view a configuration file. Some versions of NotePad may add formatting codes to the file. Use WordPad instead or some other text editor that will not add formatting codes to the file. When saving the file, do not change the “.cfg” extension in the filename or save the file with formatting codes.
- ❑ Enhanced stacking. The IP address 172.16.16.16 is reserved for the enhanced stacking feature. Do not assign this address to any device in the same subnet as an enhanced stack.
- ❑ Login password. The maximum length of a login password is 16 alphanumeric characters for manager accounts created through the RADIUS and TACACS+ authentication protocols and supplicant accounts for 802.1x port-based network access control. Passwords that exceed this limit will not work.
- ❑ TACACS+. The TACACS+ client software on the switch supports Password Protection Protocol (PAP), but not Challenge Handshake Authentication Protocol (CHAP) or AppleTalk Remote Access Protocol (ARAP). (1078)
- ❑ Port settings. A port, when removed from a port trunk, retains its settings as a member of the trunk. The parameter settings (e.g., speed and duplex mode) are not returned to the default values. (2144)
- ❑ MAC addresses. You must move the cursor manually from field to field when entering an IP or MAC address in the web browser interface. The cursor does not move automatically as you enter the parts of an address. (1699, 2123)
- ❑ SNTP. The SNTP client software on the switch sends a Transmit Time Stamp with a value NULL when synchronizing with a Network Time Protocol server. This does not affect the operation of the SNTP client software. (1676)
- ❑ IGMP. The switch, when configured for IGMP, will not register tagged IGMP queries in the IGMP routers list if ingress filtering is disabled. (1493)
- ❑ SFP modules and the AT-9408LC/SP switch. Be sure to disconnect the fiber optic cable from an SFP module in an AT-9408LC/SP switch before removing the module. The L/A LED for the slot may remain on if you remove an SFP module while it has a link to an end node. This

problem does not affect the operation of the switch or the SFP slot. The L/A LED goes off the next time you install an SFP module in the slot.

Features History

Version 2.2.0

No new features.

Version 2.1.1:

- ❑ The number of cooling fans in the AT-9424Ts switch was reduced from four to three. The AT-S63 Management Software was updated to reflect the change.

Version 2.1.0:

- ❑ Multiple IPv4 routes with Equal Cost Multi-path (ECMP). The switch now supports ECMP and multiple routes to the same remote destination.
- ❑ Variable length subnet masks for IPv4 routing. Previously, a byte in a subnet mask for a route in the IPv4 routing table had to be 0 or 255. The switch now accepts masks of variable length.
- ❑ Multiple default routes. In the previous version, there could be only one default route for the IPv4 packet routing feature and the route was not propagated by RIP. In this version, the routing table can store and propagate multiple static and dynamic default routes.
- ❑ 802.1x authenticator ports. The maximum number of supplicants that can be logged on to an authenticator port running in the multiple operating mode has been increased from 20 clients to 320 clients. However, the maximum number of logged on clients per switch remains the same at 480 clients. (4186)

Note:

The IPv4 routing feature is not supported on the AT-9408LC/SP, AT-9424T/GB, and AT-9424T/SP switches. These switches support only one routing interface to assign the device an IP address.

Version 2.0.0:

- ❑ Internet Protocol Version 4 (IPv4) packet routing. The AT-9400 Series switch features IPv4 packet routing with routing interfaces, static routes, and the Routing Information Protocol versions 1 and 2.
- ❑ Secure Shell (SSH) protocol server. The security of the SSH server on the switch has been enhanced to prevent unauthorized management access to the switch. The AT-S63 Management Software now disables the SSH server, logs an event in the event logs with the client's IP address, and sends an SNMP trap if it detects fifty consecutive failed login attempts from an SSH client.
- ❑ Class of Service and Queue 7. The range of the maximum number of transmitted packets for the CoS weighted round robin scheduling method has been changed for Queue 7 (Q7). The range was 1 to 15; the new range is 0 (zero) to 15. Setting Q7 to 0 gives its packets priority over packets in the other queues. No packets are transmitted from the lower priority queues so long as there are packets in Q7. (3803)
- ❑ Temperature threshold alert. The temperature threshold alert feature now has two levels. An ambient temperature of 55° to 60° Celsius for ten minutes activates the first level. The switch sends a SNMP trap and enters a warning event message in the event logs. The second level,

activated if the ambient temperature exceeds 60° Celsius for five minutes, sends another SNMP trap, logs an error event message, and activates the Fault LED on the front panel.

Version 1.3.0:

- ❑ Added the following new features to 802.1x port-based network access control:
 - Guest VLANs
 - VLAN Assignment and Secure VLAN features for supporting dynamic VLAN assignments with supplicant accounts.
 - MAC address-based authentication as an alternative to 802.1x username and password authentication.
- ❑ Simplified the menu interface for managing the access control entries in the Management ACL.

Version 1.2.0:

- ❑ MLD snooping for MLDv1 and MLDv2.
- ❑ 802.1x port-based network access control supports up to 20 supplicants simultaneously on an authenticator port.
- ❑ Quality of Service has the following new actions:
 - Set Type of Service (ToS)
 - Move Type of Service to 802.1p Priority
 - Move 802.1p Priority to Type of Service
 - Send to Mirror Port
- ❑ The command line interface has new command parameters for displaying and deleting specific types of MAC addresses from the MAC address table.

Version 1.1.0:

- ❑ LACP (802.3ad)
- ❑ Policy-based QoS (Classifiers, Flow Groups, Traffic Classes, and Policies)
- ❑ Flash memory operations
- ❑ Access Control Lists (ACLs)
- ❑ Syslog support
- ❑ Password reset
- ❑ Redundant power supply information
- ❑ IGMP v3 Snooping
- ❑ New web browser interface procedures

Version 1.0.0:

- ❑ Auto-Negotiation (IEEE 803.3u-compliant) for speed and duplex mode
- ❑ Auto and manual MDI/MDI-X
- ❑ Flow control (IEEE 802.3x and 802.3z-compliant)
- ❑ Head of line blocking prevention
- ❑ Unicast, multicast, and broadcast rate control
- ❑ Port mirroring

- Port trunking (IEEE 802.3ad) (static link aggregation, non LACP)
- Port security
- Port statistics (RMON)
- 1000 static MAC addresses, 16K dynamic MAC addresses, 256 static multicast addresses, 255 dynamic MAC addresses (snooping)
- Spanning Tree Protocol (IEEE 802.1D)
- Rapid Spanning Tree Protocol (IEEE 802.1w)
- Multiple Spanning Tree Protocol (IEEE 802.1s)
- Virtual LANs (IEEE 802.1Q)
- Protected ports VLANs
- Ingress filtering
- GARP VLAN Registration Protocol (GVRP)-based dynamic VLANs
- Secure Sockets Layer (SSL) Protocol (not included in AT-S63 NE)
- Secure Shell (SSH) Protocol (not included in AT-S63 NE)
- Public Key Infrastructure (PKI) Certificates (not included in AT-S63 NE)
- Static and dynamic system time (SNTP client)
- Management VLAN
- Multiple VLAN modes
- Event log
- Enhanced stacking (for management)
- IGMP Snooping (RFC 2236)
- Class of Service (IEEE 802.1p-compliant)
- Queuing - map 802.1p to CoS queue to prioritize traffic at egress
- Strict priority and weighted round robin priority scheduling
- RRP Snooping
- File system
- SNMPv1, SNMPv2c and SNMPv3 management
- CLI-based configuration file
- Denial of Service detection
- 802.1x Port-based Network Access Control
- RADIUS accounting
- Menus, CLI, web, and SNMP interfaces
- Password protected management access
- Management access control list
- Local authentication
- RADIUS and TACACS+ authentication protocols
- Xmodem and TFTP downloads and uploads, HTTP and enhanced stacking
- Static IP configuration

- ❑ BOOTP and DHCP
- ❑ Fan and temperature information
- ❑ CPU, Flash, and RAM information
- ❑ Power supply, redundant power supply, and transceiver information

Contacting Allied Telesis

This section provides Allied Telesis contact information for technical support as well as sales or corporate information.

Online Support

You can request technical support online by accessing the Allied Telesis Knowledge Base: **www.alliedtelesis.com/support/kb.aspx**. You can use the Knowledge Base to submit questions to our technical support staff and review answers to previously asked questions.

Email and Telephone Support

For Technical Support via email or telephone, refer to the Support section of the Allied Telesis web site: **www.alliedtelesis.com**.

Returning Products

Products for return or repair must first be assigned a return materials authorization (RMA) number. A product sent to Allied Telesis without an RMA number will be returned to the sender at the sender's expense. For instructions on how to obtain an RMA number, go to the Support section on our web site at **www.alliedtelesis.com**.

For Sales or Corporate Information

You can contact Allied Telesis for sales or corporate information through our web site at **www.alliedtelesis.com**.

Obtaining Management Software Updates

New releases of management software for our managed products are available from the following Internet sites:

- Allied Telesis web site: **www.alliedtelesis.com**
- Allied Telesis FTP server: **<ftp://ftp.alliedtelesis.com>**

If the FTP server prompts you to log on, enter "anonymous" as the user name and your email address as the password.