



## HP Compaq 8100 Elite Small Form Factor Business PC



- 1 Rear I/O includes (6) USB 2.0 ports, serial port, PS/2 mouse and keyboard ports, RJ-45 network interface, DisplayPort and VGA video interfaces, and audio in/out jacks
- 2 Low profile expansion slots include (1) PCI slot, (1) PCI Express x1 slots and (2) PCI Express x16 graphics slot
- 3 Front I/O includes (4) USB 2.0 ports, dedicated headphone output, and a microphone/headphone jack
- 4 HP Optical Mouse
- 5 HP Keyboard
- 6 3.5" external drive bay supporting a media card reader or a secondary hard disk drive
- 7 5.25" external drive bay supporting an optical disk drive
- 8 3.5" internal drive bay supporting primary hard disk drive
- 9 240W standard or 89% high efficiency Power Supply
- 10 HP Monitor (sold separately)

## Overview

### HP Compaq 8100 Elite Convertible Minitower Business PC



- 1 (3) 5.25" external drive bays supporting optical disk drives, removable hard disk drives, or the HP Media Card Reader
- 2 320W standard or 89% high efficiency Power Supply
- 3 Rear I/O includes (6) USB 2.0 ports, serial port, PS/2 mouse and keyboard ports, RJ-45 network interface, DisplayPort and VGA video interfaces, and audio in/out jacks
- 4 Front I/O includes (4) USB 2.0 ports, dedicated headphone output, and a microphone/headphone jack
- 5 (3) 3.5" internal drive bays supporting multiple hard disk drives
- 6 Full height expansion slots include (3) full-length PCI slots, (1) PCI Express x1 slot, and (2) full-length PCI Express x16 graphics slots

**NOTE:** Second PCIe x16 slot has x4 connectivity.

- 7 HP Optical Mouse
- 8 HP Keyboard
- 9 HP Monitor (sold separately)

## Overview

### At A Glance

- Designed for long-term deployment within corporate, enterprise, public sector and mid-market commercial organizations
- Choice of two professional chassis form factors to accommodate any desired mix between expandability and size
- BIOS developed and engineered by HP for better security, manageability and software image stability
- Intel® Q57 Express chipset
- DDR3 Synchronous Dynamic Random Access Memory (SDRAM)
- Intel® Core Processors with vPro Technology (requires select processors)
- Supports industry standard management protocols including Intel Standard Manageability and DASH 1.1 (via optional Broadcom NIC card)
- Integrated dual independent monitor support via both a VGA and DisplayPort video interface
- Standard efficiency or 89% high efficiency energy saving power supplies available
- ENERGY STAR qualified models available (dependent upon the desired configuration)
- Models can be configured with multiple hard disk drives in a RAID array
- Guaranteed lengthy purchase lifecycles and image stability
- Software image fully compatible across all models and form factors
- Created using industry leading Design for Environment standards
- Selected configurations with global availability easily set up and ordered through HP.com Business to Business portals (<http://h10019.www1.hp.com/business-site/index.html>)
- Tailored HP Factory Express deployment and lifecycle services available (<http://h71028.www7.hp.com/enterprise/cache/97688-0-0-225-121.aspx>)
- Protected by HP Services, including standard warranties up to 5-5-5 (terms and conditions vary by country; certain restrictions and exclusions apply)
- Tool-less serviceability features for easier upgrades and repairs



Standard Features and Configurable Components (availability may vary by country)

## Operating Systems

Preinstalled	Genuine Windows Vista Business (32-bit) <sup>1</sup>
	Genuine Windows Vista Home Basic <sup>1</sup>
	Genuine Windows 7 Home Basic Edition (32-bit) <sup>2</sup>
	Genuine Windows 7 Home Premium Edition (32-bit or 64-bit) <sup>2</sup>
	Genuine Windows 7 Professional Edition (32-bit or 64-bit) <sup>2</sup>
	FreeDOS
Supported	Genuine Windows Vista Enterprise Edition <sup>1</sup>
	Genuine Windows 7 Enterprise Edition <sup>2</sup>
	Genuine Windows 7 Ultimate Edition <sup>2</sup>
Certified	Novell SUSE Linux Enterprise Desktop 11 <sup>3</sup>
	Red Hat Enterprise Linux 64 <sup>3</sup>

<sup>1</sup> Certain Windows Vista product features require advanced or additional hardware. See [www.microsoft.com/windowsvista/getready/hardwarereqs.mspx](http://www.microsoft.com/windowsvista/getready/hardwarereqs.mspx) and [www.microsoft.com/windowsvista/getready/capable.mspx](http://www.microsoft.com/windowsvista/getready/capable.mspx) for details. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: [www.windowsvista.com/upgradeadvisor](http://www.windowsvista.com/upgradeadvisor)

<sup>2</sup> System may require upgraded and/or separately purchased hardware and/or a DVD drive to install the Windows 7 software and take full advantage of Windows 7 functionality. See <http://www.microsoft.com/windows/windows-7/> for details.

<sup>3</sup> The following features are not supported on Linux certified systems:

- HP 22-in-1 media card reader
- Trusted Platform Module (TPM) 1.2 Security Chip
- Intel Pro 1000 CT GbE NIC
- Broadcom NetXtreme GbE Ethernet Plus NIC
- HP 802.11 b/g/n wireless NIC (SFF and MT)
- Intel WiFi Link 5100 a/b/g/n wireless NIC (USDT)
- LSI 56K Int'l SoftModem
- HP USB Smartcard keyboard
- HP Serial port adapter
- HP Parallel port adapter
- HP eSATA port adapter
- HP FireWire/IEEE 1394 I/O card



### Standard Features and Configurable Components (availability may vary by country)

#### Value Added Software (included with all models; not included when configured with FreeDOS)

HP ProtectTools Security Suite	HP Insight Diagnostics
HP Software Management Agent	PDF Complete
Computrace for Desktops agent (optional)	

#### Value Added Software (included with select models; not included when configured with FreeDOS)

Computer Setup Utility	HP Total Care Advisor
Antivirus software*	Microsoft Office 2010 preloaded (purchase of a Product Key required to activate a full Office 2010 suite)**
Roxio Creator Business	Firefox HP Virtual Browser
HP Power Manager	Corel WinDVD

\* May be Norton or McAfee antivirus software. First 60 days included. Subscription required for live updates thereafter. Internet access required.

\*\* Microsoft Office 2010 Preloaded includes reduced functionality versions of Word and Excel. Purchase of Product Key required to activate full Office 2010 suite available at participating resellers/retailers and <http://www.office.com>.

#### HP Client Management Solutions (available for free download from the Internet)

<http://www.hp.com/go/easydeploy>

HP Client Automation Starter*	HP Client Catalog for Microsoft SMS
HP SoftPaq Download Manager	HP Systems Software Manager

\* Available from your HP Sales Representative or HP Channel Partner

#### Value Added Services and Features

HP Stable Platform Program	Factory Express Deployment and Lifecycle Services
Intel Stable Platform Program	Intel Standard Manageability
Business-to-Business Portals	Intel Core 2 Processor with vPro Technology
HP Global Series Services	Trusted Platform Module (TPM) v1.2*

#### Service and Support

On-site warranty and service<sup>1</sup>: three year (3/3/3) limited warranty and service offering delivers three years of parts, labour and on-site repair. Response time is next business day<sup>2</sup> and includes free telephone support<sup>3</sup> 24 x 7. Global coverage<sup>2</sup> ensures any product purchased in one country and transferred to another non-restricted country will remain fully covered under the original warranty and service offering. Some countries/regions do not offer one year onsite and labour.

<sup>1</sup> Terms and conditions may vary by country. Certain restrictions and exclusions apply.

<sup>2</sup> On-site services may be provided pursuant to a service contract between HP and an authorized HP third party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.

<sup>3</sup> Technical telephone support applies only to HP configured, HP and HP qualified third party hardware and software. Toll-free calling and 24 x 7 support may not be available in some countries.

#### Chipset

Intel Q57 Express



Standard Features and Configurable Components (availability may vary by country)

## Processors

**NOTE:** all models configured with Intel® Core™ processors with 4 cores require a discrete graphics solution

### Intel Pentium Processors:

Intel Pentium G6950 Processor

2.80 GHz, 3M total cache

2 cores/2 threads

Integrated Intel® HD Graphics

### Intel Core i3 Processors:

Intel Core i3-530 Processor

2.93 GHz, 4M total cache

2 cores/4 threads

Integrated Intel® HD Graphics

Intel Core i3-540 Processor

3.06 GHz, 4M total cache

2 cores/4 threads

Integrated Intel® HD Graphics

Intel Core i3-550 Processor

3.20 GHz, 4M total cache

2 cores/4 threads

Integrated Intel® HD Graphics

Intel Core i3-560 Processor

3.33 GHz, 4M total cache

2 cores/4 threads

Integrated Intel® HD Graphics

### Intel Core i5 Processors:

Intel Core i5-650 Processor

3.2 GHz, 4M total cache

2 cores/4 threads

Integrated Intel® HD Graphics

Intel® Core™ processor with vPro™ technology

Intel® Stable Image Platform Program (SIPP)

Intel Core i5-660 Processor

3.33 GHz, 4M total cache

2 cores/4 threads

Integrated Intel® HD Graphics

Intel® Core™ processor with vPro™ technology

Intel® Stable Image Platform Program (SIPP)

Intel Core i5-670 Processor

3.46 GHz, 4M total cache

2 cores/4 threads

Integrated Intel® HD Graphics

Intel® Core™ processor with vPro™ technology

Intel® Stable Image Platform Program (SIPP)



## Standard Features and Configurable Components (availability may vary by country)

### Intel Core i5-680 Processor

3.60 GHz, 4M total cache

2 cores/4 threads

Integrated Intel® HD Graphics

Intel® Core™ processor with vPro™ technology

Intel® Stable Image Platform Program (SIPP)

### Intel Core i5-750 Processor

2.66 GHz, 8M total cache

4 cores/4 threads

Requires a discrete graphics solution

### Intel Core i5-760 Processor

2.80 GHz, 8M total cache

4 cores/4 threads

Requires a discrete graphics solution

### **Intel Core i7 Processors:**

#### Intel Core i7-860 Processor

2.80 GHz, 8M total cache

4 cores/8 threads

Requires a discrete graphics solution

Intel® Core™ processor with vPro™ technology

Intel® Stable Image Platform Program (SIPP)

#### Intel Core i7-870 Processor

2.93 GHz, 8M total cache

4 cores/8 threads

Requires a discrete graphics solution

Intel® Core™ processor with vPro™ technology

Intel® Stable Image Platform Program (SIPP)

#### Intel Core i7-880 Processor

3.06 GHz, 8M total cache

4 cores/8 threads

Requires a discrete graphics solution

Intel® Core™ processor with vPro™ technology

---

## Redundant Array of Independent Drives (RAID)

Flexible implementation:

- DriveLock is supported while in RAID mode. Users can manage the DriveLock password from within F10 Setup. Locked drives will be displayed as such in the RAID option ROM interface.
- Hard drive information can be viewed within F10 Setup while in RAID mode. Previously, the hard drives will not appear in Drive Configuration when switching to RAID mode.
- DPS Self Test can be executed on physical hard drives while in RAID mode.
- The RAID Setup Utility (accessed through CTRL-I) can be protected by the F10 Setup password.

**NOTE:** RAID 1 is the only RAID configuration offered via factory configurations. The pre-configured systems:

- Are only available on the CMT and SFF form factors. The USDT does not support RAID as it does not allow for more than one hard disk drive.
- Are complete RAID systems and have both drives installed. If the CMT is configured with three hard disk drives, the third drive is would be unpartitioned and not part of the RAID array



## Standard Features and Configurable Components (availability may vary by country)

- Have the necessary Option ROM configuration.
- Are pre-loaded and pre-installed with all required Intel software.
- Include a preinstalled operating system that is mirrored mode out of the box.

Please refer to the HP White Paper titled "Advanced Host Controller Interface (AHCI) and Redundant Array of Independent Disks (RAID) on HP Compaq 8000 Elite Series PCs" at: <http://www.hp.com> for more information and instructions.

## DDR3 Synchronous DRAM NON-ECC System Memory

Memory upgrades are accomplished by adding single or multiple DIMMs of the same or varied sizes. This chart does not represent all possible memory configurations. The HP Compaq 8100 Elite Series PC supports non-ECC DDR3 PC3-10600 (1333 MHz) and PC3-8500 (1066 MHz) memory.

**CAUTION:** You must shut down the computer and disconnect the power cord before adding or removing memory modules. Regardless of the power-on state, voltage is always supplied to the memory modules as long as the computer is plugged in to an active AC outlet. Adding or removing memory modules while voltage is present may cause irreparable damage to the memory modules or system board.

## Memory Configurations

### Maximum Memory

Supports up to 16 GB of DDR3 SDRAM using DIMM modules. Slot 1 is black and must always be populated. Not all memory configurations possible are represented below.

### NOTE:

For systems configured with more than 3 GB of memory and a 32-bit operating system, all memory may not be available due to system resource requirements. Addressing memory above 4 GB requires a 64-bit operating system

Total Memory	Slot			
	Channel A		Channel B	
	1 (black)	2 (white)	3 (white)	4 (white)
1 GB	1 GB			
2 GB (dual channel symmetric)	1 GB		1 GB	
4 GB (dual channel symmetric)	1 GB	1 GB	1 GB	1 GB
8 GB (dual channel symmetric)	2 GB	2 GB	2 GB	2 GB
16 GB (dual channel symmetric)	4 GB	4 GB	4 GB	4 GB


\* The Intel Q57 Express chipset includes a built-in Management Engine (ME), which allocates memory for manageability functions. Management Engine memory is shared with system memory. If the PC contains a single SO-DIMM, 16 MB of memory is pre-allocated for it at system startup. If the PC contains two SO-DIMMs, 32 MB of memory is pre-allocated. This memory is not made available to the operating system, just as pre-allocated video memory is not available.






Standard Features and Configurable Components (availability may vary by country)

Small Form Factor



Convertible Minitower



## Storage Drive Support

	Small Form Factor			Convertible Minitower		
	MCR	ODD	HDD SSD	MCR	ODD	HDD SSD
Quantity Supported	1	1	2	1	2	3
Position	1	3	2,1	3	1,2	4,5,6

## Data Storage Drives

### 250-GB Hard Disk Drives

#### 250-GB 3.5" Hard Disk Drive

7,200 rpm, 8MB cache, 3.0 GB/s, NCQ, Smart IV

#### 250-GB Removable Hard Disk Drive

7,200 rpm, 8MB cache, 3.0 GB/s, NCQ, Smart IV

### 500-GB Hard Disk Drives

#### 500-GB 3.5" Hard Disk Drive

7,200 rpm, 16MB cache, 3.0 GB/s, NCQ, Smart IV

#### 500-GB Removable Hard Disk Drive

7,200 rpm, 16MB cache, 3.0 GB/s, NCQ, Smart IV

### 1-TB Hard Disk Drives

#### 1 TB 3.5" Hard Disk Drive

7,200 rpm, 16MB cache, 3.0 GB/s, NCQ, Smart IV

## Solid State Drives



## Standard Features and Configurable Components (availability may vary by country)

---

64-GB 2.5" Solid State Drive  
80-GB 2.5" Solid State Drive

---

### Optical Disc Drives

DVD-ROM Drive<sup>1</sup>  
SuperMulti DVD Writer Drive<sup>1,2,3</sup>  
Blu-Ray Writer Drive

<sup>1</sup>For playing DVDs, Corel WinDVD 8

<sup>2</sup>For writing CDs, choice of Sonic/Roxio Easy Media Creator 9 or Roxio Business Creator 10

<sup>3</sup>For writing CDs and DVDs, video editing and authoring DVDs, choice of Sonic/Roxio Easy Media Creator 9 or Roxio Business Creator 10

---

### Media Card Readers

Media Card Reader (22-in-1)  
Media Card Reader (22-in-1) with 1394 port

---

## Security Solutions and Capabilities

Trusted Platform Module (TPM) 1.2<sup>1</sup>  
Stringent Security (via BIOS)<sup>2</sup>  
SATA Port Disablement (via BIOS)  
Drive Lock  
RAID Configurations  
HP ProtectTools Embedded Security Software  
Serial, Parallel, USB enable/disable (via BIOS)  
Optional USB Port Disable at factory (user configurable via BIOS)  
Removable Media Write/Boot Control  
Power-On Password (via BIOS)  
Setup Password (via BIOS)  
Solenoid Hood Lock / Sensor  
Support for chassis padlocks and cable lock devices

<sup>1</sup>TPM module disabled where use is restricted by law; for example, Russia.

<sup>2</sup>This setting is defaulted to disable, but when enabled, the PW jumper will not clear the BIOS pre-boot authentication passwords.

---

## Network Interface Connections

Intel 82578 GbE Network Connection (integrated)  
Intel Gigabit CT Desktop NIC Card  
Broadcom NetXtreme GbE Ethernet Plus NIC (PCIe x1)  
HP 802.11 b/g/n Wireless PCIe x1 Card

### Note:

The integrated network connection is required to support the vPro Technology features.

---



Standard Features and Configurable Components (availability may vary by country)

---

## Modem

LSI Hi-Speed 56K International Soft Modem (PCIe x1)

---

## Graphics

Intel Graphics Media Accelerator 4500 (integrated)

Nvidia GeForce 310 Card

Nvidia Quadro NVS 290 Card

Nvidia Quadro NVS 295 Card\*

ATI Radeon HD 4550 Card

ATI Radeon HD 4650 Graphics Card

---

HP DisplayPort to DVI-D Adapter

HP DisplayPort to VGA Adapter

HP DisplayPort to HDMI Adapter

HP DisplayPort Cable

\* When ordered with an Nvidia Quadro NVS 295 card, the PC is shipped with two DisplayPort to VGA Adapters. When an Nvidia Quadro NVS 295 card is purchased as an after-market option, it comes with two DisplayPort to DVI-D Adapters.

---

## Audio/Visual

High Definition Audio with Realtek ALC261 codec (all ports are stereo)

Microphone/Headphone\* and dedicated headphone front ports

Line-out and Line-In rear Ports\*

Multi-streaming capable\*

Internal Speaker (standard)

HP Thin USB Powered Speakers

HP TV Tuner

\* The front microphone port is re-taskable as a Line-in, Microphone-in or Headphone-in port. Rear audio input ports are re-taskable as a Line-in or Microphone-in port. External speakers must be powered externally. Multi-streaming can be enabled in the Realtek control panel to allow independent audio streams to be sent to/from the front and rear jacks. This allows for different audio applications to use separate audio ports on the system. For example, the front jacks could be used with a headset for a communications application while the rear jacks are being used with external speakers and a multimedia application.

Note: The audio ports/jacks provided by all of our systems are 3.5mm in diameter. This would include both the front jacks and rear jacks, for audio in/out, mic in and headphone out.

---

## Input/Output Devices



## *Standard Features and Configurable Components (availability may vary by country)*

- PS/2 Standard Keyboard
- USB Standard Keyboard
- USB CCID SmartCard Keyboard
- USB Mini Keyboard
- USB and PS/2 Washable Keyboard

---

- PS/2 Optical Scroll Mouse
- USB Optical Scroll Mouse
- USB Laser Scroll Mouse
- USB and PS/2 Washable Mouse

---

## **Miscellaneous Devices and Configurations**

- FireWire (IEEE 1394) Card
- Serial Port Adapter (RS-232 compatible)
- Parallel Port Adapter
- eSATA Port Adapter
- PC Tower Stand
- Configure CMT in desktop orientation

After-Market Options (availability may vary by region)

Communications	SFF	CMT	Part Number
HP Wireless 802.11 b/g/n NIC Card	X	X	FH971AA
Broadcom NetXtreme GbE Ethernet Plus NIC Card	X	X	FS215AA
Intel Gigabit CT Desktop NIC Card	X	X	FH969AA
LSI Hi-Speed 56K Int'l Soft Modem Card	X	X	FH970AA
RJ11 Modem Adapter Kit	X	X	DC131C

**NOTE:** The use of a NIC Card (wired or wireless) will disable the vPro Technology features.

Graphics	SFF	CMT	Part Number
ATI Radeon HD 4550 Graphics Card	X	X	AT042AA
ATI Radeon HD 4650 DP (1GB) PCIe x16 Graphics Card		X	VN566AA
Nvidia Quadro NVS 290 Graphics Card	X	X	KG748AA
Nvidia Quadro NVS 295 Graphics Card	X	X	FY943AA
Nvidia GeForce 310 DP PCIe x16 Graphics Card	X	X	VG885AA

DMS59 DVI Dual-head Connector Cable	X	X	DL139A
HP DVI to DVI cable	X	X	DC198A
HP DisplayPort To DVI-D adapter	X	X	FH973AA
HP DisplayPort To DL DVI-D adapter	X	X	NR078AA
HP DisplayPort to VGA Adapter	X	X	AS615AA
HP DisplayPort Cable Kit	X	X	VN567AA

Hard Disk Storage Drives	SFF	CMT	Part Number
HP 250GB Hard Disk Drive	X	X	PY278AA
HP 500GB Hard Disk Drive	X	X	KW347AA

HP 64-GB Solid State Drive	X	X	VG679AA
HP 80-GB Solid State Drive	X	X	BM848AA

HP eSATA Adapter	X	X	FH966AA
HP Removable SATA Hard Drive Enclosure (frame & carrier)	X	X	RY102AA
HP Removable SATA Hard Drive Enclosure (Carrier Only)	X	X	RY103AA



After-Market Options (availability may vary by region)

<b>Input Devices</b>	<b>SFF</b>	<b>CMT</b>	<b>Part Number</b>
HP PS/2 Standard Keyboard	X	X	DT527A
HP USB Standard Keyboard	X	X	DT528A
HP USB Mini Keyboard	X	X	AS601AA
HP USB Gray Keyboard	X	X	DT529A
HP USB SmartCard Keyboard	X	X	ED707AA
HP USB Keyboard and Mouse Kit	X	X	RC465AA
<hr/>			
HP USB Washable Keyboard	X	X	VF097AA
HP USB and PS/2 Washable Mouse	X	X	BM866AA
HP USB and PS/2 Washable Keyboard and Mouse Kit	X	X	BU207AA
<hr/>			
HP PS/2 Optical Scroll Mouse	X	X	EY703AA
HP USB Optical Scroll Mouse	X	X	DC172B
HP USB Laser Mouse	X	X	GW405AA
HP USB Travel Mouse	X	X	GW405AT
<hr/>			
HP 2.4GHz Wireless Keyboard and Mouse	X	X	NB896AA
<hr/>			
<b>System Memory</b>	<b>SFF</b>	<b>CMT</b>	<b>Part Number</b>
1 GB DIMM	X	X	AT023AA
2 GB DIMM	X	X	AT024AA
4 GB DIMM	X	X	VH638AA
<hr/>			
<b>Multimedia Devices</b>	<b>SFF</b>	<b>CMT</b>	<b>Part Number</b>
HP Thin USB Powered Speakers	X	X	KK912AA
<hr/>			
DVD-ROM Drive	X	X	AR629AA
SuperMulti Drive	X	X	AR630AA
Blu-Ray Writer Drive	X	X	AR482AA
<hr/>			
<b>Removable Media Storage</b>	<b>SFF</b>	<b>CMT</b>	<b>Part Number</b>
HP USB External Diskette Drive	X	X	DC141B
HP Media Card Reader (22-in-1)	X	X	AR941AA
HP Media Card Reader (22-in-1) with FireWire (IEEE 1394)	X	X	AR942AA



After-Market Options (availability may vary by region)

Security Devices	SFF	CMT	Part Number
HP/Kensington MicroSaver Cable Lock	X	X	PC766A
HP Business PC Security Lock	X	X	PV606AA
HP SFF Solenoid Lock and Hood Sensor	X		BP428AA
HP CMT Solenoid Lock and Hood Sensor		X	DE618A
HP SFF Wall Mount/Security Sleeve	X		VN570AA

HP Client Automation Software	SFF	CMT	Part Number
HP Client Automation – Standard Edition (single seat)	X	X	T3488AA
HP Client Automation – Standard Edition (10 seats)	X	X	TA599AA
HP Client Automation – Standard Edition (100 seats)	X	X	TA600AA
HP Client Automation – Standard Edition (500 seats)	X	X	TA601AA
HP Client Automation – Standard Edition (1,000 seats)	X	X	T3489AA

Stands and Accessories	SFF	CMT	Part Number
HP SFF Tower Stand	X		VN569AA
HP Integrated Work Centre - Small Form Factor	X		QK549AA
HP Serial Port Adapter (RS-232 compatible)	X	X	PA716A
HP Parallel Port Adapter	X	X	KD061AA
HP 5.25" Blank Bezel Kit (50 pack)	X	X	DC177B
HP FireWire (IEEE 1394) Card	X	X	PA997A



## Technical Specifications

### Weights and Dimensions

(configured with 1 HDD and 1 ODD)

#### Small Form Factor

#### Convertible Minitower

Chassis (H x W x D)	3.95 x 13.30 x 14.9 in 100 x 338 x 378.5 mm	17.63 x 7.00 x 17.5 in 447.8 x 177.8 x 444.5 mm
System Volume	782.77 cu in 12.8 L	2160 cu in 35.4 L
Tower Stand (H x W x D)	1.12 x 7.01 x 7.87 in 28.5 x 178 x 200 mm	N/A
Packaging (H x W x D)	9.00 x 19.68 x 23.38 in 228.6 x 499.9 x 593.85 mm	22.64 x 12.72 x 24.41 in 575.0 x 323 x 620 mm
System Weight*	16.72 lbs 7.6 kg	24.54 lbs 11.15 kg
Shipping Weight*	17.86 lbs 8.1 kg	34.0 lbs 15.42 kg
Max Supported Weight (desktop orientation)	77 lb 35 kg	77 lbs 35 kg

### I/O Ports

USB 2.0	Front – four (4) ports Rear – six (6) ports
Serial	one RS-232 compatible port standard second port available optionally
Parallel	one port available as an option
eSATA	one port available as an option
PS/2	color coded support for keyboard (purple) and mouse (green)
Video	VGA and DisplayPort provide integrated dual independent monitor support
DVI output	available via optional DisplayPort to DVI Adapter
Audio	Front – microphone & headphone Rear – line input (supports microphone or line input), line out <b>Note:</b> See Audio/Visual section for information on re-taskable audio ports. <b>Note:</b> The audio ports/jacks provided by all of our systems are 3.5mm in diameter. This would include both the front jacks and rear jacks, for audio in/out, mic in and headphone out.
NIC	Industry standard RJ-45 port accesses the integrated network interface controller





## Technical Specifications

Slots		Small Form Factor	Convertible Minitower
PCI Slot		(1) low profile PCI slot 25W max power	(3) full height PCI slot 25W max. power
PCI Express x16		(2) low profile PCIe x16 graphics slot 35W max power	(2) full height PCIe x16 graphics slots 75W max. power - primary slot 35W max. power - secondary slot
			<b>Note:</b> Secondary slot functions as a x4 slot
PCI Express x1		(1) low profile PCIe x1 slot	(1) full height PCIe x1 slot

---

Bays		Small Form Factor	Convertible Minitower
External	3.5"	(1) bay available for Media Card Reader unless used for a secondary hard drive	N/A
	5.25"	(1) bay available for Optical Disc Drive 8.19" deep	3 bays Top two bays accept drives up to 8.19" depth Bottom bay accepts drives up to 5.7" depth

---

Controller		Small Form Factor	Convertible Minitower
Hard Drive Controller		Serial ATA Supports SATA 1.5-GB/s and 3.0-GB/s	
SATA Interfaces		(3) common SATA (1) eSATA	(4) common SATA (1) eSATA
Host SATA Controller		(1) low profile PCIe x1 slot	(1) full height PCIe x1 slot

## Unit Environment and Operating Conditions

### General Unit Operating Guidelines

- Keep the computer away from excessive moisture, direct moisture and the extremes of heat and cold, to ensure that unit is operated within the specified operating range.
- Leave a 10.2 cm (4 in) clearance on all vented sides of the computer to permit the required airflow.
- Never restrict airflow into the computer by blocking any vents or air intakes.
- Do not stack computers on top of each other or place computers so near each other that they are subject to each other's recirculated or preheated air.
- Occasionally clean the air vents on the front, back, and any other vented side of the computer. Lint, dust and other foreign matter can block the vents and limit the airflow.
- If the computer is to be operated within a separate enclosure, intake and exhaust ventilation must be provided on the enclosure, and the same operating guidelines listed above will still apply.

Temperature Range	Operating: 50° to 95° F (10° to 35° C)* Non-operating: -22° to 140° F (-30° to 60° C)
Relative Humidity	Operating: 10% to 90% (non-condensing at ambient) Non-operating: 5% to 95% (non-condensing at ambient)
Maximum Altitude (unpressurized)	Operating: 10,000 ft (3048 m) Non-operating: 30,000 ft (9144 m)



### Technical Specifications

\*Operating temperature is de-rated 1.0 deg C per 300 m (1000 ft) to 3000 m (10,000 ft) above sea level, no direct sustained sunlight. Maximum rate of change is 10 deg C/Hr. The upper limit may be limited by the type and number of options installed.

Power Supply	Small Form Factor	Convertible Minitower
Standard Efficiency	240W active PFC	320W active PFC
High Efficiency*	240W active PFC 87/89/85% efficient at 20/50/100% load	320W active PFC 87/89/85% efficient at 20/50/100% load
Operating Voltage Range	90 – 264 VAC	90 – 264 VAC
Rated Voltage Range	100 – 240 VAC	100 – 240 VAC
Rated Line Frequency	50/60 Hz	50/60 Hz
Operating Line Frequency Range	47 – 63 Hz	47 – 63 Hz
Rated Input Current	4A	5.5A
Rated Input Current with Energy Efficient* Power Supply	4A	5.5A
Current Leakage (NFPA 99)	< 275 $\mu$ A	< 450 $\mu$ A
Power Supply Fan	92mm variable speed	92mm variable speed
Power Cord Length	6 ft (1.83 m)	6 ft (1.83 m)

\*High efficiency power supply is a requirement for ENERGY STAR qualification in conjunction with a select range of processors and modules

### ROM BIOS Information

Key features of the HP BIOS include:

- Deployment and manageability – HP BIOS provides several technologies that help integrate the HP Elite PC into the enterprise, such as PXE, remote configuration, remote control, and F10 Setup support for 12 languages.
- Select models feature either Intel Standard Manageability or Core 2 processor with vPro Technology.
- Stability – HP BIOS supports the HP stable product roadmap by releasing only critical BIOS changes to the factory and advanced change notification.
- Computrace agent – For tracking and tracing services, available in select countries, separate software and purchase of a subscription is required.
- Thermal and power management – The HP BIOS provides and enables thermal and power management technologies so component temperatures are managed for high reliability and to assist in operating the HP Business Desktop computer in any enterprise environment.
- Acoustic performance – Industry leading acoustic emissions across the range of operating conditions.
- Serviceability – HP BIOS provides diagnostic and detailed service information.
- Upgrades and recovery – HP BIOS provides numerous ways to upgrade HP Business Desktop computers, including BIOS updates from within DOS (Flashbin), BIOS updates from within Windows (HPQFlash), HP Client Manager, and fail-safe recovery. In addition, the HP Business Desktop BIOS Utilities tool enables replicated BIOS setup throughout the Enterprise; it is available from within the BIOS software and from the support website.

Additional HP BIOS Features

- Power-On password – Helps prevent an unauthorized user from powering on the system.
- Administrator password – Also known as the setup password, this helps prevent unauthorized changes to the system



### Technical Specifications

configuration. If the administrator password is not known, the BIOS version cannot be changed and changes cannot be made to BIOS settings using F10 setup or under the OS.

- Advanced Configuration and Power Interface (ACPI) – Represents a significant innovation in power and configuration management, allowing operating systems and applications to manage power based on activity and usage. HP Elite models use ACPI to provide power conservation features.
- S5 Max Power Savings setting supports EU Lot6 requirement and allows the computer to power down below 1W in S5 (when turned off). When S5 Max Power Savings feature is enabled power to slots is turned off along with WOL functionality.

### Other Features

- Advanced Configuration and Power Management Interface (ACPI). Allows the system to wake from a low power mode. Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system.
- System Management BIOS v2.6
- Intel Wired for Management support; industry wide initiative to make Intel architecture based PCs, servers and mobile computers more inherently manageable out-of-the-box and over the network
- Dual State Power Button; acts as both an on/off button and a suspend-to-sleep button

### Serviceability Features

- Dual colored power LED on front of computer to indicate either normal or fault condition
- Diagnostic LED Explanation Table:
  - Number of 1-second red LED blinks followed by a 2-second pause, then repeats:
    - 2 – processor thermal protection activated
    - 3 – processor not installed
    - 4 – power supply failure
    - 5 – memory error
    - 6 – video error
    - 7 – PCA failure (ROM detected failure prior to video)
    - 8 – invalid ROM, bootblock recovery mode
    - 9 – system not fetching code
    - 10 – system hang while loading an option ROM
- System/Emergency ROM
- Flash ROM
- CMOS Battery Holder for easy replacement
- Flash Recovery with Video Configuration Record Software
- 5 Aux Power LED on System PCA
- Processor ZIF Socket for easy Upgrade
- Over-Temp Warning on Screen (Requires IM Agents)
- Clear Password Jumper
- DIMM Connectors for easy Upgrade
- Clear CMOS Button
- NIC LEDs (integrated) (Green & Amber)
- Dual Color Power and HD LED - To Indicate Normal Operations and Fault Conditions
- Color coordinated cables and connectors
- Tool-less Hood Removal
- Front power switch
- System memory can be upgraded without removing the system board or any internal components
- Tool-less Hard Drive, CD & Diskette Removal
- Green Pull Tabs, and Quick Release Latches for easy Identification



## Technical Specifications

### Additional Features

### Description

Intel Standard Manageability

- Requires the utilization of the integrated network connection
- Available with selected processors not part of the Intel Stable Intel Platform Program (SIPP)
- Intel Advanced Management Technology (AMT) v3.2
- Basic PC management capabilities such as asset inventory, HW alerting, SOL/IDE-R, remote configuration, agent presence and system defense.
- DASH 1.1 compliance. Support for profile updates.
- Host VPN support for local management VPN tunneling
- Requires the utilization of the integrated network connection
- Available with selected processors which are part of the Intel Stable Intel Platform Program (SIPP)
- Intel Advanced Management Technology (AMT) v6.0
- Intel Standard Manageability technologies (see above for a list of features)
- Fast Call for Help – client outside the firewall may initiate a call for help via BIOS screen, periodic connections, or alert triggered connection

Intel Core vPro Processor Technology

- Audit Logs – policy based log of AMT actions to deter rogue administrator actions
- Microsoft NAP Support – allows AMT to gain access to a Microsoft NAP enabled 802.1x network OOB to enable OOB SW updates, inventories, remote diagnostics, etc.
- Remote Scheduled Maintenance – Pre-schedule when the PC connects to the IT or service provider console for maintenance
- Remote Alerts – automatically alert IT or service provider if issues arise
- Access Monitor – Provides oversight to support security requirements

DASH 1.1 support (Desktop and Mobile Architecture for System Hardware)

A standards initiative for representing out-of-band management capability for computer systems. It is a secure, web-services based successor to ASF.

ASF 2.0 support (Alert Standard Format)

Industry-standard specification for network alerting in operating system-absent environments

TXT (Trusted Execution Technology) and VT-d (Virtualized devices)

TXT allows for secure management (via TPM) and measured launch of VMM, as well as teardown of secrets in unexpected reset case. TXT support provided in select Intel processors

VT-d is a chipset technology that virtualizes directed I/O  
Together, TXT and VT-d may be used to support verified launch of a known trusted VMM that also may protect VMs from accessing each other's memory.

Computrace

Computrace agent support standard

Towerable Orientation

Product can be oriented as either a desktop or a tower

Drive Lock

Implementation of the industry standard ATA Security feature set. When enabled, it prevents software access to user data on the drive until one or two user-defined passwords are provided.

Drive Protection System

DPS Access through F10 Setup during Boot  
A diagnostic hard drive self test. It scans critical physical components and every sector of the hard drive for physical faults and then reports any faults to the user  
Running independently of the operating system, it can be accessed through a Windows-based diagnostics utility or through the computer's setup procedure. It produces an evaluation on whether the hard drive is the source of the problem and needs to be replaced  
The system expands on the Self-Monitoring, Analysis, and Reporting Technology (SMART), a continuously running systems diagnostic that alerts the user to certain types



## Technical Specifications

SMART Technology (Self-Monitoring, Analysis and Reporting Technology)

of failures

Allows hard drives to monitor their own health and to raise flags if imminent failures were predicted

SMART I – Drive Failure Prediction

Predicts failures before they occur. Tracks fault prediction and failure indication parameters such as re-allocated sector count, spin retry count, calibration retry count

SMART II – Off-Line Data Collection

By avoiding actual hard drive failures, SMART hard drives act as "insurance" against unplanned user downtime and potential data loss from hard drive failure

SMART III – Off-Line Read Scanning with Defect Reallocation

IOEDC: I/O Error Detection Circuitry

SMART IV – End-to-End CRC for hard drives

Detects errors in Read/Write buffers on HDD cache RAM

Interface in F10 setup provides confirmation of SMART IV support.



## Technical Specifications - Audio

### High Definition Audio

Type	Integrated
Realtek 4-channel ALC261 HD Stereo Codec	<ul style="list-style-type: none"><li>• DAC supports 16/20/24-bit PCM format for 4 channel audio solution</li><li>• Two stereo ADCs support 16/20-bit PCM format</li><li>• All DACs support independent 44.1k/48k/96kHz sample rate</li><li>• All ADCs support independent 44.1k/48k/96kHz sample rate</li></ul>
Audio I/O Ports	Front microphone-In (150-K ohm Input Impedance) Rear Line-In/Microphone input (150-K ohm Input Impedance, function is configurable by audio driver) Rear Line-Out (190 ohms Output Impedance, expects at least a 10-K ohm load) Front Headphone-Out (0.5 Ohm Output Impedance, expects at least a 32 ohm load) Front Microphone/Headphone jack is re-task able to provide Microphone input, line-in or Headphone output to support connecting two headphones to the front of the system. When configured as a second front headphone output, both front headphone outputs are always driven with the same signal.
Speakers	System includes an internal PC speaker rated 1.5W powered by an internal amplifier. External speakers must be powered externally.
Multistreaming Capable	Multi-streaming can be enabled in the Realtek control panel to allow independent audio streams to be sent to/from the front and rear jacks.
Analog Audio	Yes

### HP Thin USB Powered Speakers

On/Off/Volume Controls	Right side of right speaker
Power LED	Front of right speaker (green)
Frequency Response	FO to 20kHz
Watts	2/3 watt (normal/maximum)
Dimensions/Speaker (H x W x D)	5.72 x 3.74 x 0.96 in 14.52 x 9.50 x 2.45 cm
Net Weight	0.68 lbs 0.31 kg
Color	Black
Environmental (all conditions non-condensing)	Operating Temperature: 14° to 104° F -10° to 40° C Relative Humidity 40% to 90%
Speaker Cable Length	Input Cord: 5.91 ft 1800mm L-channel Cord: 3.28 ft 1000mm USB Cord: 5.91 ft 1800mm



## Technical Specifications - Communications

### Intel 82578 GbE Network Connection (integrated)

Connector	RJ-45
Controller	Intel 82578 Gigabit platform LAN Connect Networking Controller
Memory	24 KB FIFO packet buffer memory
Data rates supported	10/100/1000 Mbps
Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3 ab and 802.3u compliant
Bus architecture	GLCI, LCI interface. Intel specific MAC to PHY interface
Data transfer mode	PCIe-like interface for 1000 speed, SMBus interface for lower 10/100 speeds.
Data rates supported	10/100/1000 Mbps
Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3 ab and 802.3u compliant
Data transfer mode	At gigabit GLCI (Intel proprietary 802.3 series-based interface) is for Data, LCI (parallel bus) for MDIO, at 10/100 LCI for both data and MDIO, GLCI is idle.
Hardware certifications	FCC B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union
Power requirement	Requires 3.3V & 1.2V. Power consumption 761 Milliwatts
ACBS	Intel Auto Connect Battery Saving feature
Boot ROM support	Yes
Network transfer mode	Full-duplex Half-duplex (not supported for the 1000BASE-T transceiver) 10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps
Network transfer rate	100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps
Operating temperature	0° to 85° C
Management	WOL, auto MDI crossover, PXE, Multi-port teaming, RSS, Advanced cable diagnostic.
Alerting	ASF 2.0 support, AMT 3.0 support



## Technical Specifications - Communications

### Broadcom NetXtreme GbE Ethernet Plus Network Interface Controller

Connector	RJ-45
Controller	Broadcom 5761 PCI-Express LAN Controller
Memory	8 MB NVRAM serial Flash
Data rates supported	10/100/1000 Mbps
Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB, 802.3u, and 802.3x
Bus architecture	PCI-Express
Data path width	Single Channel PCI-Express
Data transfer mode	Bus Master DMA
Hardware certifications	FCC class B, Canada and US NRTL Mark, C-Tick for Australia, BSMI for Taiwan, VCCI for Japan, MIC for Korea, GOST for Russia, UL listed (E212044), European Union Notice (CE 0682)
Power requirement	1.8W @ 3.3V
Boot ROM support	Yes
Network transfer mode	Full-duplex Half-duplex (not available for the 1000BASE-T transceiver)
Network transfer rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps
Environmental	Operating temperature 32° to 131°F (0° to 55° C) Operating humidity 131° F (55° C) with 5% to 95% non-condensing humidity
Dimensions	2.75 in x 4.13 in (7 cm x 10.5 cm), low profile compatible
Operating system driver support	Windows Vista 32-bit SP1, Windows Vista x64 SP1, Windows XP 32 bit professional
Management capabilities	ACPI, WOL and DMI 2.0, PXE 2.0, WfM 2.0, Broadcom mgmt utility, ASF2.0, DASH 1.0 and DASH 1.1 profiles

### Intel GbE CT Desktop Network Interface Connection

Connector	RJ-45
Controller	Intel 82574L Gigabit Ethernet Controller
Memory	Integrated Dual 48K configurable transmit receive FIFO Buffers
Data rates supported	10/100/1000 Mbps
Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB and 802.3u compliant, 802.3x flow control
Bus architecture	PCI-E 1.0a
Data path width	X1, 250 MB/s, Bi-directional interface
Data transfer mode	Bus-master DMA
Hardware certifications	FCC, B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union
Power requirement	Aux 3.3V, 3.0 Watts in 1000base-T and 2.0 Watts in 100Base-T
Boot ROM support	Yes





## Technical Specifications - Communications

Network transfer rate	10BASE-T (half-duplex) 10 Mbps
	10BASE-T (full-duplex) 20 Mbps
	100BASE-TX (half-duplex) 100 Mbps
	100BASE-TX (full-duplex) 200 Mbps
Environmental	1000BASE-T (full-duplex) 2000 Mbps (actual rate limited by PCI Bus)
	Operating temperature 32° to 131°F (0° to 55° C)
	Operating humidity 85% at 131° F (55° C)
Dimensions	4.75 x 2.25 x 0.8 in (12.1 x 5.7 x 2.0 cm)
Management	WOL, PXE, DMI, WFM 2.0

## HP Wireless Network Connection 802.11 b/g/n

Dimensions (L x H)	3.3 x 4.7 in	
	8.5 x 12 cm	
Weight	0.08 lbs	
	40 g	
Controller	Ralink RT2790	
System interface	PCIExpress x1	
Network standard	802.11 b/g/n	
Frequency band	2.400 - 2.497 GHz	
Operating temperature	14° to 149°F, operating (-10° to 65°C, operating)	
Storage temperature	-40° to 176°F, non-operating (-40° to 80°C, non-operating)	
Humidity	10-90% operating	
	5-95% non-operating	
Operating voltage	3.3V +/- 9%	
	12V +/- 8%	
Power consumption	Platform/WLAN Mode	Power Consumption
	Maximum Power Consumption	10 Watts
	Transmit Only	4 Watts maximum averaged power over 1 second
	Transmit Packet or Active Scanning	1000 mA peak current for 100 microseconds or longer
	Receive Only Mode or Idle without IEEE PSP mode enabled	3 Watts maximum averaged over 1 second
	Idle, with IEEE PSP mode enabled	1.0 Watts maximum averaged over 1 second
	Transmit Disabled (turned off in software)	50 mW maximum, averaged over 1 second
	Platform in S3 or S4 (power removed from Low Profile PCI Express Card)	5 mW maximum, averaged over 1 second
	802.11b mode	+19 dBm +/- 1.0 dB maximum
	802.11g mode	+17 dBm +/- 1.0 dB maximum
Output power (approximately)	EWC mode	+17 dBm +/- 1.0 dB maximum (total power in all transmit chains)



## Technical Specifications - Communications

	Mode	Data rate	Sensitivity
Receive sensitivity	802.11b	1 Mbps	-94 dBm
	802.11b	11 Mbps	-85 dBm
	802.11g	6 Mbps	-91 dBm
	802.11g	18 Mbps	-85 dBm
	802.11g	48 Mbps	-75 dBm
	802.11g	54 Mbps	-72 dBm
	EWC (2.4 GHz)	6.5 Mbps	-87 dBm
	EWC (2.4 GHz)	54 Mbps	-82 dBm
	EWC (2.4 GHz)	81 Mbps	-78 dBm
	EWC (2.4 GHz)	162 Mbps	-74 dBm
	EWC (2.4 GHz)	270 Mbps	-68 dBm
	EWC (2.4 GHz)	300 Mbps	-64 dBm

	Data Rate (MCS)	Minimum Throughput
Data transfer rate	1 Mbps (802.11 b)	700 kbps
	2 Mbps (802.11 b)	1.4 Mbps
	5.5 Mbps (802.11 b)	3.5 Mbps
	11 Mbps (802.11 b)	5.9 Mbps
	12 Mbps (802.11 g)	6 Mbps
	18 Mbps (802.11 g)	9 Mbps
	24 Mbps (802.11 g)	12 Mbps
	36 Mbps (802.11 g)	18 Mbps
	48 Mbps (802.11 g)	21 Mbps
	54 Mbps (802.11 g)	22.5 Mbps
	6.5 Mbps (20 MHz EWC)	4.5 Mbps
	13 Mbps (20 MHz EWC)	9 Mbps
	19.5 Mbps (20 MHz EWC)	13.5 Mbps
	26 Mbps (20 MHz EWC)	18 Mbps
	39 Mbps (20 MHz EWC)	27 Mbps
	52 Mbps (20 MHz EWC)	36 Mbps
	58.5 Mbps (20 MHz EWC)	40 Mbps
	65 Mbps (20 MHz EWC)	45 Mbps
	78 Mbps (20 MHz EWC)	54 Mbps
	104 Mbps (20 MHz EWC)	72 Mbps
	117 Mbps (20 MHz EWC)	81 Mbps
	130 Mbps (20 MHz EWC)	91 Mbps
	13.5 Mbps (40 MHz EWC)	8 Mbps
	27 Mbps (40 MHz EWC)	16 Mbps
40.5 Mbps (40 MHz EWC)	24 Mbps	
54 Mbps (40 MHz EWC)	32 Mbps	
81 Mbps (40 MHz EWC)	48 Mbps	
108 Mbps (40 MHz EWC)	64 Mbps	



### Technical Specifications - Communications

	121.5 Mbps (40 MHz EWC)	72 Mbps
	135 Mbps (40 MHz EWC)	81 Mbps
	IEEE and WiFi compliant 64 / 128 bit WEP encryption	
	AES: CCM	
	802.1x authentication	
Security	WPA: 802.1x, WPA-PSK and TKIP	
	WPA2 certification	
	IEEE 802.11i	
	Cisco Certified Extensions, all versions through V5	
Antenna	HP part number 497792-001	
Certifications	Wi-Fi certified	
Certifications for use by country	United States, Canada, Peru, Taiwan	

### Intel WiFi Link 5100 a/b/g/n Wireless Network Interface Connection (USDT)

	IEEE 802.11a
	IEEE 802.11b
	IEEE 802.11g
	IEEE 802.11n
Wireless LAN Standards	<p>Note:</p> <p>The specifications for 802.11n draft 2.0 are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11n WLAN devices. In countries where n draft 2.0 is not allowed, this capability is not enabled.</p> <p>Wi-Fi certified (802.11a/b/g only)</p>
Interoperability	<p>Cisco Compatible Extensions Program compliant (802.11a/b/g only) with Microsoft Windows Vista and XP</p> <p>Tested with wireless access points from several major manufacturers</p>
Frequency Band	2.4 GHz and 5 GHz
Antenna Structure	1 transmit; 2 receive (1x2)
	802.11b: 1, 2, 5.5, 11 Mbps
	802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
Data Rates	802.11n (draft): 66 possible data rates, ranging from 6 Mbps to 300 Mbps, depending on the combination of Bandwidth, Modulation Coding Scheme, and Guard Interval used, as defined in IEEE 802.11n (draft) specification
Modulation	<p>Direct Sequence Spread Spectrum</p> <p>DBPSK, DQPSK, CCK, OFDM, BPSK, QPSK, 16-QAM, 64-QAM</p> <p>Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES (support for key sizes of 128, 192, and 256 bits), 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST</p>
Security	Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4) with Microsoft Windows Vista and XP only.
Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.



## Technical Specifications - Communications

Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power (for CCK)	15 dBm
Output Power (for OFDM; power varies by data rate)	15 dBm
Power Consumption	Transmit: 2.3 Watts (average, with one spatial streams) Receive: 1.9 Watts (average with two receive chains) Idle mode: 30 mW (average) Radio off: 20 mW (max)
Power Management	ACPI compliant power management 802.11 compliant power saving mode
Receiver Sensitivity <sup>4</sup>	300 Mbps: -68 dBm, 54 Mbps: -74 dBm, 6 Mbps: -90 dBm
Antenna Connections	3 U.FL type connectors, 50 ohm nominal impedance
Range	802.11 a - Typical (@6 Mbps) 600 feet - Outdoor Open Area 150 feet - Indoor, Office environment 802.11 b - Typical (@1 Mbps) 1200 feet - Outdoor Open Area 300 feet - Indoor, Office environment 802.11 g - Typical (@1 Mbps) 1200 feet - Outdoor Open Area 300 feet - Indoor, Office environment
Form Factor	PCI-Express MiniCard
Weight	0.013 lb (6 g)
Dimensions	0.19 x 1.2 x 2.0 in (4.75 x 29.85 x 50.8 mm)
Operating Voltage	3.3V +/- 9%, 1.5V +/- 5%
Temperature	Operating: 32° to 176° F (0° to 80° C) Non-operating: -40° to 176° F (-40° to 80° C)
Humidity	Operating: 10% to 90% (non-condensing) Non-operating: 5% to 90% (non-condensing)
Altitude	Operating: 0 to 10,000 ft (3,048 m) Non-operating: 0 to 50,000 ft (15,240 m)



## Technical Specifications - Communications

	Microsoft Windows XP	Microsoft Windows Vista
Configuration Utility <sup>5</sup>	<ul style="list-style-type: none"><li>• Microsoft Windows XP Wireless Network Connection Manager</li><li>• Intel PROSet for Microsoft Windows XP (required for Cisco Compatible Extensions support)</li></ul>	<ul style="list-style-type: none"><li>• Microsoft Windows Vista Wireless Network Connection Manager.</li><li>• Intel IHV extensions for Windows Vista available to support Cisco Compatible Extensions.</li></ul>
	<ol style="list-style-type: none"><li>1. Check latest software/driver release for updates on supported security features.</li><li>2. Maximum output power may vary by country according to local regulations.</li><li>3. In Power Save Polling mode and on battery power.</li><li>4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CCK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).</li><li>5. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows XP. WLAN may also be compatible with certain third-party software supplicants. WLAN supplier IHV extensions required for Cisco Compatible Extensions support for Microsoft Windows Vista.</li></ol>	

## LSI 56K International SoftModem PCI Express x1 Card

Data Transmission	Technology speeds: 56,000 Kbps maximum downstream data, controllerless <b>Note:</b> 56 Kbps technology refers to download speeds only and requires compatible modems at server sites. Other conditions may limit modem speed. FCC limitations allow a maximum of 53 Kbps during download transmissions.
Data Speeds	(Upload only) 33,600/31,200/28,800/26,400/21,600/19,200/ 16,800/14,400/12,000/9,600/7,200/4,800/2,400/1,200/300
Data Standards	ITU-T V.90, ITU-T, ITU-T V.34, V.44, V.42, V.42bis21, V.32bis, Bell 212A, and Bell 103
Fax Speeds	14,400/12,000/9,600/7,200/4,800/2,400/1,200/300 b/
Fax Mode Capabilities	ITU-T T.31 class 1 FAX, V. 17, V.29, V.27ter, and V.21 Channel 2
Error Correction and Data Compression	V.44, 42bis, V.42 and MNP2-5
Power Management	PCI Bus Power Management Interface Specification (PCI-PM) Revision 1.2, Appendix A. D0, D3hot, and D3cold. Wake on Ring state when in D3cold. If the power management event (PME) feature is enabled in D3cold, a modem can wake the system via WAKE# (WAKEN) or beacon. Meets PCI Express 1.1 standard.
Upgradeability	Driver upgradeable for future enhancements
Video	ITU-T V.80 video ready interface TIA/EIA 602 standard AT command set
Other	Integrated DTE interface with speeds of up to 115.2 Kbps, parallel 16550a UART-compatible interface Optional ring wakeup signal
Operating Temperature	32° to 158° F (0° to 70° C)
Operating Humidity	20% to 90%, non-condensing
Power	Requires a 3.3-V auxiliary power rail on PCI express bus Uses only one PCI express load (i.e., one grant/request pair), one shared IRQ, one electrical load
Chipset	LSI SV92EX - Integrated PCI interface with 3.3-V tolerant buffers and CardBus support
Dimensions (L X H)	Complies with PCI express low profile specifications-6.7 x 2.3 in (17.0 x 5.8 cm) and supports high- and low-profile brackets



## Technical Specifications - Communications

Connection	Single RJ-11 connector
Other Features	Digital line protection, call progress monitoring via on-board piezo device, support for high profile and low profile brackets, PnP ID support
Safety	UL recognized to UL 1950, 3rd edition (U.S. and Canada); IEC 950 (TUV, NEMKO, DEMKO, SEMKO); CE Mark, EC 950 (TUV, NEMKO, DEMKO, SEMKO, CE mark
EMC	FCC Part 15, IC ES003, EN 55022, 3rd edition, EN 55024, annex A, EN 61000-4-6, EN 61000-4-8
Telecom	FCC Part 68, IC-CS-03 (Canada); Worldwide PTT approvals Not available in Korea or the Republic of South Africa.
Other	The SV92EX device is packaged in a 32-pin micro leadless chip carrier (MLCC). The SV92EX is fully compliant with the PCI Express revision 1.1 specification. WHQL approved; ASPM compliant.



## Technical Specifications - Graphics

### Intel HD Graphics

3D/2D Controller	Microsoft DirectX® 10 based with support for Pixel Shader 3.0
VGA Controller	Integrated
DisplayPort	Integrated, Multimode capable; supports HDCP
Bus Type	PCI Express™ x16
RAMDAC	Integrated, 350 MHz

### Memory

Graphics memory is shared with system memory. Graphics memory usage varies depending on the amount of system memory installed, BIOS settings, operating system, and system load. 32 MB is pre-allocated for graphics use at system boot time. Additional memory can be allocated at boot time by the BIOS for PAVP (Protected Audio Video Playback) support for playback of protected video content. For Vista, use of PAVP heavy mode preallocates an additional 96MB.

Additional memory is allocated for graphics as needed using Intel's Dynamic Video Memory Technology (DVMT), to provide an optimal balance between graphics and system memory use.

	Total System Memory	Pre-Allocated (MB)	DVMT (MB)
Windows XP Memory Usage	.5GB	32	128
	1.0GB	32	512
	1.5GB	32	768
	2.0GB & more	32	1024

Assumes Management Engine, VT-d enabled and other memory allocated for other BIOS usage

	System Memory	PVAP	Avail System Memory (MB)	Total Avail GFX Memory (MB)	Dedicated Video Memory (MB)	System Video Memory (MB)	Shared System Memory (MB)
Windows XP Memory Usage	1 GB	Lite	952	252	32	96	124
		Heavy	856	294	122	6	166
	2 GB	Lite	1976	764	32	96	636
		Heavy	1880	806	122	6	678
	4 GB	Lite	4024	1759	32	96	1631
		Heavy	3928	1759	122	6	1631
	6 GB	Lite	6072	1759	32	96	1631
		Heavy	5976	1759	122	6	1631
	8 GB	Lite	8120	1759	32	96	1631
		Heavy	8024	1759	122	6	1631

HW Video Decode	Hardware Accelerated decode for MPEG2 encrypted video; support for PAVP Lite (default) and Heavy ( or Paranoid) modes
Maximum Color Depth	32 bits/pixel
Maximum Vertical Refresh Rate	85 Hz at up to 1920x1440, 75 Hz at 2048x1536. Varies with mode and configuration. See table below.
Multi-display Support	Integrated dual independent monitor support facilitated via one VGA port and one DisplayPort integrated on the back plane of the system board and presented as part of the rear I/O set of interfaces. DVI supported via optional HP DisplayPort to DVI-D adapter.
Graphics/Video API Support	Microsoft DirectX® 10, OpenGL® 1.5 (OpenGL® 2.0 available in a driver update)

### Maximum Refresh Rate (Hz)



## Technical Specifications - Graphics

Resolutions Supported	Resolution	Analog Connection	Digital Connection
	640x480	85	60
	800x600	85	60
	1024x768	85	60
	1280x720	85	60
	1280x1024	85	60
	1440x900	75	60
	1600x1200	85	60
	1680x1050	75	60
	1920x1080	85	60-R
	1920x1200	85	60-R
	1920x1440	85	N/A
	2048x1536	75	N/A
	2560x1600	N/A	60*

\* Only supported when using a DisplayPort connection

Note:

Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Note:

60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections

## NVIDIA Quadro NVS 290 Graphics Card

Bus Type	PCI Express x16; low profile	PCI Express x1, low profile
Memory	256 MB 400MHz DDR2 SDRAM unified frame buffer, Z-buffer and Texture storage	
Connector	Single high-density DMS-59 Flex Connector	
Dimensions	Low-profile, 2.586 x 6.6 in (6.57 x 16.76 cm)	
Multi-Monitor support	Dual monitor support	
RAMDAC	Integrated dual 400MHz	
Maximum Pixel Clock	350-MHz	
Overlay planes	One 16-bit video overlay plane	One 1-bit video overlay plane
High Definition Video Processor (HDVP)	Full screen, full frame video playback of HDTV and DVD content	
	DVD ready motion compensation for MPEG-2	
	Independent hardware color controls for video overlay	
	Hardware color space conversion (YUV 4:2:2 and 4:2:0)	
	IDCT motion compensation	
	5-tap horizontal by 3-tap vertical filtering	
	8:1 up/down scaling	

### Specification

### Description

Board Configuration	Description	G86-825
	Core Clock	460-MHz
	Memory Clock	400-MHz
	Frame Buffer	256-MB DDR2, 64-bit wide





## Technical Specifications - Graphics

Display resolution support	Dual integrated analog display controllers supporting up to two analog displays at 2048x1536 @ 85Hz on both displays or dual digital displays at 1920x1200 (single-link).
Color planes	NVIEW advanced multi-display desktop and application management seamlessly integrated into Microsoft Windows
DVI support	32-bit color buffer
Supported graphics APIs	DMS-59 (to dual DVI-SL) OGL 2.1 & DX10 Support; Shader Model 4.0

Resolutions Supported	Resolution	Maximum Refresh Rate	
		Analog Connection	Digital Connection
	640x480	85	60
	800x600	85	60
	1024x768	85	60
	1280x720	85	60
	1280x1024	85	60
	1440x900	75	60
	1600x1200	85	60
	1680x1050	75	60
	1920x1080	85	60-R
	1920x1200	85	60-R
	1920x1440	85	N/A
	2048x1536	75	N/A
	2560x1600	N/A	N/A

**Note:**

Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

**Note:**

60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections



## Technical Specifications - Graphics

### NVIDIA Quadro NVS 295 Graphics Card

Form Factor	2.731 inches (H) × 6.600 inches (L), Half-Height
Graphics Controller	NVIDIA Quadro NVS 295 Graphics Board
Bus Type	PCI Express x16, Generation 2.0
Memory	256 MB GDDR3 SDRAM unified graphics memory
Connectors	2 DisplayPort Comes with 2 DisplayPort to VGA Adapters <b>Note:</b> When purchased as an after-market option, this comes instead with 2 DisplayPort to DVI-D adapters.
Maximum Resolution	Two DisplayPort outputs drive two digital displays up to 2560 x 1600 Drives DisplayPort enabled digital displays at resolutions up to 2560 × 1600 at 60 Hz with reduced blanking
Display Output	Drives DVI enabled digital displays at resolutions up to 1920 × 1200 at 60 Hz with reduced blanking (through DisplayPort to DVI-D (single link) cable)
Supported Graphics APIs	OpenGL 3.0 DirectX 10.0

### NVIDIA GeForce 310 Graphics Card

Bus type	PCI Express (x16 lanes)
Board display options	Supports two displays via the DisplayPort and DVI connectors

	Specification	Description
Board configuration	Graphics Chip	RV620
	Core clock	750 MHz
	Memory clock	500 MHz
	Frame buffer	512 MB DDR3, 64 bit wide

Audio Support (through HDMI only)	Integrated HD Audio codec supports linear PCM and Dolby® Digital (7.1) audio formats for HDMI output
-----------------------------------	------------------------------------------------------------------------------------------------------

Core power 22 W (max)

Dimensions (H x D) 2.71 in x 6.60 in  
68.90 mm x 167.65 mm

Weight 0.30 lb (134.3 g)

Maximum vertical refresh rate 85 Hz

Display support Integrated 400 MHz RAMDAC

Display max resolution 2560 x 1600 digital, 2048 x 1536 analog



## Technical Specifications - Graphics

	Resolution	Maximum Refresh Rate (Hz)	
		Analog Connection	Digital Connecti
Supported Resolutions	640x480	85	60
	800x600	85	60
	1024x768	85	60
	1280x720	85	60
	1280x1024	85	60
	1440x900	75	60
	1600x1200	85	60
	1680x1050	75	60
	1920x1080	85	60-R
	1920x1200	85	60-R
	1920x1440	85	N/A
	2048x1536	75	N/A
	2560x1600	N/A	60*

\* Only supported when using a dual-link DVI or DP connection.

Note:

Other resolutions may be available but are not recommended as they have not been tested and qualified by HP

Note:

60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections

### Option Kit Contents

NVIDIA GeForce 310 DP PCIe x16 Graphics Card with full height bracket attached  
 DVI to VGA Adapter  
 Software CD with graphics drivers  
 Low profile bracket to convert the card for use in a low profile chassis  
 Warranty documentation

### Compliance Standards

#### EMC Emissions

#### EMC Immunity

FCC Part 15, Subpart B - Unintentional Radiators, Class B Computing Devices for Home & Office Use  
 CISPR22: 1997/EN 55022:1998 - Class B - Limits and methods of measurement of radio disturbance characteristics of Information Technology Equipment  
 Canadian Standard ICES-003 is equivalent to CISPR22  
 Taiwanese Standard BSMI  
 Japanese VCCI  
 Australian C-Tick  
 Korean (MIC)

CISPR 24:1997/EN 55024:1998 - Information Technology Equipment - Immunity Characteristics - Limits and Measurement



## Technical Specifications - Graphics

### ATI Radeon HD 4550 Graphics Card

Bus type	PCI Express x16
Maximum vertical refresh rate	85 Hz
Display support	Integrated 400 MHz RAMDAC
Display max resolution	1900 x 1200 digital, 2048 x 1536 analog
Board display options	Supports two displays via included DMS-59 to dual VGA cable or 2 DVI monitors via optional DMS-59 to dual DVI cable kit part number: DL139A. 4-pin mini-DIN S-video connector for TV output

	Specification	Description
Board configuration	Graphics Chip	RV710
	Core clock	600 MHz
	Memory clock	800 MHz
	Frame buffer	512 MB DDR3, 64 bit wide
Languages supported	24 languages: English, Arabic, Chinese Simplified, Chinese Traditional, Czechoslovakian, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish	

	EMC Emissions	EMC Immunity
Compliance standards	FCC Part 15, Subpart B – Unintentional Radiators, Class B Computing Devices for Home & Office Use	CISPR 24:1997/EN 55024:1998 – Information Technology Equipment – Immunity Characteristics – Limits and Methods of Measurement
	CISPR22: 1997/EN 55022:1998 – Class B – Limits and methods of measurement of radio disturbance characteristics of Information Technology Equipment	
	Canadian Standard ICES-003 is equivalent to CISPR22	
	Taiwanese Standard BSMI	
	Japanese VCCI	
	Australian C-Tick	
	Korean (MIC)	



## Technical Specifications - Graphics

Resolutions Supported	Resolution	Maximum Refresh Rate (Hz)	
		Analog Connection	Digital Connection
	640x480	85	60
	800x600	85	60
	1024x768	85	60
	1280x720	85	60
	1280x1024	85	60
	1440x900	75	60
	1600x1200	85	60
	1680x1050	75	60
	1920x1080	85	60-R
	1920x1200	85	60-R
	1920x1440	85	N/A
	2048x1536	75	N/A
	2560x1600	N/A	N/A

**Note:**

Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

**Note:**

60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections

---

### ATI Radeon HD 4650 Graphics Card

Bus type	PCI Express x16
Maximum vertical refresh rate	85 Hz
Display support	Integrated 400 MHz RAMDAC
Display max resolution	2560 x 1600 digital, 2048 x 1536 analog



## Technical Specifications - Graphics

Resolutions Supported	Resolution	Maximum Refresh Rate (Hz)	
		Analog Connection	Digital Connection
	640x480	85	60
	800x600	85	60
	1024x768	85	60
	1280x720	85	60
	1280x1024	85	60
	1440x900	75	60
	1600x1200	85	60
	1680x1050	75	60
	1920x1080	85	60-R
	1920x1200	85	60-R
	1920x1440	85	N/A
	2048x1536	75	N/A
	2560x1600	N/A	60*

\* Only supported when using a dual-link DVI or DP connection

**Note:**

Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

**Note:**

60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections

**Board display options** Supports two displays via included two DisplayPort and one Dual Link DVI-I connectors.

Specification	Description
---------------	-------------

Graphics Chip	RV635
---------------	-------

**Board configuration**

Core clock	725 MHz
------------	---------

Memory clock	500 MHz
--------------	---------

Frame buffer	1 GB DDR3, 128 bit wide
--------------	-------------------------

**Core power** 56 W



## Technical Specifications - Graphics

**Board display options** Supports two displays via included two DisplayPort and one Dual Link DVI-I connectors.

### EMC Emissions

FCC Part 15, Subpart B - Unintentional Radiators, Class B Computing Devices for Home & Office Use  
CISPR22: 1997/EN 55022:1998 - Class B - Limits and methods of measurement of radio disturbance characteristics of Information Technology Equipment  
Canadian Standard ICES-003 is equivalent to CISPR22  
Taiwanese Standard BSMI  
Japanese VCCI  
Australian C-Tick  
Korean (MIC)

### EMC Immunity

CISPR 24:1997/EN 55024:1998 - Information Technology Equipment - Immunity Characteristics - Limits and Methods of Measurement

### Board configuration

---

#### HP DisplayPort to DVI-D Adapter

**Connectors** DisplayPort and DVI-D single link connector  
**Adapter length** 7.5 in (19.0 cm)  
**Adapter weight** .10 lbs (.05 kg)

---

#### HP DisplayPort to VGA Adapter

**Connectors** DisplayPort and VGA connector  
**Adapter length** 8 in (20 cm)  
**Adapter weight** .1 lbs (.06 kg)  
**Maximum vertical refresh rate** 85 Hz  
**Display support** 162 MHz RAMDAC  
**Display max resolution** 1600x1200



## Technical Specifications - Graphics

Resolutions Supported	Resolution	Max refresh rate
	640x480	85
	800x600	85
	1024x768	85
	1280x720	85
	1280x1024	85
	1440x900	75
	1600x1200	60
	1680x1050	60
	1920x1080	60-R
	1920x1200	60-R

Note:

Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP. Us DisplayPort to VGA Adapter may require an update to the graphics driver installed on your system. To install the most up graphics driver go to: [www.hp.com](http://www.hp.com).

Note:

60-R denotes reduced blanking timings are used. Not all monitors support reduced blanking timing.



## Technical Specifications - Hard Drives

---

### 250-GB 3.5" Hard Disk Drive

<b>Capacity</b>	250,059,350,016 bytes
<b>Rotational Speed</b>	7,200 rpm
<b>Interface</b>	Serial ATA (SATA)
<b>Synchronous Transfer Rate (Maximum)</b>	Up to 3 GB/s (limited by the system SATA controller)
<b>Buffer Size</b>	8 MB
<b>Logical Blocks</b>	488,397,168
<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track:</b> 1.0 ms <b>Average:</b> 8.5 ms <b>Full-Stroke:</b> 18 ms
<b>Height</b> (nominal)	1 in/2.54 cm
<b>Width</b> (nominal)	Media diameter: 3.5 in/8.89 cm Physical size: 4 in/10.2 cm
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)

---

### 500-GB 3.5" Hard Disk Drive

<b>Capacity</b>	500,107,862,016 bytes
<b>Rotational Speed</b>	7,200 rpm
<b>Interface</b>	Serial ATA (SATA)
<b>Synchronous Transfer Rate (Maximum)</b>	Up to 3 GB/s (limited by the system SATA controller)
<b>Buffer Size</b>	16 MB
<b>Logical Blocks</b>	976,773,168
<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	<b>Single Track:</b> 2.0 ms <b>Average:</b> 11 ms <b>Full-Stroke:</b> 21 ms
<b>Height</b> (nominal)	1 in/2.54 cm
<b>Width</b> (nominal)	Media diameter: 3.5 in/8.89 cm Physical size: 4 in/10.2 cm
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)

---

## Technical Specifications - Hard Drives

### 64-GB 2.5" Solid State Drive

Capacity	64 GB
Interface	Serial ATA (SATA)
Architecture	Multi Level Cell (MLC) NAND Flash with wear leveling 10 channel controller
Internal transfer rate	Write speed Up to 220 MB/s Read speed Up to 120 MB/s
Host transfer rate	Ultra DMA mode Up to 150 MB/s
Power	DC power requirement 5 VDC 5%-100 mV ripple p-p Total power consumption <1.12Watt
Dimensions (W x H x D)	2.74 x 0.37 x 4 in/6.98 x 0.95 x 10.2 cm
Weight	0.14 lb/65 g Operating Temperature: 32° to 158° F (0° to 70° C)
Environmental (all conditions, non-condensing)	Relative Humidity: 5% to 95% Maximum Wet Bulb Temperature (operating) 84° F (29° C)

**Note:**

For solid state disk drives, GB means 1 billion bytes. 16GB is the unformatted capacity of this drive before a portion of the drive is reserved for flash management features. Actual capacity varies by content and will be less than 15.8GB.

### 80-GB 2.5" Solid State Drive

Capacity	80-GB
Interface	Serial ATA (SATA)
Architecture	Multi Level Cell (MLC) NAND Flash with wear leveling 10 channel controller
Dimensions (W x H x D)	2.74 x 0.37 x 4 in/6.98 x 0.95 x 10.2 cm
Weight	0.18 lb/80 g
Bandwidth Performance	Sustained Sequential Read: Up to 250 MB/s Sustained Sequential Write: Up to 70 MB/s Random Read: Up to 35K IOPs Random Write: Up to 6.6K IOPs
Latency	Read: 65-ms Write: 85-ms
Power	DC power requirement 5 VDC 5%-100 mV ripple p-p Total power consumption 0.15W (active); 0.075W (idle)
Useful Drive Life	35TB written, up to 20GB/day for 5 years Operating Temperature: 32° to 158° F (0° to 70° C)
Environmental (all conditions, non-condensing)	Relative Humidity: 5% to 95% Maximum Wet Bulb Temperature (operating) 84° F (29° C) Shock: 1,500 G/0.5-ms

**Note:**

For solid state disk drives, GB means 1 billion bytes. 16GB is the unformatted capacity of this drive before a portion of the drive is reserved for flash management features. Actual capacity varies by content and will be less than 15.8GB.



### Technical Specifications - Input/Output Devices

#### HP USB Standard Keyboard

Physical characteristics	Keys	104, 105, 106, 107, 109 layout (depending upon country)
	Dimensions (L x W x H)	18.0 x 6.4 x 0.98 in 45.8 x 16.3 x 2.5 cm
	Weight	2 lb 0.9 kg
	Operating voltage	+ 5VDC $\pm$ 5%
Electrical	Power consumption	50-mA maximum (with three LEDs ON)
	System interface	USB Type A plug connector
	ESD	CE level 4, 15-kV air discharge
	EMI – RFI	Conforms to FCC rules for a Class B computing device
Mechanical	Microsoft® PC 99 – 2001	Functionally compliant
	Languages	38 available
	Keycaps	Low-profile design
	Switch actuation	55-g nominal peak force with tactile feedback
	Switch life	20 million keystrokes (using Hasco modified tester)
	Switch type	Contamination-resistant switch membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	6 ft (1.8 m)
	Microsoft PC 99 –2001	Mechanically compliant
	Acoustics	43-dBA maximum sound pressure level
Environmental	Operating temperature	50° to 122° F (10° to 50° C)
	Non-operating temperature	-22° to 140° F (-30° to 60° C)
	Operating humidity	10% to 90% (non-condensing at ambient)
	Non-operating humidity	20% to 80% (non-condensing at ambient)
	Operating shock	40 g, six surfaces
	Non-operating shock	80 g, six surfaces
	Operating vibration	2-g peak acceleration
	Non-operating vibration	4-g peak acceleration
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	42 in (107 cm) on concrete, 16-drop sequence



## Technical Specifications - Input/Output Devices

Approvals	UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC	
Ergonomic compliance	ANSI HFS 100, ISO 9241-4, and TUVGS	
Kit contents	Keyboard	Installation Guide
	Warranty Card	Safety and Comfort Guide

### HP PS/2 Standard Keyboard

Physical characteristics	Keys	104, 105, 106, 107, 109 layout (depending upon country)
	Dimensions (L x W x H)	18.0 x 6.4 x 0.98 in 45.8 x 16.3 x 2.5 cm
	Weight	2 lb 0.9 kg minimum
	Operating voltage	+ 5VDC $\pm$ 5%
Electrical	Power consumption	50-mA maximum (with three LEDs ON)
	System interface	PS/2 6-pin mini din connector
	ESD	CE level 4, 15-kV air discharge
	EMI – RFI	Conforms to FCC rules for a Class B computing device
	Microsoft® PC 99 – 2001	Functionally compliant
	Languages	38 available
	Keycaps	Low-profile design
	Switch actuation	55-g nominal peak force with tactile feedback
	Switch life	20 million keystrokes (using Hasco modified tester)
	Mechanical	Switch type
Key-leveling mechanisms		For all double-wide and greater-length keys
Cable length		6 ft 1.8 m
Microsoft PC 99 –2001		Mechanically compliant
Acoustics		43-dBA maximum sound pressure level
Operating temperature		50° to 122° F (10° to 50° C)
Non-operating temperature		-22° to 140° F (-30° to 60° C)
Operating humidity		10% to 90% (non-condensing at ambient)
Non-operating humidity	20% to 80% (non-condensing at ambient)	
Operating shock	40 g, six surfaces	



## Technical Specifications - Input/Output Devices

### ENVIRONMENTAL

Non-operating shock	80 g, six surfaces
Operating vibration	2-g peak acceleration
Non-operating vibration	4-g peak acceleration
Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
Drop (in box)	42 in (107 cm) on concrete, 16-drop sequence

### Approvals

UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC

### Ergonomic compliance

ANSI HFS 100, ISO 9241-4, and TUVGS

### Kit contents

Keyboard	Installation Guide
Warranty Card	Safety and Comfort Guide

## HP USB SmartCard Keyboard

Physical characteristics	Keys	104, 105, 106, 107, 109 layout (depending upon country)
	Form factor	USB basic Smart Card keyboard
	Colors	Carbonite/Silver
	Dimensions (H x W x D)	18.2 x 6.3 x 1.3 in 46.3 x 16.1 x 3.3 cm
	Weight	2 lb (0.9 kg) minimum
	Operating voltage	+ 5VDC $\pm$ 5%
	Power consumption	100-mA maximum (with four LEDs ON)
Electrical	System interface	USB Type A plug connector
	ESD	CE level 4, 15-kV air discharge
	EMI - RFI	Conforms to FCC rules for a Class B computing device
Mechanical	Microsoft PC 99 - 2001	Functionally compliant
	Languages	30+ available
	Keycaps	Low-profile design
	Switch actuation	55 g nominal peak force with tactile feedback
	Switch life	20 million keystrokes (using Hasco modified tester)
	Switch type	Contamination-resistant membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	6 ft (1.8 m)
	Microsoft PC 99 - 2001	Mechanically compliant
	Acoustics	43-dBA maximum sound pressure level
Operating temperature	50° to 122° F (10° to 50° C)	
Non-operating temperature	-22° to 140° F (-30° to 60° C)	
Operating humidity	10% to 90% (non-condensing at ambient)	
Non-operating humidity	20% to 80% (non-condensing at ambient)	
	Operating shock	40 g, six surfaces



## Technical Specifications - Input/Output Devices

### environmental

<b>Non-operating shock</b>	80 g, six surfaces
<b>Operating vibration</b>	2-g peak acceleration
<b>Non-operating vibration</b>	4-g peak acceleration
<b>Drop (out of box)</b>	26 in (66 cm) on carpet, six-drop sequence
<b>Drop (in box)</b>	42 in (107 cm) on concrete, 16-drop sequence
<b>Support</b>	All ISO 7816 smart cards
<b>Interface</b>	Reads from and writes to all ISO7816-1, 2, 3, 4 memory and microprocessor smart cards (T=0, T=1)
<b>Chipset</b>	SCM STCII
<b>Standard APIs supported</b>	PC/SC, EMV2000, SET
<b>Power</b>	USB Port Short circuit detection (protects smart card and reader) Power supply compliant with ISO7816 and EMV (5V, 60 mA) Supports 3-V and 5-V cards
<b>Power consumption</b>	250-mA maximum draw (50 mA for the keyboard with three LEDs ON and 200-mA maximum startup current using a high-current, 60-mA smart card)
<b>SMARTCARD function</b>	
<b>Communication</b>	<b>From card</b> Programmable from 9,600 baud to 115,200 baud <b>From computer</b> Up to 38,400 baud
<b>Landing mechanism</b>	<b>Contact device</b> Friction contact <b>Card insertions rating</b> Up to 100,000 insertion cycles
<b>Interface modes</b>	USB communications through USB port SCM protocol Automatic card insertion/removal detection
<b>Reader performance interface</b>	USB connection
<b>Electro-magnetic standards</b>	<b>Europe</b> 89/336/CEE guideline <b>USA</b> USAFCC part 15

### HP PS/2 Optical Mouse

<b>Dimensions</b> (H x L x W)	1.56 x 2.44 x 4.61 in 3.95 x 6.21 x 11.7 cm
<b>Weight</b>	4.44 oz 126 g
<b>Operating temperature</b>	-32° to 104°F 0° to 40° C
<b>Non-operating temperature</b>	-4° to 140°F -20° to 60° C
<b>Operating humidity</b>	10% to 90% (non condensing at ambient)
<b>Non-operating humidity</b>	10% to 90% (non condensing at ambient)

### Environmental



### Technical Specifications - Input/Output Devices

Electrical	Operating shock	40 g, 6 surfaces
	Non-operating shock	80 g, 6 surfaces
	Operating vibration	2 g peak acceleration
	Non-operating vibration	4 g peak acceleration
	Drop (out of box)	80 cm height onto asphalt tile over concrete or equivalent, 5-drop in 5 direction except the cable face
	Operating voltage	5 VDC $\pm$ 10%
	Power consumption	100mA
	System consumption	PS/2 mini-din connector
	ESD	CE level 4, 15 kV air discharge
	EMI-RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC99 - 2001	Functionally compliant
	Resolution	400 $\pm$ 20% DPI
	Tracking speed	10 in/s (25.4 cm/s) maximum
Mechanical	Acceleration	100 in/s/s (2.54 m/s/s)
	Switch actuation	61 g nominal peak force
	Switch life	3,000,000 operations (using Hasco modified tester)
	Switch type	Low force micro-switches
	Tracking mechanism life	155 mi (250 km) at average speed of 10 in/s
	Cable length	6 ft (1.8 m)
	Microsoft PC99 - 2001	Mechanically compliant
	Width	8 mm
Scroll wheel	Diameter	1.01 in (25.6 mm)
	Maximum rotation speed	48 rats/sec
	Switch type	Light force micro-switch
	Switch life	1 million operations
Regulatory approvals	Mechanical life	Minimum 200,000 revolutions
	Compliant	UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC



## Technical Specifications - Input/Output Devices

### HP USB Optical Mouse

<b>Dimensions</b> (H x L x W)	1.5 x 4.5 x 2.5 in 3.8 x 11.6 x 6.3 cm
<b>Weight</b>	0.27 lb 0.12 kg
<b>Cable length</b>	72.8 in 185 cm
<b>System requirements</b>	Microsoft Windows 95, 98, 2000, Me, XP and Vista Available USB port

### HP USB Laser Mouse

<b>Scroll Wheel</b>	24		
<b>Maximum Rotation Speed</b>	48 rats/sec		
<b>Switch Type</b>	wheel		
<b>Switch Life</b>	Button – 3,000,000 Wheel – 1,000,000 times Tilt switch – 500,000 times		
<b>Environmental</b>	<b>Operating Temperature</b>	32° to 104° F 0° to 40° C	
	<b>Non-operating Temperature</b>	-4° to 140° F -20° to 60° C	
	<b>Operating Humidity</b>	10% to 90% (non-condensing at ambient)	
	<b>Non-operating Humidity</b>	20% to 80% (non-condensing at ambient)	
	<b>Operating Shock</b>	40 g, six surfaces	
	<b>Non-operating Shock</b>	80 g, six surfaces	
	<b>Operating Vibration</b>	2-g peak acceleration	
	<b>Non-operating Vibration</b>	4-g peak acceleration	
	<b>Electrical</b>	<b>Operating Voltage</b>	+ 5VDC ± 5%
		<b>Power Consumption</b>	
<b>MTBF</b>		> 150,000 hrs	
<b>ESD</b>		IEC-61000-4-2 criteria B, Contact discharge: +/- 4kV, Air discharge: +/- 8kV	
<b>EMI-RFI</b>		FCC Class B	
<b>PC98</b>	PC 99 Compliant		





## Technical Specifications - Input/Output Devices

Mechanical	Resolution	800dpi
	Tracking Speed	25 cm/sec
	Acceleration	0.5mm
	Switch Actuation	0.6N (60gf)
	Switch Life	Button – 3,000,000 Wheel – 1,000,000 times Tilt switch – 500,000 times
	Cable Length	1850mm
	PC98-99	PC99 compliant
	Regulatory Approvals	UL60950-1, UL 94, UL 746 (A-E), UL 796 TUV/GS: EN 60950-1, EN 60825-1 FCC Class B, UL 1950, cUL, TUV GS, CE, C-tick, VCCI, BSMI, RRL



## Technical Specifications - Optical Storage

### HP Blu-ray Writer Drive

AMO Part Number	AR482AA
Height	5.25-inch, half-height, tray-load
Orientation	Either horizontal or vertical
Interface type	SATA
Disc capacity	50 GB DL or 25 GB standard
Dimensions (W x H x D)	5.9 x 1.7 x 7.5 in 15.0 x 4.4 x 19.0 cm
Weight (max)	2.0 lb 907g

DVD-ROM	8.5GB DL or 4.7GB standard
Blu-ray	50GB DL or 25GB standard
Full Stroke DVD	< 250 ms (seek)
Full Stroke CD	< 210 ms (seek)
Blu-ray	< 275 ms (seek)

(Time to drive ready from tray loading)

### Disc Capacity

BD-ROM (SL/DL)	25S / 28S
BD-R (SL/DL)	25S / 28S
BD-RE (SL/DL)	25S / 28S
DVD-ROM (SL/DL)	18S / 18S
DVD-R (SL/DL)	25S / 25S
DVD-RW	25S
DVD+R (SL/DL)	25S / 25S
DVD+RW	25S
DVD-RAM	45S
CD-ROM	15S

### Startup Time

### CD-ROM Read

### DVD-ROM Read

### Maximum Data Transfer Rates

CD-ROM up to 40X
CD-RW up to 40X
8x CAV
DVD-RAM up to 5X
DVD+RW up to 10X
DVD-RW up to 10X
DVD+R DL up to 8X
DVD-R DL up to 8X
DVD-ROM up to 16X
DVD-ROM DL up to 8X
DVD+R up to 12X
DVD-R up to 12X
BD-ROM up to 6X
BD-ROM DL up to 4.8X



## Technical Specifications - Optical Storage

<b>Power</b>	<b>Blu-ray</b>	BD-R up to 6X BD-R DL up to 4.8X BD-R up to 6X BD-RE SL/DL up to 4.8X
	<b>Source</b>	SATA DC power receptacle
	<b>DC Power Requirement</b>	5 VDC $\pm$ 5%-100 mV ripple p-p 12 VDC $\pm$ 5%-200 mV ripple p-p
	<b>DC Current</b>	5 VDC -1000 mA typical, 1600 mA maximum 12 VDC -600 mA typical, 1400 mA maximum
<b>Environmental</b> (all conditions non-condensing)	<b>Temperature (operating)</b>	41° to 122° F (5° to 50° C)
	<b>Relative Humidity (operating)</b>	10% to 90%
	<b>Maximum Wet Bulb Temperature (operating)</b>	86° F (30° C)

### HP SuperMulti Drive

<b>AMO Part Number</b>	AR630AT	
<b>Height</b>	5.25-inch, half-height, tray-load	
<b>Orientation</b>	Either horizontal or vertical	
<b>Interface type</b>	Serial ATA	
<b>Dimensions (W x H x D)</b>	5.9 x 1.7 x 8.0 in (15.0 x 4.4 x 20.3 cm)	
<b>Weight (max)</b>	2.6 lb (1.2 kg)	
<b>CD Media Read Access</b>	Random	< 120 ms typical
	Full Stroke	< 200 ms typical
<b>DVD Media Read Access</b>	Random	< 130 ms typical
	Full Stroke	< 240 ms typical
<b>CD Media Read Transfer</b>	CD-ROM, CD-R Read	Up to 6000 KB/s (40X)
	CD-RW Read	Up to 4800 KB/s (32X)
	Digital/Analog Audio Playback	Up to 2400 KB/s (16X)
	Digital Audio Extraction (CD-ROM, CD-R)	Up to 6000 KB/s (40X)
	Digital Audio Extraction (CD-RW)	Up to 4800 KB/s (32X)
<b>DVD Media Read Transfer</b>	Video CD Playback	Up to 2400 KB/s (16X)
	DVD-ROM SL Read	Up to 21600 KB/s (16X)
	DVD-ROM DL Read	Up to 10800 KB/s (8X)
	DVD Video Playback	Up to 10800 KB/s (8X)
	DVD Video SL (other than playback)	Up to 21600 KB/s (16X)
	DVD Video DL (other than playback)	Up to 10800 KB/s (8X)



## Technical Specifications - Optical Storage

### Performance

	DVD-R	Up to 21 600 KB/s (16X)
	DVD+R	Up to 21 600 KB/s (16X)
	DVD-RW	Up to 10 800 KB/s (8X)
	DVD-R DL	Up to 10 800 KB/s (8X)
	DVD+RW	Up to 10 800 KB/s (8X)
	CD-R Write	Up to 6 000 KB/s (40X)
	CD-RW	600 KB/s (4X)
CD Media Write Transfer	CD-RW (High speed)	1 500 KB/s (10X)
	CD-RW (Ultra speed)	Up to 3 600 KB/s (24X)
	CD-RW (Ultra speed+)	Up to 4 800 KB/s (32X)
	DVD+R	Up to 21 600 KB/s (16X)
	DVD+R DL (v1.2)	Up to 16 200 KB/s (12X)
	DVD+R DL (v1.1)	Up to 10 800 KB/s (8X)
	DVD+RW (Volume 2 v1.0)	Up to 10 800 KB/s (8X)
	DVD+RW (Volume 1 v1.3)	Up to 5 400 KB/s (4X)
	DVD-R (v2.1 rev. 6.0)	Up to 16 200 KB/s (12X)
DVD Media Write Transfer	DVD-R (v2.1 rev. 4.0)	Up to 21 600 KB/s (16X)
	DVD-R DL (v3.0 rev. 5.0)	Up to 10 800 KB/s (8X)
	DVD-R DL (v3.0 rev. 3.0)	Up to 10 800 KB/s (8X)
	DVD-RW (v1.2 rev. 3.0)	8 100 KB/s (6X)
	DVD-RW (v1.2 rev. 2.0)	Up to 5 400 KB/s (4X)
	DVD-RAM (v2.2 rev. 5.0)	Up to 16 200 KB/s (12X)
	DVD-RAM (v2.2 rev. 2.0)	Up to 6 750 KB/s (5X)

	Media	Read	Write
Media Compatibility	CD-ROM	Yes	No
	CD-R	Yes	No
	CD-RW	Yes	No
	DVD-ROM	Yes	No
	DVD-ROM DL	Yes	No
	DVD-RAM	Yes	No
	DVD+R	Yes	No
	DVD+R DL	Yes	No
	DVD+RW	Yes	No
	DVD-R	Yes	No
	DVD-RW	Yes	No
	DVD-R DL	Yes	No

Power Supply	Source	SATA DC power receptacle	
	DC Power Requirement	5 VDC $\pm$ 5%	100 mV ripple p-p
		12 VDC $\pm$ 5%	200 mV ripple p-p
	5 VDC	< 1000 mA (typical) 1 600 mA (max.)	



### Technical Specifications - Optical Storage

	DC Current	12 VDC	1200 mA (typical) 2000 mA (max.)
		Total Drive Power (Standby Mode)	< 2.5W
<b>Rear Panel</b>	SATA Power Connector, 15-pin SATA Data Connector, 7-pin Markings to identify each connector		
	Temperature (operating)	41° to 122° F (5° to 50° C)	
	Temperature (storage)	-22° F to 140° F (-30° C to 60° C)	
<b>Environmental conditions</b> (all conditions non-condensing)	Relative Humidity	10% to 90%	
	Maximum Wet Bulb Temperature	86° F (30° C)	
	Altitude	0 to 10,171 ft. (0 to 3,100 metres)	
<hr/>			
<b>HP DVD-ROM Drive</b>			
<b>AMO Part Number</b>	AR629AA		
<b>Height</b>	5.25-inch, half-height, tray-load		
<b>Orientation</b>	Either horizontal or vertical		
<b>Interface type</b>	Serial ATA		
<b>Dimensions</b> (W x H x D)	5.9 x 1.7 x 8.0 in (15.0 x 4.4 x 20.3 cm)		
<b>Weight</b> (max)	2.6 lb (1.2 kg)		
	CD Media Read Access	Random Full Stroke	< 120 ms typical < 200 ms typical
	DVD Media Read Access	Random Full Stroke	< 130 ms typical < 240 ms typical
		CD-ROM, CD-R Read	Up to 6000 KB/s (40X)
		CD-RW Read	Up to 4800 KB/s (32X)
		Digital/Analog Audio Playback	Up to 2400 KB/s (16X)
	CD Media Read Transfer	Digital Audio Extraction (CD-ROM, CD-R)	Up to 6000 KB/s (40X)
		Digital Audio Extraction (CD-RW)	Up to 4800 KB/s (32X)
<b>Performance</b>		Video CD Playback	Up to 2400 KB/s (16X)
		DVD-ROM SL Read	Up to 21600 KB/s (16X)
		DVD-ROM DL Read	Up to 10800 KB/s (8X)
		DVD Video Playback	Up to 10800 KB/s (8X)
		DVD Video SL (other than playback)	Up to 21600 KB/s (16X)



## Technical Specifications - Optical Storage

	DVD Media Read Transfer	DVD Video DL (other than playback)	Up to 10800 KB/s (8X)
		DVD-R	Up to 21600 KB/s (16X)
		DVD+R	Up to 21600 KB/s (16X)
		DVD-RW	Up to 10800 KB/s (8X)
		DVD-R DL	Up to 10800 KB/s (8X)
		DVD+RW	Up to 10800 KB/s (8X)
	<b>Media</b>	<b>Read</b>	<b>Write</b>
<b>Media Compatibility</b>	CD-ROM	Yes	No
	CD-R	Yes	No
	CD-RW	Yes	No
	DVD-ROM	Yes	No
	DVD-ROM DL	Yes	No
	DVD-RAM	Yes	No
	DVD+R	Yes	No
	DVD+R DL	Yes	No
	DVD+RW	Yes	No
	DVD-R	Yes	No
	DVD-RW	Yes	No
	DVD-R DL	Yes	No
	Source	SATA DC power receptacle	
<b>Power Supply</b>	DC Power Requirement	5 VDC $\pm$ 5%	100 mV ripple p-p
		12 VDC $\pm$ 5%	200 mV ripple p-p
		5 VDC	<1000 mA (typical) 1600 mA (max.)
	DC Current	12 VDC	1200 mA (typical) 2000 mA (max.)
<b>Rear Panel</b>		Total Drive Power (Standby Mode)	< 2.5W
	SATA Power Connector, 15-pin		
	SATA Data Connector, 7-pin		
	Markings to identify each connector		
<b>Environmental conditions</b> (all conditions non-condensing)	Temperature (operating)	41° to 122° F (5° to 50° C)	
	Temperature (storage)	-22° F to 140° F (-30° C to 60° C)	
	Relative Humidity	10% to 90%	
	Maximum Wet Bulb Temperature	86° F (30° C)	
	Altitude	0 to 10,171 ft. (0 to 3,100 metres)	



## Technical Specifications - Removable Storage

### HP 22-n-1 Media Card Reader plus 1394 Media Card Reader

USB Interface	USB 2.0 High-speed interface  <i>Note:</i> Requires the USB cable to be connected to the internal USB 2.0 port or a USB 2.0 PCI card.
1394 Interface	Two IEEE-1394a external ports; 1 IEEE-1394a internal port (connects to the pass through cable on the media card reader)  Supports hardware ECC (Error Correction Code) function  Supports hardware CRC (Cyclic Redundancy Check) function  Supports MS 4-bit parallel transfer mode  Supports MS-PRO 4-bit parallel transfer mode
Advance protocol support	Supports MS PRO-HG Duo 4-bit parallel transfer mode  Supports SD 4-bit parallel transfer mode  Supports high-speed 50Mhz SD 4-bit card (version 2.0)  Supports high-speed 52Mhz MMC 8-bit card (version 4.2)  Supports CF v4.0 with PIO mode 6 and Ultra DMA mode  CompactFlash Type I  CompactFlash Type II  Microdrive  MultiMediaCard (MMC)  Reduced Size MultiMediaCard (RS MMC)  MultiMediaCard 4.2 (MMC Plus, including MMC Plus HC)  Reduced Size MultiMediaCard 4.2 (MMC Mobile, including MMC Mobile HC)  Secure Digital Card (SD)  Secure Digital High Capacity (SDHC)  miniSD  miniSD High Capacity
Supported media type	Micro SD (T-Flash)  Micro SD HC  Memory Stick  Memory Stick Select  Memory Stick Duo (MS Duo)  Memory Stick PRO (MS PRO)



## Technical Specifications - Removable Storage

Memory Stick PRO Duo (MS PRO Duo)

Memory Stick PRO-HG Duo

MagicGate Memory Stick (MG)

MagicGate Memory Stick Duo

xD-Picture Card

Supported media type with card adapter

Memory Stick Micro (M2)

MMC Micro

Environmental

**Operational Environmental Extremes**

Test Parameters/Conditions - Power applied, unit operating on system  $\pm 5\%$

nominal supply voltage.

10°C 10% R.H. = 24 hours

10°C 90% R.H. = 24 hours

20°C 90% R.H. = 24 hours

30°C 90% R.H. = 24 hours

40°C 90% R.H. = 24 hours

50°C 90% R.H. = 24 hours

50°C 10% R.H. = 24 hours

**Storage Environmental Extremes**

Test Parameters/Conditions

140°F (60°C) @ 80% R.H. for 96 hours

-22°F (-30°C) @ 20% R.H. for 48 hours

No power applied

Delta °C < 1.0°C/min

Delta % R.H. < 1.5% R.H./min

Approvals

USB-IF, WHQL, Compliant with USB Mass Storage Class Bulk only Transport Specification Rev. 1.0

Compliant Intel Front Panel I/O Connectivity Design Guide V. 1.3

FCC, CE, BSMI, C-Tick, VCCI, MIC, cUL, TUV-T





### Technical Specifications - Environmental Data

#### Eco-Label Certifications & declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- US ENERGY STAR ®
- IT ECO declaration
- EPEAT Gold where HP registers commercial desktop products. See <http://www.epeat.net> for registration status in your country.

#### Small Form Factor

Energy Consumption (typically configured)	115 VAC	230 VAC	100 VAC
Normal Operation	39.787 W	39.547 W	39.865 W
Sleep (Energy Star low power mode)	3.2283 W	3.4659 W	3.2186 W
Off	1.0477 W	1.2128 W	1.0345 W

Heat Dissipation (typically configured)*	115 VAC	230 VAC	100 VAC
Normal Operation	136 BTU/hr	135 BTU/hr	136 BTU/hr
Sleep	11 BTU/hr	12 BTU/hr	11 BTU/hr
Off	4 BTU/hr	4 BTU/hr	4 BTU/hr

\* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

#### Declared Noise Emissions

(in accordance with ISO 7779 and ISO 9296)

System Fan Off	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Idle	3.7	27
Fixed Disk (random writes)	3.7	27

#### Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

- Mercury greater the 5ppm by weight
- Cadmium greater than 10ppm by weight

#### Battery Size

CR2032 (coin cell)

#### Battery Type

Lithium

#### Additional Information

This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive – 2002/95/EC.

This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.

This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).



## Technical Specifications - Environmental Data

This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold where HP registers commercial desktop products. See <http://www.epeat.net> for registration status in your country.

Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.

This product contains 0% post consumer recycled plastic (by wt.)

This product is 95.1% recyclable when properly disposed of at end of life.

### Packaging Materials

External	Corrugated Carton – 1700 g
Internal	EPE – Expanded Polyethylene – 198 g Polyethylene low density foam – 160 g

The Corrugated Carton packaging material is made from 100% recycled content.  
The EPE – Expanded Polyethylene packaging material is made from 100% recycled content  
The Polyethylene low density foam packaging material is made from 100% recycled content

## Convertible Minitower

<b>Energy Consumption</b> (typically configured)	115 VAC	230 VAC	100 VAC
Normal Operation	46.9450 W	47.0125 W	46.5123 W
Sleep (Energy Star low power mode)	3.7745 W	3.7250 W	3.6882 W
Off	0.7562 W	0.8895 W	0.7751 W
<b>Heat Dissipation</b> (typically configured)*	115 VAC	230 VAC	100 VAC
Normal Operation	161 BTU/hr	161 BTU/hr	159 BTU/hr
Sleep	13 BTU/hr	13 BTU/hr	13 BTU/hr
Off	3 BTU/hr	3 BTU/hr	3 BTU/hr

\* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

## Technical Specifications - Environmental Data

### Declared Noise Emissions

(in accordance with ISO 7779 and ISO 9296)

System Fan Off	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Idle	3.8	21
Fixed Disk (random writes)	3.8	21

### Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

- Mercury greater the 5ppm by weight
- Cadmium greater than 10ppm by weight:

### Battery Size

CR2032 (coin cell)

### Battery type

Li-Ion

### Additional Information

This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive – 2002/95/EC.

This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.

This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).

This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold where HP registers commercial desktop products. See <http://www.epeat.net> for registration status in your country.

Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.

This product contains 0% post consumer recycled plastic (by wt.)

This product is 90% recyclable when properly disposed of at end of life.

### Packaging Materials

External Corrugated 2550 g

Internal Polyethylene high density 160 g

The corrugated packaging material is made from 37% recycled content. The Polyethylene high density packaging material is made from 100% recycled content.

## All Models

### Reduction in Hazardous Substances (RoHS) Compliance

Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis. By July 1, 2006, RoHS substances will be virtually eliminated (virtually = to levels below legal limits) for all HP electronic products subject to the RoHS Directive, except where it is widely recognized that there is no technically feasible alternative (as indicated by an exemption under the EU RoHS Directive).

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at:



### Technical Specifications - Environmental Data

[http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen\\_specifications.html](http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html)):

#### Material Usage

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)
- Nickel finishes that release greater than 0.5 micro-grams/cm<sup>2</sup>/week, measured according to EN 1811:1998, are not used on any product surface designed to be frequently handled or touched by users.

HP follows these guidelines to decrease the environmental impact of product packaging:

#### Packaging

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

#### End-of-life Management and Recycling

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

For more information about HP's commitment to the environment:  
Global Citizenship Report  
<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>



## Technical Specifications - Environmental Data

### Hewlett-Packard Corporate Environmental Information

Eco-label certifications

<http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html>

ISO 14001 certificates:

<http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html>

---

Copyright © 2011 Hewlett-Packard Development Company, L.P.

All rights reserved. Microsoft, Windows, Windows 7, and Windows Vista are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. Intel, Core, and Pentium are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a registered trademark of Bluetooth SIG, Inc., in the U.S. and other countries. All other product names mentioned herein may be trademarks of their respective companies.

The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

