

Digital Blood Pressure Monitor

Model UA-774

Instruction Manual Original

Manuel d'instructions Traduction

Manual de Instrucciones Traducción

> Manuale di Istruzioni Traduzione

使用手册 翻譯



╂

L S L

S M S

FRAN(

1WMPD4000734F

Contents

Dear Customers	1
Preliminary Remarks	1
Precautions	
Parts Identification	3
Symbols	4
Using The Monitor	5
Installing / Changing The Batteries	5
Connecting The Air Hose	5
Connecting The AC Adapter	5
Selecting The Correct Cuff Size	6
Applying The Arm Cuff	7
How To Take Proper Measurements	7
Measurement (Operation)	
After Measurement	
Measurements	8
Normal Measurement With Storing Data	8
Measurement With The Desired Systolic Pressure	9
	9
Operation Mode	0
WHO Classification Indicator	0
Pressure Bar Indicator 1	0
What Is An Irregular Heartbeat?	1
About Blood Pressure	1
What Is Blood Pressure?	1
What Is Hypertension And How Is It Controlled?	1
Why Measure Blood Pressure At Home?	1
WHO Blood Pressure Classification	1
Blood Pressure Variations1	2
	2
	3
Technical Data1	3

Dear Customers

Congratulations on purchasing a state-of-the-art A&D blood pressure monitor, one of the most advanced monitors available today. Designed for ease of use and accuracy, this device will facilitate your daily blood pressure regimen. **We recommend that you read through this manual carefully before using the device for the first time.**

Preliminary Remarks

- □ This device conforms to the European Directive 93/42 EEC for Medical Products. This is made evident by the C€0123 mark of conformity. (0123: The reference number to the involved notified body)
- The device is designed for use on adults only, not newborns or infants.
- □ Environment for use: The device is for use in the home healthcare environment.
- □ This device is designed to measure blood pressure and pulse rate of people for diagnosis.

Precautions

- Precision components are used in the construction of this device. Extremes in temperature, humidity, direct sunlight, shock or dust should be avoided.
- □ Clean the device and cuff with a dry, soft cloth or a cloth dampened with water and a neutral detergent. Never use alcohol, benzene, thinner or other harsh chemicals to clean the device or cuff.
- □ Avoid tightly folding the cuff or storing the hose tightly twisted for long periods, as such treatment may shorten the life of the components.
- □ The device and cuff are not water-resistant. Prevent rain, sweat and water from soiling the device and cuff.
- Measurements may be distorted if the device is used close to televisions, microwave ovens, cellular telephones, X-ray or other devices with strong electrical fields.
- Used equipment, parts and batteries are not treated as ordinary household waste, and must be disposed of according to the applicable local regulations.
- □ When the AC adapter is used, make sure that the AC adapter can be readily removed from the electrical outlet when necessary.
- □ When reusing the device, confirm that the device is clean.
- □ Do not modify the device. It may cause accidents or damage to the device.
- To measure blood pressure, the arm must be squeezed by the cuff hard enough to temporarily stop blood flow through the artery. This may cause pain, numbness or a temporary red mark to the arm. This condition will appear especially when measurement is repeated successively. Any pain, numbness, or red marks will disappear with time.

Contraindications

The following are precautions for proper use of the device.

- Do not apply the cuff to an arm with another medical electrical equipment attached. The equipment may not function properly.
- People who have a severe circulatory deficit in the arm must consult a doctor before using the device, to avoid medical problems.
- Do not self-diagnose the measurement results and start treatment by yourself. Always consult your doctor for evaluation of the results and treatment.
- □ Do not apply the cuff on an arm with an unhealed wound.
- Do not apply the cuff on an arm receiving an intravenous drip or blood transfusion. It may cause injury or accidents.
- Do not use the device where flammable gases such as anesthetic gases are present. It may cause an explosion.
- Do not use the device in highly concentrated oxygen environments, such as a high-pressure oxygen chamber or an oxygen tent. It may cause a fire or explosion.



	Symbols	
Symbols	Function / Meaning	Recommended Action
Ċ	Standby and Turn the device on.	
	Battery installation guide	
	Direct current	
SN	Serial number	
2010	Date of manufacture	
	Type BF: Device, cuff and tubing are designed to provide special protection against electrical shocks.	
•	The indicator that appears while measurement is in progress. It blinks when the pulse is detected.	Measurement is in progress. Remain as still as possible.
((\))	Irregular Heartbeat indicator. (I.H.B.) The indicator that appears when an irregular heartbeat or any excessive body movement is detected during the measurement.	
M	Previous measurements stored in memory of each button.	
E Full Battery	The battery power indicator during measurement.	
Low Battery	The battery power is low when it blinks.	Replace all batteries with new ones, when the indicator blinks.
	Unstable blood pressure due to movement during the measurement.	Try the measurement again. Remain very still during the measurement.
Err	The systolic and diastolic values are within 10 mmHg of each other. The pressure value did not increase during inflation.	Check the air hose connecter plug and cuff.
Err [UF	The cuff is not applied correctly.	Apply the cuff correctly, and try the measurement
Err PUL. DISPLAY ERROR	The pulse is not detected correctly.	again.
SYS.	Systolic blood pressure in mmHg	
DIA.	Diastolic blood pressure in mmHg	
PUL./min	Pulse per minute	
CE 0123	EC directive medical device label	
X	WEEE label	
	Manufacturer	
EC REP	EU-representative	
6	Refer to instruction manual/booklet	
	Class II device	
⊖€⊕	Polarity of DC jack	

Using The Monitor

Installing / Changing The Batteries

- 1. Slide the battery cover up to open it.
- 2. Remove the used batteries and insert new batteries into the battery compartment as shown, taking care that the polarities (+) and (-) are correct.
- 3. Slide the battery cover down to close it. Use only R6P, LR6 or AA batteries.



CAUTION

- Insert the batteries as shown in the battery compartment. If installed incorrectly, the device will not work.
- □ When ^c (LOW BATTERY mark) blinks in the display, replace all batteries with new ones. Do not mix old and new batteries. It may shorten the battery life, or cause the device to malfunction.
- □ □ □ (LOW BATTERY mark) does not appear when the batteries are drained.
- The battery life varies with the ambient temperature and may be shorter at low temperatures.
- Use the specified batteries only. The batteries provided with the device are for testing the device performance and may have a limited life.
- Remove the batteries if the device is not to be used for a long time.
 The batteries may leak and cause a malfunction.
- □ The stored data are cleared when the batteries are removed.

Connecting The Air Hose

Insert the air connector plug into the air socket firmly.



Connecting The AC Adapter

Insert the AC adapter plug into the DC jack. Next, connect the AC adapter to an electrical outlet.

Use the specified AC adapter. (Refer to page 14.)





Using The Monitor

Selecting the Correct Cuff Size

Using the correct cuff size is important for an accurate reading. If the cuff is not the proper size, the reading may yield an incorrect blood pressure value.

- □ The arm size is printed on each cuff.
- □ The index ▲ and proper fit range, on the cuff, tell you if you are applying the correct cuff. (Refer to "Symbols that are printed on the cuff".)
- □ If the index ▲ points outside of the range, contact your local dealer to purchase a replacement cuff.
- □ The arm cuff is a consumable. If it becomes worn, purchase a new one.

Arm Size	Recommended Cuff Size	Catalog Number
32 cm to 45 cm	Large adult cuff	CUF-D-LA
22 cm to 32 cm	Adult cuff	CUF-D-A

Arm size: The circumference of the biceps.

Note: Model UA-774 is not designed for using a small adult cuff.

Symbols that are printed on the cuff

Symbols	Function/Meaning	Recommended Action
•	Artery position mark	Set the \bullet mark on the artery of the upper arm or in line with the ring finger on the inside of the arm.
	Index	
REF	Catalog number	
A	Proper fit range for the adult cuff. It's printed on the adult cuff.	
	Range to use the large adult cuff. Over range printed on the adult cuff.	Use the large adult cuff instead of the adult cuff.
	Proper fit range for the large adult cuff. It's printed on the large adult cuff.	
$\langle S \rangle$	Under range printed on the adult cuff.	
$\langle A \rangle$	Range to use the adult cuff. It's printed on the large adult cuff.	Use the adult cuff instead of the large adult cuff.
LOT	Lot number	



Using The Monitor

Applying The Arm Cuff

- Wrap the cuff around the upper arm, about 1-2 cm above the inside of the elbow, as shown.
 Place the cuff directly against the skin, as clothing may cause a faint pulse, and result in a measurement error.
- 2. Constriction of the upper arm, caused by tightly rolling up a shirtsleeve, may prevent accurate readings.
- 3. Confirm that the index ▲ points within the proper fit range.



How To Take Proper Measurements

For the most accurate blood pressure measurement:

- Sit comfortably on a chair. Rest your arm on the table. Do not cross your legs. Keep your feet on the floor and straighten your back.
- □ Relax for about five to ten minutes before measurement.
- □ Place the center of the cuff at the same height as your heart.
- □ Remain still and keep quiet during measurement.
- Do not measure immediately after physical exercise or a bath. Rest for twenty or thirty minutes before taking the measurement.
- □ Try to measure your blood pressure at the same time every day.

Measurement (Operation)

During measurement, it is normal for the cuff to feel very tight.

Select a measurement mode (operation of the device).

Normal measurement with storing data : Press the START1 or START2 button. Unrecorded measurement : Press both START buttons simultaneously. Recalling data :Press and hold the START1 or START2 button to recall data. Clearing data :Remove the batteries and re-install them.

After Measurement

After the measurement has completed, remove the cuff and record your data, then press the START 1 or START 2 button to turn off the power.

Note: The device has an automatic power shut-off function, which turns the power off approximately one minute after measurement.

Allow at least three minutes between measurements on the same person.

Measurements

- □ Model UA-774 is designed to detect the pulse and to inflate the cuff to a systolic pressure level automatically.
- □ If your systolic pressure is expected to exceed 230 mmHg, read "Measurement with the desired systolic pressure" on the next page.
- □ Model UA-774 can store the last thirty sets of data for each button. We recommend that if two people regularly use the device, one uses the <u>START 1</u> button and the other uses <u>START 2</u> button, to prevent confusion over stored data.

Normal Measurement With Storing Data

- 1. Place the cuff on the arm (preferably the left arm). Sit quietly during measurement.
- 2. Press the START 1 (or START 2) button. The average blood pressures and last data number are displayed briefly. Then current pressure is displayed, as the measurement begins. The cuff starts to inflate. It is normal for the cuff to feel very tight. A pressure bar indicator is displayed during measurement.
- Note: If you wish to stop inflation at any time, press either START button again.
- 3. When inflation is complete, deflation starts automatically and the ♥ (heart mark) blinks, indicating that the measurement is in progress. Once the pulse is detected, the mark blinks with each pulse beat.
- Note: If an appropriate pressure is not obtained, the device starts to inflate again automatically.
- 4. When the measurement is complete, the systolic and diastolic pressure readings and pulse rate are displayed and stored. The cuff exhausts the remaining air and deflates completely.
- 5. Press either START button again to turn off the power.
- Note: Model UA-774 is provided with an automatic power shut-off function. Allow at least three minutes between measurements on the same person.



Measurements

Measurement With The Desired Systolic Pressure

- □ If your systolic pressure is expected to exceed 230 mmHg, use this procedure.
- 1. Place the cuff on the arm (preferably the left arm).
- 2. Press and hold the START 1 (or START 2) button to display the last data number.
- 3. Press and hold the <u>START 1</u> (or <u>START 2</u>) button again until a number about 30 to 40 mmHg higher than your expected systolic pressure appears.
- 4. Release the START 1 (or START 2) button to start measurement, when the desired number is reached. Then continue to measure your blood pressure as described on the previous page.



Notes For Proper Measurement

- □ Sit down in a comfortable position. Place the arm to be used for the measurement on a table or other support so that the center of the cuff will be at the same height as your heart.
- Relax for about five to ten minutes before taking a measurement. If you are excited or depressed by emotional stress, the measurement will reflect this stress as a higher (or lower) than normal blood pressure reading and the pulse reading will usually be faster than normal.
- Your blood pressure varies constantly, depending on what you are doing and what you have eaten. What you drink can have a very strong and rapid effect on your blood pressure.
- □ This device bases its measurements on the heartbeat. If you have a very weak or irregular heartbeat, the device may have difficulty determining your blood pressure.
- □ Should the device detect a condition that is abnormal, it will stop the measurement and display an error symbol. Refer to page 4.
- Model UA-774 is intended for use by adults only. Consult with your physician before using this device on a child. A child should not use this device unattended.

Operation Mode

1. Normal measurement with storing data (Refer to page 8)

Press the START 1 (or START 2) button. Blood pressure is measured and data is stored within the device. The device can store the last thirty sets of data for each button. We recommend that if two people regularly use the device, one uses the START 1 button and the other uses START 2 button.

Recalling data

Press and hold the <u>START 1</u> (or <u>START 2</u>) button to recall the data. Stored data are automatically displayed in order from the last data.

□ Clearing data

Remove batteries to clear all data. Re-install them again.

2. **Unrecorded measurement** *(Guest mode)* Press both of the <u>START 1</u> and <u>START 2</u> buttons at once. An unrecorded measurement is started.

3. Measurement with the desired systolic pressure

Refer to the previous page for the measurement with the desired systolic pressure.

WHO Classification Indicator

Each of the six segments of the bar indicator corresponds to the WHO blood pressure classification described on the next page.

WHO Classification Indicator

- Severe hypertension
- Moderate hypertension
- Mild hypertension
 - High normal
 - Normal
 - Optimal

The indicator displays a segment, based on the current data, corresponding to the WHO classification.

Moderate

hypertension

Example:

Pressure Bar Indicator





What Is An Irregular Heartbeat?

Model UA-774 blood pressure monitor provides a blood pressure and pulse rate measurement even when an irregular heartbeat occurs. An irregular heartbeat is defined as a heartbeat that varies by 25% from the average of all heartbeats during the blood pressure measurement. It is important that you are relaxed, remain still and do not talk during measurements.

Note: We recommend contacting your physician if you see this () indicator frequently.

About Blood Pressure

What Is Blood Pressure?

Blood pressure is the force exerted by blood against the walls of the arteries. Systolic pressure occurs when the heart contracts. Diastolic pressure occurs when the heart expands. Blood pressure is measured in millimeters of mercury (mmHg). One's natural blood pressure is represented by the fundamental pressure, which is measured first thing in the morning while one is still at rest and before eating.

What Is Hypertension And How Is It Controlled?

Hypertension, an abnormally high arterial blood pressure, if left unattended, can cause many health problems including stroke and heart attack. Hypertension can be controlled by altering lifestyle, avoiding stress, and with medication under a doctor's supervision. To prevent hypertension or to keep it under control:

□ Do not smoke

- \Box Exercise regularly
- □ Reduce salt and fat intake
- □ Have regular physical checkups

□ Maintain proper weight

Why Measure Blood Pressure At Home?

Blood pressure measured at a clinic or doctor's office may cause apprehension and can produce an elevated reading, 25 to 30 mmHg higher than that measured at home. Home measurement reduces the effects of outside influences on blood pressure readings, supplements the doctor's readings and provides a more accurate, complete blood pressure history.

WHO Blood Pressure Classification

Standards to assess high blood pressure, without regard to age, have been established by the World Health Organization (WHO), as shown in the chart at the right.





Blood Pressure Variations

An individual's blood pressure varies greatly on a daily and seasonal basis. It may vary by 30 to 50 mmHg due to various conditions during the day. In hypertensive individuals, variations are even more pronounced. Normally, the blood pressure rises while at work or play and falls to its lowest levels during

sleep. So, do not be overly concerned by the results of one measurement. Take measurements at the same time dav using the procedure everv described in this manual to get to know your normal blood pressure. Regular readings give а more comprehensive blood pressure history. Be sure to note date and time when recording vour blood pressure. Consult your doctor to interpret your blood pressure data.



Problem	Possible Reason	Recommended Action
Nothing appears in the	Batteries are drained.	Replace all batteries with new ones.
display, even when the power is turned on.	Battery polarities are not in the correct position.	Reinstall the batteries with their negative and positive end matching those indicated in the battery compartment.
The cuff does not inflate.	Battery voltage is too low. (LOW BATTERY mark) blinks. If the batteries are drained completely, the mark does not appear.	Replace all batteries with new ones.
	The cuff is not applied properly.	Apply the cuff correctly.
The unit does not measure. Readings are too high or too low.	You moved your arm or body during the measurement.	Make sure you remain very still and quiet during the measurement.
	The cuff position is not correct.	Sit comfortably and still. Ensure that the cuff is the same level as the heart.
		If you have a very weak or irregular heart beat, the device may have difficulty in determining your blood pressure.

Troubleshooting

Other	The value is different from that measured at a clinic or doctor's office.	See "Why measure blood pressure at home?".
Other		Remove the batteries. Re-install them properly and try the measurement again.

Note: If the actions described above do not solve the problem, contact the dealer. Do not attempt to open or repair this product, as any attempt to do so will make your warranty invalid.

Maintenance

Do not open the device. It uses delicate electrical components and an intricate air unit that could be damaged. If you cannot fix the problem using the troubleshooting instructions, request service from your dealer or from the A&D service group. The A&D service group will provide technical information, spare parts and units to authorized dealers.

The device was designed and manufactured for a long service life. However it is generally recommended to have the device inspected every 2 years, to ensure proper functioning and accuracy. Please contact either your authorized dealer or A&D for maintenance.

Technical Data

Туре	UA-774	
Measurement method	Oscillomet	tric measurement
Measurement range		20 - 280 mmHg 40 - 200 beats / minute
Measurement accuracy		±3 mmHg ±5%
Power supply		atteries (R6P, LR6 or AA) or er (TB-233) (Not included)
Number of measurements	Approx. 450 measurements, when AA alkaline batteries are used, with pressure value of 180 mmHg at room temperature of 23°C	
Classification	Internally powered ME equipment (Supplied by batteries) / Class II (Supplied by adapter) Continuous operation mode	
Clinical test	According	to ANSI / AAMI SP-10 1992
EMC	IEC 60601	-1-2: 2007
Data memory	Last 30 me	easurements for each START button

Operating conditions	+10°C to +40°C / 15%RH to 85 %RH 800 hPa to 1060 hPa
Transport / Storage conditions	-10°C to +60°C / 15%RH to 85 %RH
Dimensions	Approx. 147 [W] x 64 [H] x 110 [D] mm
Weight	Approx. 300 g, excluding batteries
Applied part	Cuff Type BF 🖈
Useful life	Device: 5 years (when used six times a day) Cuff: 2 years (when used six times a day)
Accessory AC adapter	The adapter is to connect the blood pressure monitor to a power source at home.
TB-233	Please contact your local A&D dealer for purchasing. The AC adapter is required to be inspected or replaced periodically.
TB-233C	Input: 100-240V Output: 6V 500mA ⊖€⊕ □ ப ⊑
TB-233BF	Input: 240V Output: 6V \longrightarrow 500mA $\ominus \bullet \bullet \oplus \Box \bigtriangleup$ $\square \Box \Box$ $\square \Box$ \square

Accessories sold separately

Cuff

Catalog Number	Cuff Size	Arm Size
CUF-D-LA	Large adult cuff	32 cm to 45 cm
CUF-D-A	Adult cuff	22 cm to 32 cm

AC adapter

Catalog Number	Plug
TB-233C	Type C
TB-233BF	Type BF

Note: Specifications are subject to change without prior notice.

EMC table information is listed on our website:

http://www.aandd.jp/products/manual/medical/emc_acadapter_en.pdf



A&D Company, Limited

Asahi 1-243, Kitamoto-shi, Saitama364-8585, JAPANTelephone: [81] (48) 593-1111Fax: [81] (48) 593-1119

EC REP A&D INSTRUMENTS LIMITED

Unit 24/26 Blacklands Way, Abingdon Business Park, Abingdon, Oxfordshire OX14 1DY United Kingdom Telephone: [44] (1235) 550420 Fax: [44] (1235) 550485

A&D ENGINEERING, INC.

1756 Automation Parkway, San Jose, California 95131, U.S.A. Telephone: [1] (408) 263-5333 Fax: [1] (408)263-0119

A&D AUSTRALASIA PTY LTD

32 Dew Street, Thebarton, South Australia 5031, AUSTRALIA Telephone: [61] (8) 8301-8100 Fax: [61] (8) 8352-7409