ECX800

Intel [®] Core[™] Duo/Solo 945GM ECX Embedded Board

USER'S MANUAL

Version 1.0

Acknowledgments

Award is a registered trademark of Award Software International, Inc.

PS/2 is a trademark of International Business Machines Corporation.

Intel and Intel® Core Duo/Solo processors are registered trademarks of Intel Corporation.

Microsoft Windows is a registered trademark of Microsoft Corporation.

Winbond is a registered trademark of Winbond Electronics Corporation.

All other product names or trademarks are properties of their respective owners.

Table of Contents

Introduction	1
Product Description	2
ECX800 SpecificationsBoard Dimensions	
Installations	5
Installing the Memory Setting the Jumpers Connectors on ECX800	7
BIOS Setup	21
Drivers Installation	45
Intel Chipset Software Installation UVGA Drivers Installation	
AC97 Codec Audio Driver Installation LAN Drivers Installation	
Appendix	53
A. I/O Port Address Map B. Interrupt Request Lines (IRQ) C. Watchdog Timer Configuration	

This page is intentionally left blank.

Introduction

Product Description

The ECX800 ECX (Embedded Compact Extended) board incorporates the Mobile Intel® 945GM Express Chipset for Embedded Computing, consisting of the Intel® 945GM Graphic Memory Controller Hub (GMCH) and Intel® I/O Controller Hub 7-M (ICH7-M), an optimized integrated graphics solution with a 533MHz and 667MHz front-side bus. Dimensions of the board are 105mm x 146mm.

The integrated powerful 3D graphics engine, based on Intel® Graphics Media Accelerator 950 (Intel® GMA 950) architecture, operates at core speeds of up to 400 MHz. It features a low-power design, is validated with the Intel® Core Duo/Solo on 65nm process. With DDR2 667MHz SO-DIMM socket on board, the board supports up to 2GB of DDR2 system memory.

Intel® Graphics supports a unique intelligent memory management scheme called Dynamic Video Memory Technology (DVMT). DVMT handles diverse applications by providing the maximum (224MB) availability of system memory for general computer usage, while supplying additional graphics memory when a 3D-intensive application requests it. The Intel GMA 950 graphics architecture also takes advantage of the high-performance Intel processor. Intel GMA 950 graphics supports Dual Independent Display technology.

The main features of the board are:

- Supports Intel® CoreTM Duo/Solo processors
- Supports up to 667MHz FSB
- One DDR2 SDRAM SO-DIMM, Max. 2GB memory
- Onboard Marvell PCI-Express Gigabit LAN
- Intel® 945GM Express VGA for CRT / LVDS
- 1x SATA, 4x USB 2.0, 2x COM, Watchdog timer,
- Region C Type III (LPC, PCI, 1xPCI-E(x1) and SDVO-C) expansion slot.

Checklist

Your ECX800 package should include the items listed below.

- The ECX800 ECX embedded board
- This User's Manual
- 1 CD containing chipset drivers and flash memory utility




THE ECX800 ECX SINGLE BOARD COMPUTER

ECX800 Specifications

Zenoo spee.			
Form Factor	ECX		
CPU Type	Intel Core Duo/Solo Mobile Processors		
CPU Voltage	0.700V ~ 1.5V		
System Speed	Up to 1.66GHz or above		
CPU Operate Frequency	533MHz/667MHz FSB		
Cache	2MB		
Green /APM	APM1.2		
CPU Socket	BGA CPU on board / mPGA 478MT Socket		
Chipset	INTEL 945GM Chipset		
	GMCH: 82945GM 1466-pin FCBGA		
	ICH7M: 82801GBM 652-pin mBGA FWH		
BIOS	Award BIOS, support ACPI Function		
Memory	DDR2 667/533 SO-DIMM x1 (w/o ECC function), Max. 2GB		
VGA/TV	945GM built-in, supports CRT/ S-VIDEO		
LVDS LCD PANEL	945GM built-in, supports 18+18 bits, single or dual channel		
	LVDS		
LAN	Marvell 88E8053 PCI Express Gigabit LAN controller x1		
USB (Universal Serial	ICH7M built-in USB 2.0 host controller, support 4 ports		
Bus)			
Serial ATA Ports	ICH7M built-in SATA controller, supports 1 ports		
Parallel IDE	ICH7M built-in one channel Ultra DMA 33/66/100,CF		
Audio	ICH7M Built-in Audio controller + AC97 Codec ALC655 w/ 6		
	channels (Line-out, Line-in, Mic.), SPDIF-OUT		
LPC I/O	W83627EHF: COM1, COM2 (RS232), LPT1, Slim FDC		
	1.44MB, IrDA x1 & Hardware monitor (3 thermal inputs, 4		
	voltage monitor inputs, 1 fan Header)		
Digital IO	4 in & 4 out		
Keyboard/Mouse	Supports PS/2 Keyboard/Mouse		
Connector			
Expansion Region	Region C Type III also provides one PCI Express x 1, LPC, PCI,		
	SDVO		
Edge Connector	PS/2 Connector x1 for keyboard/mouse		
	Gigabit LAN RJ-45 Dual USB stack connector		
	I Dual LISB stack connector		
	DB9 x1 for COM 1		
	DB9 x1 for COM 1 DB15 x1 for VGA		
On Board	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out		
On Board Header/Connector	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1		
On Board Header/Connector	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1		
	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2		
	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1		
	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2 26 pins film header x1 for Slim Floppy@ solder side		
	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2 26 pins film header x1 for Slim Floppy@ solder side CF Connector x1 @ solder side		
	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2 26 pins film header x1 for Slim Floppy@ solder side CF Connector x1 @ solder side 10 pins pin-headerx1 for Digital I/O 8 pins pin-header x 1 for USB 3,4 5 pins pin-header x 1 for IrDA		
	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2 26 pins film header x1 for Slim Floppy@ solder side CF Connector x1 @ solder side 10 pins pin-headerx1 for Digital I/O 8 pins pin-header x 1 for USB 3,4 5 pins pin-header x 1 for IrDA DF13-40 Connector x1 for LVDS		
	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2 26 pins film header x1 for Slim Floppy@ solder side CF Connector x1 @ solder side 10 pins pin-headerx1 for Digital I/O 8 pins pin-header x 1 for USB 3,4 5 pins pin-header x 1 for IrDA DF13-40 Connector x1 for LVDS 3 pins pin-header x1 for SPDIF-OUT		
	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2 26 pins film header x1 for Slim Floppy@ solder side CF Connector x1 @ solder side 10 pins pin-headerx1 for Digital I/O 8 pins pin-header x 1 for USB 3,4 5 pins pin-header x 1 for IrDA DF13-40 Connector x1 for LVDS 3 pins pin-header x1 for SPDIF-OUT 11 pins pin-header x1 for audio Line-Out & Line-In &		
	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2 26 pins film header x1 for Slim Floppy@ solder side CF Connector x1 @ solder side 10 pins pin-headerx1 for Digital I/O 8 pins pin-header x 1 for USB 3,4 5 pins pin-header x 1 for IrDA DF13-40 Connector x1 for LVDS 3 pins pin-header x1 for SPDIF-OUT 11 pins pin-header x1 for audio Line-Out & Line-In & Microphone		
	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2 26 pins film header x1 for Slim Floppy@ solder side CF Connector x1 @ solder side 10 pins pin-headerx1 for Digital I/O 8 pins pin-header x 1 for USB 3,4 5 pins pin-header x 1 for IrDA DF13-40 Connector x1 for LVDS 3 pins pin-header x1 for SPDIF-OUT 11 pins pin-header x1 for audio Line-Out & Line-In & Microphone 4 pins pin-header x1 for CD-IN		
Header/Connector	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2 26 pins film header x1 for Slim Floppy@ solder side CF Connector x1 @ solder side 10 pins pin-headerx1 for Digital I/O 8 pins pin-header x 1 for USB 3,4 5 pins pin-header x 1 for IrDA DF13-40 Connector x1 for LVDS 3 pins pin-header x1 for SPDIF-OUT 11 pins pin-header x1 for audio Line-Out & Line-In & Microphone 4 pins pin-header x1 for CD-IN SATA connector x1 for SATA ports		
Header/Connector Watchdog Timer	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2 26 pins film header x1 for Slim Floppy@ solder side CF Connector x1 @ solder side 10 pins pin-headerx1 for Digital I/O 8 pins pin-header x 1 for USB 3,4 5 pins pin-header x 1 for IrDA DF13-40 Connector x1 for LVDS 3 pins pin-header x1 for SPDIF-OUT 11 pins pin-header x1 for audio Line-Out & Line-In & Microphone 4 pins pin-header x1 for CD-IN SATA connector x1 for SATA ports Yes (256 segments, 0, 1, 2255 sec/min)		
Header/Connector Watchdog Timer System Voltage	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2 26 pins film header x1 for Slim Floppy@ solder side CF Connector x1 @ solder side 10 pins pin-headerx1 for Digital I/O 8 pins pin-header x 1 for USB 3,4 5 pins pin-header x 1 for IrDA DF13-40 Connector x1 for LVDS 3 pins pin-header x1 for SPDIF-OUT 11 pins pin-header x1 for audio Line-Out & Line-In & Microphone 4 pins pin-header x1 for CD-IN SATA connector x1 for SATA ports Yes (256 segments, 0, 1, 2255 sec/min) +5V, +3.3V, +12V, 5VSB		
Header/Connector Watchdog Timer	DB9 x1 for COM 1 DB15 x1 for VGA S-Video for TV-Out 44 pins box-header x1 for IDE1 26 pins box-header x1 for LPT1 10 pins box-header x1 for COM2 26 pins film header x1 for Slim Floppy@ solder side CF Connector x1 @ solder side 10 pins pin-headerx1 for Digital I/O 8 pins pin-header x 1 for USB 3,4 5 pins pin-header x 1 for IrDA DF13-40 Connector x1 for LVDS 3 pins pin-header x1 for SPDIF-OUT 11 pins pin-header x1 for audio Line-Out & Line-In & Microphone 4 pins pin-header x1 for CD-IN SATA connector x1 for SATA ports Yes (256 segments, 0, 1, 2255 sec/min)		

Board Dimensions



Installations

This section provides information on how to use the jumpers and connectors on the ECX800 in order to set up a workable system. The topics covered are:

Installing the Memory	6
Setting the Jumpers	
Connectors on ECX800	


Installing the Memory

The ECX800 board supports one DDR2 SO-DIMM memory socket for a maximum total memory of 2GB, DDR2 667/533 (w/o ECC function).

Installing and Removing Memory Modules

To install DDR2 modules, locate the memory socket on the board and perform the following steps:

- 1. Hold the DDR2 module so that the keys of the DDR2 module align with those on the memory slot.
- 2. Gently push the DDR2 module in an angle as shown in the picture below until the clips of the sockets lock to hold the DDR2 module in place when the DDR2 module touches the bottom of the socket.
- 3. To remove the DDR2 module, press the clips with both hands.




Setting the Jumpers

Jumpers are used on ECX800 to select various settings and features according to your needs and applications. Contact your supplier if you have doubts about the best configuration for your needs. The following lists the connectors on ECX800 and their respective functions.

Jumper Locations on ECX800	8
JP5: CPU FSB Selection(reserved)	9
JP8: LCD Panel Power Selection	9
JP4: Clear CMOS Setting	9
JP6: CompactFlash Slave/Master Selection	

IMPORTANT NOTE: When the system boots without the CRT being connected, there will be no image on screen when you insert the CRT/VGA cable. To show the image on screen, the hotkey must be pressed.

Jumper Locations on ECX800



JP5: CPU FSB Selection (reserved)

JP5	CPU FSB
123	533MHz
123	667MHz

JP8: LCD Panel Power Selection

JP8	LCD Panel Power
123	3.3V
123	5V

JP4: Clear CMOS Setting

JP4	Setting	
123	Normal	
123	Clear CMOS	

JP6: CompactFlash Slave/Master Selection


JP6	CF Setting
□ □ Short	Master
o o	Slave

Connectors on ECX800

The connectors on ECX800 allows you to connect external devices such as keyboard, floppy disk drives, hard disk drives, printers, etc. The following table lists the connectors on ECX800 and their respective functions.

Connector Locations on ECX800	11
CN3: PS/2 Keyboard and PS/2 Mouse Connectors	12
CN1: Serial ATA Connectors	12
CN2: TV-OUT (S-Video) Connector	12
J18, CN4: COM1 and VGA Connector	12
FAN1: System Fan Power Connector	13
FDD1: Floppy Drive Connector	13
J1: System Function Connector	13
J2: IrDA Connector	15
J3: Region C Type III Connector	15
J4: LVDS Connectors (1st channel, 2nd channel)	16
J5: IDE Connector	17
J6: LCD Backlight Connector	17
J7: Parallel Port Connector	18
J8: Digital I/O	18
J9: ATX Power Supply Connector	19
J10: Front Audio Connector	19
J11: USB3/4 Port Pin Header	19
J12: COM2 Serial Port	20
J13: Gigabit LAN RJ-45	20
J14, J15: USB1/2 Ports	20
J16: CD-In Pin Header	20
J17: SPDIF Out Connector (optional)	20
I19: Compact Flash Connector	20

Connector Locations on ECX800



CN3: PS/2 Keyboard and PS/2 Mouse Connectors

CN3 uses a Y-cable with dual D-connectors for a PS/2 keyboard and a PS/2 mouse.




Pin:	Signal Name
1	Mouse data
2	Keyboard data
3	Ground
4	Vcc
5	Mouse Clock
6	Keyboard Clock


CN1: Serial ATA Connectors

CN2: TV-Out (S-Video) Connector

J18, CN4: COM1 and VGA Connector



Signal Nar e	Pin ^t	Pin #	Signal Nan e
DCD	1	6	DSR
RXD	2	7	RTS
TXD	3	8	CTS
DTR	4	9	RI
GND	5	10	Not Used



Signal Nar e	Pin ^t	Pin #	Signal Nan e
Red	1	2	Green
Blue	3	4	N.C.
GND	5	6	GND
GND	7	8	GND
N.C.	9	10	GND
N.C.	11	12	N.C.
HSYNC	13	14	VSYNC
NC	15		

FAN1: System Fan Power Connector


FAN1 is a 3-pin header for system fans. The fan must be a 12V (500mA).



Pin#	Signal Name		
1	Ground		
2	+12V		
3	Rotation detection		

FDD1: Floppy Drive Connector


FDD1is a slim 26-pin connector and will support up to 2.88MB FDD.



Signal Nam :	Pin #	Pin #	Signal Name
VCC	1	2	INDEX
VCC	3	4	DRV_SEL
VCC	5	6	DSK_CH
NC	7	8	NC
NC	9	10	MOTOR
NC	11	12	DIR
NC	13	14	STEP
GND	15	16	WDATA
GND	17	18	WGATE
GND	19	20	TRACK
GND	21	22	WPROT
GND	23	24	RDATA
GND	25	26	SIDE


J1: System Function Connector

J1 provides connectors for system indicators that provide light indication of the computer activities and switches to change the computer status. J3 is a 20-pin header that provides interfaces for the following functions.




Speaker: Pins 1 - 4

This connector provides an interface to a speaker for audio tone generation. An 8-ohm speaker is recommended.



Pin #	Signal Nam :		
1	Speaker out		
2	No connect		
3	Ground		
4	+5V		


Power LED: Pins 11 - 15



Pin #	Signal Nam :
11	Power LED
12	No connect
13	Ground
14	No connect
15	Ground

ATX Power ON Switch: Pins 7 and 17

This 2-pin connector is an "ATX Power Supply On/Off Switch" on the system that connects to the power switch on the case. When pressed, the power switch will force the system to power on. When pressed again, it will force the system to power off.



Reset Switch: Pins 9 and 19

The reset switch allows the user to reset the system without turning the main power switch off and then on again. Orientation is not required when making a connection to this header.




Hard Disk Drive LED Connector: Pins 10 and 20

This connector connects to the hard drive activity LED on control panel. This LED will flash when the HDD is being accessed.



Pin #	Signal Nam e		
10	HDD Active		
20	+5V		

J2: IrDA Connector




Pin:	Signal Name		
1	+5V		
2	No connect		
3	Ir RX		
4	Ground		
5	Ir TX		

J3: Region C Type III Connector

While the baseboard meets the minimal embedded application needs, the rich I/O interconnects available through the Region C expansion area facilitate extending the SBC's functionality to meet the demands of a variety of market segments.

J4: LVDS Connectors (1st channel, 2nd channel)

The LVDS connectors on board consist of the first channel and second channel and supports 18-bit or 36-bit.



Signal Nan e	Pin #	Pin #	Signal Nan e
1TX0-	2	1	1TX0+
1TX1-	4	3	1TX1+
Ground	6	5	Ground
1TX2-	8	7	1TX2+
NA	10	9	NA
Ground	12	11	Ground
1TXC-	14	13	1TXC+
Ground	16	15	Ground
2TX0-	18	17	2TX0+
2TX1-	20	19	2TX1+
Ground	22	21	Ground
2TX2-	24	23	2TX2+
NA	26	25	NA
Ground	28	27	Ground
2TXC-	30	29	2TXC+
Ground	32	31	Ground
+V(LCD)	34	33	+V(LCD)
+V(LCD)	36	35	+V(LCD)
Ground	38	37	BKL_Enable
Ground	40	39	Ground

J5: IDE Connector

1		2
- 1	00	_
	0 0	
	00	
	00	
	00	
	00	
	00	
	00	
	00	
	00	
	00	
	00	
43	00	44
1		1 1

Signal Nam	Pin i	Pin i	Signal Nam :
Reset IDE	1	2	Ground
Host data 7	3	4	Host data 8
Host data 6	3 5 7	6	Host data 9
Host data 5		8	Host data 10
Host data 4	9	10	Host data 11
Host data 3	11	12	Host data 12
Host data 2	13	14	Host data 13
Host data 1	15	16	Host data 14
Host data 0	17	18	Host data 15
Ground	19	20	Protect pin
DRQ0	21	22	Ground
Host IOW	23	24	Ground
Host IOR	25	26	Ground
IOCHRDY	27	28	Host ALE
DACK0	29	30	Ground
IRQ14	31	32	No connect
Address 1	33	34	Cable Detect
Address 0	35	36	Address 2
Chip select 0	37	38	Chip select 1
Activity	39	40	Ground
+5V	41	42	+5V
Ground	43	44	NC

J6: LCD Backlight Connector



Pin#	Signal Name		
1	+12V		
2	Backlight Enable		
3	Ground		


J7: Parallel Port Connector

	Signal Name	Pin #	Pin #	Signal Nam:
	Line printer strobe	1	14	AutoFeed
	PD0, parallel data 0	2	15	Error
1 14	PD1, parallel data 1	3	16	Initialize
	PD2, parallel data 2	4	17	Select
	PD3, parallel data 3	5	18	Ground
	PD4, parallel data 4	6	19	Ground
0 0	PD5, parallel data 5	7	20	Ground
0 0	PD6, parallel data 6	8	21	Ground
13 - 26	PD7, parallel data 7	9	22	Ground
J7	ACK, acknowledge	10	23	Ground
	Busy	11	24	Ground
	Paper empty	12	25	Ground
	Select	13	N/A	N/A

J8: Digital I/O


	Signal Nan e	P n	Pı	Signal Nam :
1 🔳 0 2	GND	1	2	VCC
00	OUT3	3	4	OUT1
00	OUT2	5	6	OUT0
9 0 0 10	IN3	7	8	IN1
	IN2	9	10	IN0

J9: ATX Power Supply Connector



Pin i	Signal Name
1	PS-ON
2	Ground
3	Ground
4	+12V
5	+3.3V
6	Ground
7	+3.3V
8	+5V
9	+5V
10	5VSB

J10: Front Audio Connector




Signal Nam	Pin i	Pin i	Signal Nam :
LINE-OUT_R	1	2	LINE-OUT_L
Ground	3	4	Ground
LINE-IN_R	5	6	LINE-IN L
Ground	7	8	Ground
Mic-In	9	10	VREF-Mic
Ground	11	12	Protect pin

J11: USB3/4 Port Pin Header



Signal Nan e	P n	Pı	Signal Nam :
Vcc	1	5	Ground
D-	2	6	D+
D+	3	7	D-
Ground	4	8	Vcc

J12: COM2 Serial Port



COM₂

Signal Name	Pin #	Pin #	Signal Name
DCD, Data carrier detect	1	6	DSR, Data set ready
RXD, Receive data	2	7	RTS, Request to send
TXD, Transmit data	3	8	CTS, Clear to send
DTR, Data terminal ready	4	9	RI, Ring indicator
GND, ground	5	10	Not Used

J13: Gigabit LAN RJ-45

J14, J15: USB1/2 Ports

J16: CD-In Pin Header

1	
4	

Pin #	Signal Name
1	CD Audio L
2	Ground
3	Ground
4	CD Audio R

J17: SPDIF Out Connector (optional)



Pin#	Signal Name
1	out
2	+5V
3	Ground

J19: Compact Flash Connector

BIOS Setup

This chapter describes the different settings available in the Award BIOS that comes with the board. The topics covered in this chapter are as follows:

BIOS Setup	
Standard CMOS Setup	4
Advanced BIOS Features	
Advanced Chipset Features	30
Integrated Peripherals	
Power Management Setup	
PNP/PCI Configurations	
PC Health Status	41
Frequency/Voltage Control	42
Load Fail-Safe Defaults	
Load Optimized Defaults	43
Set Supervisor/User Password	
Save & Exit Setup	
Exit Without Saving	

BIOS Introduction

The Award BIOS (Basic Input/Output System) installed in your computer system's ROM supports Intel processors. The BIOS provides critical low-level support for a standard device such as disk drives, serial ports and parallel ports. It also adds virus and password protection as well as special support for detailed fine-tuning of the chipset controlling the entire system.

BIOS Setup

The Award BIOS provides a Setup utility program for specifying the system configurations and settings. The BIOS ROM of the system stores the Setup utility. When you turn on the computer, the Award BIOS is immediately activated. Pressing the key immediately allows you to enter the Setup utility. If you are a little bit late pressing the key, POST (Power On Self Test) will continue with its test routines, thus preventing you from invoking the Setup. If you still wish to enter Setup, restart the system by pressing the "Reset" button or simultaneously pressing the <Ctrl>, <Alt> and <Delete> keys. You can also restart by turning the system Off and back On again. The following message will appear on the screen:

Press to Enter Setup

In general, you press the arrow keys to highlight items, <Enter> to select, the <PgUp> and <PgDn> keys to change entries, <F1> for help and <Esc> to quit.

When you enter the Setup utility, the Main Menu screen will appear on the screen. The Main Menu allows you to select from various setup functions and exit choices.

Phoenix - AwardBIOS CMOS Setup Utility

0	- "	
Standard CMOS Features	Frequency/Voltage Control	
Advanced BIOS Features	Load Fail-Safe Defaults	
Advanced Chipset Features	Load Optimized Defaults	
Integrated Peripherals	Set Supervisor Password	
Power Management Setup	Set User Password	
PnP/PCI Configurations	Save & Exit Setup	
PC Health Status	Exit Without Saving	
ESC : Quit	$\uparrow \downarrow \rightarrow \leftarrow$: Select Item	
F10 : Save & Exit Setup		
Time, Date, Hard Disk Type		

The section below the setup items of the Main Menu displays the control keys for this menu. At the bottom of the Main Menu just below the control keys section, there is another section, which displays information on the currently highlighted item in the list.

Note: If the system cannot boot after making and saving system changes with Setup, the Award BIOS supports an override to the CMOS settings that resets your system to its default.

Warning: It is strongly recommended that you avoid making any changes to the chipset defaults. These defaults have been carefully chosen by both Award and your system manufacturer to provide the absolute maximum performance and reliability. Changing the defaults could cause the system to become unstable and crash in some cases.

Standard CMOS Setup

"Standard CMOS Setup" choice allows you to record some basic hardware configurations in your computer system and set the system clock and error handling. If the board is already installed in a working system, you will not need to select this option. You will need to run the Standard CMOS option, however, if you change your system hardware configurations, the onboard battery fails, or the configuration stored in the CMOS memory was lost or damaged.

Phoenix - AwardBIOS CMOS Setup Utility Standard CMOS Features

Date (mm:dd:yy)	Mon, May 8 2006	Item Help
Time (hh:mm:ss)	17 : 53 : 00	Menu Level >
155.01		
IDE Channel 0 Master	None	Change the day, month,
IDE Channel 0 Slave	None	Year and century
IDE Channel 1 Master	None	
IDE Channel 1 Slave	None	
Drive A	None	
Drive B	None	
Video	EGA/VGA	
Halt On	All , But Keyboard	
Base Memory	640K	
Extended Memory	515072K	
Total Memory	516096K	

At the bottom of the menu are the control keys for use on this menu. If you need any help in each item field, you can press the <F1> key. It will display the relevant information to help you. The memory display at the lower right-hand side of the menu is read-only. It will adjust automatically according to the memory changed. The following describes each item of this menu.

Date

The date format is:

Day: Sun to Sat Month: 1 to 12 Date: 1 to 31

Year: 1999 to 2099

To set the date, highlight the "Date" field and use the PageUp/PageDown or +/- keys to set the current time.

Time

The time format is: Hour : 00 to 23

Minute: 00 to 59 Second: 00 to 59

To set the time, highlight the "Time" field and use the <PgUp>/ <PgDn> or +/- keys to set the current time.

IDE Channel Master/Slave

The onboard PCI IDE connector provides Primary and Secondary channels for connecting up to two IDE hard disks or other IDE devices.

Press <Enter> to configure the hard disk. The selections include Auto, Manual, and None. Select 'Manual' to define the drive information manually. You will be asked to enter the following items.

Capacity: Capacity/size of the hard disk drive

Cylinder: Number of cylinders

Head: Number of read/write heads **Precomp:** Write precompensation

Landing Zone: Landing zone

Sector: Number of sectors

The Access Mode selections are as follows:

CHS (HD < 528MB)

LBA (HD > 528MB and supports Logical Block Addressing)

Large (for MS-DOS only)

Auto

Drive A / Drive B

These fields identify the types of floppy disk drive A or drive B that has been installed in the computer. The available specifications are:

360KB 1.2MB 720KB 1.44MB 2.88MB 5.25 in. 5.25 in. 3.5 in. 3.5 in. 3.5 in.

Video

This field selects the type of video display card installed in your system. You can choose the following video display cards:

EGA/VGA	For EGA, VGA, SEGA, SVGA
	or PGA monitor adapters. (default)
CGA 40	Power up in 40 column mode.
CGA 80	Power up in 80 column mode.
MONO	For Hercules or MDA adapters.

Halt On

This field determines whether or not the system will halt if an error is detected during power up.

No errors The system boot will not be halted for any error

that may be detected.

All errors Whenever the BIOS detects a non-fatal error,

the system will stop and you will be prompted.

All, But Keyboard The system boot will not be halted for a

keyboard error; it will stop for all other errors

All, But Diskette The system boot will not be halted for a disk

error; it will stop for all other errors.

All, But Disk/Key

The system boot will not be halted for a key-

board or disk error; it will stop for all others.

Advanced BIOS Features

This section allows you to configure and improve your system and allows you to set up some system features according to your preference.

Phoenix - AwardBIOS CMOS Setup Utility Advanced BIOS Features

CPU Feature	Press Enter	ITEM HELP
Hard Disk Boot Priority	Press Enter	
Virus Warning	Disabled	Menu Level >
CPU L1 and L2 Cache	Enabled	
Quick Power On Self Test	Enabled	
First Boot Device	Floppy	
Second Boot Device	Hard Disk	
Third Boot Device	CDROM	
Boot Other Device	Enabled	
Swap Floppy Drive	Disabled	
Boot Up Floppy Seek	Disabled	
Boot Up NumLock Status	On	
Gate A20 Option	Fast	
Typematic Rate Setting	Disabled	
Typematic Rate (Chars/Sec)	6	
Typematic Delay (Msec)	250	
Security Option	Setup	
APIC Mode	Enabled	
MPS Version Control for OS	1.4	
OS Select For DRAM>64MB	Non-OS2	
Report No FDD For WIN 95	Yes	
Small Logo (EPA) Show	Disabled	

CPU Feature

Press Enter to configure the settings relevant to CPU Feature.

Hard Disk Boot Priority

With the field, there is the option to choose, aside from the hard disks connected, "Bootable add-in Cards" which refers to other external devices.

Virus Warning

If this option is enabled, an alarm message will be displayed when trying to write on the boot sector or on the partition table on the disk, which is typical of the virus.

CPU L1 and L2 Cache

Cache memory is additional memory that is faster than conventional DRAM (system memory). CPUs from 486-type on up contain internal cache memory, and most, but not all, modern PCs have additional (external) cache memory. When the CPU requests data, the system transfers the requested data from the main DRAM into cache memory, for even faster access by the CPU. These allow you to enable (speed up memory access) or disable the cache function.

Quick Power On Self Test

When enabled, this field speeds up the Power On Self Test (POST) after the system is turned on. If it is set to *Enabled*, BIOS will skip some items.

First/Second/Third Boot Device

These fields determine the drive that the system searches first for an operating system. The options available include *Floppy*, *LS120*, *Hard Disk*, *CDROM*, *ZIP100*, *USB-Floppy*, *USB-ZIP*, *USB-CDROM*, *LAN* and *Disable*.

Boot Other Device

These fields allow the system to search for an OS from other devices other than the ones selected in the First/Second/Third Boot Device.

Swap Floppy Drive

This item allows you to determine whether or not to enable Swap Floppy Drive. When enabled, the BIOS swaps floppy drive assignments so that Drive A becomes Drive B, and Drive B becomes Drive A. By default, this field is set to *Disabled*.

Boot Up Floppy Seek

This feature controls whether the BIOS checks for a floppy drive while booting up. If it cannot detect one (either due to improper configuration or its absence), it will flash an error message.

Boot Up NumLock Status

This allows you to activate the NumLock function after you power up the system.

Gate A20 Option

This field allows you to select how Gate A20 is worked. Gate A20 is a device used to address memory above 1 MB.

Typematic Rate Setting

When disabled, continually holding down a key on your keyboard will generate only one instance. When enabled, you can set the two typematic controls listed next. By default, this field is set to *Disabled*.

Typematic Rate (Chars/Sec)

When the typematic rate is enabled, the system registers repeated keystrokes speeds. Settings are from 6 to 30 characters per second.

Typematic Delay (Msec)

When the typematic rate is enabled, this item allows you to set the time interval for displaying the first and second characters. By default, this item is set to 250msec.

Security Option

This field allows you to limit access to the System and Setup. The default value is *Setup*. When you select *System*, the system prompts for the User Password every time you boot up. When you select *Setup*, the system always boots up and prompts for the Supervisor Password only when the Setup utility is called up.

APIC Mode

APIC stands for Advanced Programmable Interrupt Controller. The default setting is *Enabled*.

MPS Version Control for OS

This option is specifies the MPS (Multiprocessor Specification) version for your operating system. MPS version 1.4 added extended configuration tables to improve support for multiple PCI bus configurations and improve future expandability. The default setting is 1.4.

OS Select for DRAM > 64MB

This option allows the system to access greater than 64MB of DRAM memory when used with OS/2 that depends on certain BIOS calls to access memory. The default setting is *Non-OS/2*.

Report No FDD For WIN 95

If you are using Windows 95/98 without a floppy disk drive, select Enabled to release IRQ6. This is required to pass Windows 95/98's SCT test. You should also disable the Onboard FDC Controller in the Integrated Peripherals screen when there's no floppy drive in the system. If you set this feature to Disabled, the BIOS will not report the missing floppy drive to Win95/98.

Small Logo (EPA) Show

The EPA logo appears at the right side of the monitor screen when the system is boot up. The default setting is *Disabled*.

Advanced Chipset Features

This Setup menu controls the configuration of the chipset.

Phoenix - AwardBIOS CMOS Setup Utility Advanced Chipset Features

DRAM Timing Selectable	By SPD	ITEM HELP
CAS Latency Time	Auto	Menu Level >
DRAM RAS# to CAS# Delay	Auto	
DRAM RAS# Precharge	Auto	
Precharge delay (tRAS)	Auto	
System Memory Frequency	Auto	
SLP_S4# Assertion Width	1 to 2 Sec	
System BIOS Cacheable	Enabled	
Video BIOS Cacheable	Enabled	
Memory Hole at 15M-16M	Disabled	
PCI Express Root Port Func	Press Enter	
** On-Chip VGA Setting **		
PEG/On Chip VGA Control	Auto	
On-Chip Frame Buffer Size	8MB	
DVMT Mode	DVMT	
DVMT/FIXED memory Size	128MB	
SDVO Device Setting	None	
SDVO LVDS Protocol	1CH SPWG, 18bit	
SDVO Panel Number	1024x768	
Boot Display	CRT	
Panel Scaling	Auto	
Panel Number	1024x768 18 bit SC	
TV Standard	Off	
Video Connector	Automatic	
TV Format	Auto	
Onboard PCI-E LAN	Enabled	
LAN PXE Option ROM	All Disable	

DRAM Timing Selectable

This option refers to the method by which the DRAM timing is selected. The default is *By SPD*.

CAS Latency Time

You can configure CAS latency time in HCLKs as 3 or 4 or 5 or 6. The system board designer should set the values in this field, depending on the DRAM installed. Do not change the values in this field unless you change specifications of the installed DRAM or the installed CPU.

DRAM RAS# to CAS# Delay

This option allows you to insert a delay between the RAS (Row Address Strobe) and CAS (Column Address Strobe) signals. This delay occurs when the SDRAM is written to, read from or refreshed. Reducing the delay improves the performance of the SDRAM.

DRAM RAS# Precharge

This option sets the number of cycles required for the RAS to accumulate its charge before the SDRAM refreshes. The default setting for the Active to Precharge Delay is *Auto*.

Precharge Delay (tRAS)

The default setting for the Precharge Delay is Auto.

System Memory Frequency

The default setting is *Auto*.

SLP_S4# Assertion Width

The default setting is 1 to 2 Sec.

System BIOS Cacheable

The setting of *Enabled* allows caching of the system BIOS ROM at F000h-FFFFh, resulting in better system performance. However, if any program writes to this memory area, a system error may result.

Video BIOS Cacheable

The Setting *Enabled* allows caching of the video BIOS ROM at C0000h-F7FFFh, resulting in better video performance. However, if any program writes to this memory area, a system error may result.

Memory Hole At 15M-16M

In order to improve performance, certain space in memory can be reserved for ISA cards. This memory must be mapped into the memory space below 16 MB. The choices are *Enabled* and *Disabled*.

VGA Setting

The fields under the On-Chip VGA Setting and their default settings are:

PEG/On Chip VGA Control: Auto On-Chip Frame Buffer Size: 8MB

DVMT Mode: DVTM

DVMT/Fixed Memory Size: 128MB

SDVO Device Setting: None

SDVO LVDS Protocol: 1Ch SPWG, 18bit

SDVO Panel Number: 1024x768

Boot Display: CRT Panel Scaling: Auto

Panel Number: 1024x768 18 bit SC

TV Standard: Off

Video Connector: Automatic

TV Format: Auto

Panel Scaling

The default setting is *Auto*. The options available include *On* and *Off*.

Panel Number

These fields allow you to select the LCD Panel type. The default values for these ports are:

640x480	18bit SC
800x480	18bit SC
800x600	18bit SC
1024x768	18bit SC
1280x1024	18bit DC
1280x768	18bit SC
1400x1050	18bit DC
1600x1200	18bit DC

Onboard PCI-E LAN

By default, this setting is enabled.

LAN PXE Option ROM

By default, this setting is disabled. Other selections include ICH6 Integrated LAN and Marvell PCI-E LAN.

Integrated Peripherals

This section sets configurations for your hard disk and other integrated peripherals. The first screen shows three main items for user to select. Once an item selected, a submenu appears. Details follow.

Phoenix - AwardBIOS CMOS Setup Utility Integrated Peripherals

		ITEM LIELD
OnChip IDE Device	Press Enter	ITEM HELP
Onboard Device	Press Enter	Menu Level >
SuperIO Device	Press Enter	

Phoenix - AwardBIOS CMOS Setup Utility OnChip IDE Device

	•	
IDE HDD Block Mode	Enabled	ITEM HELP
On-chip Primary PCI IDE	Enabled	
IDE Primary Master PIO	Auto	Menu Level >
IDE Primary Slave PIO	Auto	
IDE Primary Master UDMA	Auto	
IDE Primary Slave UDMA	Auto	
On-Chip Secondary PCI IDE	Enabled	
IDE Secondary Master PIO	Auto	
IDE Secondary Slave PIO	Auto	
IDE Secondary Master UDMA	Auto	
IDE Secondary Slave UDMA	Auto	
*** On-Chip Serial ATA Setting ***		
On-Chip Serial ATA	Auto	
SATA PORT Speed Settings	Disabled	
PATA IDE Mode	Primary	
SATA port	P1, P3 is Secondary	

Phoenix - AwardBIOS CMOS Setup Utility Onboard Device

USB Controller	Enabled	ITEM HELP
USB 2.0 Controller USB Keyboard Support	Enabled Disabled	Menu Level >
USB Controller USB 2.0 Controller USB Keyboard Support Azalia/AC97 Audio Select	Auto	

Phoenix - AwardBIOS CMOS Setup Utility SuperIO Device

POWER ON Function	BUTTON ONLY	ITEM HELP
KB Power ON Password	Enter	
Hot Key power ON	Ctrl-F1	
Onboard FDC Controller	Enabled	
Onboard Serial Port 1	3F8/IRQ4	Menu Level >
Onboard Serial Port 2	2F8/IRQ3	
UART Mode Select	Normal	
RxD , TxD Active	Hi, Lo	
IR Transmission Delay	Enabled	
UR2 Duplex Mode	Half	
Use IR Pins	IR-Rx2Tx2	
Onboard Parallel Port	378/IRQ7	
Parallel Port Mode	SPP	
EPP Mode Select	EPP1.7	
ECP Mode Use DMA	3	
PWRON After PWR-Fail	Off	

IDE HDD Block Mode

This field allows your hard disk controller to use the fast block mode to transfer data to and from your hard disk drive.

On-chip Primary PCI IDE Enabled

This field, by default, is enabled

OnChip Primary/Secondary PCI IDE

The integrated peripheral controller contains an IDE interface with support for two IDE channels. Select *Enabled* to activate each channel separately.

IDE Primary/Secondary Master/Slave PIO

These fields allow your system hard disk controller to work faster. Rather than have the BIOS issue a series of commands that transfer to or from the disk drive, PIO (Programmed Input/Output) allows the BIOS to communicate with the controller and CPU directly.

The system supports five modes, numbered from 0 (default) to 4, which primarily differ in timing. When Auto is selected, the BIOS will select the best available mode.

IDE Primary/Secondary Master/Slave UDMA

These fields allow your system to improve disk I/O throughput to 33Mb/sec with the Ultra DMA/33 feature. The options are *Auto* and *Disabled*.

On-Chip Serial ATA Setting

The fields under the SATA setting include On-Chip Serial ATA (Auto), PATA IDE Mode (Primary) and SATA Port (P1, P3 is Secondary).

USB Controller

The options for this field are *Enabled* and *Disabled*. By default, this field is set to *Enabled*.

USB 2.0 Controller

The options for this field are *Enabled* and *Disabled*. By default, this field is set to *Enabled*. In order to use USB 2.0, necessary OS drivers must be installed first. *Please update your system to Windows 2000 SP4 or Windows XP SP2*.

USB Keyboard Support

The options for this field are *Enabled* and *Disabled*. By default, this field is set to *Disabled*.

Azalia/AC97 Audio Select

This field, by default, is set to Auto.

Power ON Function

This field is related to how the system is powered on – such as with the use of conventional power button, keyboard or hot keys. The default is **BUTTON ONLY**.

KB Power ON Password

This field allows users to set the password when keyboard power on is the mode of the Power ON function.

Hot Key Power ON

This field sets certain keys, also known as hot keys, on the keyboard that can be used as a 'switch' to power on the system.

Onboard FDC Controller

Select *Enabled* if your system has a floppy disk controller (FDC) installed on the board and you wish to use it. If you install an add-in FDC or the system has no floppy drive, select Disabled in this field. This option allows you to select the onboard FDD port.

Onboard Serial/Parallel Port

These fields allow you to select the onboard serial and parallel ports and their addresses. The default values for these ports are:

Serial Port 1 3F8/IRQ4 Serial Port 2 2F8/IRQ3 Parallel Port 378/IRQ7

UART Mode Select

This field determines the UART 2 mode in your computer. The default value is *Normal*. Other options include *IrDA* and *ASKIR*.

Parallel Port Mode

This field allows you to determine parallel port mode function.

SPP Standard Printer Port
EPP Enhanced Parallel Port
ECP Extended Capabilities Port

ECP+EPP Combination of ECP and EPP capabilities

Normal Normal function

PWRON After PWR-Fail

This field sets the system power status whether *on or off* when power returns to the system from a power failure situation.

Power Management Setup

Phoenix - AwardBIOS CMOS Setup Utility Power Management Setup

ACPI Function	Enabled	ITEM HELP
ACPI Suspend	S1(POS)	
RUN VGABIOS if S3 Resume	Auto	Menu Level >
Power Management	User Define	
Video Off Method	V/H SYNC+Blank	
Video Off In Suspend	Yes	
Suspend Type	Stop Grant	
Modem Use IRQ	3	
Suspend Mode	Disabled	
HDD Power Down	Disabled	
Soft-Off by PWR-BTTN	Instant-Off	
CPU THRM-Throttling	75.0%	
Wake-Up by PCI Card	Disabled	
Resume by Alarm	Disabled	
Date (of Month) Alarm	0	
Time (hh:mm:ss) Alarm	0:0:0	
** Reload Global Timer Events **		
Primary IDE 0	Enabled	
Primary IDE 1	Enabled	
Secondary IDE 0	Enabled	
Secondary IDE 1	Enabled	
FDD, COM, LPT Port	Enabled	
PCI PIRQ[A-D] #	Enabled	

ACPI Function

Enable this function to support ACPI (Advance Configuration and Power Interface).

ACPI Suspend

The default setting of the ACPI Suspend mode is S1(POS).

RUN VGABIOS if S3 Resume

The default setting of this field is Auto.

Power Management

This field allows you to select the type of power saving management modes. There are four selections for Power Management.

Min. Power Saving Minimum power management Max. Power Saving Maximum power management.

User Define Each of the ranges is from 1 min. to 1hr.

Except for HDD Power Down which

ranges from 1 min. to 15 min.

Video Off Method

This field defines the Video Off features. There are three options.

V/H SYNC + Blank Default setting, blank the screen and turn

off vertical and horizontal scanning.

DPMS Allows BIOS to control the video display.

Blank Screen Writes blanks to the video buffer.

Video Off In Suspend

When enabled, the video is off in suspend mode. The default setting is **Yes**.

Suspend Type

The default setting for the Suspend Type field is *Stop Grant*.

Modem Use IRQ

This field sets the IRQ used by the Modem. By default, the setting is 3.

Suspend Mode

When enabled, and after the set time of system inactivity, all devices except the CPU will be shut off.

HDD Power Down

When enabled, and after the set time of system inactivity, the hard disk drive will be powered down while all other devices remain active.

Soft-Off by PWRBTN

This field defines the power-off mode when using an ATX power supply. The *Instant Off* mode allows powering off immediately upon pressing the power button. In the *Delay 4 Sec* mode, the system powers off when the power button is pressed for more than four seconds or enters the suspend mode when pressed for less than 4 seconds.

CPU THRM-Throttling

When the system enters Doze mode, the CPU clock runs only part of the time. You may select the percent of time that the clock runs.

Wake up by PCI Card

By default, this field is disabled.

Resume by Alarm

This field enables or disables the resumption of the system operation. When enabled, the user is allowed to set the *Date* and *Time*.

Reload Global Timer Events

The HDD, FDD, COM, LPT Ports, and PCI PIRQ are I/O events that can prevent the system from entering a power saving mode or can awaken the system from such a mode. When an I/O device wants to gain the attention of the operating system, it signals this by causing an IRQ to occur. When the operating system is ready to respond to the request, it interrupts itself and performs the service.

PNP/PCI Configurations

This option configures the PCI bus system. All PCI bus systems on the system use INT#, thus all installed PCI cards must be set to this value.

Phoenix - AwardBIOS CMOS Setup Utility PnP/PCI Configurations

Init Display First	PCI Slot	ITEM HELP
Reset Configuration Data	Disabled	
		Menu Level
Resources Controlled By	Auto (ESCD)	
IRQ Resources	Press Enter	Select Yes if you are
		using a Plug and Play
PCI/VGA Palette Snoop	Disabled	capable operating system Select No if
INT Pin 1 Assignment	Auto	you need the BIOS to
INT Pin 2 Assignment	Auto	configure non-boot
INT Pin 3 Assignment	Auto	devices
INT Pin 4 Assignment	Auto	
INT Pin 5 Assignment	Auto	
INT Pin 6 Assignment	Auto	
INT Pin 7 Assignment	Auto	
INT Pin 8 Assignment	Auto	

PCI Express relative items	4096	
Maximum Payload Size	4090	

Init Display First

The default setting is **PCI Card**.

Reset Configuration Data

This field allows you to determine whether to reset the configuration data or not. The default value is *Disabled*.

Resources Controlled by

This PnP BIOS can configure all of the boot and compatible devices with the use of a PnP operating system such as Windows 95.

PCI/VGA Palette Snoop

Some non-standard VGA display cards may not show colors properly. This field allows you to set whether or not MPEG ISA/VESA VGA cards can work with PCI/VGA. When this field is enabled, a PCI/VGA can work with an MPEG ISA/VESA VGA card. When this field is disabled, a PCI/VGA cannot work with an MPEG ISA/VESA card.

Maximum Payload Size

The default setting of the PCI Express Maximum Payload Size is 4096.

PC Health Status

This section shows the parameters in determining the PC Health Status. These parameters include temperatures, fan speeds and voltages.

Phoenix - AwardBIOS CMOS Setup Utility PC Health Status

Shutdown Temperature	Disabled	ITEM HELP
CPU Warning Temperature	Disabled	
System Temp	45°C/113°F	Menu Level >
CPU Temp	45°C/113°F	
CPU Fan Speed(FAN1)	6750 RPM	
Vcore(V)	1.08 V	
+12 V	12.24 V	
1.8 V	1.87 V	
+5 V	5.14 V	
3.3 V	3.26 V	
VBAT (V)	3.23 V	
5VSB (V)	5.56 V	
Smart Fan Temperature	Disabled	
Fan Tolerance Value	5	

Shutdown Temperature

This field allows the user to set the temperature by which the system automatically shuts down once the threshold temperature is reached. This function can help prevent damage to the system that is caused by overheating.

CPU Warning Temperature

This field allows the user to set the temperature so that when the temperature is reached, the system sounds a warning. This function can help prevent damage to the system that is caused by overheating.

Temperatures/Voltages

These fields are the parameters of the hardware monitoring function feature of the board. The values are read-only values as monitored by the system and show the PC health status.

Smart Fan Temperature

This field enables or disables the smart fan feature. At a certain temperature, the fan starts turning. Once the temperature drops to a certain level, it stops turning again.

Fan Tolerance Value

The default value is 5.

Frequency/Voltage Control

This section shows the user how to configure the processor frequency.

Phoenix - AwardBIOS CMOS Setup Utility Frequency/Voltage Control

Auto Detect PCI Clk	Disabled	ITEM HELP
Spread Spectrum Modulated	Disabled	Menu Level >

Auto Detect PCI CIk

This field enables or disables the auto detection of the PCI clock.

Spread Spectrum Modulated

This field sets the value of the spread spectrum. The default setting is *Disabled*. This field is for CE testing use only.

Load Fail-Safe Defaults

This option allows you to load the troubleshooting default values permanently stored in the BIOS ROM. These default settings are non-optimal and disable all high-performance features.

Load Optimized Defaults

This option allows you to load the default values to your system configuration. These default settings are optimal and enable all high performance features.

Set Supervisor Password

These two options set the system password. Supervisor Password sets a password that will be used to protect the system and Setup utility. User Password sets a password that will be used exclusively on the system. To specify a password, highlight the type you want and press <Enter>. The Enter Password: message prompts on the screen. Type the password, up to eight characters in length, and press <Enter>. The system confirms your password by asking you to type it again. After setting a password, the screen automatically returns to the main screen.

To disable a password, just press the <Enter> key when you are prompted to enter the password. A message will confirm the password to be disabled. Once the password is disabled, the system will boot and you can enter Setup freely.

Save & Exit Setup

This option allows you to determine whether or not to accept the modifications. If you type "Y", you will quit the setup utility and save all changes into the CMOS memory. If you type "N", you will return to Setup utility.

Exit Without Saving

Select this option to exit the Setup utility without saving the changes you have made in this session. Typing "Y" will quit the Setup utility without saving the modifications. Typing "N" will return you to Setup utility.

This page is intentionally left blank.

Drivers Installation

This section describes the installation procedures for software and drivers under the Windows 2000 and Windows XP. The software and drivers are included with the board. If you find the items missing, please contact the vendor where you made the purchase. The contents of this section include the following:

Intel Chipset Software Intallation Utility	46
VGA Drivers Installation	48
AC97 Codec Audio Driver Installation	50
LAN Drivers Installation	51

IMPORTANT NOTE:

After installing your Windows operating system (Windows 2000/ XP), you must install first the Intel Chipset Software Installation Utility before proceeding with the drivers installation.

Intel Chipset Software Installation Utility

The Intel Chipset Drivers should be installed first before the software drivers to enable Plug & Play INF support for Intel chipset components. Follow the instructions below to complete the installation under Windows 2000/XP.


1. Insert the CD that comes with the board. Click *Intel Chipsets* and then *Intel(R) 1945GMChipset Drivers*.




Support Intel(R) 1945GM Chipart Dervers

2. Click Intel(R) Chipset Software Installation Utility.


3. When the Welcome screen appears, click *Next* to continue.



4. Click **Yes** to accept the software license agreement and proceed with the installation process.



5. On Readme Information screen, click *Next* to continue the installation.




6. The Setup process is now complete. Click *Finish* to restart the computer and for changes to take effect. When the computer has restarted, the system will be able to find some devices. Restart your computer when prompted.


VGA Drivers Installation

To install the VGA drivers, follow the steps below to proceed with the installation.


- 1. Insert the CD that comes with the board. Click *Intel Chipsets* and then *Intel(R) 1945GM Chipset Drivers*.
- 2. Click Intel(R) 1945GM Chipset Family Graphics Driver.



3. When the Welcome screen appears, click *Next* to continue.



4. Click **Yes** to to agree with the license agreement and continue the installation.



5. Restart the computer as promted and for changes to take effect.



IMPORTANT NOTE:

When you have restarted the computer, your computer screen will be blank. At this point, press CTRL-ALT-F1 simultaneously, if you are using CRT monitor. If you are using LVDS LCD panel, press CTRL-ALT-F3. If you are using DVI monitor, press CTRL-ALT-F4.

AC97 Codec Audio Driver Installation

Follow the steps below to install the Realtek AC97 Codec Audio Drivers.

- 1. Insert the CD that comes with the board. Click *Intel Chipsets* and then *Intel(R) 1945GM Chipset Drivers*.
- 2. Click Realtek AC'97 Codec Audio Driver.



3. Click *Finish* to restart the computer and for changes to take effect. .



LAN Drivers Installation

Follow the steps below to install the **Marvell Gigabit LAN** drivers.

1. Insert the CD that comes with the board. Click *LAN Card* and then *Marvell LAN Controller Driver*.



2. Click Next when the InstallShield Wizard welcome screen appears.



3. Click Next to agree with the license agreement. Click Next when the Readme Information screen appears to proceed with the drives installation process. When the Installation is complete, click Finish for the changes to take effect.

This page is intentionally left blank.

Appendix

A. I/O Port Address Map

Each peripheral device in the system is assigned a set of I/O port addresses which also becomes the identity of the device. The following table lists the I/O port addresses used.

Address	Device Description
000h - 01Fh	DMA Controller #1
020h - 03Fh	Interrupt Controller #1
040h - 05Fh	Timer
060h - 06Fh	Keyboard Controller
070h - 07Fh	Real Time Clock, NMI
080h - 09Fh	DMA Page Register
0A0h - 0BFh	Interrupt Controller #2
0C0h - 0DFh	DMA Controller #2
0F0h	Clear Math Coprocessor Busy Signal
0F1h	Reset Math Coprocessor
1F0h - 1F7h	IDE Interface
278 - 27F	Parallel Port #2(LPT2)
2F8h - 2FFh	Serial Port #2(COM2)
2B0 - 2DF	Graphics adapter Controller
378h - 3FFh	Parallel Port #1(LPT1)
360 - 36F	Network Ports
3B0 - 3BF	Monochrome & Printer adapter
3C0 - 3CF	EGA adapter
3D0 - 3DF	CGA adapter
3F0h - 3F7h	Floppy Disk Controller
3F8h - 3FFh	Serial Port #1(COM1)

B. Interrupt Request Lines (IRQ)

Peripheral devices use interrupt request lines to notify CPU for the service required. The following table shows the IRQ used by the devices on board.

Level	Function
IRQ0	System Timer Output
IRQ1	Keyboard
IRQ2	Interrupt Cascade
IRQ3	Serial Port #2
IRQ4	Serial Port #1
IRQ5	Reserved
IRQ6	Floppy Disk Controller
IRQ7	Parallel Port #1
IRQ8	Real Time Clock
IRQ9	Reserved
IRQ10	Reserved
IRQ11	Reserved
IRQ12	PS/2 Mouse
IRQ13	80287
IRQ14	Primary IDE
IRQ15	Secondary IDE

C. Watchdog Timer Configuration

The WDT is used to generate a variety of output signals after a user programmable count. The WDT is suitable for use in the prevention of system lock-up, such as when software becomes trapped in a deadlock. Under these sorts of circumstances, the timer will count to zero and the selected outputs will be driven. Under normal circumstance, the user will restart the WDT at regular intervals before the timer counts to zero.

SAMPLE CODE:

```
// THIS CODE AND INFORMATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY
// KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
// IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR
// PURPOSE.
#include <stdio.h>
#include <stdlib.h>
#include "W627EHF.H"
int main (int argc, char *argv[]);
void copyright(void);
void EnableWDT(int);
void DisableWDT(void);
int main (int argc, char *argv[])
      unsigned char bBuf;
      unsigned char bTime;
      char **endptr;
      copyright();
      if (argc != 2)
             printf(" Parameter incorrect!!\n");
             return 1:
      if (Init W627EHF() == 0)
             printf(" Winbond 83627HF is not detected, program abort.\n");
             return 1;
      bTime = strtol (argv[1], endptr, 10);
      printf("System will reset after %d seconds\n", bTime);
      EnableWDT(bTime);
      return 0;
```

```
void copyright(void)
                    ===== Winbond 83627EHF Watch Timer Tester (AUTO DETECT) =======\n"\
                          Usage: W627E\_WD\ reset\_time \backslash n" \backslash
                          Ex : W627E_WD 3 => reset system after 3 second\n"\
                             W627E_WD 0 \Rightarrow disable watch dog timer(n'');
void EnableWDT(int interval)
      unsigned char bBuf;
      bBuf = Get\_W627EHF\_Reg(\ 0x2D);
      bBuf \&= (!0x01);
      Set_W627EHF_Reg( 0x2D, bBuf);
                                                             //Enable WDTO
       Set_W627EHF_LD( 0x08);
                                                             //switch to logic device 8
      Set_W627EHF_Reg( 0x30, 0x01);
                                                             //enable timer
      bBuf = Get_W627EHF_Reg( 0xF5);
      bBuf \&= (!0x08);
      Set_W627EHF_Reg( 0xF5, bBuf);
                                                             //count mode is second
      Set_W627EHF_Reg( 0xF6, interval);
                                                             //set timer
//====
void DisableWDT(void)
       Set\_W627EHF\_LD(0x08);
                                                             //switch to logic device 8
      Set_W627EHF_Reg(0xF6, 0x00);
                                                             //clear watchdog timer
       Set_W627EHF_Reg(0x30, 0x00);
                                                             //watchdog disabled
```

```
// THIS CODE AND INFORMATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY
/\!/ KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
/\!/\,IMPLIED\,WARRANTIES\,OF\,MERCHANTABILITY\,AND/OR\,FITNESS\,FOR\,A\,PARTICULAR
// PURPOSE.
//==
#include "W627EHF.H"
#include <dos.h>
unsigned int W627EHF_BASE;
void Unlock_W627EHF (void);
void Lock_W627EHF (void);
unsigned int Init_W627EHF(void)
      unsigned int result;
      unsigned char ucDid;
      W627EHF\_BASE = 0x2E;
      result = W627EHF_BASE;
      ucDid = Get_W627EHF_Reg(0x20);
      if (ucDid == 0x88)
            goto Init_Finish;
      W627EHF BASE = 0x4E;
      result = W627EHF_BASE;
      ucDid = Get_W627EHF_Reg(0x20);
      if (ucDid == 0x88)
            goto Init_Finish;
      W627EHF\_BASE = 0x00;
      result = W627EHF_BASE;
Init_Finish:
      return (result);
void Unlock_W627EHF (void)
      outportb(W627EHF_INDEX_PORT, W627EHF_UNLOCK);
      outportb(W627EHF_INDEX_PORT, W627EHF_UNLOCK);
void Lock_W627EHF (void)
      outportb(W627EHF_INDEX_PORT, W627EHF_LOCK);
void Set_W627EHF_LD( unsigned char LD)
      Unlock_W627EHF();
      outportb (W627EHF\_INDEX\_PORT, W627EHF\_REG\_LD);
      outportb(W627EHF_DATA_PORT, LD);
      Lock_W627EHF();
```

```
void Set_W627EHF_Reg( unsigned char REG, unsigned char DATA)
      Unlock_W627EHF();
      outportb(W627EHF_INDEX_PORT, REG);
      outportb(W627EHF_DATA_PORT, DATA);
     Lock_W627EHF();
unsigned char Get_W627EHF_Reg(unsigned char REG)
      unsigned char Result;
      Unlock_W627EHF();
      outportb(W627EHF_INDEX_PORT, REG);
      Result = inportb(W627EHF_DATA_PORT);
      Lock_W627EHF();
      return Result;
// THIS CODE AND INFORMATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY
// KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
// IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR
// PURPOSE.
//===
#ifndef __W627EHF_H
#define __W627EHF_H
                                   1
#define
           W627EHF_INDEX_PORT
                                         (W627EHF_BASE)
#define
           W627EHF\_DATA\_PORT
                                         (W627EHF_BASE+1)
#define
           W627EHF_REG_LD
                                         0x07
#define W627EHF_UNLOCK
                                         0x87
#define
           W627EHF_LOCK
                                         0xAA
unsigned int Init_W627EHF(void);
void Set_W627EHF_LD( unsigned char);
void Set_W627EHF_Reg( unsigned char, unsigned char);
unsigned char Get_W627EHF_Reg( unsigned char);
#endif //__W627EHF_H
```