

Bush Hog® TOUGH

2247QT Quick Attach Front-Push Loader

Pin-On Attachments

BUSH HOG® TOUGH FEATURES

- TOUGH Boxed Boom Design
- TOUGH Large Diameter Cross Tubes
- TOUGH Robotic Welds
- TOUGH High Strength Chrome Plated Cylinder Rods
- TOUGH Bush Hog Made Buckets
- TOUGH Powder Coat Paint



MODEL	Specifications Based on 1997 ASAE STANDARDS	2247QT
Tractor PTO HP Range		15 - 35
2WD/FWA		2WD/FWA
Maximum Lift Height - Measured at Pivot Pin		97 inches
Maximum Lift Height - Under Level Bucket		90 inches
Maximum Dump Angle		50°
Digging Depth		4 inches
Lift Capacity to Maximum Height - At Pivot Pin		1150 lbs
Lift Capacity to Maximum Height - 19.5 inches Forward of Pivot Pin		875 lbs
Lift Capacity to 59 inch Height - At Pivot Pin		1365 lbs
Lift Capacity to 59 inch Height - 19.5 inches Forward of Pivot Pin		1085 lbs
Breakout Force - At Pivot Pin		1995 lbs
Breakout Force - 19.5 inches - Forward of Pivot Pin		1525 lbs
Rollback Force at Maximum Height - 19.5 inches Forward of Pivot Pin		2040 lbs
Rollback Force at 59 inch Height - 19.5 inches Forward of Pivot Pin		2410 lbs
Rollback Force at Ground Level - 19.5 inches Forward of Pivot Pin		1820 lbs
Raising Time (Ground Level to Full Height)		4 seconds
Lowering Time (Full Height to Ground Level)		2 seconds
Bucket Dumping Time (Full Rollback to Full Dump)		4 seconds
Bucket Rollback Time (Full Dump to Full Rollback)		2 seconds
Hydraulics	Two 1.77 inch Bore, 19.25 inch Stroke Double Acting Bucket Cylinders and Two 1.77 inch Bore, 19.25 inch Stroke Double Acting Lift Cylinders	
Specifications Based on Tractor System of	2000 PSI hyd. Pressure & 6 GPM pump capacity	
Pin-On Buckets	Available in 48, 60 and 72 inch widths	
Options	Forklift Attachment (36 inch tines), Bucket Level Indicator, and Grill Guards	
Warranty	1 year limited warranty	
FEATURES	Available in major tractor colors	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE