JGP970TEK/KEK/BEK GE Profile™ 36" Built-In Gas Cooktop

Dimensions and Installation Information

AGA Requirement: All gas cooktop models require 7/16" free area below cooktop height to combustible material. Requires 18" minimum from countertop to adjacent overhead cabinets.

Note: Curved front may interfere with some raised bullnose countertops. If installing with a GE Profile™ Telescopic Downdraft System, consult both cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft.

Electrical Rating: 120V, 60Hz, 5A

Installation With Single Wall Oven Information:

30" Gas Cooktops are approved for use over select GE 27" and 30" Wall Ovens and Warming Drawers. 30" and 36" Gas cooktops are approved for use over 30" Wall Ovens and Warming Drawers. Refer to cooktop and wall oven/warming drawer installation instructions packed with product for current dimensional data.

Installation Information: Before installing, consult installation instructions, packed with product, for current dimensional data.

21-5/16 13" MAX Cooktop 3-3/16* depth 19-1/8 30" MIN. to unprotected 6" MIN. 18" MIN. cabinet to cabinet clearance to side wall 33-7/8 2-1/4" to from cut-out. rear wall 2-1/2 (Min.) 3-3/4" MIN. clearance to *Allow 5-3/4" depth at rear for electrical and side wall gas connections from cut-out Electrical junction Cut should box 12" MIN. not interfere below countertop with cabinet structure at front

For answers to your Monogram,® GE Profile™ or GE® appliance questions, visit our website at ge.com or call GE Answer Center® service, 800.626.2000.

Dimension and installation information are shown in inches.





JGP970TEK/KEK/BEK GE Profile™ 36" Built-In Gas Cooktop

Features and Benefits

- Gas On Glass Cooktop Features a flat one-piece ceramic glass surface that is sleek and easy-to-clean
- Sealed Cooktop Burners Eliminates the space between the burners and the cooktop to help contain spills and boil over liquids, ensuring easy cleanup
- Power Boil™ Burner Delivers 15,000 BTUs of forceful heat for rapid boiling
- High Output Burner Provides a powerful burner output for efficient heat-up and boiling
- Precise Simmer Burner Delivers a low setting of 140 degrees, ideal for delicate foods and sauces
- Continuous Grates Provide a flat, sturdy surface allowing easy movement of pans between burners
- Control Lock Capability Shuts off gas to prevent unintended activation.
 Only GE has it!



- Deluxe Cast Grates Constructed from a premium cast iron material for a long-lasting performance and durability
- Upfront Controls Controls are placed within easy reach at the front center of the cooktop
- Electronic Pilotless Ignition Provides reliable burner ignition operation, eliminating the need for a standing pilot
- Heavy-Duty Die-Cast Knobs Add durability and brushed chrome for enhanced style and performance
- Model JGP970TEKWW True white
- Model JGP970KEKCC True bisque
- Model JGP970BFKBB Black on black



