

Snell *Performance Series* IW-SR7

Versatile Flush-mount Surround Select for Diffuse or Direct Operation


The IW-SR7 is a high-performance, surround speaker with a selectable radiation pattern. IW-SR7 can be either a diffuse dispersion pattern dipole or can radiate with a wide dispersion direct-pattern. In the diffuse mode, the IW-SR7 directs its energy away from the listening area, performing like an array of movie theater surround speakers. This creates a diffuse, lifelike ambient sound field. In the direct mode the IW-SR7 functions as a wide dispersion direct radiator, perfect for localized surround effects or wide coverage front channel use. Voiced to match all Snell speakers, the IW-SR7 mounts flush and virtually disappears in the listening room.



Dimensions:
Finish
8 1/4" High
15 1/8" Wide
3 1/2" Deep

Dimensions:
Rough
7 1/2" High
14 1/2" Wide

Application Alternatives:



SR7 On Wall

System Suggestions:



IW BASIS 300
Subwoofer



IW-K7

Like all Snell loudspeakers, each IW-SR7 is hand tuned for natural imaging and sonic depth.

Design:

Infinite Baffle, multi pattern, in wall surround with integrated tweeter enclosure.

Frequency Response

80Hz-20kHz \pm 3dB

Sensitivity

[1 Watt (2.83v) @ 1m] 85 dB

Impedance

Nominal 8 Ohms

Maximum Output

102 dB

Recommended Power

10 Watts Minimum

150 Watts Maximum

Tweeter

2) 2.5-inch cone tweeters

Woofer

5.25-inch copolymer cone

Crossover Frequency

900Hz

Crossover

Selectable "Diffuse/Direct" mode by sophisticated switching network. Each crossover is individually tuned by our technicians to \pm 1.0db of the Master Reference.

Connections

5-way gold plated terminals accept spades as large as 5/16", pins, banana plugs, and bare wire to 12 gauge.

Cabinet Construction

Open back design of high impact plastic. Sandwich bracket accepts mounting surfaces to 1.5 inches.

Grille

Perforated steel metal

Finishes

Paintable white finish with powder coat paint. Can be ordered in most paint finishes.

Weight

5 lbs.

