

CARBON MONOXIDE ALARMS

First Alert®



Cat. FCD2BN 120V AC Plug-In



Description:

The FCD2BN is an AC-powered plug-in CO alarm. It is microprocessor controlled for accurate and reliable operation. Meets UL2034. Single-button test/silence. Permanent CO sensor. Alarm indicator light: Power shines constant red, during Alarm LED flashes when CO alarm levels are detected. Also have malfunction/service mode alert. Loud, 85dB horn. 5-Year Limited Warranty.



Cat. FCD2DDBN 120V AC Plug-In w/Digital Display



Description:

The FCD2DDBN is an AC-powered plug-in CO alarm with digital display. It is microprocessor controlled for accurate and reliable operation. Meets UL2034. Single-button test/silence. Permanent CO sensor. Peak Level Memory displays highest CO sensed. Alarm indicator light: Power shines constant red, during Alarm LED flashes when CO alarm levels are detected. Also have malfunction/service mode alert. Loud, 85dB horn. 5-Year Limited Warranty.



Cat. FCD3BN 9V Battery Operated



Description:

The FCD3BN is a basic battery-operated CO alarm designed for portability. Easily mounts on wall, ceiling or rests on dresser or shelf. Includes action chart describing how to respond to an alarm. Meets UL2034. Includes 9-volt alkaline battery. Test/silence button silences the alarm while continuing to monitor CO levels. Permanent CO sensor. Three indicator lights: Battery flashes green for power, Alarm flashes red when CO alarm levels are detected, Service flashes yellow if service or replacement is required. Loud, 85dB horn. 5-Year Limited Warranty.



Cat. FCD4CN-3 120V AC Plug-In w/9V Battery Back-up and Digital Display



Description:

The FCD4CN-3 is an AC-powered plug-in CO alarm with 9V battery backup, digital display and exclusive, patented IR remote control test/silence. Can be operated with most household TV/VCR remote controls. Microprocessor-controlled for accurate and reliable operation. Meets UL2034. Single-button test/silence/scroll function. 9-volt alkaline battery included. Digital display with Peak Level Memory. Permanent CO sensor. Alarm indicator light: Power shines constant red, during Alarm LED flashes when CO alarm levels are detected. Also have malfunction/service mode alert. Loud, 85dB horn. 5-Year Limited Warranty.



Cat. SC01BN 9V Battery Operated Combination Smoke & Carbon Monoxide Alarm



Description:

The SC01BN is a battery-operated smoke and CO combination alarm. Can be mounted on wall or ceiling. Meets both UL217 and UL2034. Includes 9-volt alkaline battery. Ionization smoke sensing technology provides warning in case of fire. CO alarm warns of elevated CO levels. Easy alarm identification through different horn sounds and lights. Test/silence button. Three indicator lights: Battery flashes green for power, Alarm flashes red when CO alarm levels are detected, Service flashes yellow if service or replacement is required. Loud, 85dB horn. 5-Year Limited Warranty.

BRK ELECTRONICS®




BSI Registered Firm—Certificate #FM21268

CARBON MONOXIDE ALARMS

First Alert®

FCD2BN Technical Specs

Alarm Dimensions: 5.3"L, 3.3"W, 1.4"H
 Weight: 5.9 oz.
 Operating Voltage: 120 VAC, 60 Hz
 Power: .09 amps
 Temp Range: 40°F (4°C) to 100°F (38°C)
 Humidity Range: 10% to 90% Relative Humidity
 Audio Alarm: 85dB at 10 ft.
 Test Button: Electronically simulates a carbon monoxide condition, causing the unit to alarm
 Alarm Reset: Automatic when CO clears; Press Test/Silence button to reset manually
 Indicator LEDs: AC Power: Constant Red LED
 CO Alarm: Audio Alarm (4 beeps, pause, 4 beeps) and rapidly flashing Red LED
 Listing: UL2034




FCD2BN Packaging Specs

Packaging Type: Carton

	Individual Carton	Master Pack
Dimensions:	8.66"L, 2.47"D, 5.66"H	15.63"L, 9.00"D, 6.31"H
Weight:	0.65 lbs	3.90 lbs
Cube:	0.07 ft ³	0.51 ft ³
UPC:	0 29054 15001 1	100 29054 15001 8
Quantity:	1	6

FCD2DDBN Technical Specs

Alarm Dimensions: 5.3"L, 3.3"W, 1.4"H
 Weight: 5.9 oz.
 Operating Voltage: 120 VAC, 60 Hz
 Power: .09 amps
 Temp Range: 40°F (4°C) to 100°F (38°C)
 Humidity Range: 10% to 90% Relative Humidity
 Audio Alarm: 85dB at 10 ft.
 Test Button: Electronically simulates a carbon monoxide condition, causing the unit to alarm
 Alarm Reset: Automatic when CO clears; Press Test/Silence button to reset manually
 Indicator LEDs: AC Power: Constant Red LED
 CO Alarm: Audio Alarm (4 beeps, pause, 4 beeps) and rapidly flashing Red LED
 Listing: UL2034




FCD2DDBN Packaging Specs

Packaging Type: Carton

	Individual Carton	Master Pack
Dimensions:	8.66"L, 2.47"D, 5.66"H	15.63"L, 9.00"D, 6.31"H
Weight:	0.68 lbs	4.08 lbs
Cube:	0.07 ft ³	0.51 ft ³
UPC:	0 29054 85633 3	100 29054 85633 0
Quantity:	1	6

FCD3BN Technical Specs

Alarm Dimensions: 5"L, 4.9"W, 1.5"H
 Weight: 11.36 oz.
 Operating Voltage: 9V DC
 Temp Range: 40°F (4°C) to 100°F (38°C)
 Humidity Range: 10% to 90% Relative Humidity
 Audio Alarm: 85dB at 10 ft.
 Test Button: Electronically simulates a carbon monoxide condition, causing the unit to alarm
 Alarm Reset: Automatic when CO clears; Press Test/Silence button to reset manually
 Indicator LEDs: DC Power: Flashes Green when unit is receiving power; Horn "chirps" every 30 seconds when battery is low
 Service Status: Flashes Yellow when unit needs service or replacement; Horn "chirps" when light flashes
 CO Alarm: Audio Alarm (4 beeps, pause, 4 beeps) and rapidly flashing Red LED
 Listing: UL2034




FCD3BN Packaging Specs

Packaging Type: Carton

	Individual Carton	Master Pack
Dimensions:	8.66"L, 2.16"D, 5.66"H	13.69"L, 9.00"D, 6.31"H
Weight:	0.72 lbs	4.32 lbs
Cube:	0.06 ft ³	0.451 ft ³
UPC:	0 29054 15000 4	100 29054 15000 1
Quantity:	1	6

FCD4CN-3 Technical Specs

Alarm Dimensions: 5.3"L, 3.3"W, 1.4"H
 Weight: 7.6 oz.
 Operating Voltage: 120 VAC, 60 Hz, 9V DC
 Power: .09 amps
 Temp Range: 40°F (4°C) to 100°F (38°C)
 Humidity Range: 10% to 90% Relative Humidity
 Audio Alarm: 85dB at 10 ft.
 Test Button: Electronically simulates a carbon monoxide condition, causing the unit to alarm
 Alarm Reset: Automatic when CO clears; Press Test/Silence button to reset manually
 Indicator LEDs: AC Power: Constant Red LED
 CO Alarm: Audio Alarm (4 beeps, pause, 4 beeps) and rapidly flashing Red LED
 Listing: UL2034




FCD4CN-3 Packaging Specs

Packaging Type: Clam

	Individual Clam	Master Pack
Dimensions:	9.75"H, 2.40"D, 6.63"L	7.13"H, 5.25"D, 10.88"W
Weight:	0.74 lbs	2.22 lbs
Cube:	0.09 ft ³	0.20 ft ³
UPC:	0 29054 85618 0	800 29054 85618 6
Quantity:	1	3

SC01BN Technical Specs

Alarm Dimensions: 5.6" Dia., 1.8"H
 Weight: 11.2 oz.
 Operating Voltage: 9V DC
 Temp Range: 40°F (4°C) to 100°F (38°C)
 Humidity Range: 10% to 90% Relative Humidity
 Audio Alarm: 85dB at 10 ft.
 Test Button: Electronically simulates a carbon monoxide condition, causing the unit to alarm
 Alarm Reset: Automatic when CO clears; Press Test/Silence button to reset manually
 Indicator LEDs: DC Power: Flashes Green when unit is receiving power; Horn "chirps" every 30 seconds when battery is low
 Service Status: Flashes Yellow when unit needs service or replacement; horn "chirps" when light flashes
 Smoke Alarm: Audio Alarm (3 beeps, pause, 3 beeps) and rapidly flashing Red Smoke LED
 CO Alarm: Audio Alarm (4 beeps, pause, 4 beeps) and rapidly flashing Red CO LED
 Listing: UL2034



SC01BN Packaging Specs

Packaging Type: Carton

	Individual Carton	Master Pack
Dimensions:	8.59"L, 2.16"D, 7.29"H	8.94"L, 7.19"D, 7.94"H
Weight:	0.97 lbs	2.91 lbs
Cube:	0.08 ft ³	0.30 ft ³
UPC:	0 29054 15002 8	100 29054 15002 5
Quantity:	1	3

Manufactured By:
 BRK Brands, Inc
 3901 Liberty Street Road
 Aurora, IL 60504-8122

Distributed By:

www.brkelectronics.com

BRK ELECTRONICS® is a registered trademark of BRK Brands, Inc.
 First Alert® is a registered trademark of the First Alert Trust.

©2003 BRK Brands, Inc. CM2462