

# Universal Cleaner

## RM 555 ASF

# PRODUCT INFORMATION

### High-pressure multi- purpose cleaner

#### Properties:

- multi-purpose cleaner to use in high pressure cleaners
- liquid, neutral pH-value
- for cleaning oil, grease and mineral soiling
- fast separation of oil and water in the oil separator (ASF)
- very gentle to materials
- manual applicable
- easily biodegradable in accordance with OECD guidelines
- pH- value in concentrate approx. 7
- clear, yellow liquid with fresh odour

#### Fields of application:

- car wash
- house and garden
- special applications
- cleaning of all water resistant surfaces

#### Processing:

	<b>pre-dilution</b>	<b>dosage</b>	<b>temperature</b>
• manual normal soiling	1+9	pre-dilution	up to 40°C
heavy soiling	pure	pre-dilution	up to 40°C
• high pressure cleaning	pure	1-5%	up to 60°C

#### Economy:

1 l RM 555 ASF is sufficient for cleaning of approx. 20 m<sup>2</sup>, dosage 5% at the high-pressure appliance, medium soiled area.

#### Handling:

manual application: pre-dilution: first measure the necessary amount of water, then add RM 555 ASF under stirring and mix properly.  
high pressure cleaning: fill the cleaning agent into the tank of the high pressure machine or put the suction pipe into the RM bottle.

#### Remarks:

- store frost-free

# ***Universal Cleaner***

RM 555 ASF

## PRODUCT INFORMATION

### **Attention:**

- S 2 Keep out of the reach of children
- S 23 Do not breathe aerosol

### **Certificates from neutral institutes:**

- DEKRA certificate of ASF-efficiency

### **Further information:**

- Material safety data sheet

### **Process:**

Object: e.g. vehicle cleaning

- fill the cleaning agent into the tank of the high pressure machine or put the suction pipe into the RM bottle.
- dosage approx. 5% at the high pressure cleaner, temperature up to 60°C
- clean the car starting below upward in steady and overlapping traces
- rinse with clear water