

ELECTRIC DOWNDRAFT COOKTOP



PRODUCT DIMENSIONS

CENTIMETERS

INCHES

	INCHES	CENTIMETERS
А	28 7/8 ± 1/16	73.3 ± .2
В	21 ³ /8 ± ¹ /16	53.7 ±.2
С	10	25.4
D	6 ³ /8	16.2
F	16 ¹ /2	41.9
G	2 min	5.1 min
Н	17 ¹ /2 min	44.5 min
J	12 ¹ /2	31.8
Κ	12 1/2	31.8
L ²	2 min	5.1 min
М	4 5/8	11.7
Ρ	29 ^{3/4}	75.9
Q	22	55.9
MODEL SKUs		
JED8430BDB		
JED8430BDF		
JED8430BDN		
JED8430BDS		
1		

NOTES:

- 1. Where possible, 6" (15.2 cm) is recommended for motor blower service. Minimum clearance of 1" (2.5 cm) is required to sidewalls and 3/4" (1.9cm) to rear wall.
- 2. Provide 2" minimum (5.1 cm) cabinet clearance to motor for cooling purpose.
- 3. Unit may be safely installed as near as 0" (0 cm) from a side wall if space limitations requires. However, a side clearance of at least 6" (15.24 cm) is recommended for optimum ventilation.
- 4. Vents up to 60 equivalent feet.
- 5. This appliance has been designed in accordance with the requirements of various safety agencies and comply with the maximum allowable wood cabinet temperatures of 194° F. If these appliances are installed with cabinets that have a lower working temperature than 194° F, discoloration, delamination or melting may occur.

Electrical requirements: Provide for 120/240 or 120/208 VAC, 60 Hz. The unit must be properly circuitprotected and wired according to local electrical codes.