

Business Keyboard K-1 J82-16001



Key benefits

- Comfortable key action
- Space-efficient compact keyboard
- Abrasion-proof writing on keycaps

Delivery performance

Keyboard Printed manual

Approvals

FCC, CE, c-tick cURus, GHOST-R, Microsoft Windows ™ XP

System requirements

USB or PS/2 interface

Technical data

Number of keys:

104 position US key layout

Weight:

approx. 650 g (keyboard) approx. 780 g (with packaging)

Measurements:

approx. 360 x 160 x 32 mm (keyboard) approx. 485 x 190 x 36 mm (packaging)

Cable length:

approx. 1.80 m

Storage temperature:

-20 °C to 60 °C

Operating temperature:

0 °C to 50 °C

Keyswitch Lifetime:

> 10 million operations

Interface:

USB (USB versions) PS/2 (PS/2 versions)

Current input:

typ. 40 mA

Packaging unit:

10 keyboards per master carton 20 master cartons per pallet

Warranty:

2 years

Order description

Part numbers	Color	Interface
J82-16001LUNEU-0	light grey	USB
J82-16001LUNEU-2	black	USB
J82-16001LPNEU-0	light grey	PS/2
J82-16001LPNEU-2	black	PS/2

Cherry Electrical Products 11200 88th Avenue Pleasant Pairie, WI 53158 USA

Phone: 800 510 1689 Internet: www.cherrycorp.com

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.