

Black and White Monitor

SSM-920

Operating Instructions

Before operating the unit, please read this manual thoroughly and retain it for future reference.

Owner's Record

The model and serial numbers are located at the rear.
Record the serial number in the space provided below.
Refer to these numbers whenever you call upon your Sony dealer regarding this product.


Model No. SSM-920 Serial No. _____

Features

- This unit can be used as a closed circuit television monitor or a video preview/playback monitor.
- Loop through connection allows up to three monitors to display the same picture.
- Electronic circuits provide safeguards against interference, noise and change of signal strength to maintain a clear and stable picture.


Connections

Connecting a Video Camera or a VCR



Connecting More Than One Monitor


Up to 3 monitors can be connected using the loop-through feature of this unit. When this monitor is connected to additional monitors, the same picture can be obtained on all the connected monitors.



Adjust the picture contrast and brightness on each monitor.

Location and Function of Controls

Front



1 H-HOLD (horizontal hold) control

When the picture has slanting horizontal bars, turn the H-HOLD control in either direction until a stationary picture is obtained.

2 V-HOLD (vertical hold) control

When the picture rolls up or down on the screen, turn the V-HOLD control until a single stationary picture is obtained.

3 POWER switch

To turn the monitor on, depress this switch. The green indicator lights up.
To turn the monitor off, press the switch again.


4 CONTRAST control

Turn clockwise to increase picture contrast and counterclockwise to decrease it.

5 BRIGHT (brightness) control

Turn clockwise for a brighter picture and counterclockwise for a darker picture.

Rear



6 IMPEDANCE selector

Set to 75 Ω when only one monitor is used, or when the monitor is used as the last of looped chain.
Set to HIGH when another monitor is connected to the VIDEO OUT connector.

7 VIDEO IN connector (BNC type)


Connect to the video output of a VCR, a video camera, or another monitor (for loop-through connection).

8 VIDEO OUT connector (BNC type)

Connect the video input of a VCR or another monitor (for loop-through connection).


Connections

Connecting a Video Camera or a VCR



Connecting More Than One Monitor

Up to 3 monitors can be connected using the loop-through feature of this unit. When this monitor is connected to additional monitors, the same picture can be obtained on all the connected monitors.



Adjust the picture contrast and brightness on each monitor.

Precautions

Safety

- Operate the unit only on 120 V AC, 60 Hz.
- Should any liquid or solid object fall into the cabinet, unplug the unit and have it checked by the qualified personnel before operating it any further.
- Unplug the unit from the wall outlet if it is not going to be used for several days or more. To disconnect the cord, pull it out by the plug. Never pull the cord itself.
- Allow adequate air circulation to prevent internal heat build-up. Do not place the unit on surfaces (rugs, blankets, etc.) or near materials (curtains, draperies) that may block the ventilation holes.
- Height and vertical linearity controls located at the rear panel are for special adjustments by qualified personnel only.

Installation

- Do not install the unit in an extremely hot or humid place or in a place subject to excessive dust or mechanical vibration.
- The unit is not designed to be waterproof. Exposure to rain or water may damage the unit.

Cleaning

Clean the unit with a slightly damp soft cloth. Use a mild household detergent. Never use strong solvents such as thinner or benzine as they might damage the finish of the unit.

If you have any question or problem concerning your unit that is not covered in this manual, please consult your nearest Sony dealer.

Specifications

System	EIA standard
Picture tube	9-inch picture measured diagonally 90-degree deflection
Resolution	More than 650 TV lines (horizontal)
Video input	Composite: 0.5 – 2 V p-p, sync negative
Video input impedance	High impedance for loop-through; 75 Ω terminated
Video output	Composite: 0.5 – 2 V p-p, sync negative
Video output impedance	Over 10 k Ω
Power requirements	120 V AC, 60 Hz
Power consumption	27 W
Dimensions	220 × 241 × 247 mm (w/h/d) (8 ³ / ₄ × 9 ¹ / ₂ × 9 ³ / ₄ inches)
Weight	Approx. 5.9 kg (13 lb)

Design and specifications subject to change without notice.