



Philips
CRT monitor

17"
real flat

107Q62



style and ideal screen size plus lead-free design

With elegant styling, ideal screen size and a High Bright Hot Key for instant brightness adjustment, the 107Q6 delivers superb display in a stylish package along with lead-free Green design that protects your health and our environment.

Outstanding front of screen performance

- Philips breakthrough advanced Digital Deflection CPU
- High Bright Hot Key instantly adjusts brightness levels
- SXGA 1280 x 1024 resolution for sharper display
- Easy-on-the-eyes high-bright, high-contrast tube
- Real flat CRT for natural, distortion and glare-free display
- sRGB ensures color matching between display and printouts

Great convenience

- Compatibility with PC and Mac platforms
- Quick and easy to personalize On-Screen-Display control
- Easy, user friendly plug-and-play installation

Green design

- Lead-free design safeguards our environment
- Lower power consumption than the industry average
- MPRII ensures safety by limiting electromagnetic radiation

PHILIPS
sense and simplicity

Specifications

Picture/Display

- **Display screen type:** Real Flat picture tube
- **Panel Size:** 17"/ 41 cm
- **Phosphor:** P22
- **Recommended display area(mm):** 306 x 230 mm
- **Recommended Display Area(inch):** 12" x 9"
- **Dot pitch:** 0.25 mm
- **Dot Pitch (horizontal):** 0.21 mm
- **White Chromaticity, 5500K:** x = 0.332 / y = 0.347
- **White Chromaticity, 6500K:** x = 0.313 / y = 0.329
- **White Chromaticity, 9300K:** x = 0.283 / y = 0.297
- **Maximum Resolution:** 1600 x 1200 @ 65 Hz
- **Optimum Resolution:** 1024 x 768 @ 85 Hz
- **Factory Preset Modes:** 8 modes
- **Factory Preset Mode:** 640 x 480 @ 75 Hz, 640 x 480 @ 85Hz, 720 x 400 @ 70 Hz, 800 x 600 @ 75 Hz, 800 x 600 @ 85 Hz, 1024 x 768 @ 75 Hz, 1024 x 768 @ 85 Hz, 1280 x 1024 @ 75 Hz
- **Factory Preload Modes:** 21 modes
- **Video Dot Rate:** 185 MHz
- **Horizontal Scanning Frequency:** 30 - 86 kHz
- **Vertical Scanning Frequency:** 50 - 160 Hz
- **Recommended Refresh Rate:** 85 Hz
- **Screen enhancement:** Anti-glare Polarizer, Anti-Reflection, Anti-Static, High Brightness, High Contrast
- Digital deflection
- sRGB
- GTF

Connectivity

- **Cables:** D-sub Video Cable, Power Cord
- **Sync input impedance:** 2.2k ohm
- **Video input impedance:** 75 ohm
- **Video input signal levels:** 0.7 Vpp

- **Video Sync Input Signal:** Separate Sync
- **Video Sync Polarities:** Positive and Negative
- **Cable Connection:** AC Power in

Convenience

- **User convenience:** Menu Languages, On-screen Display
- **Monitor Controls:** Bright Direct Access, Contrast Direct Access, High Bright Hotkey, Menu, Power On/Off
- **OSD Languages:** English, French, German, Italian, Spanish, Portuguese, Korean, Simplified Chinese
- **Plug & Play Compatibility:** DDC 2B, Windows 98/ME/2000/XP
- **Regulatory Approvals:** CCC, MPR-II, Low Emission
- **Swivel:** +/- 90°
- **Tilt:** -5° to 13°

Accessories

- **Included Accessories:** AC Power Cord
- User Manual

Dimensions

- **Dimensions (with base) (W x H x D):** 397 x 383 x 424 mm
- **Temperature range (operation):** 0°C to 40°C
- **Temperature range (storage):** -25°C to 65°C
- **Weight:** 15 kg

Power

- **Consumption (On mode):** 68 W (Typical)
- **Consumption (Off Mode):** < 2 W
- **Power LED indicator:** Off - Flashing Green, Operation - green
- **Power supply:** Built-in

Product highlights

Digital Deflection CPU

An exclusive Philips innovation – the world's first one-chip CRT solution – combines the deflection and the Microcontroller in a single chip to process and control input sync digitally. This innovative technology prevents electronic noise that can harm display quality, reduces display jitter and improves geometry for better front of screen performance.

High Bright Hot Key

A feature that delivers instant brightness adjustment to the ideal level for viewing text, Internet, game or multimedia applications, providing comfortable viewing and an enhanced experience for each type of application.

SXGA, 1280 x 1024 resolution

For graphics monitors, the screen resolution signifies the number of dots (pixels) on the entire screen. For example, a 1280-by-1024 pixel screen is capable of displaying 1280 distinct dots on each of 1024 lines, or about 1.3 million pixels.

High-bright-high-contrast tube

A CRT tube designed to increase display brightness and contrast by increasing the CRT ray gun's beam current.

Real flat CRT display

Philips advanced flat CRT technology reduces glare and reflection more efficiently than a conventional CRT. The special high-bright, high-contrast shadow mask helps maintain sharper focus and eliminates 'color blooming' compared to standard tubes. It displays images on a monitor that look like images on paper: Viewing the image is more comfortable. Straight lines are straight. Finding a reflection-free viewing position is much easier. This adds up to reduced eyestrain for a comfortable viewing experience.

sRGB ready

sRGB is an industry standard that ensures the best possible match between the colors displayed on your screen and those in your printouts.

Two-platform compatibility

The ability to work with a variety of platforms; Philips monitors are compatible to connect with PC by employing a VGA connection and connect with Macintosh.

OSD On-Screen-Display control

An on-screen panel for adjusting a monitor. The OSD is used for contrast, brightness, horizontal, vertical positioning and other monitor adjustments.

Easy plug-and-play

Plug-and-play is a peripheral connectivity standard. A plug and play display device can be connected to a PC and operate without requiring user intervention to adjust complicated settings.

Lead-free

Lead-free display products are designed and produced in compliance with strict European Community Restriction of Hazardous Substances (RoHS) standards that restrict lead and other toxic substances that can harm the environment.

Energy efficiency

Reduction of the electrical power required to operate a device to achieve real savings.

MPRII compliant

The world standard setting stringent levels for electromagnetic radiation emitted by monitors.

Flame retardant cabinet

PC/ABS plastic composite is the industry's best and toughest flame-retardant casing material; and is a space-age compound deployed in the aerospace and automotive industries as well as in fire detectors that is compliant with most stringent fire safety standards.



Issue date 2009-02-12

Version: 1.0.3

12 NC: 8639 000 16441
EAN: 87 10895 90972 3

© 2009 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com