



RX-W19



▶ FEATURES

- High 1440 x 900 WXGA⁺ resolution and high contrast ratio 1000:1
- Image sticking (burn-in) prevention function added to secure your investment
- Quick signal-switching time (≤ 0.8 sec.)
- Real-time displaying the image upon signal connection
- Video input settings will resume when power re-plug
- Looping video inputs for multiple connections
- Auto termination
- Supports NTSC/PAL/SECAM video system
- Supports color and B/W picture
- Selectable signal source
- PC & Mac compatible
- Auto-adjustment for optimal settings when VGA input is selected
- NeoV Optical Glass™
- Slim border & bezel design
- Distinctive metal alloy housing for added strength
- Kensington® security socket
- VESA standard wall mount

▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	19" (481mm)
	Max. Resolution	WXGA ⁺ 1440 x 900
	Pixel Pitch	0.285mm
	Brightness	380cd/m ² (Typical)
	Contrast Ratio	1000:1 (Typical)
	Viewing Angle (H/V)	170°/160° (Typical)
	Display Color	16.7M
	Response Time	5ms (GTG)
	Frequency (H/V)	H: 24kHz – 80kHz V: 56Hz – 75Hz
Input Connector	Max. Pixel Clock	150MHZ
	Life Time	50,000hrs (Minimum)
	Analog	15-Pin D-Sub
Input Signal	Digital	24-Pin DVI-D
	BNC Security	BNC Connector
	Analog	RGB H.V Sync
Output Connector	Digital	TMDS
	Auto Composite System	NTSC/PAL/SECAM
	BNC Security	BNC Connector
NeoV Optical Glass	Thickness	3.0mm (0.18")
	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	Tilt	0° ~ +20°
Mounting	VESA FPMPI	Yes (100mm)
Regulation Approval	Certifications & Compliance	FCC, UL/CUL, NOM, CB, CE, TUV/Baurt, BSMI, NORDIC, GOST, WEEE, RoHS
Power	VESA	DDC 1/2B, DDC-CI
	Power Source	100 - 240V, 50 - 60Hz
	Consumption	<48W (On) <1W (Off)
Temperature	Operation	0°C ~ 40°C
	Storage	-20°C ~ 60°C
Dimensions	Net (W x H x D)	448 x 351 x 155 mm (17.6" x 13.8" x 6.1")
	Packing (W x H x D)	534 x 472 x 195 mm (21.0" x 18.6" x 7.7")
Weight	Net Weight	5.4kg (11.8 lbs)
	Gross Weight	7.9kg (17.5 lbs)
Packing	1 Pallet	48 Sets
	20' Container	480 Sets
	40' Container	960 Sets

All specifications are subject to change without prior notice