

Professional Large LCD Monitor

Specially designed for professional surveillance and monitoring room environments.



Professional Large LCD Monitor SMT-3222/4022

Superior Image Quality

SMT-3222/4022 feature up to Full HD(1920x1080) resolution, 8ms response time, 40,000:1 dynamic contrast (4,000:1 standard), 450cd/m² brightness and 178° view angle.




Conventional



SMT-3222/4022

Super High Resolution of 600 TV Lines

SMT-3222/4022 is capable of resolving 600 TV Lines (NTSC/PAL) from composite video signal. It provides perfect reproduction of high resolution CCTV images without degradation.




Conventional

SMT-3222/4022

DNie (Digital Natural Image engine) Technology

With Samsung's DNie technology, the SMT-3222/4022 provide enhanced image reproduction with optimized color, enhanced contrast and higher resolution. It delivers rich color and crystal clear image for more comfortable monitoring

Motion Optimizer :
Clear Moving images



Detail Enhancer :
Fine Details



DNie



Contrast Enhancer :
Sharp Contrast



Color Optimizer :
Natural Color

Impressive Video Walls

SMT-3222/4022 can display the pictures in multi display video wall mode without any distortion resulted from the cabinet bezel. This function produces natural images so that users can monitor the scene more comfortably.



Conventional



SMT-3222/4022

Signal Balance for Long Distance Installation

The signal balance function, featured by Samsung SMT-3222/4022 monitors, eliminates the attenuation of RGB signal in the long signal cables, signal dividers, and graphic cards.




Conventional

SMT-3222/4022

Various Video Wall Formats by Image Enlarging Processor

SMT-3222/4022 supports various video wall formats, including 2x2, 3x3, 4x4, 5x5, 1x2, 2x1, 1x5, and 5x1. Moreover, no additional device is required to set the format.



SMT-3222/4022


Professional Large LCD Monitor



I Features

- Support up to 1920 x 1080 resolution(SMT-4022)
- High contrast ratio 4,000:1
- 178 degree horizontal and vertical viewing angle
- Superior image quality DNIe
- HDMI, DVI, RGB and composite inputs
- Built-in Speaker
- Extended video wall format (1x5 ~ 5x5)
- Multi-Language setup support
- Built-in Fan prevents overheating and image corruption
- Anti-image retention mode
- Signal balance function for weak RGB signal

I Dimensions (unit: mm)




* Foot stand sold separately

I Specifications

Model	SMT-3222	SMT-4022		
General	Screen Size	32"	40"	
	Resolution (HxV)	1366 x 768	1920 x 1080	
	Pixel Pitch (mm)	0.511 x 0.511 (HxV)	0.46125 x 0.46125 (HxV)	
	Brightness(cd/m ²)	450		
	Contrast Ratio	4,000:1 (Dynamic Contrast Ratio 40,000:1)		
	Response Time (ms)	8 (G-to-G)		
	Viewing Angle (H/V)	178° / 178°		
	Panel Lamp Life	50,000HR		
	Display Colors	16.7M		
	Horizontal Frequency	30 ~ 81KHz		
	Vertical Frequency	56 ~ 85Hz		
	Horizontal Resolution	600TV Lines		
	Comb Filter	3D		
Sync Format	NTSC : 3.5 / PAL : 4.43 / Secam			
Feature	Screen Aspect Ratio	4:3 / 16:9		
	Language	English / French / German / Italian / Portuguese / Russian / Spanish / Swedish / Chinese / Japanese / Korean / Turkish / Taiwanese		
	Front Panel Control	Menu, Adjust down / up / left / right, Enter, Source, D.Menu, Power		
	Speaker Output	10W (5W x 2 built-in)	20W (10W x 2 built-in)	
	Indicator	LED (Power)		
	VESA Mount	200 x 200 mm	400 x 600 mm	
	Input Interface	Video	1 composite(RCA), 1 HDMI	
		PC	1 RGB (D-sub), 1 DVI, 1 RS-232	
		Audio	2 RCA	
	Power Requirement	AC100-240V, 50/60Hz		
Power Consumption	130W (Typ), 143W (Max)	180W (Typ), 220W (Max)		
Weight	13.7Kg	19Kg		
Dimensions	Without Stand	780(W)x482(H)x109(D)mm	971(W)x582(H)x118.5(D)mm	
	With Stand	780(W)x545(H)x311(D)mm	971(W)x643(H)x311(D)mm	
Accessories	Remote Control, Battery x 2, Quick Setup Guide, Warranty Card, User's Guide, Power Cord, RCA to BNC Cable			

I Optional Accessory (unit: mm)



SAMSUNG ELECTRONICS CO., LTD.

416, Maetan 3 Dong, YeongTong-Gu, Suwon City, Kyeonggi-Do, Korea, 443-742
Tel: +82-31-277-3342-3347 Fax: +82-31-277-6597
<http://www.samsungsecurity.com>

Distributed by

* Design and specifications are subject to change without notice