



PK301

Portable Power, Big Impact

Optoma's PK301 Pico pocket projector provides projection power anywhere. Featuring up to 50 ANSI lumens and native widescreen WVGA resolution, the palm-sized PK301 enables you to easily share videos, photos and graphics at home or on the road. Enjoy unlimited

Features

- Truly portable palm-sized, lightweight, and rechargeable
- Project large widescreen images of up to 120" diagonal
- LED light source lasts over 20,000 hours while producing excellent color
- Full assortment of I/O ports, including USB, VGA, HDMI and video, allows for easy connection to most analog or digital devices

Connectivity Capabilities through Optional Accessories

- Female USB adapter project images and videos from USB flash drives
- Component video for higher quality video and gaming

Sp

Pro Re Ма

Bri

Co Lig Thr Pro

Ası Bat Bat Dis Auc

Vid Me Vid

Ima I/O

We

Din Wa Sta

Op

UP













pecifications	
ojection Type:	DLP®
solution	Native WVGA (854 x 480)
aximum Resolution	WXGA (1280 x 800) through VGA Adapter; HD (1080i) through HDMI
ightness	50 ANSI Lumens Bright Mode (with AC Power Adapter or Optional Extended Power Battery Pack); 20 ANSI Lumens STD Mode
ontrast Ratio	2000:1 (Full On/Full Off)
jht Source	LED (RGB); Estimated Life of Over 20,000 Hours*
row Ratio	1.8:1 (Distance/Width)
ojection Distance	8" to 189"
age Size (Diagonal)	5" to 120" (16:9 Native)
pect Ratio	16:9 Native; 4:3 Compatible
ttery (Standard)	Li-ion Rechargeable (3.7V, 1410mAh)
ttery Life (ECO/STD)	Estimated at 90+ Minutes/45+ Minutes
splayable Colors	100% NTSC Color Gamut
dio	One 0.5-Watt Speaker, Headphone-Out
mputer Compatibility	WXGA, XGA, SVGA, VGA, VESA, PC and Macintosh Compatible with Included VGA Adapter
leo Input Compatibility	NTSC, PAL, SDTV (480i), EDTV (480p), HDTV (720p, 1080i)
emory	28MB Internal; microSD Slot Supports up to 32GB SDHC
leo File Compatibility	AVI, MOV, MP4, 3GP (Common Video Formats are Converted Using Optoma Pico Video Encoder**)
age File Compatibility	JPEG, BMP (PowerPoint Files are Converted Using Optoma Pico Video Encoder**)
Connectors	24-Pin Universal Port, 2.5mm Jack AV Input (Composite Video and Stereo Audio-In), Micro USB, Mini HDMI, microSD Slot, 3.5 mm Audio-Out Jack, DC Input Jack
eight	8 oz (227g) with Standard Battery
mensions (W x H x D)	4.7" x 1.2" x 2.7"; (120.1 x 29.7 x 69.8mm)
arranty	1 Year Limited Parts and Labor, 90 Days on Battery
andard Accessories	Power Adapter, Rechargeable Li-ion Battery, Male USB Cable, Standard A/V Cable (RCA to Mini-Jack), Universal to VGA Cable, Bag
itional Accessories	iPod Kit with AV Connector, Universal to Component Cable, Universal to Female USB Cable, Additional Standard Battery, Extended Power Battery Pack, Mini HDMI to HDMI Cable, Remote Control
РС О	796435 41 172 5
o brightness can decrease over time stoma Pico Video Encoder is not Mac compatibl coptomausa.com > Support > FAQ.	