

M NO	
ОЈЕСТ	
CATION	
TE	QTY



FIP-50 SERIES Ice Cream And Novelty Display Merchandiser

MODEL

FEATURES

CONSTRUCTION

- 24 gauge painted steel interior and exterior
- 60" x 19" top stainless steel serving deck
- Extra large, non-fogging front display window
- Four panes of tempered glass with a viewing area of 11.7 square feet
- Removable backlit merchandising sign in stainless steel frame
- Anodized aluminum trim with black vinyl inlay
- Four adjustable heavy-duty, white epoxy-coated, welded wire shelves
- Protective front bumper
- Full length fluorescent lamp
- Automatic condensate evaporator
- Independent on/off light switch
- 2" foamed-in-place "zero ODP" urethane insulation

FINISH

• Sparkling white polyester enamel interior and exterior

DOORS

- Replaceable magnetic door gasket
- Foamed-in-place rear doors
- Self-closing

REFRIGERATION

- Self-contained, semi-hermetic condensing unit
- Rear air intake and discharge
- Automatic defrost
- Refrigerant: R-404A
- Temperature range: 0° to -20°F (-18° to -29°C)
- R-factor (insulation efficiency rating): 17.24

WARRANTY

• Standard limited four year extended compressor and one year limited parts and labor

OPTIONS

Custom colorsCasters





FIP-50 SERIES ICE CREAM AND NOVELTY DISPLAY MERCHANDISER

TECHNICAL SPECIFICATIONS

	DIMENSIONS (in.)		DIMENSIONS (mm)							STANDARD SHELF	DISPLAY		SHIP	SHIP	
MODEL	L	D	н	L	D	н	VOLTS	AMPS	UNIT H.P.	NO. OF SHELVES	SIZE (in inches)	AREA SQ. FT.	CAP. CU. FT.	CU. FT.	WT. (LB/KG)
FIP-50	60	31	50	1524	787	1270	115	13.4	3/4	4	*	18.0	18.1	87.0	640/291

*Upper right hand and upper left hand shelves measure 12" x 27". Lower right hand and lower left hand shelves measure 15" x 27".







ELEVATION VIEW

REMOVABLE LENS DIMENSIONS

2-5/16"--

57" (ACTUAL LENS SIZE) 52-3/8" (VIEWING AREA)

LISTINGS

L3/8"

RADIUS: 1/4"



BID SPECIFICATIONS

Item no. FIP-50

Provide Low Temp Ice Cream and Novelty Display

Merchandiser(s), Master-Bilt model no. FIP-50

)

Merchandiser to have 60" x 19" top stainless steel serving deck, extra large non-fogging front display window, four panes of tempered front glass, backlit merchandising sign in stainless steel frame, anodized aluminum trim with black vinyl

HOOKUP

Via plug in, 9 foot long, flexible 3 wire 14/3 cord with molded plug. Fifteen amp service is required.



inlay, protective front bumper, four adjustable heavy-duty, white epoxy-coated welded wire shelves, and a full length fluorescent lamp.

Merchandiser to also have automatic condensate evaporator and independent on/off light switch. Cabinet to be foamed-in-place with "zero ODP" urethane insulation and to have a sparkling white polyester enamel interior and exterior. The doors are to be self-closing and have magnetic door gaskets. Rear doors are to be foamed-in-place.

The refrigeration system is to have a self-contained, semi-hermetic condensing unit using R-404A refrigerant. Refrigeration system will also contain a low maintenance bare tube condenser coil. The temperature range is to be 0° to -20°F (-18° to -29°C).

Merchandiser to have standard limited four year extended compressor warranty and one year limited parts and labor warranty. Merchandiser to be UL, C-UL & NSF listed.

NOTE: Cabinet designed for optimum performance in air-conditioned area at 75°F ambient and 55% relative humidity. All specifications subject to change without notice.



908 Highway 15 North • New Albany, MS 38652 PHONE: 800-647-1284 or 662-534-9061 • FAX: 800-232-3966 or 662-534-6049 • www.master-bilt.com



296-5/07-web ©Master-Bilt Products division of Standex International, Inc. All rights reserved, Printed in U.S.A.