

# CyberPower®

Model #: 615

UPC: 649532006151

MSRP: \$11.99



The CyberPower 615 offers basic surge suppression for small electronics with 900 joule MOV power protection. Guarding against lightning induced spikes/surges and utility company line disturbances, your equipment will have a first-line of defense against AC power fluctuations. This surge suppressor is ideal for TVs, stereos, CD players, and other small electronic devices. The suppressor is also equipped with EMI/RFI filtering that blocks unwanted line noise from all connected electronics. CyberPower fully stands behind its products with a lifetime product warranty and Connected Equipment Guarantee of \$45,000.

- MOV (Metal Oxide Varistor) - MOV technology allows normal current to pass through the device, while diverting any surge/spikes through the ground circuit. This safely protects all connected electronics along with the surge suppressor itself.
- Transformer-spaced Outlets - Widely spaced outlets allow you to conveniently add large transformer-based plugs without compromising the utility of other outlets.
- EMI/RFI Shielding - Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or "humming" that occurs over telephone lines or stereo electronics.
- ISO & Safety Certifications - All CyberPower's manufacturing facilities are ISO-9001 Quality Tested. Our products are also UL Listed and CSA Certified.
- Keyhole Mounting Slots – Convenient mounting slots are located on the back on the surge suppressor.
- Sturdy ABS Case – Constructed of impact-resistant composite material for maximum durability.

## Technical Specifications

<b>General</b>	
Model #	615
<b>Input</b>	
Voltage	110/120V Nominal
Plug Type	NEMA 5-15P
Plug Style	Right-angle
Cord Length	4 ft
<b>Output</b>	
Outlets - Total	6
Outlets - Widely Spaced	2 x NEMA 5-15R
Outlets - Normal Spaced	4 x NEMA 5-15R
<b>Surge Protection and Filtering</b>	
Surge Suppression	900 Joules
Phone Protection (RJ11)	None
Ethernet Protection (RJ45)	None
Coax Protection (RG6)	None
Maximum Surge Current	42,500 Amps
Maximum Surge Current H-N	15,000 Amps
Maximum Surge Current H-G	15,000 Amps
Maximum Surge Current N-G	15,000 Amps
Maximum Surge Voltage	6,000V
Clamping Voltage	330 V
Response Time	<1 ns
EMI/RFI Filtration	EMI/RFI 150KHz to 100MHz
Attenuation	Up to 58dB
<b>Indicators</b>	
Indicator Lights	Power (Red); Surge (Red)
<b>Physical</b>	
Dimensions (WxHxD)	11" x 2" x 1.25"
Weight	0.975 lbs.
Color	Black
<b>Warranty</b>	
Product Warranty	Lifetime
Connected Equipment Guarantee	Lifetime
CEG Amount	\$45,000