

# RX-W22



## ► FEATURES

- High 1680 x 1050 WSXGA<sup>+</sup> resolution and high contrast ratio 900:1
- Image sticking (burn-in) prevention function added to secure your investment
- Quick signal-switching time (≤ 0.8 sec.)
- Real-time displaying the image upon signal connection
- Video input settings will resume when power re-plug in
- Looping video inputs for multiple connections
- Auto termination
- Supports NTSC/PAL/SECAM video system
- Supports color and B/W picture
- Selectable signal source
- PC & Mac compatible
- Auto-adjustment for optimal settings when VGA input is selected
- NeoV Optical Glass™
- Slim border& bezel design
- Distinctive metal alloy housing for added strength
- Kensington® security socket
- VESA standard wall mount

## ► SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD
	<b>Panel Size</b>	22.0" (559mm)
	<b>Max. Resolution</b>	WSXGA <sup>+</sup> 1680 x 1050
	<b>Pixel Pitch</b>	0.282mm
	<b>Brightness</b>	300cd/m <sup>2</sup> (Typical)
	<b>Contrast Ratio</b>	900:1 (Typical)
	<b>Viewing Angle (H/V)</b>	170°/160° (Typical)
	<b>Display Color</b>	16.7M
	<b>Response Time</b>	5ms (GTG)
	<b>Frequency (H/V)</b>	H: 24kHz – 83kHz V: 50Hz - 76Hz
Input Connector	<b>Max. Pixel Clock</b>	160MHZ
	<b>Life Time</b>	30,000hrs (Minimum)
	<b>Input Connector</b>	<b>Analog</b> 15-Pin D-Sub <b>Digital</b> 24-Pin DVI-D <b>BNC Security</b> BNC Connector
Input Signal	<b>Input Signal</b>	<b>Analog</b> RGB H.V Sync <b>Digital</b> TMDS <b>Auto Composite System</b> NTSC/PAL/SECAM
	<b>Output Connector</b>	<b>BNC Security</b> BNC Connector
	<b>NeoV Optical Glass</b>	<b>Thickness</b> 3.0mm (0.18") <b>Reflection Rate</b> <1% <b>Transmission Rate</b> >96% <b>Hardness</b> >6H (MOH's Rating)
Tilt	<b>Tilt</b>	0° ~ +20°
Mounting	<b>VESA FPMPI</b>	Yes (100mm)
Regulation Approval	<b>Certifications &amp; Compliance</b>	FCC-B, UL/CUL, NOM, CB, CE, TUV/Baurt, BSMI, NORDIC, GOST, WEEE, RoHS, <b>VESA</b> DDC 1/2B, DDC-CI
Power	<b>Power Source</b>	100 - 240V, 50 - 60Hz
	<b>Consumption</b>	<48W (On) <1W (Off)
Temperature	<b>Operation</b>	0°C ~ 40°C
	<b>Storage</b>	-20°C ~ 60°C
Dimensions	<b>Net (W x H x D)</b>	512 x 392 x 155 mm (20.2" x 15.4" x 6.1")
	<b>Packing (W x H x D)</b>	586 x 508 x 195 mm (23.1" x 20.0" x 7.7")
Weight	<b>Net Weight</b>	6.9kg (15.2 lbs)
	<b>Gross Weight</b>	10.5kg (23.1 lbs)
Packing	<b>1 Pallet</b>	40 Sets
	<b>20' Container</b>	400 Sets
	<b>40' Container</b>	840 Sets

All specifications are subject to change without prior notice