

Monet
SERIES

KX·P
SERIES **8410**

Digital
Color
Laser
Printer



Panasonic

the color of
communication™

KX·P SERIES 8410



Affordable quality color— only from Panasonic. The KX-P8410 Series brings available, high-quality color printing to every business environment. Available in three powerful configurations, you will find a Panasonic 8410 Series Printer to meet your specific needs.



KX-P8410
Entry level 600 x 600 dpi color laser printer, 8 MB RAM upgradable to 72 MB, 350 sheet letter size paper capacity.

KX-P8410D
1200 x 1200 dpi color laser printer for departmental use (optional Ethernet network card), 72 MB RAM, 350 sheet letter size paper capacity

KX-P8410N
1200 x 1200 dpi color laser printer for network color laser printing (Ethernet network card included), 72 MB RAM, 850 sheet letter size paper capacity.

Warranty and Support Programs

- One year limited warranty (excluding consumables)
- 90-day free on-site coverage with product registration
- One to three year on-site service upgrades available
- Toll free color support



**TOLL-FREE
Color Support**



the color of communication™

Panasonic Computer Peripheral Company
Division of Panasonic Communications & Systems Company
Unit of Matsushita Electric Company of Japan

Headquarters: Two Panasonic Way, Secaucus, NJ 07094

www.panasonic.com/alive

printer

Resolution	Up to 1200 x 1200 dpi ⁺
Print Speed (black)	14 ppm @ 600 x 600 dpi; 7 ppm @ 1200 x 1200 dpi
Print Speed (full color)	3.5 ppm @ 600 x 600 dpi; 1.75 ppm @ 1200 x 1200 dpi
Color Matching Emulation	Windows ICM, Panasonic Hyper-Tetra patented color matching GDI (Windows 3.1, 95, Windows for Workgroups & NT 4.0 ⁺⁺)
Memory	Up to 72 MB; 8 MB Standard ⁺ 2 SIMM slots, up to 32 MB/slot
Interfaces	IEEE 1284 & SCSI-II
Recording Method	Electrophotographic, four color
Dimensions / Weight	20.1" (W) x 19.4" (D) x 18.2" (H); 127 lbs. (shipping weight)

paper handling

Paper Size / Media Paper Input	Letter, legal, A4, transparencies, laser labels & #10 laser envelopes Standard: 250 sheets/up to 24 lbs. Standard: Built-in multipurpose tray w/manual feed Up to 100 sheet paper (20 lbs.) Up to 44 lb paper stock Up to 50 transparency sheets #10 Laser-quality envelopes Laser-quality labels Optional: 2 cassettes (250 sheets each/Up to 24 lbs.) Optional: Transparency cassette (100 sheets)
Output Tray Manual Feed Mode	Face up/down, up to 500 sheets Face up with auto switching

consumables & accessories

Starter Kit	3,000 prints each color (C,M,Y,K)	
Cost Per Page (black)	Approximately 3¢ @ 5% coverage including all consumables	
Cost Per Page (color)	Approximately 10¢ @ 5% coverage/color in four color, including all consumables	
Replaceable Components	Imaging kit, fuser kit, transfer kit, web unit	
	Specification	Part Number
Black Toner	12,000 prints	KX-PDPK5
Cyan Toner	10,000 prints	KX-PDPC5
Magenta Toner	10,000 prints	KX-PDPM5
Yellow Toner	10,000 prints	KX-PDPV5
Color Imaging Unit	60,000 prints	KX-PPRC5
Fuser Unit	30,000 prints	KX-PFSU5
Web Unit	15,000 prints	KX-PWBR5
Transfer Unit	60,000 prints	KX-PTRU5
Paper Cassettes	2-250 sheet letter size (KX-PCSF1), 250 sheet legal size (KX-PKC7), 100 sheet transparency (KX-PKC5)	
Memory Upgrade Kits	4 MB (CLBP-RAM4), 8 MB (CLBP-RAM8), 16 MB (CLBP-RAM16), 32 MB (CLBP-RAM32)	
Network Option	Ethernet Card	KX-PNBC4
Printer Stands	16.5" high, 4 casters	CLBP High stand
	6" high, 4 casters	CLBP Low stand

memory requirements

Total Memory	Selectable Print Quality Mode	Printable
20 MB	Standard (600 DPI)	Letter, A4, Legal
64 MB	High Quality (1200 DPI)	Letter, A4
72 MB	High Quality (1200 DPI)	Letter, A4, Legal

recommended system requirements

133 MHz Pentium Processor or Greater
500 MB Free Hard Disk Space
IEEE 1284 High Speed Parallel Interface or SCSI-II Interface
Windows 3.1, 3.11, 95 or Windows NT

power requirements

110V 60Hz 9.1 Amps—operational; 0.4 Amps—standby
Energy Star Compliant

⁺ Requires a minimum of 24MB of printer RAM ⁺⁺ Windows NT 4.0 will be available Fall, '97. All product and/or brand names are trademarks or registered trademarks of their respective holders. This product may be subject to export control regulations. Product may be shown with optional stand and paper cassette.