



## E218c1

<b>Cabinet Color</b>	Black Cabinet with Polished/Glossy Black Bezel
<b>Panel</b>	TFT Active Matrix LCD VIS: 22" (55.9cm) Widescreen, Diagonal Hard Coating (3H), Anti-glare Treatment
<b>Pixel Pitch</b>	0.282mm x 0.282mm
<b>Display Area</b>	474mm x 296mm
<b>Brightness</b>	300 cd/m2 (typ)
<b>Contrast Ratio</b>	700:1 (typ)
<b>Response Time</b>	5ms (typ)
<b>Viewing Angle</b>	Horizontal: 170 Degrees (CR>10) Vertical: 160 Degrees (CR>10)
<b>Compatibility</b>	VESA, WSXGA+, WXGA+, SXGA, XGA, SVGA, VGA Mac® Equipped With Analog VGA Dsub or DVI Port
<b>Scanning Frequency</b>	Horizontal: 30K~80KHz Vertical: 50~75 Hz
<b>Pixel Frequency</b>	146MHz
<b>Maximum Resolution</b>	1680x1050x60Hz
<b>Recommended Resolution</b>	1680x1050@60Hz
<b>Resolutions Supported</b>	720x400@70Hz, 640x480@60, 67, 75Hz 800x600@56, 60, 72, 75Hz, 848x480@60Hz 1024x768@60, 70, 75Hz, 1152x864@75Hz 1280x720@60Hz, 1280x960@60Hz, 1280x768@60, 75Hz 1280x1024@60, 75Hz, 1360x768@60Hz, 1440x900@60, 75Hz 1440x900@60,
<b>Color</b>	16M
<b>Signal Input</b>	Video: 0.7Vp-p, RGB Analog Separate Sync: TTL Level H/V Sync: Positive / Negative
<b>Digital Input</b>	DVI-D (TMDS) with HDCP*
<b>Connectors</b>	Analog RGB Signal: 15-pin D-sub Male Digital Signal: 24-pin DVI-D Power: (3-Pin Plug CEE22) Audio: 3.5mm Stereo Headphone: 3.5mm mini jack Microphone: 3.5mm mini jack USB: 1x upstream & 3x downstream
<b>Power Source</b>	Universal 90~264VAC, 50/60Hz
<b>Power Consumption</b>	58Watts (Max)
<b>Plug &amp; Play</b>	DDC2B
<b>EPA ENERGY STAR®</b>	Yes
<b>User Control</b>	Menu, Down/Brightness, Up/Contrast, Confirm, Power On/Off
<b>OSD Function</b>	Auto Adjust, Contrast, Brightness, Input Select (Analog, Digital), Audio Adjust (Volume, Mute), Color Adjust (9300K, 6500K, 5400K, User), Information (H/V Frequency, Resolution, Pixel Clock, Serial Number, Model Number, Manual Image Adjust (Horizontal Size)
<b>OSD Languages</b>	English, French, Spanish
<b>Regulations</b>	cULus, FCC, CE, Certified for Windows Vista Logo
<b>Built-in Speakers</b>	Total 5W Built-in 1.3MP Webcam & Microphone Echo Cancellation 720p/1080i HD Compatible Height Adjustment, Swivel Stand USB 2.0 Hub Application Software VESA 100mm Wall Mount Compliant**
<b>Other Features</b>	Kensington Security Slot
<b>Dimensions (WxHxD mm)</b>	Monitor: 518.4x403.4x216.0; Carton: 565x522x150
<b>Dimensions (WxHxD inches)</b>	Monitor: 20.4x15.9x8.5; Carton: 22.2x20.6x5.9
<b>Weight</b>	16.5 lbs (7.5 kgs) Net, 12.7 lbs (5.8 kgs) w/o base 21.36 lbs (9.7 kgs) Gross
<b>Loading Qty w/pallet</b>	40' Std = 704
<b>UPC Code</b>	685417103188