



LCD MONITOR

Display size	21,6" (54,86 cm) WIDE					
Panel Type	Active Matrix TFT					
Brightness	300 cd/m ² (typ.)					
Contrast (typ.)	1000:1					
X-Contrast (dyn.)	-					
Pixel pitch	0,277(H) x 0,277(V) mm					
Resolution (H x V)	WSXGA+ 1680 x 1050					
Response time	5 ms (typ.)					
View angles (CR>10)	H/V 170° / 160°					
View angles (CR>5)						
Display colors	16,7 Mio colors					
Display Surface	AG					
Input 1	VGA, Audio					
Input 2	HDMI (HDCP)					
Input 3						
Headphone						
Speakers	1 W x 2					
Supply	AC 100~240V, 50~60Hz					
Consumption	On:	55 W	Stand-by:	<2 W	Off:	<1 W
Operation Temp/Hum	0 ~ 40°C			20 - 90%		
Dimension (W*D*H)	520 x 235 x 410 mm					
Net weight	5,8 kg					
Tilt	0°~ 20°					
Kensington Lock	✓					
VESA mounting	VESA Standard, 100mm					
On screen display	EN,TC,DE,FR,ES,IT,PT,NL,SC,JS,KR					
Safety	CE, FCC, BSMI, C-Tick, VCCI, Nemko CB, UL/CUL, 3C, Nemko GS, Vista Premium					
Emission	TCO03					
Power saving	Energystar					
Extras 1						
Extras 2						
Extras 3						
EAN	4710859555021					
incl Accessory	Cables (Power, VGA, Audio), Quickstart, User manual, Warranty card					



© HANNspree Europe GmbH. Information in this document is subject to change without notice. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screenshots are simulated.