


Overview



- 1. Menu button
- 2. - adjust

- 3. + adjust
- 4. Power on/off

Models

P9602A#ABA

HP Care Pack Services

Next Day Onsite Response, 3 years

Next Day Onsite Response, 4 years

Next Day Onsite Response, 5 years

Basic 8-5, 4 Hour Onsite Response, 3 years

Basic 8-5, 4 Hour Onsite Response, 4 years

Basic 8-5, 4 Hour Onsite Response, 5 years

Post Warranty Service, Next Day Onsite

H2754E

U7934E

U7935E

U8317E

U8318E

U8319E

U4925PE

Technical Specifications

Panel	Type	19-inch Active Matrix TFT (thin film transistor)
	Viewable Image Area (diagonal)	19.0 in (48.25 cm) maximum, diagonal
	Screen Opening (W x H)	14.81 x 11.85 in (37.6 x 30.1 cm)
	Viewing Angle (typical)*	Up to 140 degrees horizontal/ 140 degrees vertical (10:1 minimum contrast ratio)
	Brightness (typical)*	Up to 250 nits (cd/m ²)
	Contrast Ratio (typical)*	Up to 500:1 (typical)
	Response Rate (typical)*	16 ms (typical) (rise + fall)
	Pixel Pitch	0.294 mm
	Colour Depth Support	> 16 million colours
	Backlight Lamp Life (to half brightness)	40K hours
<p>*All performance specifications are provided by the component manufacturers. Performance specifications represent the highest specification of all HP's component manufacturers' typical level specifications for performance. Actual performance may vary either higher or lower.</p>		
Video Input	Plug and Play	Yes
	Input Signal	Attached 15-pin D-sub (analog VGA)
	Input Impedance	75 ohms DC ± 1.5 ohms
	Sync Input	TTL separate sync
	Video Cable	VGA
	Video Cable Length	5.9 ft (1.8 m); captive
Signal Interface/ Performance	Horizontal Frequency	30 to 81 kHz
	Vertical Frequency	56 to 76 Hz
	Graphics Controller	Genesis or ST or MST
	Native Resolution	1280 x 1024 @ 60 Hz (recommended)
	Maximum Resolution (Digital)	N/A
	Preset VESA Graphic Modes (non-interlaced)	1280 x 1024 @ 60 Hz and 75 Hz
		1024 x 768 @ 60 Hz, 70 Hz, and 75 Hz
		800 x 600 @ 60 Hz, 72 Hz, and 75 Hz
		640 x 480 @ 60 Hz, 72 Hz, and 75 Hz
	Maximum Pixel Clock Speed	140 MHz
	User Programmable Modes	15
	Anti-Glare	Yes
	Anti-Static	Yes
Default Colour Temperature	6500 sRGB	

Technical Specifications

On Screen Display (OSD) Controls	Buttons or Switches	Power on/off 3 button OSD (menu, plus, minus)	
	Languages	English, Spanish, French, Italian, German, Dutch	
	User Controls	Brightness	
		Contrast	
		Horizontal/vertical position	
		Colour temperature (6500k, 9300k, Custom)	
		Clock, clock phase	
		Power saver, power on recall	
		Mode display	
		Sleep timer	
		Horizontal OSD position, vertical OSD position, OSD timeout	
		Factory reset	
Power	Input Power	Universal/auto-sensing, 100 to 240 VAC, 50 to 60 Hz	
	Typical Power Consumption	33 watts	
	Maximum	< 40 watts	
	Power Saving	< 2 watts	
	Power Cable Length	5.9 ft (1.8 m)	
Mechanical	Dimensions (H x W x D)	Unpacked w/ stand	16.8 x 16.6 x 7.8 in (42.7 x 42.2 x 19.7 cm)
		Unpacked w/o stand	14.2 x 16.6 x 2.9 in (36.1 x 42.2 x 7.5 cm)
		Packaged	20.1 x 7.0 x 20.1 in (17.8 x 51.2 x 51.2 cm)
	Weight	Unpacked	14.4 lb (6.5 kg)
		Packaged	18.8 lb (8.5 kg)
	Tilt Range	-5 to +30 degrees vertical tilt	
	Swivel Range	None	
	Height Adjustable	No	
	Pivot Rotation	No	
	Base	Detachable	
Environmental	Temperature – Operating	41° to 95° F (5° to 35° C) (non-condensing)	
	Temperature – Non-operating	-4° to 140° F (-20° to 60° C)	
	Humidity – Operating	20% to 80% (non-condensing)	
	Humidity – Non-operating	5% to 90%	
	Altitude – Operating	0 to 12,000 ft (0 to 3,658 m)	
	Altitude – Non-operating	0 to 40,000 ft (0 to 12,100 m)	
Options	HP Desktop Access Centre	Optional; Features integrated microphone/headset jacks, dual function headset for phone/PC support, a MultiBay slot for adding an optical drive (sold separately), and four USB ports for easy integration of third-party digital solutions; part number DK985A. For more information, refer to the HP Desktop Access Centre QuickSpecs.	

Technical Specifications

Other	Accessories Included	Attached VGA Cable, AC Power Cable
	User Guide Languages	English, French, German, Spanish, Italian, Dutch
	Warranty Languages	English, French, German, Spanish, Italian, Dutch
	Colour	Carbonite/Silver
	VESA Mounting	100 mm x 100 mm screw-mounting option; pedestal is attached
	VESA External Mounting	Yes (Standard 4 hole pattern, 100 mm)
	Kensington Lock-ready	Yes
Certification and Compliance	ISO 9241-3,7,8 VDT guidelines, ISO 13406-2 pixel defect guidelines, MPR-II, CISPR, VCCI, C-UL or CSA (Canada), ACA (Australia), TUV and GS Mark (German ergonomic), BSMI (Taiwan), CCC (China), MIC (South Korea), NOM (Mexico), Nemko, Fimko, Demko, Semko (Nordic) Eastern European approvals, CE Marking, FCC approval, Energy Star, TCO '03 (emissions, ergonomics, environment), Microsoft® Windows® certified (Microsoft® Windows® 2000 and Microsoft Windows XP), UL listed	
Compatibility	Compatible with platforms using VESA standard video modes. Recommended for use with HP products.	
Service and Warranty	Three years parts, labour, and on-site service. 24-hour 365-day 1-800 technical support. Replacement options include 2nd business day on-site service or next business day direct replacement. With direct replacement, HP will ship a replacement display product directly to you. Using the shipping labels provided, return your failed display to HP. Certain restrictions and exclusions apply. For details, consult the Product Information Centre at 1-888-882-6672.	

© 2005 Hewlett-Packard Development Company, L.P.

Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the U.S. and other countries.

HP shall not be liable for technical or editorial errors or omissions contained herein. The information is provided as is without warranty of any kind and is subject to change without notice. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. All performance specifications are provided by the component manufacturer. Performance specifications represent component manufacturer averages and actual performance may vary.