



ProLite E2207WS-2

The 22" widescreen LCD continues to provide excellent value for money for the home and office user, with high specification and the OptiColour' mode. This feature automatically adjusts contrast, brightness and RGB colour balance to its optimum conditions to whichever mode you chose whether Game, Text, Scenic or Cinema – and also enabling you to switch through these modes with ease and speed. The 1.8 mega-pixel resolution offers outstanding graphics. ProLite E2207WS-2 has an impressive 60 000: 1 Advanced Contrast Ratio which can be disabled for greater colour accuracy and a 2msec response time ensuring the best possible video and animation playback with minimal blurring. The display has been tested to meet all of the technical requirements to be Certified for Windows VistaTM.

DISPLAY CHARACTERISTICS

Diagonal	22"		
Panel	TN		
Display area h x w	296.1 x 477.7 mm; 11.66" x 18.81"		
Response time	2 ms		
Contrast	1000 : 1 typical		
Contrast	60 000 : 1 ACR		
Brightness	300 cd/m² typical		
Viewing zone	horizontal/vertical: 170°/ 160°; right/left: 85°/ 85°; up/down: 80°/ 80°		
Viewing zone CR>5	horizontal/vertical: 178°/ 178°; right/left: 89°/ 89°; up/down: 89°/ 89°		
Display colour	16.7 million		
Pixel pitch h x v	0.282 x 0.282 mm		
Native resolution	1680 x 1050 (1.8 megapixel)		
Horizontal sync	31 - 80 KHz		
Vertical sync	56 - 75 Hz		
Bandwidth	146 MHz		
Synchronization	Separate Sync		
Aspect ratio	16:10		

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	38 W typical; max. 2 W in Power management mode
Power management	VESA DPMS

INTERFACES CONNECTORS

Analog input connector	D-Sub
Digital input connector	DVI-D
HDCP	yes

SPECIAL FEATURES

Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.		
Plug & Play	VESA DDC 1/2B™		
Controls	On-Screen-Display in 9 languages (EN, FR, DE, IT, ES, JP, FI, Chinese - traditional and simplified) and 5 Front controls (Menu, Scroll down /Brightness/ Contarst/ ACR/ ECO, Scroll up/ OptiColour Mode, Select /Input Select, Power)		
User controls	auto adjust, contrast, brightness, ACR, ECO mode, input select, audio (volume, mute), colour adjust, manual image adjust (horizontal size, H position, V position, fine tune, sharpness, video mode adjust, OptiColour mode), setup menu (OSD language, OSD position, OSD time out, OSD background), restore		
Speakers	2 x 2 W (Stereo)		
Anti-theft-device	Kensington-lock™ prepared		
Safety	CE, TUV/Baurt		
Tilt angle	20° up; ° down		
VESA mounting	100 mm		
Colour	Black		
Vista premium	Yes		

DIMENSIONS & WEIGHT

Dimensions w x h x d	517 x 410 x 220 mm	ACCESSORIES		
Weight	5.1 kg		Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
			Included accessories	power cable, D-Sub cable, DVI-D cable,
				audio cable, user manual, stand

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.