

Personal Systems Reference Lenovo® Consumer Monitors

December 2011 - Version 411



Lenovo L2363d Wide Monitor

L2062 Wide Flat Panel Monitor Name High gloss black with metal gray 1173-US1 Case color

Type-model

TFT-LCD, twisted nematic (TN), white LED backlight Panel

Viewable image size 20.0" / 508mm (diagonal) 17.4" x 9.8" / 443mm x 249mm Max view area (W x H)

Optimum resolution 1600x900 Max pixel rate 153 MHz Aspect ratio 16:9 Pixel pitch (mm) 0.277mm Dot/Pixel per Inch 92 dpi

Brightness 250 nits or cd/m2 (typical)

Contrast ratio 1000:1 (typical) Dynamic contrast ratio 5,000,000:1 Pixel response time 5ms (typical) Color gamut

Anti-reflective Anti-reflective, anti-glare

170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Viewing angle at 10:1 CR

Tilt adjustable stand Stand Bezel width Sides: 0.63" (16mm); Dimensions (HxWxD)

14.3" H x 18.9" W x 6.9" D; 362.5mm H x 480.0mm W x 174.8mm D 17 watts typical, 22 watts maximum, Power supply

<1 watts standby/suspend, universal, integrated (no external brick-like power supply) 7.99 lb; 3.63 kg

Weight 1 year Limited warranty4

(includes backlight) Available date May 2011

VESA-compliant² VESA DDC2B/CI, VESA DPMS-compliant

ENERGY STAR®35.0 Power management ISO 9241-307 Ergonomics Emission standards Environmental

FCC Class B TCO (TCO Displays 5.2), WEEE (EU Directive 2002/96/EC),

RoHS (EU Directive 2002/95/EC)

Preset resolutions 640x350, 640x480, 720x400 VGA:

SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 1366x768 WXGA: SXGA: 1280x1024

WXGA+: 1440 x 900, 1600x900 Standard presets: 24; user settings: 20

Viewing adjustments Tilt: 20° back, -5° forward; detachable stand

Rotating screen On screen display with digital user controls (8 languages) On screen display Control features Direct access (control buttons on front) for automatic image setup

USB hub

Presets / user settings

Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Multiple input

Monitor connectors

(1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D) for digital attach [white], **HDCP-compliant**

Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter

Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPMI® (100mm mount) Security

Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)

Ship group Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, analog signal cable, 1.8m power cord

Limited Warranty

- 1 year limited warranty⁴
- Advanced Exchange Service at 1-877-453-6686
- Replacement normally arrives in five business days, excluding holidays
- Lenovo pays all shipping costs for valid warranty claims⁶
- 24x78 day toll-free support for warranty issues during the warranty period4

Features

- Widescreen 20-inch monitor
- View images in a 16x9 wide aspect ratio
 High-bandwidth Digital Content Protection (HDCP)-compliant
- Tilt and cable management stand
- Compliance with ENERGY STAR 5.0
- Mercury-free and Arsenic-free panel glass
 Kensington® lock slot ready for enhanced security
- Microsoft® Windows® 7 certified



Lenovo L2062 Wide Monitor

Accessories

Kensington® MicroSaver® Cable Lock 73P2582 Kensington Twin Head Cable Lock 45K1620

See details at www.lenovo.com/support/monitoraccessories

More information at www.lenovo.com/support/monitors

L2262 Wide Flat Panel Monitor Name High gloss black with metal gray 0560-US1 Case color Type-model

Panel TFT-LCD, twisted nematic (TN), white LED backlight

Viewable image size

21.5" (**546mm**) diagonal 18.8" x 10.6" / 476.6mm x 268.1mm Max view area (W x H) Optimum resolution 1920x1080 Max pixel rate VGA: 205MHz; DVI: 165MHz

Aspect ratio 16:9 Pixel pitch (mm) .248mm Dot/Pixel per Inch 103 dpi

Brightness 250 nits or cd/m2 (typical)

1000:1 (typical) Contrast ratio Dynamic contrast ratio 5,000,000:1 Pixel response time 5ms (typical) Color gamut 72% 50 to 76Hz Vertical frequency Horizontal frequency 30 to 83kHz

Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical

Stand Tilt adjustable stand

Bezel width

Sides: 0.75" (19.0mm); top: 0.72" (18.2mm); bottom: 1.07" (27.3mm) 15.08" H x 20.31" W x 7.07" D; 383mm H x 516mm W x 179.6mm D Dimensions (HxWxD) 23 watts typical, 27 watts maximum. Power supply

<1 watts standby/suspend, universal, integrated (no external brick-like power supply)

9.13 lb; 4.14 kg Weight

1 year (includes backlight) Limited warranty4

Available date June 2011

VESA DDC2B/CI, VESA DPMS-compliant VESA-compliant²

ENERGY STAR®3 5.0 Power management Ergonomics ISO 9241-307 Emission standards

Environmental

ISO 9241-307 FCC Class B TCO (TCO Displays 5.1), WEEE (EU DIRECTIVE 2002/96/EC), RoHS (EU DIRECTIVE 2002/95/EC)

640x350, 640x480 800x600, 832x624 Preset resolutions VGA: SVGA:

XGA: 1024x768, XGA+: 1152x864 SXGA: 1280x1024 HD: 1366x768 WXGA+: 1440x900 WSXGA+: 1680x1050 Full HD: 1920x1080

Presets / user settings Standard presets: 26; user settings: 20

Viewing adjustments Tilt: 20° back, -5° forward; detachable stand

Rotating screen None

On screen display On screen display with digital user controls (8 languages)

Control features Direct access (touch sensitive buttons on front) for automatic image setup, dual input, brightness, and NOVO vision USB hub

Camera

Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) Monitor connectors

(1) VGA 15-pin D-shell, analog, blue

Signal cables

(2) Digital Visual Interface (DVI-D) for digital attach [white], HDCP-compliant
(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter
Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPMI® (100mm mount) Mounting features

Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)

Ship group Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor

installation files, 1.8 meter analog signal cable, 1.8 meter black power cord

Limited Warranty

- 1 year limited warranty⁴
- Advanced Exchange Service at 1-877-453-6686
- Replacement normally arrives in five business days, excluding holidays
- Lenovo pays all shipping costs for valid warranty claims⁶
- 24x78 day toll-free support for warranty issues during the warranty period4

Features

- Widescreen 21.5-inch monitor with white LED backlight
- View images in a 16x9 wide aspect ratio
- High-bandwidth Digital Content Protection (HDCP)-compliant
- Tilt and cable management standCompliance with ENERGY STAR 5.0
- Touch sensitive control buttons can give user new comfortable experiences
- Kensington® lock slot ready for enhanced security
- Microsoft® Windows® 7 certified



Lenovo L2262 Wide Monitor

Accessories

73P2582 Kensington® MicroSaver® Cable Lock Kensington Twin Head Cable Lock 45K1620

See details at www.lenovo.com/support/monitoraccessories More information at www.lenovo.com/support/monitors

LI2361d Wide Flat Panel Monitor Name High gloss black with metal gray 1192-US1 Case color

Type-model

Panel TFT-LCD, twisted nematic (TN), white LED backlight

Viewable image size

23.0" (584mm) diagonal 20.04" x 11.28" / 509.2mm x 286.4mm 1920x1080 Max view area (W x H) Optimum resolution Max pixel rate 205MHz (VGA), 165MHz (HDMI/DVI)

Aspect ratio 16:9 Pixel pitch (mm) .265mm Dot/Pixel per Inch 96 dpi

Brightness 250 nits or cd/m2 (typical)

1000:1 (typical) 10,000,000:1 Contrast ratio Dynamic contrast ratio Pixel response time

5ms (typical) 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Viewing angle at 10:1 CR

Tilt adjustable stand Stand Bezel width

Sides: 0.74" (18.7mm) 16.18" H x 21.61" W x 7.47" D; 411.0mm H x 549.0mm W x 189.8mm D Dimensions (HxWxD)

40 watts typical, 45 watts maximum, Power supply <1 watts standby/suspend, universal,

integrated (no external brick-like power supply)

Weight Limited warranty⁴ 11.0 lb; 5.0kg 1 year January 2012 Available date

VESA-compliant² VESA DDC2B/CI, EDID 1.4A, VESA DPMS-compliant

ENERGY STAR®3 5.1 Power management Ergonomics ISO 9241-307 FCC Class B Emission standards

Environmental WEEE (EU Directive 2002/96/EC), RoHS (EU Directive 2002/95/EC)

Preset resolutions VGA: 640x350, 640x480, 720x400

SVGA: 800x600, 832x624 XGA: 1024x768,1152x864 SXGA: 1280x1024

1280x768, 1280x800, 1366x768 1440x900, 1600x900 WXGA:

WXGA+: WSXGA+: 1680x1050

WUXGA: 1920x1080 Presets: 26 (VGA), 24 (HDMI); Presets / user settings

user settings: 20

Features

Widescreen 23-inch monitor

• 1080p full HD support, HDCP-compliant Lenovo's 3D monitor, supports new FPR 3D technology

(FPR: Film-type Patterned Retarder)

• Built-in VGA, DVI and HDMI 1.4 connectors for attachment to

three systems concurrently

• Compliance with ENERGY STAR 5.1

Kensington® lock slot ready for enhanced security

Microsoft® Windows 7 certified



LI2361d Wide Monitor

Tilt: 20° back, -5° forward Viewing adjustments

Rotating screen None

On screen display On screen display with digital user controls (8 languages)

Direct access (control buttons on front) for automatic image setup and adjustment for brightness Control features

Triple input (three different PCs attach to three different connectors; one PC shows image; select via button) Multiple input

(1) Digital Visual Interface (DVI-D), digital, white, **HDCP-compliant** (2) HDMI (1.4), digital, black, **HDCP-compliant** Monitor connectors

(3) VGA 15-pin D-shell, analog, blue

Signal cables

detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter
Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPMI® (100mm mount) Mounting features Security Security

Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)

Monitor, attached Stand and Base, 3D glasses, 3D poster, Monitor shopping bag, Warranty information, Ship group

1 CD with multilingual User's Guide, quick setup guide and monitor installation files,

1.8 meter analog signal cable, 1.8 meter black power cord

Limited Warranty

- 1 year limited warranty⁴
- Replacement normally arrives in five business days, excluding holidays
- Lenovo pays all shipping costs for valid warranty claims⁶
- 24x7° day toll-free support for warranty issues during the warranty period⁴

Accessories

Kensington MicroSaver® Cable Lock Kensington Twin Head Cable Lock 73P2582 45K1620

See details at www.lenovo.com/support/monitoraccessories

See all monitors at www.lenovo.com/support/monitors

See footnotes for important warranty information US model announced December 6, 2011

L2362p Wide Flat Panel Monitor Name High gloss black with metal gray 0559-US1 Case color Type-model Panel TFT-LCD, twisted nematic (TN), white LED backlight **23.0**" (**584mm**) diagonal 20.0" x 11.3" / 509.2mm x 286.4mm Viewable image size Max view area (W x H) Optimum resolution 1920x1080 Max pixel rate VGA: 205MHz; HDMI: 165MHz Aspect ratio 16:9 Pixel pitch (mm) .265mm Dot/Pixel per Inch 96 dpi Brightness 250 nits or cd/m2 (typical) Contrast ratio 1000:1 (typical) Dynamic contrast ratio 5,000,000:1 Pixel response time 5ms (typical) Color gamut 72% Vertical frequency 50 to 75Hz Horizontal frequency 30 to 83kHz 30 to 83kHz 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Tilt and swivel adjustable stand Sides: 0.74" (18.7mm); top: 1.05" (26.7mm); bottom: 1.06" (26.8mm) 16.18" H x 21.61" W x 7.47" D; 411mm H x 549mm W x 189.8mm D Viewing angle at 10:1 CR Stand Bezel width Dimensions (HxWxD) 41 min in x 349mm w x 169.5mm D
40 watts typical, 45 watts maximum,
<1 watts standby/suspend, universal,
integrated (no external brick-like power supply)
11.79 lb; 5.35 kg Power supply Weight 1 year (includes backlight) Limited warranty4 Available date July 2011 VESA DDC2B/CI, VESA DPMS-compliant VESA-compliant² ENERGY STAR®3 5.0 Power management Ergonomics ISO 9241-307 TCO (TCO Displays 5.1), WEEE (EU DIRECTIVE 2002/96/EC), ROHS (EU DIRECTIVE 2002/95/EC) Emission standards Environmental Preset resolutions (VGA) VGA: 640x480 SVGA: 800x600 XGA: 1024x768 XGA+: 1152x864 SXGA: 1280x1024

Features

- Widescreen 23-inch monitor with white LED backlight
- · View images in a 16x9 wide aspect ratio
- 1080p full HD support, HDCP-compliant
- Tilt, swivel, and cable management stand
 Compliance with ENERGY STAR 5.0

- Integrated camera (0.3 megapixel) and digital microphone
 Internal speaker (3 watts x 2) on bottom
 Integrated USB 2.0 Hub (1 port into PC, 4 ports for accessories)
- Touch sensitive control buttons can give user new comfortable experiences
- Kensington® lock slot ready for enhanced security
 Microsoft® Windows® 7 certified



Lenovo L2362p Wide Monitor

user settings: 20 Tilt: 20° back, -5° forward; swivel: +/-150°; detachable stand Viewing adjustments Rotating screen On screen display On screen display with digital user controls (8 languages)

1366x768

1680x1050

1920x1080

1440x900, 1600x900

Standard presets: VGA: 26; HDMI: 24;

Control features Direct access (touch sensitive buttons on front) for volume up/down, mute, automatic image setup, dual input,

brightness, and NOVO vision

USB hub USB 2.0 Hub (1 port into PC, 4 ports for accessories) Camera Integrated camera (0.3 megapixel) and digital microphone

Internal speaker (3 watts x 2) on bottom, audio in jack (3.5mm) and audio out jack (3.5mm) on rear Speaker Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)

Monitor connectors

HD:

WXGA+:

Full HD:

WSXGA+:

Signal cables

(1) VGA 15-pin D-shell, analog, blue (2) HDMI (1.3), digital, black, **HDCP-compliant** (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter

(2) detachable, HDMI at each end, digital, 1.8 meter

Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPMI® (100mm mount) Security

Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)

Monitor, attached stand, Setup poster, Warranty Information, CD with multilingual User's Guide and monitor installation files, clean cloth, 1.8 meter analog signal cable, 1.8 meter HDMI cable, 1.8 meter USB cable, 1.8 meter power cord, Ship group

1.8 meter audio cable

Limited Warranty

1 year limited warranty⁴

Presets / user settings

- Advanced Exchange Service at 1-877-453-6686
- Replacement normally arrives in five business days, excluding holidays
- Lenovo pays all shipping costs for valid warranty claims
- 24x78 day toll-free support for warranty issues during the warranty period

Accessories

Kensington® MicroSaver® Cable Lock 73P2582 Kensington Twin Head Cable Lock 45K1620

See details at www.lenovo.com/support/monitoraccessories More information at www.lenovo.com/support/monitors

L2363d Wide Flat Panel Monitor Name High gloss black with metal gray 4452-US1 Case color Type-model Panel TFT-LCD, twisted nematic (TN), CCFL backlight 23.0" (584mm) diagonal 20.04" x 11.28" / 509.2mm x 286.4mm 1920x1080 Viewable image size Max view area (W x H) Optimum resolution Max pixel rate 290MHz (DVI), 165MHz (HDMI) Aspect ratio 16:9 Pixel pitch (mm) .265mm Dot/Pixel per Inch 96 dpi Brightness 400 nits or cd/m2 (typical) Contrast ratio 1000:1 (typical) Dynamic contrast ratio 20000:1 5ms (typical) Anti-reflective, anti-glare Pixel response time Anti-reflective Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Tilt adjustable stand Sides: 1.13" (28.7mm) 16.69" H x 22.40" W x 6.57" D; Stand Bezel width Dimensions (HxWxD) 423.8mm H x 569.0mm W x 167.0mm D 55 watts typical, 60 watts maximum, Power supply <2 watts standby/suspend, universal, integrated (no external brick-like power supply) Weight Limited warranty⁴ 13.2 lb; 6.0kg

1 year (includes backlight) April 2011 Available date VESA DDC2B/CI, EDID 1.3, VESA DPMS-compliant VESA-compliant² Power management ENERGY STAR®35.0 Ergonomics ISO 9241-307 Emission standards FCC Class B WEEE (EU Directive 2002/96/EC), Environmental RoHS (EU Directive 2002/95/EC) Preset resolutions 640x350, 640x480, 720x400 800x600, 832x624 VGA: SVGA: XGA: 1024x768,1152x864 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900, 1600x900 WSXGA+: 1680x1050 1920x1080 (support 120Hz refresh rate WUXGA: for 3D display mode) Presets: 29 (DVI), 24 (HDMI); Presets / user settings

Features

- Widescreen 23-inch monitor
- 1080p full HD support, HDCP-compliant
- Lenovo's first 3D monitor, supports NVIDIA® 3D Vision™ (requires selected NVIDIA graphics card configurations)
- Supports 120Hz refresh rate
- Integrated 3D Web Camera to record 3D images
- Built-in DVI and HDMI 1.3 connectors for attachment to two systems concurrently
- 10-60 degree easily adjustable stand and VESA mount
 Compliance with ENERGY STAR 5.0

- Arsenic free glass
 Kensington® lock slot ready for enhanced security
 Microsoft® Windows 7 certified



L2363d Wide Monitor

user settings: 20 Tilt: 10°-60° back, 0° forward; adjustable stand Viewing adjustments Rotating screen None On screen display with digital user controls (8 languages) Direct access (control buttons on front) for automatic image setup and adjustment for brightness USB 2.0 Hub (1 port into PC, 3 ports for accessories) On screen display Control features USB hub Integrated camera (3D, 0.3 megapixel) and dual array microphone NVIDIA 3D Vision kit includes GeForce 3D Vision active shutter glasses, 3D Vision USB controller/IR emitter Camera module 3D Vision kit Multiple input Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) Digital Visual Interface (DVI-D), digital, white, **HDCP-compliant** (2) HDMI (1.3), digital, black, **HDCP-compliant** Monitor connectors Signal cables (1) detachable, dual-link DVI-D at each end, digital, 1.8 meter (2) detachable, HDMI at each end, digital, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPMI® (100mm mount) Mounting features Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible) Monitor, attached stand, cable cover, Setup poster, Health and Safety Information and 3D Camera Setup Guide, 2 CDs with multilingual User's Guide, quick setup guide and monitor installation files, NVIDIA 3D vision kit, 1.8 meter dual-link DVI-D cable, 1.8 meter HDMl cable, 1.8 meter USB cable, 1.8 meter black power cord Ship group

	Limited Warranty	Accordation	
	⇒ 1 year limited warranty ⁴	Accessories	
ı	Rapid Replacement Service at 1-877-453-6686	Kensington MicroSaver® Cable Lock 73P2582	
ı	Replacement normally arrives in two business days, excluding holidays	Kensington Twin Head Cable Lock 45K1620	
	← Lenovo pays all shipping costs for valid warranty claims ⁶		
ı	24x78 day toll-free support for warranty issues during the warranty period4		
		See details at www.lenovo.com/support/monitoraccessories	
ı		See all monitors at www.lenovo.com/support/monitors	

L2364 Wide Flat Panel Monitor Name High gloss black with metal gray 1187-US1 Case color

Type-model

Panel TFT-LCD, twisted nematic (TN), white LED backlight

23.0" (**584mm**) diagonal 20.0" x 11.3" / 509.2mm x 286.4mm Viewable image size

Max view area (W x H) Optimum resolution 1920x1080 Max pixel rate VGA: 205MHz; HDMI/DVI: 165MHz

Aspect ratio 16:9 Pixel pitch (mm) .265mm Dot/Pixel per Inch 96 dpi

Brightness 250 nits or cd/m² (typical)

1000:1 (typical) Contrast ratio Dynamic contrast ratio 5,000,000:1 Pixel response time 5ms (typical) Color gamut 72% 50 to 75Hz Vertical frequency Horizontal frequency 30 to 83kHz

Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical

Stand Tilt adjustable stand

Sides: 0.71" (18.0mm); top: 0.71" (18.0mm); bottom: 0.89" (22.5mm)
15.90" H x 21.57" W x 7.20" D;
403.9mm H x 547.8mm W x 183mm D Bezel width

Dimensions (HxWxD)

30 watts typical, 35 watts maximum, Power supply

<0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)

7.28 lb; 3.30 kg Weight

1 year (includes backlight) Limited warranty4

Available date July 2011

VESA DDC2B/CI, EDID 1.4A, VESA DPMS-compliant VESA-compliant²

ENERGY STAR®3 5.0 Power management Ergonomics ISO 9241-307 Emission standards

Environmental

ISO 9241-307 FCC Class B TCO (TCO Displays 5.2), WEEE (EU DIRECTIVE 2002/96/EC), RoHS (EU DIRECTIVE 2002/95/EC)

640x350, 640x480, 720x400 800x600, 832x624 Preset resolutions (VGA) VGA:

SVGA: XGA: 1024x768

XGA+: 1152x864 WXGA: 1280x768, 1280x800 SXGA: 1280x1024 WXGA+: 1440x900, 1600x900

WSXGA+: 1680x1050 Full HD: 1920x1080

Presets / user settings Standard presets: VGA: 29; HDMI: 26;

user settings: 20

Tilt: 20° back, -5° forward; detachable stand Viewing adjustments

Rotating screen

On screen display On screen display with digital user controls (8 languages)

Control features Direct access (buttons at the middle bottom of the front bezel) for volume up/down, mute, automatic image setup,

dual input, brightness, and NOVO vision

USB hub

Multimedia Audio in jack (3.5mm) and audio out jack (3.5mm) on rear

Multiple input Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)

Monitor connectors

(1) VGA 15-pin D-shell, analog, blue (2) HDMI (1.3), digital, black, **HDCP-compliant**

(3) Digital Visual Interface (DVI-D) for digital attach [white], HDCP-compliant
Detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter
Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPMI® (100mm mount)

Signal cable

Mounting features Security

Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)

Monitor, attached stand, base, Setup poster, Warranty Information, CD with multilingual User's Guide and monitor Ship group

installation files, shopping bag, 1.8 meter analog signal cable, 1.8 meter power cord

Limited Warranty

- 1 year limited warranty⁴
- Advanced Exchange Service at 1-877-453-6686
- Replacement normally arrives in five business days, excluding holidays
- Lenovo pays all shipping costs for valid warranty claims⁶
- 24x78 day toll-free support for warranty issues during the warranty period4

Accessories

Kensington® MicroSaver® Cable Lock 73P2582 Kensington Twin Head Cable Lock 45K1620

See details at www.lenovo.com/support/monitoraccessories More information at www.lenovo.com/support/monitors

Features

Widescreen 23-inch monitor with white LED backlight

• View images in a 16x9 wide aspect ratio

• 1080p full HD support, HDCP-compliant

• Tilt and cable management stand

Mercury free panel

Compliance with ENERGY STAR 5.0

• Built-in VĞA, DVI-D, and HDMI 1.3 connectors

Kensington® lock slot ready for enhanced security
 Microsoft® Windows® 7 certified

Lenovo L2364 Wide Monitor

Availability: All offers subject to availability. Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo is not responsible for photographic or typographic errors.

Warranty: For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC, 27709, Attn: Dept ZPYA/B676. Lenovo makes no representation or warranty regarding third party products or services.

- ¹ ISO-compliant: Compliance with ISO 9241 Part 3, ISO Part 7, ISO Part 8, and/or ISO 13406 Part 2 is dependent on a complete ISO-capable platform of a system unit, monitor, video subsystem, operating system and fonts.
- VESA: Requires attachment to suitably configured system with similarly enabled operating system.
- ³ ENERGY STAR: As an ENERGY STAR partner, Lenovo has determined that this product meets the ENERGY STAR 4.0 or 4.1 guidelines for energy efficiency. Requires attachment to suitably configured system.
- ⁴ Limited warranty: Support unrelated to a warranty issue may be subject to additional charges.
- 6 Lenovo pays all shipping costs for warranty repairs during limited warranty period.
- Telephone support may be subject to additional charges, even during the limited warranty period. In the United States call 877-453-6686. Response times may vary. May exclude some holidays.



Trademarks: Lenovo, the Lenovo logo, New World. New Thinking., Access Connections, Rescue and Recovery, Think-Centre, ThinkPad, ThinkStation, ThinkVantage, and ThinkVision are trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Other company, product, or service names may be trademarks or service marks of others.

This publication was developed for products and services offered in the United States. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to alter specifications and other product information at any time without prior notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANT-ABILITY OR FITNESS FOR A PARTICU-LAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore this disclaimer may not apply to you. This publication was developed in the US.

Visit www.lenovo.com/safecomputing periodically for the latest information on safe and effective computing.

Visit www.lenovo.com/psref for the latest version of Personal Systems Reference.

© Lenovo, 2011. All rights reserved.

> Lenovo 1009 Think Place Morrisville, NC 27560 U.S.A.

December 2011 cmbook.pdf