FLATRON ED

# L1952H



# 19" (19.0" VIS) Active Matrix LCD Color Monitor



#### **HIGH PERFORMANCE**











#### PRODUCT INFO

An ergonomically designed workhorse. The FLATRON LCD L1952H has a footprint that's ideal for any office environment, large or small. Its color is extraordinary, and its viewing capabilities and digital on-screen adjustments especially convenient. The L1952H is backed by 3 Year Quick Swap Warranty.

#### KEY FEATURES

- Brilliant Active Matrix TFT Display
- Integrated f:∈NGINE™ (Picture-Quality Enhancing Chip)
- Ultra Fast 8ms Response Time
- Digital (DVI-D) and VGA Analog (15 pin D-Sub) Inputs
- 1400:1 High Contrast Ratio
- Tilt and Height adjustable
- Universal 90-264 VAC Power
- EPA Energy Star and VESA DPMS Compliant
- TCO'03 Low-Emission Compliant
- Simple One Touch-Auto-Setup Function



#### SPECIFICATIONS

**DISPLAY TYPE** 

**DISPLAY AREA** 

**DISPLAY COLORS PIXEL PITCH** 

**PIXEL CONFIGURATION** 

SURFACE TREATMENT

FLECTRONIC INTERFACE

**BACKLIGHTING** 

**MAXIMUM RESOLUTION** 

**BRIGHTNESS** 

**CONTRAST RATIO** 

**RESPONSE TIME VIEWING ANGLE** 

**HORIZONTAL SCANNING** 

**FREQUENCIES VERTICAL SCANNING** 

**FREQUENCIES** 

**AUTO-SYNC SUPPORT** 

**CONTROL TYPE** INPUT SIGNAL INPUT TERMINALS 19.0" (19.0" VIS) Active Matrix TFT Color

LCD Screen

(H x V) 14.8" x 11.9" (376mm x 301mm)

16.2 Million

0.294mm x 0.294mm Pixel **RGB Stripe Arrangement** 

Hard Coating 3H, Anti-Glare

LVDS

4CCFL 1280 x 1024

300cd/m2 (Typical)

1400:1 (Typical)

8 ms (Typical)

H: 160°, V: 160°

30-83KHz, Auto-Synchronous

56-75Hz, Auto-Synchronous

640 x 350 up to 70Hz, 640 x 480 up to 70Hz, 720 x 400 up to 70Hz, 800 x 600 up to 75Hz, 832 x 624 up to 75Hz,  $1024 \times 768$  up to 75Hz,  $1152 \times 870$  up to 75Hz,  $1280 \times 1024$  up to 75Hz

On-Screen Display of Adjustments

**RGB** Analog and Digital

Digital (DVI-D)and standard VGA D-Sub 15-pin

Connector

SYNC SIGNALING **VESA PLUG AND PLAY LEVEL DIGITAL ON-SCREEN CONTROLS** 

FRONT PANEL CONTROLS

**POWER REQUIREMENTS** DPMS POWER CONSUMPTION TILT/HEIGHT ADJUSTABLE **VESA MOUNTING COMPLIANCE** 

**DIMENSIONS (WxHxD)** 

WEIGHT

SAFETY/REGULATORY

**ACCESSORIES** 

**LGEUS WARRANTY UPC Code #** 

Separate H/V DDC2B, DDC1

Brightness, Contrast, Horizontal/Vertical Position, Clock, Phase (+/-), Language Select, Auto-Adjust, OSD Position, Color Temp (9300K, 6500K, User), Information

Source, Menu, f-ENGINE, Auto-Set/Select, Power

90-264 VAC, 50-60Hz

On: 39 Watts, Standby: 1 Watts

Standard VESA Mounting, 75mm x 75mm Screw Spacing

Set: 158.28" x 184.25" x 81.89" Boxed: 178.35" x 151.18" x 61.02"

TCO'03, UL1950, FCC-B, EPA Energy Star, IEC950, CSA, CE, TUV-GS, SEMKO, GOST, ISO 9241-3,7,8, C-TICK, VCCI-2

Power Cord, Signal Cable, Manual, Install

3 Year QuickSwap Replacement Program 71919218229

#### **VIEWS**





## **UP CLOSE**







#### WARRANTY

- The L1952H LCD Monitor Comes with LG's 3 Year Quick Swap Warranty
- 3 Year Parts, Labor and Backlight
- LG Pays Shipping Both Ways
- 48 Hour Swap Program
- Call Toll-Free 1-800-243-0000 (24 Hous 7 Days a Week)

### Additional Products

www.LGusa.com

#### **CONTACT US**

- For More Information, please visit ww.LGUSA.com
- Phone: 201-816-2000, 800-243-0000
- Email: lgsuperseller@lge.com

www.LGSuperSeller.com www.LGusa.com



LG ELECTRONICS U.S.A., INC.

920 Sylvan Avenue, Englewood Cliffs, NJ 07632 Tel: (201) 816-2000 Fax: (201) 816-2188 Design and specifications subject to change without notice. 4/2006



LCD Monitors





Memory Products