

LCD Commercial Monitor

ENHANCE PRODUCTIVITY

The LG L1942 19.0" Class Monitor Series is the choice for commercial solutions with a remarkable Digital Fine 8000:1 contrast ratio, 5ms response time and a 1280x1024 display resolution. Find what you need in our three models:

L1942S-BF for fundamental functionality L1942T-BF for DVI-D connectivity L1942P-BF for swivel, height and pivot adjustments.

From web browsing to desktop publishing, the LG L1942 Monitor Series can enhance productivity in professional environments.

DFC 8,000:1 HIGH CONTRAST RATIO

5MS RESPONSE TIME

300 CD/M² HIGH BRIGHTNESS

F-ENGINETM INTEGRATED DIGITAL PICTURE SYSTEM

 ${\sf VESA^{\sf TM}}\,{\sf COMPLIANT}\,{\sf WALL}\,{\sf MOUNTABLE}\,(75\,{\sf X}\,75{\sf MM})$

EPA ENERGY STAR® COMPLIANT

3 YEAR LIMITED WARRANTY (parts/labor/backlight)



L1942S-BF/T-BF L1942P-BF

www.LGcommercial.com



Customer Service: 888.865.3026

Contact your LG Regional Sales Representative: IT: 800.321.5501 Channel Markets: 800.897.88871 B2B: 800.897.87888 Hospitality: 800.228.1236

SPEC_L1942S-T-P LG060810_PR

		48 Hour Swap Program available
		Call Toll-Free 1-800-243-0000
	UPC CODE	
	7 19192 18489 3	L1942S-BF
	7 19192 18491 6	L1942T-BF
	7 19192 18472 5	L1942P-BF
	Capel Vale Foreign ENERGY STAR	ROHS FENGINE
LG Electronics U.S.A., Inc. nmercial Products Division	All screen images are simulated. Dimensions and weights are approximate. Design, features and specifications subject to change without notice.	

DISPLAY LCD Panel Type

Pixel Pitch

Display Area Color

Aspect Ratio

Brightness

POWER

WEIGHT Set w/Stand

STAND

Safety EMC

Set w/o Stand

CERTIFICATIONS

Low Radiation

Power Saving

VESA MOUNTING

SPECIAL FEATURES

ACCESSORIES

LIMITED WARRANTY

Environment

Normal Usage Stand-by Usage

DIMENSIONS

Set w/Stand (W x D x H)

Set w/o Stand (W x D x H)

Contrast Ratio Response Time

Surface Treatment

USER INTERFACE PC Input

Maximum Resolution

Horizontal Viewing Angle Vertical Viewing Angle

19" Widescreen

18.9" diagonal

Black

5:4 1280 x 1024

5ms

170°

D-Sub

33W

1W

(L1942S-BF/T-BF)

(L1942S-BF/T-BF)

(L1942S-BF/T-BF)

7.1 lbs (3.2 kg)

Swivel (L1942P-BF only)

Height (L1942P-BF only) Pivot (L1942P-BF only) Base Detachable

FCC-B, CE

RoHS

f-FNGINF

Power Cord D-Sub Cable

sRGB

TCO'03, TCO'99

EPA Energy Star

75mm x 75mm

(L1942P-BF)

(L1942P-BF)

(L1942P-BF)

0.294mm

 300 cd/m^2

DFC 8000:1

170° (L1942S-BF/T-BF), 176° (L1942P-BF)

16.0"x 7.3" x 16.5" (406.3 x 184.8 x 419.7mm)

16.0" x 9.5" x 16.6" (406.3 x 241.6 x 421.8mm)

16.0" x 2.5" x 13.6" (406.3 x 63.6 x 344.5mm)

16.0" x 2.3" x 13.7" (406.3 x 58.4 x 344.5mm)

18.4" x 4.6" x 15.5" (468 x 116 x 394mm)

19.7" x 15.6" x 8.8" (500 x 395 x 223mm)

7.5 lbs (3.4 kg) (L1942S-BF/T-BF) 9.5 lbs (4.3 kg) (L1942P-BF)

10.4 lbs (4.7 kg) (L1942S-BF/T-BF) 13.2 lbs (6.0 kg) (L1942P-BF)

UL (cUL), TUV-GS (TUV-Type), SEMKO

Intelligent Auto (Auto Resolution)

Plug & Play - DDC/CI, DDC2B Forte Pivot (L1942P-BF only) HDCP (L1942T-BF, L1942P-BF only)

3 Years (parts/labor/backlight)

Anti-Glare, Hard Coating (3H)

DVI-D (L1942T-BF, L1942P-BF only)

© Copyright 2008 LG Electronics USA, Inc. All Rights Reserved. "LG Life's Good" is a registered trademark of LG Corp. f-Engine is a registered trademark of LG Electronics USA, Inc.

VESA is a trademark of Video Electronics Standards Association. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks or registered trademarks of their respective companies



