

WM0.5

Miniature stage monitor

features

- ▶ High power compact system
- ▶ Miniature low-profile enclosure
- ▶ Twin angle cabinet design



applications

- ▶ Unobtrusive stage monitoring
- ▶ Broadcast monitoring



The WM0.5 is a miniature high performance stage monitor intended for use where stage space is restricted and for broadcast situations where visually unobtrusive floor monitors are required. The enclosure has been specially designed to enable it to be used at two different angles - 40° (normal) and 25° (close-up).

overall dimensions



WM0.5

technical specifications

TYPE	Miniature two-way passive stage monitor
FREQUENCY RESPONSE (5)	70Hz-18kHz \pm 3dB -10dB @ 50Hz
DRIVERS	8" (200mm) bass driver 1" (25mm) exit HF compression driver
RATED POWER (2)	125W AES, 500W peak
RECOMMENDED AMPLIFIER	300-400W into 4 ohms
SENSITIVITY (6)	94dB
MAXIMUM SPL (7)	114dB continuous, 120dB peak
NOMINAL IMPEDANCE	8 ohms
DISPERSION (-6dB)	50° horizontal, 70° vertical
CROSSOVER	3kHz passive
FINISH	Textured grey paint
PROTECTIVE GRILLE	Grey perforated steel
CONNECTORS	2 x Neutrik NL4
FITTINGS	4 x M8 threaded inserts
DIMENSIONS	(W) 391mm x (H) 270mm x (D) 334mm (W) 15.4ins x (H) 10.6ins x (D) 13.1ins
WEIGHT	9kg (19.8lbs)

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HP12 3SL, England.
Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2006 Martin Audio Ltd.



www.martin-audio.com

touring and theatre