

- Multi-format playback lets you play CDs, CD-Rs, or CD-RWs loaded with hundreds of MP3 or WMA songs¹.
- The full-motion, 4-line fluorescent LCD display makes it easy to read song information and the front auxiliary input lets you connect almost any portable audio device to your car's sound system.
- USB⁵ 1-Wire for iPod^{®2} products, iPhone^{®2}, and other USB DMPs lets you directly connect, charge, and control your digital music player via the USB jack in the front of the unit, as well as view metadata like song title and artist on the front display.
- Search and select songs by category, including artist, album, genre, or playlist. Jump Mode allows you to fast forward through a music category in 10 percent increments.
- Use Zappin function to play 6, 9, or 30-second music clips until you find the song you want.
- Passenger Control lets your co-pilot control the music playing from your iPod^{®2} device via connected USB⁵ 1-Wire, and as they scan through your music, artist and album information is conveniently shown on the receiver display.
- Search and select songs by category, including artist, album, genre, or playlist. Jump Mode allows you to fast forward through a music category in 10 percent increments.
- Use Zappin function to play 6, 9, or 30-second music clips until you find the song you want.
- Passenger Control lets your co-pilot control the music playing from your iPod^{®2} device via connected USB⁵ 1-Wire, and as they scan through your music, artist and album information is conveniently shown on the receiver display.
- The CDX-GT740UI integrates seamlessly with Satellite Radio³ and HD Radio Sony[®] Bus adaptors so you can receive digital satellite radio or HD Radio broadcasts.
- The CDX-GT740UI delivers 52 watts of peak power to all four speakers while DSO and EQ3 stage 2 lets you adjust the mix for a dynamic sound experience.
- Built-in Front, Rear and Subwoofer pre-outs with selectable LPF/HPF functionality gives you the power to customize the sound to your external amplifiers and other components.
- The included Wireless Card Remote (RM-X172) lets you control the basic functions of your Sony[®] Xplod[™] system while keeping your eyes on the road.
- Illuminated keys help you find and select control functions in low light and complement the CDX-GT740UI's selectable red, blue or green backlit display.



CDX-GT740UI

CD Receiver MP3/WMA/AAC Player

Features

- MP3/WMA playback¹ Multi-format playback lets you play CDs, CD-Rs, or CD-RWs loaded with hundreds of MP3 or WMA songs¹.
- Flip-down Face with Front Aux In The full-motion, 4-line fluorescent LCD display makes it easy to read song information and the front auxiliary input lets you connect almost any portable audio device to your car's sound system.
- USB⁵ 1-Wire for Digital Music Players USB⁵ 1-Wire for iPod®² products, iPhone®², and other USB DMPs lets you directly connect, charge, and control your digital music player via the USB jack in the front of the unit, as well as view metadata like song title and artist on the front display.
- Quick-BrowZer® with Jump Mode feature Search and select songs by category, including artist, album, genre, or playlist. Jump Mode allows you to fast forward through a music category in 10 percent increments.
- Zappin™ function Use Zappin function to play 6, 9, or 30-second music clips until you find the song you want.
- Passenger Control Passenger Control lets your co-pilot control the music playing from your iPod®² device via connected USB⁵ 1-Wire, and as they scan through your music, artist and album information is conveniently shown on the receiver display.
- Satellite Radio³ / HD Radio™ ready⁴ The CDX-GT740UI integrates seamlessly with Satellite Radio³ and HD Radio™ Sony® Bus adaptors so you can receive digital satellite radio or HD Radio⁴ broadcasts.

ADDITIONAL FEATURES

- EQ3, DSO and 52 Watts x 4 High Power
- Selectable Pre-outs with LPF/HPF
- Wireless Card Remote included
- Selectable Key illumination

Specifications

Convenience Features

CD Text Display: CD/MP3/WMA/AAC data displayed
On-Screen Clock: 12H
Dimmer Adjust: Selectable Auto/on/off
Key Illumination: Switchable: Blue/Red/Green

General

Disc Capacity: 1
Color: Dark Titanium / Black

Audio

Preout Impedance: 220 ohms
Preout Voltage: 4 volt
S/N Ratio: Audio Power: CEA2006 S/N 80 dBA
Frequency Response: CD: 10.20.000 Hz
Wow and Flutter: Below measurable limit
Station Preset(s): 18 FM / 12 AM
Digital-to-Analog Converter: 24bit
Tuner Frequency Range:
FM: Tuner Frequency Range (MHz): 87.5-107.9
AM: Tuner Frequency Range (kHz): 530-1710
Tuner Type: SSIREXA
Volume Control: Tel/Nav Attenuation Circuitry
Band: AM / FM
Signal-to-Noise Ratio (dB): CD: 120 dB
Format(s) Supported: MP3/WMA/AAC files¹

Equalizer: EQ3 Parametric: 3 band EQ

+/- 10 dB at 60/100 Hz

+/- 10 dB at 500/1 kHz

+/- 10dB at 10/12.5 kHz

Convenience

Tilt Range: 0-45° mounting angle

Display

Technology: Fluorescent/Dot/Full Motion
Display Color: Black / Blue
Text Displayed: Source, artist, track, playback time, menu and clock
Text Lines: 4 lines of information

Amplifier Section

Speaker Impedance: 4-8 Ohms
Max power output: 52 watts x 4 at 4 ohms

Tuner

FM Usable Sensitivity: 10 dBf
Selectivity: 75 dB at 400 kHz
S/N Ratio: 70 dB (mono)
Frequency Response: FM: 20-15,000 Hz
Stereo Separation: 40 dB at 1 KHz

Power

Output Power: 52W x4 Watts Max Power - CEA2006 Standard Power Output: 17 Watts RMS per channel into 4 Ohms, 4 channels driven from 20 Hz to 20 kHz with less than 1% THD+N.
Current Drain: 3 - 5 amps
Input Voltage: 12 V DC car battery (negative ground)

Inputs and Outputs

RCA Audio Output(s): Front, Rear, and Subwoofer RCA pre-amp outputs
Digital Audio Input(s): - Ability to use all forms of USB devices may vary as not all devices are compatible.

This unit can be connected to the following iPods. Update your iPod to the latest software before you use it.

iPod Nano 1st generation*

iPod Nano 2nd generation (aluminum)

iPod Nano 3rd generation (video)

iPod 5th generation (video)*

iPod Classic

iPod Touch

iPhone

This unit is compliant with MSC (Mass Storage Class) and MTP (Media Transfer Protocol) type USB devices compliant with the USB standard.

This unit cannot recognize USB devices via a USB hub.

If you have any questions or problems concerning your unit that are not covered in the owners manual, consult your nearest Sony dealer

USB Port(s): Front USB - Full Speed
Antenna Terminal(s): AM/FM Antenna Input Terminal
12V Trigger Output(s):
Power antenna

Amplifier turn on
Remote Jack: Optional wired remote input terminal
Audio In:

Front Aux with variable level: -8dB ~ +18dB

Front USB input

Sony Bus terminals
Infrared Port: Wireless remote

Dimensions

Weight: 1.3 kg (2 lb. 14 oz.)
Measurements: 178 x 50 x 179mm

Supplied Accessories

Parts for installation and connections (1 set)

RM-X172 wireless remote

Optional Accessories

CD changer (10 discs): CDX-757MX
CD changer (6 discs): CDX-T69
Source selector: XA-C40
Aux-in selector: XA-300
HD Radio® tuner: XT-100HD
USB Connection Cable for iPod®: RC-100IP

Color: Dark Titanium / Black

UPC Code: 027242774391

1. Not all MP3, WMA, AAC files may playback due to file variations. Copyright protected ACC-LC files cannot be played back.
2. Ability to use all generations of iPod products may vary as not all products are compatible.
3. Satellite radio service requires a satellite radio tuner and service subscription, sold separately.
4. HD Radio® capability requires an optional HD Radio tuner (XT-100HD).
5. Ability to use all forms of USB devices may vary as not all devices are compatible.

© 2009 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony, Quick-BrowZer, Walkman, Xplod®, and the Sony and Xplod logos are trademarks of Sony. iPhone and iPod are trademarks of Apple Inc., registered in the U.S. and other countries. All other trademarks are trademarks of their respective owners. Features and specifications are subject to change without notice. Non-metric weights and measures are approximate.



Please visit the Dealer Source for current information at
www.sony.com/dealersource