

NEC MultiSync® EA Series

Desktop LCDs ideal for corporate environments



Take your productivity to new heights. With its MultiSync EA Series, NEC has developed desktop displays that combine cutting-edge technologies with dynamic design accents, giving you the ability to increase your productivity while adding a modern flair to your desktop. The 19" NEC MultiSync EA191M, 22" EA221WM, 24" EA241WM and 26" EA261WM, which tout flexibility for any number of applications and environments, meet the diverse needs of businesses of all kinds.

A new perspective on productivity. These displays' wide-format screens (except EA191M) provide roughly the same work area as two smaller-sized LCD screens, allowing you to work simultaneously in multiple/side-by-side application windows.

Enhanced screen performance. With contrast ratios up to 1500:1 (typical) and brightness quality of up to 400 cd/m², outstanding LCD monitor front-of-screen visual performance is NEC Display Solutions' #1 goal. Rapid Response™ technology provides for lifelike full-motion video display without distortion at a response time as quick as 5ms.

Wide compatibility for today and tomorrow. With Ambix® dual-input technology—which utilizes both DVI-D and traditional 15-pin VGA connectors—you can bridge the gap between analog and digital systems by allowing the same monitor to work seamlessly in either environment. Ambix provides compatibility with today's computer systems and is on the forefront of tomorrow's digital output.

Features & Benefits

Height-adjust, pivot, tilt and swivel capabilities add flexibility and comfort to your viewing preferences

Integrated USB 2.0 hub gives you convenient connections to peripherals (except EA191M)

Built-in multimedia speakers with headphone jack save significant desktop space

Built-in, multi-directional NaViKey™ allows for easy screen setting adjustments

5-setting Dynamic Video Mode enhances video and images with real-time optimization of brightness, color and contrast

High-bandwidth Digital Content Protection (HDCP) safeguards high-definition and encrypted content during transmission from a source device to the display

ECO Mode™ helps save power, reduce heat and extend the life of the display by allowing the user to dim the backlight

EPEAT Gold and Silver compliance ensures the displays reduce hazardous waste and electricity usage, resulting in lower energy costs and increased protection for the environment

Carbon footprint meter helps track and calculate the reduction of green gas emissions

Recessed carrying handle on the back of the display provides easier transport (except EA191M)

Rapid Response technology delivers virtually uninterrupted, undistorted viewing of high-speed, full-motion video

Ambix dual-input technology allows for digital/analog compatibility with upgraded video cards and software as well as connection to two systems

XtraView® technology provides for some of the widest viewing angles available

NaViSet™ software offers an expanded and intuitive interface, allowing you to more easily adjust display settings via mouse and keyboard

NEC Display Solutions' quality and reliability provide peace of mind with a 3-year limited parts and labor warranty (including backlight) and unrivaled customer service and technical support

NEC MultiSync EA Series models feature built-in speakers (A), which are integrated into the bottom of the cabinet. Along with a headphone jack (B), these space-saving speakers add multimedia connectivity and excitement to the desktop computing experience without adding bulk to the display's design.

These models feature swivel (nearly 360°) (C), tilt (D) and pivot (E) capabilities and a height-adjustable stand (up to 110mm) (F), allowing you to create an ideal ergonomic display orientation for maximum viewing comfort. A built-in, recessed handle (G) also makes the displays easily transportable.

The display's discreet control button arrangement (H) includes the NaViKey. This multi-directional key not only allows for a thinner frame around the screen and helps reduce the number of control buttons required, it provides an easier means of reaching your preferred display settings.



Model	MultiSync EA191M	MultiSync EA221WM	MultiSync EA241WM	MultiSync EA261WM
Display Viewable Image Size Pixel Pitch Pixels Per Inch Brightness (typical) Contrast Ratio (typical) Viewing Angle (typical) Response Time (typical) Display Colors	19" 0.294mm 86 @ native resolution 250 cd/m ² 1500:1 170° Vert., 176° Hor. (88U/88D/88L/88R) (CR > 10) Rapid Response (25ms) More than 16.7million	22" 0.282mm 90 @ native resolution 250 cd/m ² 1000:1 170° Vert., 176° Hor. (85U/85D/88L/88R) (CR > 5) Rapid Response (5ms) More than 16.7million	24" 0.270mm 94 @ native resolution 400 cd/m ² 1000:1 160° Vert., 160° Hor. (80U/80D/80L/80R) (CR > 10) Rapid Response (5ms) More than 16.7million	26" 0.292mm 87 @ native resolution 400 cd/m ² 1000:1 160° Vert., 160° Hor. (80U/80D/80L/80R) (CR > 10) Rapid Response (5ms) More than 16.7million
Synchronization Range Horizontal Vertical	31.5-81.1KHz (Analog/ Digital) 56-75Hz (Analog/Digital)	31.5-81.1KHz (Analog/ Digital) 56-75Hz (Analog/Digital)	31.5-81.1KHz (Analog/ Digital) 56-76Hz (Analog/Digital)	31.5-81.1KHz (Analog/ Digital) 56-76Hz (Analog/Digital)
Input Signal Video Sync	Analog 0.7 Vp-p / 75 Ohms Separate Sync: TTL Level (positive/negative)	Analog 0.7 Vp-p / 75 Ohms Separate Sync: TTL Level (positive/negative)	Analog 0.7 Vp-p / 75 Ohms Separate Sync: TTL Level (positive/negative)	Analog 0.7 Vp-p / 75 Ohms Separate Sync: TTL Level (positive/negative)
Inputs	DVI-D and VGA 15-pin D-Sub	DVI-D and VGA 15-pin D-Sub	DVI-D and VGA 15-pin D-Sub	DVI-D and VGA 15-pin D-Sub
Resolutions Supported	Analog/Digital 720 x 400 @ 70 Hz 640 x 480 @ 60-75 Hz 800 x 600 @ 56-75 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-75 Hz 1152 x 864 @ 70-75 Hz 1152 x 870 @ 75 Hz 1280 x 960 @ 60-75 Hz 1280 x 1024 @ 60-75 Hz	Analog/Digital 720 x 400 @ 70 Hz 640 x 480 @ 60-75 Hz 800 x 600 @ 56-75 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-75 Hz 1152 x 864 @ 70-75 Hz 1152 x 870 @ 75 Hz 1280 x 960 @ 60-75 Hz 1280 x 1024 @ 60-75 Hz 1360 x 768 @ 60 Hz 1440 x 900 @ 60-75 Hz 1440 x 1050 @ 60-70 Hz 1680 x 1050 @ 60 Hz	Analog/Digital 720 x 350 @ 70-85 Hz 720 x 400 @ 70-85 Hz 640 x 480 @ 60-75 Hz 800 x 600 @ 56-75 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-75 Hz 1152 x 864 @ 75 Hz 1152 x 870 @ 75 Hz 1280 x 720 @ 60 Hz 1280 x 768 @ 60-75 Hz 1280 x 960 @ 60/75/85 Hz 1280 x 1024 @ 60-75 Hz 1360 x 768 @ 60 Hz 1440 x 900 @ 60 Hz 1440 x 1050 @ 60 Hz 1680 x 1050 @ 60 Hz 1600 x 1200 @ 60 Hz 1920 x 1200 @ 60 Hz	Analog/Digital 720 x 350 @ 70/85 Hz 720 x 400 @ 70/85 Hz 640 x 480 @ 60-75 Hz 800 x 600 @ 56-75 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-75 Hz 1152 x 864 @ 75 Hz 1152 x 870 @ 75 Hz 1280 x 720 @ 60 Hz 1280 x 768 @ 60-75 Hz 1280 x 960 @ 60/75/85 Hz 1280 x 1024 @ 60-75 Hz 1360 x 768 @ 60 Hz 1440 x 900 @ 60 Hz 1440 x 1050 @ 60 Hz 1680 x 1050 @ 60 Hz 1600 x 1200 @ 60 Hz 1920 x 1200 @ 60 Hz
Native Resolution	1280 x 1024 @ 60 Hz	1680 x 1050 @ 60 Hz	1920 x 1200 @ 60 Hz	1920 x 1200 @ 60 Hz
Additional Features	Thin-frame (bezel), integrated speakers, height-adjustable stand (110mm), pivot, tilt, swivel, No Touch Auto Adjust, cable management, AccuColor color control, digital smoothing, digital controls, DDC/CI, NaViSet software, Plug and Play (VESA DDC 1/2B), VESA DPMS power management, OSD user controls, ISO 13406-2 Class II, Windows Vista Premium-certified, Dynamic Video Mode, HDCP, ECO Mode, carbon meter, EPEAT Silver	Thin-frame (bezel), wide-screen format, integrated speakers, USB 2.0 hub, height-adjustable stand (110mm), pivot, tilt, swivel, No Touch Auto Adjust, cable management, AccuColor color control, digital smoothing, digital controls, DDC/CI, NaViSet software, Plug and Play (VESA DDC 1/2B), VESA DPMS power management, OSD user controls, ISO 13406-2 Class II, Windows Vista Premium-certified, Dynamic Video Mode, HDCP, 720p, ECO Mode, carbon meter, HDMI-capable with adapter, EPEAT Gold	Thin-frame (bezel), wide-screen format, integrated speakers, USB 2.0 hub, height-adjustable stand (110mm), pivot, tilt, swivel, No Touch Auto Adjust, cable management, AccuColor color control, digital smoothing, digital controls, DDC/CI, NaViSet software, Plug and Play (VESA DDC 1/2B), VESA DPMS power management, OSD user controls, ISO 13406-2 Class II, Windows Vista Premium-certified, Dynamic Video Mode, HDCP, 720p and 1080p from DVI-D, ECO Mode, carbon meter, HDMI-capable with adapter, EPEAT Gold	Thin-frame (bezel), wide-screen format, integrated speakers, USB 2.0 hub, height-adjustable stand (110mm), pivot, tilt, swivel, No Touch Auto Adjust, cable management, AccuColor color control, digital smoothing, digital controls, DDC/CI, NaViSet software, Plug and Play (VESA DDC 1/2B), VESA DPMS power management, OSD user controls, ISO 13406-2 Class II, Windows Vista Premium-certified, Dynamic Video Mode, HDCP, 92% color gamut, 720p and 1080p from DVI-D, ECO Mode, carbon meter, HDMI-capable with adapter, EPEAT Gold
Voltage Rating	AC 100-120V / AC 220-240V	AC 100-120V / AC 220-240V	AC 100-120V / AC 220-240V	AC 100-120V / AC 220-240V
Power Consumption (typical) On (w/ USB + audio) Power Savings Mode ECO Mode ON (with USB & Audio) (without USB & Audio)	39W 2W 31W 27W	59W 2W 47W 27W	71W < 2W 57W 38W	99W < 2W 67W 50W
Dimensions (W x H x D) Net (with stand) Net (without stand)	16.1 x 15.1 - 19.4 x 8.7 in. / 408 x 383.5-493.5 x 220mm 16.1 x 13.3 x 2.6 in. / 408 x 338 x 65mm	20 x 15 - 19.4 x 8.7 in. / 507.8 x 382 - 492 x 220mm 20 x 13.1 x 2.8 in. / 507.8 x 332.1 x 71.8mm	22 x 17.3-21.7 x 10.7 in. / 558.6 x 440.5-550.5 x 272.4mm 22 x 14.4 x 3.1 in. / 558.6 x 366.2 x 89mm	23.4 x 17.8-22.1 x 10.7 in. / 594.4 x 451-561 x 272.4mm 23.4 x 15.3 x 3.8 in. / 594.2 x 389.8 x 95.6mm
Weight Net (with stand) Net (without stand)	15.4 lbs. / 7 kg 9.7 lbs. / 4.4 kg	17.4 lbs. / 7.9 kg 11.7 lbs. / 5.3 kg	23.1 lbs. / 10.5 kg 14.3 lbs. / 6.5 kg	27.1 lbs. / 12.3 kg 18.7 lbs. / 8.5 kg
VESA Hole Configuration Specifications	100 x 100mm	100 x 100mm	100 x 100mm	100 x 100mm; 200 x 100mm
Environmental Conditions Operating Temperature Operating Humidity Operating Altitude Storage Temperature Storage Humidity Storage Altitude	5-35°C / 41-95°F 20-80% 4572m / 15,000 ft. -10-60°C / 14-140°F 10-85% 12,192m / 40,000 ft.	5-35°C / 41-95°F 20-80% 2000m / 6562 ft. -10-60°C / 14-140°F 10-85% 12,192m / 40,000 ft.	5-35°C / 41-95°F 20-80% 2000m / 6562 ft. -10-60°C / 14-140°F 10-85% 12,192m / 40,000 ft.	5-35°C / 41-95°F 20-80% 2000m / 6562 ft. -10-60°C / 14-140°F 10-85% 12,192m / 40,000 ft.
Limited Warranty	3 years parts and labor, including backlight	3 years parts and labor, including backlight	3 years parts and labor, including backlight	3 years parts and labor, including backlight
Technical Support	M - F (7am - 7pm CST)	M - F (7am - 7pm CST)	M - F (7am - 7pm CST)	M - F (7am - 7pm CST)



Ambix, MultiSync and XtraView are registered trademarks and ECO Mode, NaViKey, NaViSet and Rapid Response are trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change. 11/08 ver. 4.

©2008 NEC Display Solutions of America, Inc. All rights reserved.

NEC Display Solutions
500 Park Boulevard, Suite 1100
Itasca, IL 60143
866-NEC-MORE

NEC