



MultiSync® V520/V521/V521M

CRT Type:	38 cm (15 inch) Dot Trio mask CRT, 90° deflection
Active Screen Size:	35 cm
Anti-Reflection System:	OptiClear™ coating
Active Display Area*:	280 x 210 mm (Full scan)
Dot Pitch:	0.28 mm
Dot Clock:	122 MHz
Horizontal Frequency:	31–70 kHz
Vertical Frequency:	55–120 Hz
Maximum Resolution:	1280 x 1024 at 66 Hz
Recommended Resolution:	1024 x 768 at 85 Hz
Other Resolutions:	1152 x 870 at 77 Hz, 1024 x 768 at 87 Hz, 832 x 624 at 106 Hz, 800 x 600 at 110 Hz, 640 x 480 at 120 Hz
Features/Adjust Functions:	Plug & Play (DDC1 + DDC2B) for Windows 95/98, Asset Management, contrast, brightness, geometry, rotation, colour control, monitor info, reset, VESA/EPA/NUTEK compliant
Safety/Ergonomics:	V520: CE, TÜV GS, MPR II V521/V521M: CE, TÜV GS, TÜV ERGONOMIE, TCO 99
Dimensions (W x H x D):	360 x 360 x 381 mm
Weight:	12.1 kg
Power Supply:	100–120 V/220–240 V, 50–60 Hz
Power Requirements:	75 W typ. on mode, ≤ 15 W suspend mode, ≤ 5 W sleep mode
Connection:	Mini 15 pin D-sub 1.5 m signal cable
Warranty:	3 years warranty
Shipping Contents:	Monitor, power cord, user manual

- Monitor data manageable over networks due to Asset Management feature
- Ergonomics and safety compliant to state-of-the-art standards
- V521M: 2 x 1W speakers in monitor stand, 3.5 mm headphone jack

* Depending on signal of graphics card
All specifications are subject to change without notice. Status June 2000

