

## SpectraView<sub>II</sub><sup>™</sup> LCD Series

Color calibration solution (24" NEC MultiSync<sup>®</sup> LCD2490W2-BK-SV, 26" LCD2690W2-BK-SV and 30" LCD3090W-BK-SV) ideal for color-critical applications

**Unparalleled display performance for color-critical applications.** Featuring standard and ultra-wide color gamuts, the 24" NEC MultiSync LCD2490WUXi<sup>2</sup>, 26" LCD2690WUXI<sup>2</sup> and 30" LCD3090WQXi deliver an entirely new perspective to your desktop and allow you to view photographs and graphics in optimum color. These displays include the SpectraView<sub>II</sub> Color Calibration Solution, which combines award-winning NEC LCD monitor technology with a color measurement sensor and sophisticated software. The result is a highly accurate, reliable, repeatable and feature-rich display calibration and profiling solution.

Color and brightness uniformity were paramount in the design of these high-performance displays, making them ideal for graphic arts, desktop publishing, photography and other color-critical environments. In addition, with their wide-format design (16:10 aspect ratio), which provides roughly the same work area as two smaller-sized displays, you can simultaneously view/work in multiple application windows.



SpectraView<sub>II</sub><sup>™</sup>

- Standard and wide color gamut models (up to 97.5% coverage of AdobeRGB)
- Custom-calibrated colorimeter matched for NEC's wide color gamut displays as well as standard gamut displays
- Auto Luminance control with X-Light<sup>™</sup> Pro backlight/sensor design for consistent brightness and color
- ColorComp<sup>™</sup> technology compensates for slight variations in luminance and color uniformity, providing even color across the screen
- IPS active matrix LCD provides superior screen performance, including wide viewing angles, lifelike flesh tones and dark black levels
- Supports internal programmable 12-bit lookup tables (LUTs) for calibration
- High resolution allows for more content to be displayed on a single monitor
- Designed for landscape or portrait usage without degradation of performance or the display's lifecycle
- Digital and analog inputs with true MultiSync support for non-native resolutions

# SpectraView<sub>II</sub> Color Calibration Solution Features and Benefits

**Quick and easy measurements.** The SpectraView<sub>II</sub> system, available for Mac OS, Windows and Linux\*, uses an ultra-sensitive, custom-calibrated NEC/X-rite iOne Display 2 colorimeter to take color measurements of the display screen during calibration. The software analyzes these measurements and sends color adjustment commands directly to the display monitor. This means that color adjustments are made in the monitor rather than in the video graphics adapter, resulting in full use of the number of colors available on the graphics adapter and a much brighter image with the maximum possible color gamut. With SpectraView<sub>II</sub>, the video graphics adapter is not used at all to make any gamma or tone response curve corrections to the display, so the full color resolution and fidelity of the system is maintained.

**12-bit Internal Look Up Tables (LUTs)** - Each LCD monitor supported by SpectraView<sub>II</sub> features three internal 12-bit LUTs. These tables allow precise adjustments to be made to the display's tone response curve with minimal reduction to the number of displayable colors. Since the tone response curve correction is stored within the display and not on the host system's video graphics card LUT, the display can be calibrated on one machine and then used on another and still maintain calibration as long as a digital video signal is used.

**Display Data Channel Command Interface (DDC/CI)** - SpectraView<sub>II</sub> communicates with the monitor using DDC/CI, which is a two-way communications link between the video graphics adapter and display monitor using the standard video signal cable. No extra cables are necessary. All adjustments to the monitor settings are done automatically using this communications link.

**Multiple calibration sets** - Different monitor calibrations can be easily loaded, allowing quick and easy switching between different calibration settings without the need to re-calibrate the display. Each time a calibration set is loaded, the necessary monitor settings and ICC/ColorSync profiles are automatically updated.

**Calibrated display information** - At the end of each monitor calibration, an information window is displayed, which shows the results of the calibration and includes a wealth of information about the display such as the measured color gamut, grayscale color tracking, Delta-E and luminance values. Additional information about the display monitor such as the model name, serial number and the total number of hours that it has been in use are also displayed.

\* Limited Linux support for large installations



**Calibration status validation** - SpectraView<sub>II</sub> will query each calibrated monitor to see if any controls have changed since the last calibration. If anything has changed, the previous calibrated state can be restored automatically.

**Application flexibility** - SpectraView<sub>II</sub> provides many features and options that make it flexible enough to be used in a large variety of applications, including full DICOM support for medical imaging. The display luminance can be adjusted to either a specific user-defined value or set to the maximum the display can achieve. In addition, custom target response curves can be created in addition to presets such as L\* and SMPTE.

**Network support (Windows only)** - SpectraView<sub>II</sub> integrates with the NEC NaViSet™ Administrator network software (available separately from your NEC representative) to provide remote network access and monitoring of display monitors. NaViSet™ Administrator is able to read, display and log the current calibration settings and status of displays on an existing network (LAN). This feature is particularly useful for large installations where central monitoring and asset management is needed.

**Monitor locking** - Once calibrated, the On Screen Display (OSD®) controls for the display monitors can be locked to prevent accidental or unauthorized adjustment, which may invalidate the calibrated state of the monitor.

**Monitor profiling** - After calibration, the display is automatically profiled and highly accurate ICC/ColorSync color profiles are generated and automatically registered with the color management system. These profiles use the Bradford Chromaticity Adaptation matrix.

**Colorimeter function** - The software features a colorimeter function, which allows direct measurements to be taken by the color sensor and the results displayed in a variety of different formats.

Model	MultiSync LCD2490W2-BK-SV	MultiSync LCD2690W2-BK-SV	MultiSync LCD3090W-BK-SV	
<b>Display</b>	Viewable Size Image Pixel Pitch Pixels Per Inch Brightness (typical) Contrast Ratio (typical) Viewing Angle (typical) Response Time (typical) Panel Bit Depth  Color Gamut* Coverage Size	25.5" 0.287mm 89 @ native resolution 320 cd/m <sup>2</sup> 1000:1 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR > 10 Rapid Response™ (8ms G-to-G; 16ms B-to-B) 12-bit internal LUTs, displays 16.7 million colors out of 68.5 billion color palette  AdobeRGB** - 75.2% / sRGB - 96.7% AdobeRGB - 75.6% / sRGB - 102%	25.5" 0.287mm 89 @ native resolution 320 cd/m <sup>2</sup> 1000:1 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR > 10 Rapid Response™ (8ms G-to-G; 16ms B-to-B) 12-bit internal LUTs, displays 16.7 million colors out of 68.5 billion color palette  AdobeRGB** - 97.3% / sRGB - 100% AdobeRGB - 106.5% / sRGB - 143.6%	29.8" 0.251mm 102 @ native resolution 350 cd/m <sup>2</sup> 1000:1 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR > 10 Rapid Response™ (6ms G-to-G; 12ms B-to-B) 12-bit internal LUTs, displays 16.7 million colors out of 68.5 billion color palette  AdobeRGB** - 97.5% / sRGB - 100% AdobeRGB - 106.6% / sRGB - 143.9%
<b>Synchronization Range</b>	Horizontal Vertical Video Bandwidth	Horizontal Vertical Video Bandwidth	Horizontal Vertical Video Bandwidth	
<b>Input Signal</b>	Video Sync	Video Sync	Video Sync	
<b>Inputs</b>	DVI-D, DVI-I & VGA 15-pin D-sub	DVI-D, DVI-I & VGA 15-pin D-sub	DVI-D (HDCP), DVI-I	
<b>Resolutions Supported (Analog/Digital)</b>	720 x 400 @ 70-85 Hz 640 x 480 @ 60-85 Hz 800 x 600 @ 56-85 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-85 Hz 1024 x 1280 @ 60 Hz 1152 x 864 @ 70-85 Hz 1152 x 870 @ 75 Hz 1280 x 960 @ 60 Hz 1280 x 1024 @ 60-75 Hz 1400 x 1050 @ 60-75 Hz 1440 x 900 @ 60-85 Hz 1600 x 1200 @ 60 Hz 1920 x 1200 @ 60Hz 720 x 480p @ 60 Hz 720 x 576p @ 50 Hz 1280 x 720p @ 50/60Hz 1920 x 1080p @ 50/60 Hz	720 x 400 @ 70-85 Hz 640 x 480 @ 60-85 Hz 800 x 600 @ 56-85 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-85 Hz 1024 x 1280 @ 60 Hz 1152 x 864 @ 70-85 Hz 1152 x 870 @ 75 Hz 1280 x 960 @ 60 Hz 1280 x 1024 @ 60-75 Hz 1400 x 1050 @ 60-75 Hz 1440 x 900 @ 60-85 Hz 1600 x 1200 @ 60 Hz 1920 x 1200 @ 60Hz 720 x 480p @ 60 Hz 720 x 576p @ 50 Hz 1280 x 720p @ 50/60Hz 1920 x 1080p @ 50/60 Hz	640 x 400 @ 70-85 Hz*** 720 x 480p @ 60 Hz 720 x 400 @ 70-85 Hz 720 x 576p @ 50 Hz 640 x 480 @ 60-85 Hz 1280 x 720p @ 50-60 Hz 800 x 600 @ 56-85 Hz 1920 x 1080p @ 50-60 Hz 832 x 624 @ 75 Hz 1024 x 768 @ 60-85 Hz 1152 x 864 @ 70-85 Hz 1152 x 870 @ 75 Hz 1280 x 960 @ 60 Hz 1280 x 1024 @ 60-85 Hz 1400 x 1050 @ 60-75 Hz 1440 x 900 @ 60-85 Hz 1600 x 1200 @ 60-75 Hz**** 1680 x 1050 @ 60-75 Hz**** 1920 x 1200 @ 60 Hz 1920 x 1440 @ 30-60Hz**** 2560 x 1600 @ 30-60 Hz****	
<b>Native Resolution</b>	1920 x 1200 @ 60Hz	1920 x 1200 @ 60Hz	2560 x 1600 @ 60 Hz landscape / 1600 x 2560 @ 60 Hz portrait	
<b>Additional Features</b>	ColorComp - uniformity correction, X-Light Pro - backlight stabilization, AmbiBright - ambient light sensor, ultra-thin frame (bezel), No Touch Auto Adjust™, VESA Mount, sRGB, tilt, swivel, height-adjustable stand (150mm), pivot, quick-release stand, vacation switch (zero-watt mode), 12-bit LUTs, black level adjustment, overdrive, ECO Mode™, real-time clock, Analog/Digital CableComp™, TileMatrix™, TileComp™, SpectraView™ software-enabled	ColorComp - uniformity correction, X-Light Pro - backlight stabilization, AmbiBright - ambient light sensor, ultra-thin frame (bezel), No Touch Auto Adjust™, VESA Mount, sRGB, tilt, swivel, height-adjustable stand (150mm), pivot, quick-release stand, vacation switch (zero-watt mode), 12-bit LUTs, black level adjustment, overdrive, ECO Mode™, real-time clock, Analog/Digital CableComp™, TileMatrix™, TileComp™, SpectraView™ software-enabled	Ultra-thin frame (bezel), No Touch Auto Adjust™, NaViSet™ software, tilt, VESA Mount, sRGB, tilt, swivel, height-adjustable stand (190mm), pivot, quick-release stand, vacation switch, 12-bit LUTs, black level adjustment, AmbiBright, ColorComp, overdrive, ECO Mode™, real-time clock, X-Light Pro, Analog/Digital CableComp™, TileMatrix™, TileComp™, GammaComp™ MD software, standalone calibration, SpectraView™ software-enabled, Windows Vista™ Premium-certified	
<b>Voltage Rating</b>	AC 100-120V / AC 220-240V	AC 100-120V / AC 220-240V	AC 100-120V / AC 220-240V	
<b>Power Consumption (typical)</b>	On Power Savings Mode	On Power Savings Mode	On Power Savings Mode	
<b>Net Dimensions (WxHxD)</b>	with stand without stand	with stand without stand	with stand without stand	
<b>Net Weight</b>	with stand without stand	with stand without stand	with stand without stand	
<b>VESA Hole Configuration Specifications</b>	100 x 100mm / 200 x 100mm	100 x 100mm	100 x 100mm and 200 x 100mm	
<b>Environmental Conditions</b>	Operating Temperature Operating Humidity Operating Altitude Storage Temperature Storage Humidity Storage Altitude	Operating Temperature Operating Humidity Operating Altitude Storage Temperature Storage Humidity Storage Altitude	Operating Temperature Operating Humidity Operating Altitude Storage Temperature Storage Humidity Storage Altitude	
<b>Safety Standards</b>	UL/C-UL, UL60601, CE, Gost/PCT, PSB, CCC, TUV GS, FCC Class B/Canadian DOC, C-tick, MPR II / MPR III, VCCI (class 2), JIS C 61000-3-2, static electricity guideline, low emission guideline, TUV-Ergonomie, ISO9241-307, TCO '03, TCO '06, US Mercury regulations, WEEE, RoHS, SASO, Energy Star 4.0 Tier 2, GEEA, JEITA VOC Guideline. J-Moss, Windows XP, DEN-TORI	UL/C-UL, UL60601, CE, Gost/PCT, PSB, CCC, TUV GS, FCC Class B/Canadian DOC, C-tick, MPR II / MPR III, VCCI (class 2), JIS C 61000-3-2, static electricity guideline, low emission guideline, TUV-Ergonomie, ISO9241-307, TCO '03, TCO '06, US Mercury regulations, WEEE, RoHS, SASO, Energy Star 4.0 Tier 2, GEEA, JEITA VOC Guideline. J-Moss, Windows XP, DEN-TORI	UL/C-UL, UL60601, CE, Gost/PCT, PSB, CCC, TUV GS, FCC Class B/Canadian DOC, C-tick, MPR II / MPR III, VCCI (class 2), JIS C 61000-3-2, static electricity guideline, low emission guideline, TUV-Ergonomie, ISO9241-307, TCO '03, TCO '06, US Mercury regulations, WEEE, RoHS, SASO, Energy Star 4.0 Tier 2, GEEA, JEITA VOC Guideline. J-Moss, Windows XP, DEN-TORI	
<b>Limited Warranty</b>	4 years parts and labor, including backlight / 2-day Advanced Exchange service	4 years parts and labor, including backlight / 2-day Advanced Exchange service	4 years parts and labor, including backlight / 2-day Advanced Exchange service	
<b>Technical Support</b>	M - F (7am - 7pm CST)	M - F (7am - 7pm CST)	M - F (7am - 7pm CST)	

### SpectraView<sub>II</sub> Software Requirements

Apple Mac OS X 10.2.8 or higher/Microsoft Windows 2000, XP, XP x64, Server 2003 or Vista 32 bit.  
Linux version of SpectraView<sub>II</sub> is available for customers with large installations of NEC monitors.  
At least one available USB port for GretagMachbeth color sensor.

Visit [www.necdisplay.com](http://www.necdisplay.com) for the latest requirements.

\* Color gamut size and coverage calculated as 2-D gamut area in CIE 1931 xy colorspace. Size is the total relative display gamut area and includes any colors outside the reference gamut. Coverage is the relative display gamut area contained inside the reference gamut. NTSC values provided for comparison purposes - modern broadcast video uses SMPTE-C, ITU-R BT, 709/5sRGB or EBU primaries.

\*\* AdobeRGB is a standard defined by Adobe Systems Incorporated.

\*\*\* 640 x 400 available with DIGITAL input only

\*\*\*\* 30 Hz refresh rate available with ANALOG input only



MultiSync and OSD are registered trademarks, and ColorComp, NaViSet, SpectraView<sub>II</sub> and X-Light Pro are trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change. 5/09 ver. 2.

©2009 NEC Display Solutions of America, Inc. All rights reserved.

**NEC Display Solutions**  
500 Park Boulevard, Suite 1100  
Itasca, IL 60143  
866-NEC-MORE