



170V9FB













Great value within your budget

This slim, compact 170V9 pumps up productivity with good performance and great convenience while delivering the best value for money.

Best Value for Money

- 5ms fast response time
- Empowered for Windows Vista
- Energy Star for energy efficiency and low power consumption
- Complies with RoHS standards to care for the environment

Great convenience

- Screen tilts to your ideal, individualized viewing angle
- Embedded power supply eliminates external power adaptors
- sRGB ensures color matching between display and printouts
- · Kensington anti-theft lock-ready for added security



Specifications

Picture/Display

LCD panel type: 1280 x 1024 pixels, Anti-glare polarizer, RGB vertical stripe

Panel Size: 17"/ 43 cm

Effective viewing area: 337.9 x 270.3 mm

Pixel pitch: 0.264 x 0.264 mm Brightness: 300 cd/m²

Contrast ratio (typical): 800:1

Display colors: 16.7 M

Viewing angle: 160° (H) / 160° (V), @ C/R > 10

Response time (typical): 5 ms

Maximum Resolution: 1280 x 1024 @ 75 Hz

Recommended Resolution: 1280 x 1024 @ 60 Hz

Video Dot Rate: 140 MHz

Horizontal Scanning Frequency: 30 - 83 kHz
Vertical Scanning Frequency: 56 -75 Hz

sRGB

Connectivity

Signal Input: Analog (VGA)

Video Sync Input Signal: Composite Sync, Separate Sync, Sync on Green

Video input impedance: 75 ohm

Sync input impedance: 2.2k ohm

Video input signal levels: 0.7 Vpp

Convenience

Convenience Enhancements: On-screen Display

Monitor Controls: Auto (Back), Input (Down), Brightness (Up), Menu, Power On/Off

OSD Languages: English, French, German, Italian, Portuguese, Russian, Simplified Chinese, Spanish,

Other convenience: Kensington lock compatible

Plug & Play Compatibility: DDC/CI, sRGB, Windows 98, Windows 2000, Windows XP, Windows Vista

Regulatory Approvals: CE Mark, Energy Star, FCC Class B, UL/cUL

Tilt: -5° to 20°

VESA Mount: 100 x 100 mm

Dimensions

Box dimensions (W \times H \times D): 375 x 145 x 419 mm

Box dimensions in inch (W x H x D):

 $14.8 \times 5.7 \times 16.5$ inch

Set dimensions (W \times H \times D): 372 x 323 x 59.0 mm

Set dimensions in inch ($W \times H \times D$): $14.6 \times 12.7 \times 2.3$ inch

Set dimensions with stand (W \times H \times D): 372 x 373 x 192 mm

Set dimensions with stand in inch ($W \times H \times D$): $14.6 \times 14.7 \times 7.6$ inch

MTBF: 50,000 hrs

Relative humidity: 20% - 80%

Temperature range (operation): 0°C to 40°C

Temperature range (storage): -20°C to 60°C

Product weight (+stand): 3.65 kg

Product weight (+stand) (lb): 8.0 lb

Weight incl. Packaging: 4.87 kg

Weight incl. Packaging (lb): 10.7

Complies with: Energy Star

Consumption: < 36 W

Off Mode: < I W

Power LED indicator: Operation - green, Stand by/sleep - Amber

Power supply: Built-in, 100-240VAC, 50/60Hz

Product highlights

5ms on/off response time

On-Off response time is the period required for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Faster is better: Lower response time means faster transitions and, therefore, results in fewer visible image artifacts in the display of transition of texts and graphics. On-Off response time is a more important measure in the display of business content like documents, graphs and photos.

Windows Vista ready

Philips Vista-ready monitors are empowered for vibrant, exciting display of this new, visually sophisticated and demanding Windows operating system, designed to enhance your entertainment experience, make you more productive and help you control your computing experience at home and in the office, making viewing, finding and organizing information for work or play quick, efficient and easy.

Energy Star

Energy Star-labeled home electrical products are designed to use less energy - saving you money while reducing environmental pollution. In fact, Energy Starcompliant products consume less than I watt of power while in standby mode. As an Energy Star partner, Philips develops products that meet the Energy Star guidelines for energy efficiency. This is achieved by having low standby power consumption through innovatively designed standby circuitry and stringent selection of components made with high efficiency materials.

Compliant with RoHS standards

Philips designs and produces display products in compliance with strict Restriction of Hazardous Substances (RoHS) standards that restrict lead and other toxic substances that can harm the environment.

Adjustable tilt

Adjustable tilt is backward and forward movement of a screen on its base to achieve custom positioning for an ideal viewing angle and more comfort for people who spend long hours working on the computer.

Embedded power supply

An embedded power supply is a power adaptor built into the body of a display device that replaces a bulky external power adaptor.

sRGB ready

sRGB is an industry standard that ensures the best possible match between the colors displayed on your screen and those in your printouts.

Kensington lock compatible

Small abertures built into the display's frame for use with a locking device that secures a display to a fixed object for added protection against theft.



Issue date 2008-11-15

Version: 3.0.3

© 2008 Koninklijke Philips Electronics N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

12 NC: 8670 000 40133 EAN: 87 12581 42700 9

www.philips.com