# 19 inch LCD Monitor

190S5FG

# when screen size matters

Big screen, great features: With its large screen and great performance plus SmartManage for remote, LAN-based monitor management and low power consumption, the Philips 190S5 delivers convenience and an outstanding return on your investment.

#### Lower total cost of ownership

- SmartManage manages display devices remotely
- Lower power consumption than industry average
- · Kensington anti-theft lock secures monitor against theft

#### Outstanding front of screen performance

- Fast response time is capable of handling fast moving pictures (12 ms)
- SXGA 1280 x 1024 resolution for sharper display
- sRGB ensures color matching between display and printouts

#### **Great convenience**

- Embedded power supply eliminates external power adaptors
- VESA mounting pattern for easy wall mounting of display













# 19 inch I CD Monitor

## **Commercial Specifications**

#### **Picture**/ **Display**

- LCD Panel Type
- Panel Size
- Effective Viewing Area
- Pixel Pitch
- Brightness (nits)
- Contrast Ratio
- Display Colors
- Viewing Angle (C/R > 5)
- Response Time

- Maximum Resolution
- Recommended Resolution
- Factory Preset Modes User Definable Modes

- Refresh Rate (V) • sRGB

# Connectivity

• Signal Input

### Convenience

Convenience Enhancements

- Monitor Controls
- OSD Languages
- Other Convenience Features
- Plug & Play Compatibility
- Regulatory Approvals

• Tilt

• VESA Mount

#### Accessories

User Manual

Included Accessories

1280 x 1024 pixels, Anti-glare Polarizer, RGB Vertical Stripe 19"/ 48 cm 376.3 x 301.1 mm 0.294 x 0.294 mm 250 500:1 16 M - Horizontal : 160° - Vertical : 160° 12 ms • White Chromaticity,  $6500^{\circ}$  K x = 0.313 / y = 0.329• White Chromaticity,  $9300^{\circ}$  K x = 0.283 / y = 0.2971280 x 1024 @ 75Hz 1280 x 1024 @ 60Hz 15 modes 14 modes Horizontal Scanning Frequency 30 - 82 KHz 56 - 76 Hz

Yes

Analog (VGA)

On-screen Display, SmartManage

Auto, Brightness control,

Power On/Off, Up/Down,

English, French, German,

Italian, Simplified Chinese,

CE Mark, E2000, NUTEK, Energy Star, SEMKO. TCO'03, TCO'99, TÜV/GS, TÜV-Ergo, FCC-B, UL, CSA

100 mm x 100 mm

Stranish

-5° to 25

Yes

Kensington Lock

DDC/CI, sRGB, Windows 98/ME/2000/XP

Left/Right, Menu (OK),

#### **Dimensions** • Depth (with base)

- Height (with base) • Width (with base)
- MTBF
- Relative Humidity
- Temperature Range (Operation)

235 mm

419 mm

425 mm

50,000 hrs (excl.

CCFL 40,000) hrs

20 % - 80 %

5°C to 35°C

5.8 kg

NUTEK

1 W

Amber

Built-in

-20°C to 60°C

E2000, Energy Star,

34 W (Typical)

Operation, Green;

Stand by/Sleep.

- Temperature Range (Storage)

- Consumption

- Power Supply

## **Product Highlights**

#### **SmartManage**

A system for monitoring, managing and checking status of display devices as well as delivering remote support to users who experience difficulties all accomplished over a LAN.

#### Lower power consumption

Reduction of the electrical power required to operate a device.

#### Kensington anti-theft lock

A security device that fixes the monitor in place to prevent theft.

#### Fast response time

The amount of time it takes for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Lower numbers mean faster transitions and therefore result in fewer visible image artifacts.

#### SXGA, 1280 x 1024 resolution

For graphics monitors, the screen resolution signifies the number of dots (pixels) on the entire screen. For example, a 1280-by-1024 pixel screen is capable of displaying 1280 distinct dots on each of 1024 lines, or about 1.3 million pixels.

#### sRGB ready

Calibrated RGB that is optimized for the vast majority of computer peripherals, monitors, operating systems and browsers, allowing accurate color mapping with very little data overhead.

#### **Embedded** power supply

A power adaptor built into the body of a display device that replaces a bulky external power adaptor.

#### **VESA** mounting holes

A unified industry standard for mounting IT equipment set by the Video Electronics Standards Association.

AC Power Cord, VGA Cable





Trademarks owned by Royal Philips Electronics 2004 © Royal Philips Electronics - All rights reserved As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency. Microsoft and Windows are registered trademarks of Microsoft Corporation. All data subject to change without notice Release date: June 2004 www.philips.com

