



Philips  
LCD monitor

19"  
SXGA

190B5CB



## the best productivity solution

Superior performance for tough jobs: With superior ergonomics and excellent, clear display plus SmartManage for remote, LAN-based monitor management and low power consumption, the Philips 190B5 delivers a big-screen productivity edge.

### Outstanding front of screen performance

- Wide viewing angle for extra freedom
- Fast response time for great display of moving images
- SXGA 1280 x 1024 resolution for sharper display
- Dual input accepts both analog VGA and digital DVI signals
- sRGB ensures color matching between display and printouts

### Maximum comfort for maximum productivity

- Built-in speakers for audio without desktop clutter
- Adjustable screen height for the ideal viewing angle
- Tilt and swivel adjustment for an ideal viewing angle

### Lower total cost of ownership

- SmartManage compatibility enables LAN-based asset management
- Power consumption below the industry average

### Great convenience

- Embedded power supply eliminates external power adaptors

**PHILIPS**  
sense and simplicity

## Specifications

### Picture/Display

- **LCD panel type:** 1280 x 1024 pixels, Anti-glare polarizer, RGB vertical stripe
- **Panel Size:** 19"/ 48cm
- **Effective viewing area:** 376.3 x 301.1 mm
- **Pixel pitch:** 0.294 x 0.294 mm
- **Brightness:** 250 cd/m<sup>2</sup>
- **Contrast ratio (typical):** 500:1
- **Display colors:** 16 M
- **Viewing angle:** @ C/R > 10
- **Viewing angle (H / V):** 176 / 176 degree
- **Response time (typical):** 25 ms
- **White Chromaticity, 6500K:** x = 0.313 / y = 0.329
- **White Chromaticity, 9300K:** x = 0.283 / y = 0.297
- **Maximum Resolution:** 1280 x 1024 @ 75 Hz
- **Optimum Resolution:** 1280 x 1024 @ 60 Hz
- **Factory Preset Modes:** 15 modes
- **User definable modes:** 14 modes
- **Horizontal Scanning Frequency:** 30 - 82 kHz
- **Refresh Rate (V):** 56 - 76 Hz
- sRGB

### Connectivity

- **Signal Input:** VGA (Analog), DVI-D, PC Audio in
- **I/O interface on pad:** Headphone jack

### Convenience

- **Built-in Audio:** 2W RMS x 2 stereo speakers
- **User convenience:** On-screen Display, SmartManage
- **Monitor Controls:** Auto, Brightness Control, Left/Right, Menu (OK), Power On/Off, Up/Down, Volume control
- **OSD Languages:** English, French, German, Italian,

- Simplified Chinese, Spanish
- **Other convenience:** Kensington lock
- **Plug & Play Compatibility:** DDC CI, sRGB, Windows 98/ME/2000/XP
- **Regulatory Approvals:** CE Mark, E2000, EMC, FCC-B, UL, CSA, NUTEK, Energy Star, SEMKO, TCO '99, TÜV/GS, TÜV Ergo
- **Swivel:** +/- 175°
- **Tilt:** -5° to 30°
- **VESA Mount:** 100 x 100 mm

### Accessories

- User Manual
- **Included Accessories:** AC Power Cord, Audio Cable, Protective film, VGA cable
- **Optional accessories:** Super Ergo Base

### Dimensions

- **Dimensions (with base) (W x H x D):** 425 x 410 x 235 mm
- **Height adjustment range:** 40 mm
- **MTBF:** 50,000 hrs
- **Relative humidity:** 20% - 80%
- **Temperature range (operation):** 5°C to 35°C
- **Temperature range (storage):** -20°C to 60°C
- **Weight:** 7.8 kg

### Power

- **Complies with:** E2000, Energy Star, NUTEK
- **Consumption (On mode):** 40 W (Typical)
- **Consumption (Off Mode):** 1 W
- **Power LED indicator:** Operation - green, Stand by/sleep - Amber
- **Power supply:** Built-in

## Product highlights

### Wide viewing angle

A wide viewing angle provides the clearest display with little reflection from virtually any angle.

### Fast response time

Response time measures signal reaction speed in milliseconds. On/off response time measures the time required for the screen to turn from completely white to completely black and vice versa. Fast on/off response time improves display of text. Gray-to-grey response time measures the average time of transition between several sets of random gray levels - Lower numbers mean faster transitions. Faster is better because a fast response time eliminates visible image artifacts that could dampen your experience when viewing fast moving images or objects.

### SXGA, 1280 x 1024 resolution

For graphics monitors, the screen resolution signifies the number of dots (pixels) on the entire screen. For example, a 1280-by-1024 pixel screen is capable of displaying 1280 distinct dots on each of 1024 lines, or about 1.3 million pixels.

### Dual input

Dual input provides connectors to accommodate input of both analog VGA and digital DVI signals.

### sRGB ready

sRGB is an industry standard that ensures the best possible match between the colors displayed on your screen and those in your printouts.

### Built-in speakers

Audio speakers built into a display device.

### Adjustable height

Adjustable height is the ability of a monitor to travel up or down on its base and lock into position when the desired height is reached, delivering a comfortable, individualized viewing angle that is just right for the user's height, weight, body-type and posture, alleviating possible eyestrain or fatigue that can come from long hours working on a computer.

### Screen tilt and swivel

Screen tilt and swivel is a mechanism built into the base permits the monitor to swivel and tilt backward or forward.

### SmartManage enabled

SmartManage is a system for monitoring, managing and checking status of display devices as well as delivering remote support to users who experience difficulties - all accomplished over a LAN.

### Lower power consumption

Reduction of the electrical power required to operate a device.

### Embedded power supply

An embedded power supply is a power adaptor built into the body of a display device that replaces a bulky external power adaptor.

