

Ultra Slim Frame ... Delivers a front-to-back depth and bezel width that leads the industry.



- **19-inch Color LCD SXGA Monitor**

Enjoy excellent display performance providing an optimum resolution of 1280 x 1024 for amazing image clarity.

- **Standard VGA Analog Input**

Provides support for traditional analog signals.

- **Embedded Universal AC Power Supply**

Conveniently adapts to a variety of mounting configurations using a built-in power supply that eliminates the hassle of external power supplies.

- **Advanced AUTOMATIC Adjustment optimizes picture quality**

A perfect picture is only three seconds away. Philips auto adjustment provides optimal screen position and performance with the press of a single button.

- **Adjustable Tilt and Swivel Function**

Enjoy the most comfortable, productive viewing angle regardless of viewer's height or the placement of the monitor.

- **Adjustable Viewing Height**

You can position the screen to the most comfortable and productive viewing height using the height-adjustable base.

- **sRGB Compliance**

Eliminating color reproduction differences, sRGB compliance assures real life colors are consistently and precisely reproduced in CRT monitors, LCD panels, projectors and other devices.

- **Philips First Choice Program**

One-call support includes a comprehensive 3-year warranty with a 1-year 48-hour advance swap guarantee.



KEY TECHNOLOGIES

- 
190B4CS/74
- 
- 
- 
USB Module (Mist White Only) PCHU411
- 
Stealth Black Model 190B4CB

PHILIPS

Product Number 190B4CB/74 (Stealth Black)
190B4CS/74 (Silver-Black)



Technical Specifications

LCD

- Panel TFT LCD
- Screen Size (inch/cm) 19 inch / 48.26 cm
- Pixel Pitch 0.294 x 0.294mm
- Display Format 1280 x 1024 pixels, RGB Vertical Stripe, Anti-glare Polarizer, Hard Coated
- Display Area 376.32 x 301.06mm
- Display Colors 16.7M colors

Scanning

- Vertical Refresh Rate 56 - 76 Hz
- Horizontal Frequency 30 - 82 kHz

Video

- Video Dot Rate 135 MHz
 - Input Impedance -Video 75Ω
 - -Sync 2kΩ
 - Input Signal Levels 0.7Vp-p
 - Sync Input Signal Separate Sync, Composite Sync, Sync on Green
 - Sync Polarities Positive and Negative
 - Video Interface Analog (D-Sub) Input
- Models 190B4CB/74 and 190B4CS/74 are D-Sub (analog) only. DVI-D (digital) is available only on 190B4CB/94 and 190B4CS/94.

Optical Characteristics

- Contrast Ratio 500 : 1 (typ.)
- Brightness 250 cd/m2 (typ.)
- Peak Contrast Angle 6 o'clock
- White Chromaticity x=0.283 y=0.297 (at 9300° K)
- x=0.313 y=0.329 (at 6500° K)
- Viewing Angle V=170° Upper ≥ 85°(typ.)
- (C/R >10) Lower ≥ 85°(typ.)
- H=170° Left ≥ 85°(typ.)
- Right ≥ 85°(typ.)
- Response Time ≤25 ms (typ.)
- (Tr ≤15ms, Tf ≤10ms)

Resolution and Preset Modes

- Max. Resolution 1280 x 1024 at 75Hz
- Recom. Resolution 1280 x 1024 at 60Hz
- 15 Factory Preset Modes:

Resolution	H.freq	V.freq
640 x 350	31.5(kHz)	70(Hz)
720 x 400	31.5	70
640 x 480	31.5	60
640 x 480	35.0	67
640 x 480	37.5	75
800 x 600	35.2	56
800 x 600	37.9	60
800 x 600	46.9	75
832 x 624	49.7	75
1024 x 768	48.4	60
1024 x 768	60.0	75
1152 x 870	69.0	75
1152 x 900	71.8	76
1280 x 1024	63.9	60
1280 x 1024	80.0	75

(Interlace mode is not supported)

Plug and Play Compatibility

- Display Data Channel DDC 2B (VESA)
- Microsoft®, Windows® Me/2000 XP Compatible

Power Management

- Complies with EPA Energy Star and NUTEK specifications
- Typical Operation 45W
- Sleep Mode 1W

Low-Emission Characteristics

- Complies with TCO '03 (190B4CS), TCO '99 (190B4CB), MPRII and prEN50279 (so call MPRII) specifications

Monitor Controls and Functions

- Front

Power on/off	-Tact Switch
OK	-Tact Switch
Auto	-Tact Switch
Up/Down (Brightness)	-Tact Switch
Left/Right	-Tact Switch
Steady Blue	-Power On
Amber	-Power Save/Off Mode
Flashing Blue	-New Mode
- LED indicator

Connections and Cables

- Connections on Monitor Body

-Video	15-pin D-sub (analog)
-Power	IEC/CEE-22 Type Male Power Inlet
• Cables	D-Sub Video Cable, Power Cord

Regulatory Approvals

- TÜV/GS, TÜV-Ergo
- SEMKO
- CE Mark
- TCO '03 (190B4CS)
- FCC-B, UL, CSA
- prEN50279 Low Emission
- NUTEK, Energy Star
- TCO '99 (190B4CB)

Physical Specifications

- UPC Code 190B4CB/74 (Stealth Black) 0 37849 93801 0
- 190B4CS/74 (Silver-Black) 0 37849 93800 3
- Unit Dimensions (WxHxD) 16.8" x 14.9" x 9.3"
- 425 x 377 x 235 mm (incl base)
- 16.8" x 14.2" x 2.6"
- 425 x 377 x 235 mm (excl base)
- Unit Weight 17.4 lbs / 6.5 kg
- Carton Dimensions (WxHxD) 17.8" x 18.9" x 7.0"
- 450 x 480 x 176 mm
- Carton Weight 19.4 lbs / 8.81 kg
- Tilt -5°~35° / ±175°
- Height Adjustment Range 70mm
- Power Supply 100 - 240 VAC, 50/60Hz
- Power Consumption 45W* (typ.)
- Temperature (operating) +5°C to +35°C / 41°F to 95°F
- Temperature (storage) -20°C to +60°C / -4°F to 140°F
- Relative Humidity 20% to 80%
- System mthf 50K hrs (excluding CCFL 40K hrs)

* Resolution 1280x1024, standard size, contrast max., brightness 50%, 9300°K, Full white pattern, without Audio. We recommend using 1280 x 1024 at 60Hz non-interlaced mode for the best picture quality

User Options Accessories (sold separately)

- USB module PCHU411 (Mist White)

Carton Contains: 190B4 Monitor, power cord, and user's manual on CD.

INTERNET ADDRESS: <http://www.philips.com>
TECHNICAL SUPPORT: (877) 835-1838 (USA)
(402) 536-4171 (outside USA)

Printed in the U.S.A., ©2003 Philips Consumer Electronics Co. A Division of Philips Electronics North America Corp. As an Energy Star partner, Philips has determined th at this product meets the Energy Star guidelines for energy efficiency. Microsoft and Windows are registered trademarks of Microsoft Corporation. Macintosh is a registered trademark.

CCM-141 2/04

Literature Order Number: 190B4CB/74 / 190B4CS/74

