



Philips
LCD monitor

17"

SXGA

170C6FS



elegance matters

Designed for you! Matching superb front-of-screen performance and convenience with elegant design, the 170C6 delivers great value for the money while adding style to any room with sleek lines and cool colors.

Outstanding front of screen performance

- Fast 8ms On/off response time: Great text & graphics display
- SXGA 1280 x 1024 resolution for sharper display
- sRGB ensures color matching between display and printouts

Design that complements any interior

- Sleek, elegant design complements your home decor
- Compact and slim design that fits in every room

Best Value for Money

- Lead-free design safeguards our environment
- TCO guarantees the highest safety and ergonomics standards
- Power consumption below the industry average

Great convenience

- Easy to adjust display settings with Philips SmartControl
- Embedded power supply eliminates external power adaptors
- Auto adjustment for perfect picture display with one touch

PHILIPS
sense and simplicity

Specifications

Picture/Display

- **LCD panel type:** 1280 x 1024 pixels, Anti-glare polarizer, RGB vertical stripe
- **Panel Size:** 17"/ 43.3 cm
- **Effective viewing area:** 337.9 x 270.3 mm
- **Pixel pitch:** 0.264 x 0.264 mm
- **Brightness (nits):** 250 nit
- **Contrast ratio (typical):** 500:1
- **Display colors:** 16.2 M
- **Viewing angle:** @ C/R > 5
- **Viewing angle (H / V):** 160 / 145 degree
- **Response time (typical):** 8 ms
- **White Chromaticity, 6500K:** $x = 0.313$ / $y = 0.329$
- **White Chromaticity, 9300K:** $x = 0.283$ / $y = 0.297$
- **Maximum Resolution:** 1280 x 1024 @ 75 Hz
- **Optimum Resolution:** 1280 x 1024 @ 60 Hz
- **Factory Preset Modes:** 15 modes
- **User definable modes:** 50 modes
- **Video Dot Rate:** 140 MHz
- **Horizontal Scanning Frequency:** 30 - 83 kHz
- **Vertical Scanning Frequency:** 56 - 76 Hz
- **sRGB**

Connectivity

- **Signal Input:** VGA (Analog)
- **Video Sync Input Signal:** Composite Sync, Separate Sync, Sync on Green

Convenience

- **Buttons and controls:** Front keys
- **User convenience:** On-screen Display, SmartControl
- **Monitor Controls:** Auto, Brightness Control, Left/

- Right, Menu (OK), Power On/Off, Up/Down
- **OSD Languages:** English, French, German, Italian, Simplified Chinese, Spanish
- **Other convenience:** Kensington lock compatible
- **Plug & Play Compatibility:** DDC/CI, sRGB, Windows 98/ME/2000/XP
- **Regulatory Approvals:** CE Mark, E2000, EMC, FCC-B, UL, CSA, Energy Star, SEMKO, TCO '99, TÜV/GS, TÜV Ergo
- **Tilt:** -5° to 20°

Accessories

- **Included Accessories:** AC Power Cord, VGA cable
- User Manual

Dimensions

- **Dimensions (with base) (W x H x D):** 403 x 392 x 171 mm
- **MTBF:** 50,000 hrs
- **Relative humidity:** 20% - 80%
- **Temperature range (operation):** 5°C to 35°C
- **Temperature range (storage):** -20°C to 60°C
- **Weight:** 4.5 kg

Power

- **Complies with:** E2000, Energy Star, NUTEK
- **Consumption (On mode):** 30W (Typical)
- **Consumption (Off Mode):** < 1 W
- **Power LED indicator:** Operation - green, Stand by/sleep - Amber
- **Power supply:** Built-in, 90-264 VAC, 50/60 Hz

Product highlights

8ms response time (On/Off)

On-Off response time is the period required for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Faster is better: Lower response time means faster transitions and, therefore, results in fewer visible image artifacts in the display of transition of text and graphics. On-Off response time is a more important measure in the display of business content like documents, graphs and photos.

sRGB ready

sRGB is an industry standard that ensures the best possible match between the colors displayed on your screen and those in your printouts.

Lead-free

Lead-free display products are designed and produced in compliance with strict European Community Restriction of Hazardous Substances (RoHS) standards that restrict lead and other toxic substances that can harm the environment.

TCO '99 compliance

A TCO (Swedish Confederation of Professional Employees) standard even more stringent than MPR-II for safety and ergonomics, especially concerning alternating electric fields (AEF).

SmartControl

PC software for fine tuning display performance and settings. Philips offers users two choices for display setting adjustment. Either navigate the multilevel On Screen Display menu through buttons on the display itself or use the Philips SmartControl software to easily adjust the various display settings in a familiar way.

Embedded power supply

An embedded power supply is a power adaptor built into the body of a display device that replaces a bulky external power adaptor.

