



CONVECTION OVEN



SPECIFICATIONS

Half-size electric, forced air, single convection type oven. Standard specifications include 3.2 KW per cavity with two high-speed fans and dual fan motors.

A 120-minute timer with alarm which controls the heating elements, oven lights and convection fans or continuous-run setting without timer.

The oven interior features easy-to-clean cove corners and measures 21" wide (533mm) by 14 1/2" high (368mm) by 13 1/2" deep (343mm). The cooking chamber is stainless steel with removable 11-position rack guides with 1" spacing (25mm) and 4 heavy-duty adjustable chrome-plated racks.

The oven exterior measures 27" wide (686mm) by 21 3/4" deep (553mm) by 22" high (559mm) plus adjustable feet. Standard features include chrome-plated adjustable feet, 2 1/2" to 4" (64mm to 102mm).

Front, top and sides and trim are constructed with stainless steel.

A single fold-down door with double-pane thermoglass opens for easy viewing and sideways loading of 1/2-size sheet pans.

One year limited parts & labor warranty.

Job _____

ELECTRIC CONVECTION OVENS \searrow

□ Model BP-200

STANDARD FEATURES

- Energy efficient 3.2 KW per oven direct forced air heat system
- 208v or 240v, 60hz; 1 phase with cord & plug
- Electro mechanical temperature control
- Double-pane thermal glass door window
- Oven lights
- □ 120-Minute timer with alarm
- □ 175°F (80°C) to 520°F (271°C) temperature range
- Cool down fan mode
- Elements-on and temperature-ready indicator lights
- Stainless steel oven interior
- □ 11-Position removable rack guides with 1" (25mm) spacing
- □ 4 Heavy-duty, positive-stop, chrome-plated wire racks
- □ Stainless steel stainless front, top & sides
- Bottom hinged glass door
- □ Adjustable legs 2 1/2" (64mm) to 4" (102mm)
- □ Front mounted control panel for easy service access
- Heavy-duty industrial grade insulation in top, sides and back
- One year limited parts & labor warranty

OPTIONS & ACCESSORIES

Stainless steel stand with or without casters

CERTIFICATIONS







FRONT VIEW



SIDE VIEW — Single Unit



TOP VIEW

ALL DIMENSIONS NOMINAL

SHIPPING INFORMATION													
	Shipping Weight		Carton Size		Carton Dimensions								
Model	Lbs.	Kilos	Cubic Feet	Cubic Meters	Wi Inches	dth mm	De Inches	pth mm	Hei Inches	ght mm			
BP-200	150	68	10.1	.29	27	686	30	762	26	641			

POWER SUPPLY								
Model	KW	Voltage	Phase	Amps	Breaker			
BP-200	3.2	208	1	15.3	20			
	3.2	240	1	13.4	20			

Each oven requires separate electrical connections



