

Feature packed display for increased productivity

With SmartImage, SmartContrast and SmartControl to boost your work output plus TrueVision for the best-ever LCD display, the TCO'03 certified, Vista-ready Philips Brilliance 190S9 is ready to get the job done.

Best total cost of ownership solution

- TrueVision ensures top quality LCD display delivered to you
- TCO'03 guarantees the highest safety and ergonomic standards
- Empowered for Windows Vista

Outstanding front of screen performance

- SmartImage: For an optimized display experience
- SmartContrast: Dynamic, optimized contrast for visual clarity

Eco-friendly design

· Green design conserves resources and reduces operating costs

Great convenience

- Dual input accepts both analog VGA and digital DVI signals
- Tilt and swivel adjustment for an ideal viewing angle
- · Hassle-free display performance tuning with SmartControl II
- · Cable management for a tidy work space



190S9FB



















Specifications

Picture/Display

- LCD panel type: I280 x I024 pixels, Anti-glare polarizer, RGB vertical stripe
- Panel Size: 19"/ 48 cm
- Effective viewing area: 14.8×11.9 inch
- Pixel pitch: 0.294 x 0.294 mm
- Brightness: 300 cd/m²
- Contrast ratio (typical): 800:1
- SmartContrast ratio (dynamic): 8000:1
- Display colors: 16.7 M
- Viewing angle: 176° (H) / 170° (V), @ C/R > 5
- Response time (typical): 5 ms
- Maximum Resolution: 1280 x 1024 @ 75 Hz
- Recommended Resolution: 1280 x 1024 @ 60 Hz
- Horizontal Scanning Frequency: 30 83 kHz
- Vertical Scanning Frequency: 56 -75 Hz
- · Picture enhancement: SmartImage
- sRGB

Connectivity

- Signal Input: Analog (VGA), DVI-D
- Video Sync Input Signal: Composite Sync, Separate Sync, Sync on Green

Convenience

- Convenience Enhancements: On-screen Display, SmartManage enabled, SmartControl II
- Monitor Controls: SmartImage, Auto (Back), Power On/Off, Brightness (Up), Menu (OK), Input (Down)
- · OSD Languages: English, French, German, Italian, Portuguese, Russian, Simplified Chinese, Spanish
- Other convenience: Kensington lock compatible
- Plug & Play Compatibility: DDC/CI, sRGB, Windows 98, Windows 2000, Windows XP. Windows Vista, Mac OS X

- · Regulatory Approvals: CE Mark, Energy Star, FCC Class B, SEMKO, TÜV/GS, TÜV Ergo, TCO '03, UL/
- Tilt: -5° to 20°
- VESA Mount: 100 x 100 mm

Dimensions

- Box dimensions (W x H x D): 451 x 465 x 151 mm
- Box dimensions in inch ($W \times H \times D$): $17.8 \times 18.3 \times 5.94$ inch
- Set dimensions (W \times H \times D): 404 \times 350 \times 68 mm
- Set dimensions in inch (W \times H \times D): $15.9 \times 13.8 \times 2.68$ inch
- Set dimensions with stand ($W \times H \times D$): 404 x 418 x 186 mm
- Set dimensions with stand in inch (W x H x D): $15.9 \times 16.5 \times 7.32$ inch
- MTBF: 50,000 hrs
- Relative humidity: 20% 80%
- Temperature range (operation): 0°C to 40°C
- Temperature range (storage): -20°C to 60°C
- Product weight (+stand): 3.85 kg
- Product weight (+stand) (lb): 8.49 lb
- Weight incl. Packaging: 5.24 kg
- · Weight incl. Packaging (lb): 11.6 lb

- Complies with: Energy Star
- Consumption: < 36 W (Typical)
- Consumption (economy mode): 27 W
- Off Mode: < 0.8 W
- · Power LED indicator: Operation Blue, Stand by/ sleep -blue(blinking)
- Power supply: Built-in, 100-240VAC, 50/60Hz



TrueVision is industry-leading, proprietary Philips testing and algorithm technology for monitor adjustment and fine tuning, an extensive process that ensures ultimate display performance in compliance with a standard four-times more stringent than Microsoft's Vista requirements from each and every monitor that leaves the factory - not just a few review samples. Only Philips goes to these lengths to deliver this exacting level of color accuracy and display quality in every new monitor.

TCO '03 compliance

190S9FB/27

A TCO (Swedish Confederation of Professional Employees) standard even more stringent than MPR-II for safety and ergonomics, especially concerning alternating electric fields (AEF).

Windows Vista ready

Philips Vista-ready monitors are empowered for vibrant, exciting display of this new, visually sophisticated and demanding Windows operating system, designed to enhance your entertainment experience, make you more productive and help you control your computing experience at home and in the office, making viewing, finding and organizing information for work or play quick, efficient and easv.

SmartImage

SmartImage is an exclusive, leading edge Philips technology that analyzes the content displayed on your screen. Based on a scenario you select, SmartImage dynamically enhances the contrast, color saturation and sharpness of images and videos for ultimate display performance - all in real time with the press on a single button.

SmartContrast

SmartContrast is Philips technology that analyzes the contents you are displaying, automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and optimum contrast for more entertainment fun when viewing videos or playing games where dark hues are displayed, when you select the Economy mode, contrast is adjusted and backlighting finetuned for just-right display of everyday office applications and lower power consumption.

Eco-friendly design

Green design is based on environmentally conscious engineering of a display device to minimize power consumption, reduce packing materials and eliminate environmentally sensitive materials.

Dual input provides connectors to accommodate input of both analog VGA and digital DVI signals.

Screen tilt and swivel

Screen tilt and swivel is a mechanism built into the base permits the monitor to swivel and tilt backward or forward.

SmartControl II

SmartControl II is monitor-based software with an easy-touse on-screen graphic interface that guides you through fine-tuning resolution, color calibration and other display settings including brightness, contrast, clock & phase, position, RGB, white point and - on models with onboard speakers - volume adjustments.

Cable management

Cable management is a system that maintains tidy workspace by organizing cables and wires required for the operation of a display device.



Issue date 2008-10-29

UPC: 6 09585 15641 8

Version: 2.0.2

12 NC: 8670 000 40641

© 2008 Koninklijke Philips Electronics N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com