

CE42SR1

SunlightReadable Weatherproof Monitor



WEATHERPROOF LCD MONITOR

SANYO has used all of its expertise in creating a lightweight aluminum framed LCD monitor, which is protected by anti reflected tamper glass. Newly integrated sun-readable panel is perfect solution for outside under the sun light.

Its brightness is more than 1000 (cd/m² for panel) with ideal condition under sunlight .

This means that the SANYO weather proof monitor can be used in a wide variety of environments due to it being fully approved **IP66** weather-resistant and under sun light situation on the outdoor. The SANYO weatherproof LCD will make the ideal display for Out-door Digital signage or in-door public displays

New product for outdoor applications:

- Bus stops
- Railway lines
- Highways

Indoor

- Shops window
- Restaurant entrances
- Commercial malls

SANYO

SANYO Canada Inc.
1-300 Applewood Cres.,
Ontario, Canada
L4K 5C7

www.sanyo.ca Tel 905-760-9944.

Specifications

Type	Liquid Crystal Display Panel
Screen Size	42V
Aspect Ratio	16:9
Resolution	WXGA 1366 (horizontal) x 768 (vertical) pixels
Brightness	At indoor 830 At 80Klux outdoor 1.500 cd/m ²
Contrast Ratio	1200:1 (typical)
Viewing Angle	178° (Vertical/Horizontal)
Response Time	9 ms (gray to gray)
Computer Compatibility	VGA, SVGA, XGA, SXGA WXGA, UXGA
Speaker	N/A
Color System	PAL / NTSC3.58(AV-IN)/SECAM
Input Terminals	
AV1	Video / Audio (Scart)/ RGB
AV2	Component (Y,Pb,Pr) / RGBHV (BNC x 5) Audio (RCA x 2)
AV3	Video (BNC x1)
Computer 1	RGB (D-Sub 15) Audio (mini-jack)
DVI-D	W / HDCP
RS-232	Serial (D-Sub 9)
Output Terminals	Component (Y,Pr,Pb) / RGBHV (BNC x 5) Audio (RCA x 2)
AV2	Audio (RCA x 2)
AV3	Video (BNC x1)
RS-232	Serial (D-Sub 9)
Audio Monitor Output	Audio (RCA x 2)
External Speaker Out	6 W + 6 W
Power Supply	AC 100V - 240V 50 / 60 Hz
Power Consumption	200 W
Operation Temperature (with winter mode)	Operation 0-45 °C (32 - 113 ° F) Operation -20-45 °C (-4 - 113 ° F)
Dimensions (WxHxD)	1027 x 620 x 167.5 mm 40.4" x 24.4" x 6.6"
Net Weight	41 Kg
Packed Dimensions (WxHxD)	1194 x 273 x 794 mm 41.3" x 25.7" x 6.6"
Packed Weight	45.5 Kg
Included Accessories	Owner's Manual; Remote Control w/Batteries; AC Power Cord
IP Rating	IP66 Weather Proof
Safety / EMC	EN60950 2002 EN55022 1998+A2 EN55024 1998+A2 EN61000-3/2-2000 -3/3-1995+A1 2001 UL60950 2002 CAN/CSA-C22.2 FCC part15 Class B, UL Listed
Warranty	3 Years Parts & Labor, QRP
Container	66 sets/ 20FT, 132sets/ 40FT, 154sets/40HC

Because our products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.