

HD
ready



42SRE1

- Screen Dimensions : 105 cm (42")
- Sunlight Readable
- Hotel Mode (restricts user settings)
- Ideally suited for 24/7 applications
- Extensive input & output terminals
- Impressive Picture Quality: HD Ready
- Fast image response times
- Suitable for Point of Sale, Shop Windows, Hotel lobbies and Digital Signage (Airports, Railway stations)

42SRE1

Model	42SRE1
EAN Code	4994334252807
Category	Professional LCD Monitor
Type	Liquid crystal display panel
Screen size (diagonal image)	42" (105 cm)
Active screen area (W x H)	93.0 x 52.3 cm
Aspect ratio	16 : 9
Resolution in pixels	1,366 x 768 (WXGA)
Pixel pitch	0.227 x 0.681 mm
Brightness	1500 cd/m with ideal conditions under sunlight
Contrast ratio	1,500 : 1
Viewing angle	178° (horizontal and vertical)
Response time	6 ms (grey to grey)
Grey scale value	8 bit
Number of colours	16.7 M
Colour Systems	PAL, NTSC3.58, SECAM
Computer compatibility	UXGA, WXGA, SXGA, XGA, SVGA, VGA
Input terminals	DVI-D (digital/HDCP) D-sub15 5 x BNC (RGBHV,Y-Pb/Cb-Pr/Cr) Component (Y,Pb,Pr) BNC (Video) RS232 (D-Sub 9 pin) 2 x RCA (R/L mono) for Audio 3.5 mm Stereo Jack for Audio
Output terminals	5 x BNC (RGBHV,Y-Pb/Cb-Pr/Cr) Component (Y-Pb-Pr) BNC (Video) Scart (RGB) RS232 (D-Sub 9 pin) 2 x RCA (R/L mono) for Audio External speaker output (2 x 6W)
Operating temperature	0 °C to +35 °C
Storage Temperature	-20 °C to +60 °C
Voltage	220 – 240 V (50Hz)
Power consumption	188 W / 1.2 W (Stand-by Mode)
Dimensions (W x H x D)	1,032 x 625 x 127 mm
Weight	22.5Kg
Vesa mounting sizes	400 x 400, 800 x 400 mm
Colour of cabinet	Black
Warranty	2 years
Standard accessories	User Manual, Remote control, Power Cable
Special features	Sunlight Readable- Adaptive brightness in accordance with prevailing light conditions, Anti reflective acrylic panel.



Technical specifications subject to change without notice. Date 04/2008

