



CHRISTIE LX25a

The Perfect Image – From a Small, Sleek, Sharable Resource

Uses

Classrooms
Campuses
Conference centers
Small meeting rooms
Break-out rooms

For powerful presentation projection on the move, the Christie LX25a is the perfect resource. Weighing just 6.2 lb and delivering 2500 ANSI lumens, the LX25a fits anywhere and delivers bright, high-impact presentations.

Lightweight and low profile with native XGA resolution and a 450:1 contrast ratio, this dynamo projector provides displays with crisp, detailed images. The short-throw zoom lens is perfect when space is limited. Latest progressive-scan video electronics provide improved video performance and detailed, artifact-free images for brilliant presentations. Optional ChristieNET™ connectivity provides network-enabled monitoring and control.

Easy to use, auto set-up simplifies start-up with image adjustments and automatic keystone alignment at the push of a button. An intuitive graphic user interface makes navigation simple. A customizable start-up logo lets you make an impression immediately – while the new security PIN code prevents unauthorized operation.

Compact and ultra-portable for presentations with eye-catching appeal.

Christie LX25a

Specifications



The Christie LX25a's small, sleek profile makes installation unobtrusive and easy.

IMAGE

- 2500 ANSI lumens
- 85% brightness uniformity
- Contrast ratio: 450:1 on/off

DISPLAY TECHNOLOGY AND RESOLUTION

- 3 x 0.8" p-Si Active Matrix TFT LCD panels with Micro Lens Array
- True XGA (1024 x 768)
- 8-bit color resolution offering 16.7 million displayable colors

INPUT SIGNAL COMPATIBILITY

- VGA to SXGA
- STV, DTV and HDTV
- Digital Visual Interface (DVI-I) HDCP compliant
- Progressive scan video decoding with automatic 3-2 pulldown

SCAN RATES

- Horizontal – 15 kHz to 100 kHz
- Vertical – 50 Hz to 100 Hz

OUTPUTS

- HD15 (analog RGB)
- Audio (stereo mini-jack)
- Single 1W speaker

ENHANCED FEATURE SET

- PIN code security for power on
- "Blackboard" mode to optimize display on green chalk boards
- Color management system (built-in)
- Horizontal and vertical digital keystone correction, +/- 40° vertical, +/- 20° horizontal
- Dual mode input/output HD15 connector for loop through or monitor connection
- Digital zoom and pan (max. x49)
- User-definable start-up screen
- Software lock for keypad or remote
- Front/rear/ceiling mount orientations

GRAPHICAL USER INTERFACE

- Easy set-up, on-screen display (OSD)
- Image aspect ratios: standard 4:3 or wide 16:9
- Menus in eleven languages



The short-throw zoom lens produces large images when space is limited.



Auto set-up gives you perfect image and automatic vertical keystone correction.

PIXEL CLOCK

- 140 MHz

STANDARD LENS

- Manual zoom: 1.25 – 1.95:1
- Screen size: 40" – 300"
- Manual zoom and focus

INPUTS, CONTROL AND NETWORKING

- DVI-I (24-pin digital RGB); audio input (stereo mini-jack)
- HD15 (analog RGB, YPbPr); audio input (stereo mini-jack)
- Composite (RCA); S-Video (4-pin mini-DIN); audio input (2 x RCA L/R)
- Control port input: 8-pin mini DIN and USB Type B
- Automatic set-up (phase/tracking/positioning/keystone correction)
- Optional ChristieNET™ for connection to TCP/IP network
- IR remote keypad with laser pointer and mouse control

LAMP

- 200W lamp
- Lamp life of 1500 hours (typical)

POWER REQUIREMENTS

- 100 VAC to 240 VAC +/- 10% @ 50/60 Hz
- Power consumption: 300W maximum
- Thermal dissipation: 1025 BTU/hr
- Operating temperature: 40 to 95° F (5 to 35° C) [storage 14 to 140° F (-10 to 60° C)]
- Acoustic noise level: 34dBA

DIMENSIONS

- Weight: 6.2 lb (2.9 kg)
- Size: 11.7" W x 2.8" H x 8.4" L (298mm W x 71mm H x 214mm L)

STANDARD ACCESSORIES

- User manual
- HD15-DVI-I computer cable
- Mouse control cable (USB)
- Soft-sided carrying case
- AC cord x 2 (UL and European line cord)

OPTIONAL ACCESSORIES

- ChristieNET™ networking
- Lamp module
- Component to HD15 video cable
- Ceiling mount
- Shipping case

ANTI-THEFT SECURITY

- Compatible with Kensington® Microsaver

REGULATORY APPROVAL

- UL/CSA/IEC 60950 (3rd edition)
- FCC Class A, CE, CCC (pending)
- This product conforms to all relevant European directives, standards, safety, health and environmental concerns

WARRANTY

- Limited 3 years parts and labor (excluding lamp)
- Lamp warranty 120 days or 500 hours (whichever comes first)

Corporate Offices

USA
10550 Camden Drive
Cypress, CA 90630
PH: 714-236-8610
FX: 714-503-3385
Toll free: 866-880-4462 (NA only)
sales-us@christiedigital.com

CANADA
809 Wellington Street North
Kitchener, Ontario N2G 4Y7
PH: 519-744-8005
FX: 519-749-3136
Toll free: 800-265-2171 (NA only)
sales-canada@christiedigital.com

Worldwide Offices

UNITED KINGDOM
PH: +44 118 977 8000
FX: +44 118 977 8100
sales-europe@christiedigital.com

GERMANY
PH: +49 2161 664540
FX: +49 2161 664546
sales-europe@christiedigital.com

FRANCE
PH: +33 (0) 1 47 48 28 07
FX: +33 (0) 1 47 48 26 06
Mobile: +33 (0) 6 76 47 43 62
sales-france@christiedigital.com

SINGAPORE
PH: +65 6877 8737
FX: +65 6877 8747
sales-singapore@christiedigital.com

SHANGHAI
PH: +86 21 6278 7708
FX: +86 21 6270 5816
sales-china@christiedigital.com

BEIJING
PH: +86 10 6561 0240
FX: +86 10 6561 0546
sales-china@christiedigital.com

JAPAN
PH: +81 3 3559 7481
FX: +81 3 3559 7482
sales-japan@christiedigital.com

For the most current specification information, please visit www.christiedigital.com

