

TOSHIBA
Leading Innovation >>>

P1710A/P1910A
HIGH-RESOLUTION LCD MONITORS



- Available in 17-inch and 19-inch LCD monitors
- Resolutions up to 1280 x 1024 @ 60/75 Hz
- Standard VESA 100 mount
- DVI-D Video Input
- 12V DC Power
- Up to 380cd/m2 brightness
- 1000:1 contrast ratio to enhance image detail
- Audio input/output with stereo speakers
- Picture-in-picture
- Simple on-screen display menu to adjust picture controls
- Plug-and-play connectivity for cameras, NVRs and PCs

P1710A/P1910A High Resolution LCD Monitors

MODEL NUMBER	P1710A	P1910A
Panel Size	17.0"	19.0"
Aspect Ratio	5:4	5:4
Resolution / Scan	640 x 480 @ 60/73/75 800 x 600 @ 56/60/72/75 1024 x 768 @ 60/70/75 1280 x 1024 @ 60/75	
Brightness	380cd/m2 (Typ.)	250cd/m2 (Typ.)
Contrast	1000:1 (Typ.)	
Panel Viewing Angle (H/V)	170° / 170° (Typ.)	
Response Time	5ms (Typ.)	
Display color	16.7M	
Sync. Format	NTSC / PAL	
Frequency (Horizontal)	VGA/DVI: 31.5K - 80KHz, Video: 15750 / 15625Hz (NTSC/ PAL)	
Frequency (Vertical)	VGA/DVI: 56Hz -75Hz, --Video: 50 / 60Hz	
Interfaces	Video Input x 2 (BNC), Video Output x 2 (BNC) 75 ohm (Auto Termination)	
Video Interface Termination	75 ohm (Auto Termination)	
Graphic Interface	Analog RGB Input x 1 (D-Sub 15), Digital RGB (DVI-D) Input x 1	
Audio Interface	Audio Input x 1, Audio Output (volume engaged) x 1	
Built-in Speakers	1W x 1	
PIP (Picture in Picture)	Yes	
OSD Language	English, Traditional Chinese, Simplified Chinese, French, German, Spanish, Italian	
VESA Mounting	VESA 100	
Weight	10.2lb (4.6kg)	10.9lb (4.8kg)
Dimensions (W x H x D)	15.2 x 16.0 x 9.4 inch (386 x 407 x 240 mm)	16.7 x 17.2 x 9.4 inch (424 x 437 x 240 mm)
Safety & EMI	AC adapter: UL, CUL, FCC/B, Monitor: FCC/B	
Power supply	12V DC ± 10 %	
Current Consumption (max.)	12V DC / 3A	12V DC / 2A
Temp (Oper.)	32° F – 104° F (0° C-40° C)	
Humidity	20% ~ 80%	
Accessories	Pedestal, AC Adapter, Power cord, VGA cable, User's Manual	

