

The Biggest Thing in HD LCD Monitors

LCD-3200HD LCD-3200HDL LCD-2600HD

with
RS-232 and
HDMI & DVI



LCD-3200HD

Shown without detachable speakers.



LCD-2600HD

Active Matrix 32" and 26" LCD HD Monitors

• **HD compatible (supports 480p/i, 720p, 1080i)**

• **RS-232 feature allows external devices to control the monitor through the serial port.**

- PIP: Picture in picture capability
- Widescreen 16:9 aspect ratio, 4:3, zoom
- LCD-3200HD: 2 detachable speakers provide 3D MTS stereo and superior listening pleasure.
LCD-2600HD: 2 built-in 10W speakers provide 3D MTS stereo and superior listening pleasure
- Environmental protection includes power-saving capabilities, and the unit emits no x-ray radiation
- Absence of video oscillations and anti-reflective hard coating provides enhanced viewing pleasure
- Composite, S-Video, component, DVI, PC
- Case made of durable plastic (black color)
- Built-in removable desk stand included
- Wireless remote control works within 30 ft.
- 3-comb filter
- LCD-3200HD: Response time: 12/12ms (rising/falling)
LCD-2600HD: Response time: 15/5ms (rising/falling)

Optional Accessories

PLT-2300	VESA conversion plate (for landscape & portrait positioning)
WM-3018VT	Fixed wall mount bracket
WM-4200VT	4-way pan/tilt wall mount bracket (order w/ PLT-2300)
WMC-2342	Ceiling mount (order w/ PLT-2300)

**For unit in flush mount kit order
model LCD-3200HDL.**

Dimensions (WH): 33-3/8" x 21-3/8"

Distance between horizontal mounting holes: 32-3/8"

Resolution: 1366 (H) x 768 (V) dots
Brightness rating: 500 cd/m² (Nit)
Contrast Ratio: 800:1

Display: LCD-3200HD: 32.0" TFT LCD active matrix
LCD-2600HD: 26.0" TFT LCD active matrix

Input Signal: Composite NTSC/PAL, S-Video,
analog RGB, component, HDMI, DVI

PC compatibility: IBM compatible

Colors: 16.7M

Viewing angle L/R/T/B: 85/85/85/85 degrees

Number of Pixels: 983,040

LCD-3200HD: Dimensions (WHD): 1026 x 536 x 231mm / 40.4" x 21.1" x 9.1"

LCD-2600HD: Dimensions (WHD): 804 x 536 x 230mm / 31.6" x 21.1" x 9.1"

LCD-3200HD: Dimensions w/o speakers & deskstand (WHD): 804 x 496 x 120mm / 31.7" x 19.5" x 4.7"

LCD-2600HD: Dimensions w/o deskstand (WHD): 804 x 496 x 120mm / 31.7" x 19.5" x 4.7"

Actual visible screen size (WH): LCD-3200HD: 988 x 406mm / 38.9" x 16"

LCD-2600HD: 567 x 340mm / 22.3" x 13.4"

Operating temperature/humidity: 50 ~ 104°F / 10 ~ 40°C, 20% ~ 90% humidity

Power Requirements: 12VDC, 10.5A

Power Consumption: 130W (max.)

Rear Terminal Connections: [RCA video IN and RCA R/L IN audio jack] x 2

S-Video IN jack x 2,

[RCA Y/Pb/Pr inputs & R/L audio inputs],

[RCA Y/Cb/Cr & R/L audio inputs]

RCA audio R & L output, PC audio IN jack,

15-pin D-sub, AC IN, 9-pin RS-232,

HDMI, DVI

LCD-3200HD: Weight: Net: 16 kg./ 35 lbs. Gross: 24 kg./ 52 lbs.

LCD-2600HD: Weight: Net: 15.1 kg./ 33 lbs. Gross: 19 kg./ 42 lbs.

1319 Dexter Ave. N • Ste. 020 • WA 98109
Tel: 206-623-6000 • FAX: 206-623-6609

E-mail: sales@totevision.com
http://www.totevision.com

**TOTE
VISION**