

LCD-2300HD

with
RS-232 and
HDMI & DVI



Active Matrix 23" Color LCD HD Monitor

• **HD compatible (supports 480p/i, 720p, 1080i)**

• **RS-232 feature allows external devices to control the monitor through the serial port.**

- PIP: Picture in picture capability
- 2 built-in speakers provide 3D MTS stereo and superior listening pleasure.
- Environmental protection includes power-saving capabilities, and the unit emits no x-ray radiation.
- Absence of video oscillations and anti-reflective hard coating provides enhanced viewing pleasure.
- Composite, S-Video, component, DVI, RS-232, and PC capability
- Case made of durable plastic (silver color)
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Built-in removable desk stand included
- Includes switching power supply 100-240VAC, 50/60 Hz
- Closed-caption and V-chip features
- Wireless remote control works within 30 feet.
- Widescreen 16:9 aspect ratio, 4:3, zoom
- 3D-comb filter
- Response time: 15/10ms (rising/falling)

Optional Accessories

- | | |
|-----------|---|
| PLT-2300 | VESA conversion plate (for landscape & portrait) |
| WM-3018VT | Fixed wall mount bracket |
| WM-4200VT | 4-way pan/tilt wall mount bracket (order w/ PLT-2300) |
| WMC-2342 | Ceiling mount (order w/ PLT-2300) |



WM-3018VT



WM-4200VT

Resolution: 1366 (H) x 768 (V) dots

Brightness rating: 500 cd/m² (Nit)

Contrast Ratio: 400:1

Display: 23.0" TFT LCD active matrix

Back Light: Built-in (12 CCFT)

Input Signal: Composite NTSC/PAL, S-Video component, analog RGB, HDMI, DVI
Has digital RGB

C compatibility: IBM compatible

Dot Pitch: 0.39(V) x 0.39(H)mm

Colors: 16.7M

Contrast Ratio: 400:1

Number of Pixels: 983,040

Response Time: 15/10ms

Audio output: 10W x 2

Speakers: 10W + 10W

Viewing angle L/R/T/B: 85/85/85/85 degrees

Pixel Configuration: Stripe

Input Signal Level: 1.0V P-P (positive) 75 Ohm

Dimensions (WHD): 720 x 475 x 240mm / 28.3" x 18.7" x 9.4"

Dimensions w/o deskstand (WHD): 720 x 413 x 81mm / 28.3" x 16.3" x 3.2"

Actual visible screen size (WH): 499 x 299mm / 19.6" x 11.8"

Operating temperature/humidity: 50 ~ 104°F / 10 ~ 40°C, 20% ~ 90% humidity

Power Requirements: 12VDC, 10A

Power Consumption: 120 W (max)

Rear Terminal Connections: [RCA video IN and RCA R/L IN audio jack] x 2
S-Video IN jack x 2, [RCA Y/Pb/Pr inputs & R/L audio inputs],
[RCA Y/Cb/Cr & R/L audio inputs]
RCA audio R & L output, PC audio IN jack,
15-pin D-sub, AC IN, 9-pin RS-232,
HDMI, DVI

Net Weight: 11.58 kg. / 25.5 lbs.

Gross Weight: 14.56 kg. / 32.8 lbs.

1319 Dexter Ave. N • Ste. 020 • WA 98109

Tel: 206-623-6000 • FAX: 206- 623-6609

E-mail: sales@totevision.com

http://www.totevision.com

**TOTE
VISION®**