

LCD-4200HD LCD-4000HD



with
RS-232 and
HDMI & DVI

The Biggest Thing in LCD HD Monitors

Active Matrix 42" and 40" Color LCD HDTV Monitor

• True HD displays 1080p/i without down scaling
(also supports 480p/i, 567p/i, 720p)

• RS-232 feature allows external devices to
control the monitor through the serial port.


- PIP: Picture in picture capability
- 2 rear speakers provide 3D MTS stereo and superior listening pleasure.
- SRS technology provides surround sound experience.
- Environmental protection includes power-saving capabilities, and the unit emits no x-radiation.
- Absence of video oscillations and user selection of color temperature (9300°, 7500°, 6500°) provides enhanced viewing pleasure.
- Hard anti-glare coating enhances viewing pleasure.
- Composite, S-Video, component, HDMI, DVI and PC capability
- Top controls for volume up/down, source, menu
- Case made of durable plastic (black color)
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Built-in removable desk stand included
- Includes built-in power supply 100~200 VAC.
- Wireless remote control works within 30 feet.
- Widescreen 16:9 aspect ratio, 4:3, zoom

Optional Accessories

- | | |
|-----------|---|
| PLT-3742 | VESA conversion plate for landscape or portrait |
| WM-3742VT | Fixed wall mount bracket |
| WM-4200VT | 4-way pan/tilt wall mount bracket (order w/ PLT-3742) |
| WMC-2342 | Ceiling mount bracket (order w/ PLT-3742) |



WM-3742



WM-4200VT

Resolution: 1920 (H) x 1080 (V) dots
Brightness rating: 500 cd/m² (Nit)
Contrast Ratio: 1000:1

- Display: LCD-4200HD: 42.0" TFT LCD active matrix
LCD-4000HD: 40.0" TFT LCD active matrix
- Back Light: Built-in (16 CCFT)
- Input Signal: Composite NTSC/PAL, S-Video, component, analog RGB, HDMI, DVI
- PC compatibility: IBM compatible
- Dot Pitch: 0.681(V) x 0.227(H)mm
- Colors: 16.7M
- Number of Pixels: 1,049,088
- Response Time:(rising/falling) : LCD-4200HD: 16/16mS, LCD-4000HD: 10/6mS
- Audio output: 8W x 2
- Speakers: 8W + 8W
- Viewing angle L/R/T/B: 85/85/85/85 degrees
- Pixel Configuration: Stripe
- Input Signal Level: 1.0V P-P (positive) 75 Ohm
- Dimensions (WHD): LCD-4200HD: 1038 x 698 x 254mm / 40.9" x 27.5" x 10"
LCD-4000HD: 1038 x 698 x 254mm / 40.9" x 27.5" x 10"
- Dimensions w/o deskstand (WHD): LCD-4200HD: 1038 x 639 x 90mm / 40.9" x 25.2" x 3.5"
LCD-4000HD: 1038 x 639 x 90mm / 40.9" x 25.2" x 3.5"
- Actual visible screen size (WH): LCD-4200HD: 914 x 520mm / 36" x 20.5"
LCD-4000HD: 885.6 x 498mm / 34.9" x 19.6"
- Operating temperature/humidity: 32 ~ 140°F / 0 ~ 60°C, 20% ~ 90% humidity
- Power Requirements: 90 ~ 240 VAC / 50 ~ 60 Hz
- Power Consumption: 360 W (max)
- Rear Terminal Connections: [RCA video IN and RCA R/L IN audio jack] x 2
S-Video IN jack x 2, [RCA Y/Pb/Pr inputs & R/L audio inputs],
[RCA Y/Cb/Cr & R/L audio inputs]
RCA audio R & L output, PC audio IN jack,
15-pin D-sub, AC IN, 9-pin RS-232,
HDMI, DVI
- Net Weight: 31.6 kg. / 70 lbs.
- Net Weight w/o desk stand: 24 kg. / 53 lbs.
- Gross Weight: 42.6 kg. / 94 lbs.

1319 Dexter Ave. N • Ste. 020 • WA 98109
Tel: 206-623-6000 • FAX: 206-623-6609
E-mail: sales@totevision.com
http://www.totevision.com

